

<template>

Elements that contain reusable blocks of HTML markup:

```
<template id="user">    <!-- use an id to select the template -->
  <div class="user">
    <img class="user__avatar" alt="avatar">    <!-- the src attribute will be set using JavaScript -->
    <p class="user__name"></p>    <!-- the textContent will be set using JavaScript -->
  </div>
</template>
```

Note: A `<template>` and its content will not be rendered on the page.

Rendering `<template>` elements with JavaScript

```
// parent is the container where the users will be rendered
const userList = document.querySelector(".users");

// select the template
const userTemplate = document.querySelector("#user")
    .content                // access the content of the template tags
    .cloneNode(true);       // clone the node and all of its contents

// insert content as needed
userElement.querySelector(".user__avatar").src = "tinyurl.com/v4pfzwy";
userElement.querySelector(".user__name").textContent = "Duke, mayor of Cormorant";

// make it appear on the page
userList.append(userElement);
```

Adding Elements to the DOM

Each of these functions accepts a comma-separated list of parameters.

The parameters can be DOM nodes or strings:

- `node.append(firstParam, secondParam, ...)` adds the parameters after the last child of the `node`
- `node.prepend(firstParam, secondParam, ...)` adds the parameters before the first child of the `node`
- `node.after(firstParam, secondParam, ...)` inserts the parameters after the `node`
- `node.before(firstParam, secondParam, ...)` inserts the parameters before the `node`
- `node.replaceWith(firstParam, secondParam, ...)` replaces `node` with the parameters