Roadmap and Team Plan

Current real-data build, practical milestones, and the IBM BOB/GitHub handoff

1. What is implemented now

Capability	Status
Real map and street geometry	OpenStreetMap tiles and bounded Overpass street graph
Live hourly weather	Open-Meteo temperature, humidity, cloud cover and shortwave radiation
Route comparison	Local shortest and heat-budget routing on mapped street segments
Shade estimate	Nearby mapped tree/building proxy, visibly labeled as approximate
Local run and handoff	README, Windows start script, requirements, .gitignore and IBM BOB brief

2. Recommended build sequence

Phase	Work	Done when
1. Local demo	Run from the Project folder; plan a route in Jaipur and a second area; confirm the browser map attribution and live-service errors are clear.	A new developer can launch it using README steps.
2. Routing quality	Validate OSM footway topology, one-way/steps/accessibility tags, snapped points and closed-edge behavior on field-selected trips.	Observed trips follow walkable paths and bad tag coverage is surfaced.
3. Shade quality	Collect shade observations by street side and time; add canopy width, building height and solar position where licensed data permits.	Estimate error is measured against field observations.
4. Resilience	Add explicit request timeouts, provider status, persistent cache, retry/backoff and configurable provider URLs.	Provider outage leaves useful errors and does not hang the UI.
5. Publish	Select commercial-capable tile, weather and data hosting terms; add privacy notice and deploy backend plus static UI.	Usage complies with each provider's terms and has operational monitoring.

3. GitHub and IBM BOB handoff

- Open this Project folder as the repository root in IBM BOB.
- Use BOB_IMPLEMENTATION_BRIEF.md as the short continuation prompt; README.md is the source of truth for setup.
- Commit the source files and PDFs. Do not commit .venv, generated caches or secrets.
- The public free services are not commercial production guarantees. Choose licensed or self-hosted providers before monetizing the app.
- Use the new implementation plan PDF to review the architecture and acceptance criteria.

4. Known limitations

- Shade is inferred from mapped nearby features and has not been calibrated against measured street shadows.
- Step-free routing filters OSM tags but cannot prove curb cuts or accessibility conditions that were never mapped.
- A small-area graph and nearest-node snapping are suitable for a local demo, not a complete city routing service.
- Weather radiation and a relative heat score do not represent personal health risk or individual heat exposure.