

For_Git_FM332_RSM

```
[2]: import numpy as np
print(np.version.version)
from numpy import loadtxt
import matplotlib.pyplot as plt
from scipy.optimize import curve_fit
import glob
from numpy import diff
import pandas as pn
import math
import scipy.constants as sc
import pickle
import copy
from scipy import interpolate
from matplotlib import rcParams, cycler, cm, rc
plotall = True
overview_plot = True
from pylab import   
↪ meshgrid, cm, imshow, contour, clabel, colorbar, axis, title, show, pcolor
import pandas as pd
import os
import matplotlib.ticker
from matplotlib.ticker import ScalarFormatter
from matplotlib.ticker import (MultipleLocator, AutoMinorLocator)
from numpy.polynomial import Polynomial
from scipy.interpolate import griddata
import matplotlib.cm as cm
import matplotlib as mpl
import numpy.ma as ma
```

1.24.3

```
[3]: %run XRD_Functions.ipynb
```

0.1 Closest Element

```
[4]: def closest_element(array, value):
    element = min(array, key=lambda x:abs(x-value))
    closest_element = np.where(array == element)[0][0]
```

```
return closest_element
```

0.2 Closest Element Range

```
[5]: def closest_element_index(array,value):  
    array1 = np.sort(array)  
    closest_element = min(array1, key=lambda x:abs(x-value))  
    closest_element_index = np.where(array1 == closest_element)[0][0]  
    closest_index_range = array1[closest_element_index-1 :  
↪closest_element_index+1]  
    mylist = []  
    for i in closest_index_range:  
        closest_index_actual = np.where(array == i)[0]  
        mylist = np.sort(np.append(mylist,closest_index_actual))  
    return mylist
```

```
[6]: "----Folder Paths----"  
  
folder_STO_103_plus = r"C:  
↪\Users\pblah\Data\XRD\FM332\Exfoliated\RSM\hkl\Analysed\STO 103+"  
pathlist_STO_103_plus = folderpath(folder_STO_103_plus)  
  
folder_SRO_103_plus = r"C:  
↪\Users\pblah\Data\XRD\FM332\Exfoliated\RSM\hkl\Analysed\SRO 103+"  
pathlist_SRO_103_plus = folderpath(folder_SRO_103_plus)  
  
folder_STO_103_minus = r"C:  
↪\Users\pblah\Data\XRD\FM332\Exfoliated\RSM\hkl\Analysed\STO 103-"  
pathlist_STO_103_minus = folderpath(folder_STO_103_minus)  
  
folder_SRO_103_minus = r"C:  
↪\Users\pblah\Data\XRD\FM332\Exfoliated\RSM\hkl\Analysed\SRO 103-"  
pathlist_SRO_103_minus = folderpath(folder_SRO_103_minus)  
  
print(pathlist_STO_103_plus)  
print(pathlist_SRO_103_plus)  
print(pathlist_STO_103_minus)  
print(pathlist_SRO_103_minus)
```

```
['C:\\Users\\pblah\\Data\\XRD\\FM332\\Exfoliated\\RSM\\hkl\\Analysed\\STO  
103+\\Take_2_STO_103+_hkl.txt']  
['C:\\Users\\pblah\\Data\\XRD\\FM332\\Exfoliated\\RSM\\hkl\\Analysed\\SRO  
103+\\Take_2_SRO_103+_hkl.txt']  
['C:\\Users\\pblah\\Data\\XRD\\FM332\\Exfoliated\\RSM\\hkl\\Analysed\\STO
```

```
103-\\Take_2_STO_103-_hkl.txt']
['C:\\Users\\pblah\\Data\\XRD\\FM332\\Exfoliated\\RSM\\hkl\\Analysed\\SRO
103-\\Take_2_SRO_103-_hkl.txt']
```

0.3 STO 103+

```
[7]: %%time

import sys
np.set_printoptions(threshold=1000) # can change to sys.maxsize, default is 1000

fig = plt.figure(figsize=(8,6))
ax = fig.add_subplot(111)
cm = plt.get_cmap('inferno', 30)

#npts = 200
ngridx = 300
ngridy = 300

for i,data in enumerate(pathlist_STO_103_plus):

    print("i",i)
    print("data",data)

    dataextracted = np.loadtxt(data,encoding="utf-8-sig", unpack = True)
    l = dataextracted[0]
    h = dataextracted[1]
    counts = dataextracted[2]

    l = np.ma.masked_invalid(l)
    h = np.ma.masked_invalid(h)

    print(len(h))

    x = np.linspace(0.929580673,1.066431362, ngridx)
    y = np.linspace(3.061808196,2.940177011, ngridy)
    xi_STO, yi_STO = np.meshgrid(x, y)

    zi_STO = griddata((h,l), counts, (xi_STO, yi_STO), method='linear')
    zi_STO = np.ma.masked_invalid(zi_STO)
    zi_array_STO = np.asarray(zi_STO)
    zi_array_one_STO = np.ndarray.flatten(zi_array_STO)
```

```

print("max count value",np.nanmax(zi_STO))
print("max count value index",np.where(zi_STO == np.nanmax(zi_STO)))
z_max = np.where(zi_STO == np.nanmax(zi_STO)) # The linear interpolation of
→griddata is not perfect...Note: Say you get array[149],array[152]. This means
→it's the 152nd element of the xi_STO array. The xi-STO array goes over a range
→while yi_STO stays the same.
print("z_max",z_max)
y_max_index = z_max[0][0] # The yi_STO where we find the max count value,
→where yi-STO is kept constant and you sweep through a range of values for xi_STO.
→SO the xi_STO and yi_STO indexes are the same.
print("y_max index",y_max_index)
print('y_max',yi_STO[z_max])
x_max_index = z_max
print("x_max index",x_max_index)
print('x_max',xi_STO[z_max])

y_correction = (3-yi_STO[y_max_index])[0]
x_correction = (1-xi_STO[x_max_index][0])
print('y_correction',y_correction)
print('x_correction',x_correction)

##### Showing what I explained in comment of z_max #####
#x_max_index = z_max[0][0]
#print("x_max index",x_max_index)
#print("zi_STO with x_max index", zi_STO[x_max_index])
#print("index of max value in 'zi_STO with x_max index'",np.
→where(zi_STO[x_max_index] == np.nanmax(zi_STO[x_max_index]))[0][0])
#print("x_max index actual",zi_STO[x_max_index][152])
#####

yi_STO = yi_STO + y_correction
xi_STO = xi_STO + x_correction

#zi_min = np.nanmin(zi_array_one)
#zi_max = np.nanmax(zi_array_one)

#STO Max value at (8.0998, 0.002905), found via excel

```

```

#STO Max value at (3.03326, 0.002905), found via excel after converting

#qx_Peak_STO = 0.0029

#NNO Max value at (8.3042,-0.0319), found via Excel

#qx_Peak_NNO = -0.0319
#NNO_a_parameter = 0.3905*(1+qx_Peak_NNO-qx_Peak_STO)
#print('NNO_a_parameter',NNO_a_parameter)

#plt.contour(xi,yi,zi, levels = np.arange(zi_min+4,100+zi_min,0.01),cmap =
→ 'inferno',norm = matplotlib.colors.LogNorm(vmin=np.nanmin(counts)+1, vmax=np.
→ nanmax(counts), clip=False),linewidths = 0.1)
plt.contourf(xi_STO,yi_STO,zi_STO, levels =
→ [5,10,50,100,500,1000,5000,100000,120000,132000,140000,142000,143000,144500],norm
→ = matplotlib.colors.LogNorm(vmin = 5, vmax = 144500),cmap =
→ 'viridis',linewidths = 1, alpha = 1)
plt.title(r'$[103]+$ STO',fontsize = 20, pad = 20)
plt.ylabel(r'l (r.l.u)',fontsize =20, labelpad = 20)
plt.xlabel("h (r.l.u) ",fontsize =20,labelpad = 20)
#plt.hlines(3,0.9525,1.05)
#sm = plt.cm.ScalarMappable(cmap=cm,norm = matplotlib.colors.
→ LogNorm(vmin=np.nanmin(zi_min)+1, vmax=1000, clip=False))
#cax = fig.add_axes([0.2, 0.65, 0.02, 0.20])
#cbar = plt.colorbar(sm, cax=cax, shrink = 0.01, orientation='vertical',
→ extend = 'max')
#cbar_scale=np.arange(np.nanmin(counts),np.nanmax(counts),np.nanmax(counts)/
→ 4)

#plt.savefig(r"C:\Users\pblah\Data\XRD\FM317\RSM\103 Plus\hkl\FM318 103 Plus
→ RSM hkl.png", bbox_inches = "tight")

#counts = np.ma.masked_invalid(counts)
#print(l)
#print(h)
#print(counts)
#print('xi',xi)
#print('yi',yi)
#print('zi',zi)

```

```

    #print('zi_array_one',zi_array_one)
    #print(zi_min)
    #print(np.nanmin(counts))
    #print(np.nanmax(counts))


xi_ST0_plus = xi_ST0
yi_ST0_plus = yi_ST0
zi_ST0_plus = zi_ST0

y_max_index_plus = yi_ST0[z_max][0]
x_max_index_plus = xi_ST0[z_max][0]

i 0
data C:\Users\pblah\Data\XRD\FM332\Exfoliated\RSM\hkl\Analysed\STO
103+\Take_2_STO_103+_hkl.txt
57589
max count value 540763.6157068422
max count value index (array([152], dtype=int64), array([154], dtype=int64))
z_max (array([152], dtype=int64), array([154], dtype=int64))
y_max index 152
y_max [2.99997562]
x_max index (array([152], dtype=int64), array([154], dtype=int64))
x_max [1.00006564]
y_correction 2.4379652173944777e-05
x_correction -6.56432541805696e-05
CPU times: total: 5.11 s
Wall time: 5.77 s

<timed exec>:92: UserWarning: Log scale: values of z <= 0 have been masked
<timed exec>:92: UserWarning: linewidths is ignored by contourf

```



0.4 SRO 103+

```
[8]: %%time

import sys
np.set_printoptions(threshold=1000) # can change to sys.maxsize, default is 1000

fig = plt.figure(figsize=(8,6))
ax = fig.add_subplot(111)
cm = plt.get_cmap('inferno', 30)

npts = 200
ngridx = 300
ngridy = 300
```

```

for i,data in enumerate(pathlist_SRO_103_plus):

    print("i",i)
    print("data",data)

    dataextracted = np.loadtxt(data,encoding="utf-8-sig", unpack = True)
    l = (dataextracted[0])
    h = dataextracted[1]
    counts = dataextracted[2]

    l = np.ma.masked_invalid(l)
    h = np.ma.masked_invalid(h)

    x = np.linspace(0.952316359, 1.085023209 , ngridx)
    y = np.linspace(3.004203516,2.881096502 , ngridy)
    xi_NNO, yi_NNO = np.meshgrid(x, y)

    zi_NNO = griddata((h,l), counts, (xi_NNO, yi_NNO), method='linear')
    zi_NNO = np.ma.masked_invalid(zi_NNO)

    zi_array_NNO = np.asarray(zi_NNO)
    zi_array_one_NNO = np.ndarray.flatten(zi_array_NNO)
    #zi_min = np.nanmin(zi_array_one)
    #zi_max = np.nanmax(zi_array_one)

    #yi_NNO = yi_NNO - (STO_max-3)

    #NNO Max value at (3.0798,0.986455), found via Excel

    #print(np.nanmax(zi_STO))

    #y_max = np.where(zi_STO == np.nanmax(zi_STO))[1][0]

    #print(y_max)
    #print((3-yi_STO[y_max]))

    #xi_NNO_max = 0.9681
    #yi_NNO = yi_NNO + y_correction # Taking into account the fact that
    ↳ interpolation of STO data not perfect, using STO correction can't get
    ↳ correction for NNO
    #xi_NNO = xi_NNO + x_correction # Taking into account the fact that
    ↳ interpolation of STO data not perfect, using STO correction can't get
    ↳ correction for NNO

    z_max_NNO = np.where(zi_NNO == np.nanmax(zi_NNO))

```



```

print("z_max_NNO",z_max_NNO)
y_max_index_NNO = z_max_NNO[0][0] # The yi_STO where we find the max count
↪value, where yi-STO is kept constant and you sweep through a range of values for
↪xi-STO. So the xi-STO and yi-STO indexes are the same.
print("y_max index_NNO",y_max_index_NNO)
print('y_max_NNO',yi_NNO[z_max_NNO])
x_max_index_NNO = z_max_NNO
print("x_max index_NNO",x_max_index_NNO)
print('x_max_NNO',xi_NNO[z_max_NNO])

yi_NNO = yi_NNO + y_correction
xi_NNO = xi_NNO + x_correction


#x_max_index = z_max
#x_max_NNO = np.where(zi_NNO == np.nanmax(zi_NNO)) # The linear
↪interpolation of griddata is not perfect...
#print(x_max_NNO)
#y_max_NNO = np.where(zi_NNO == np.nanmax(zi_NNO)) # The linear
↪interpolation of griddata is not perfect...
#print(y_max_NNO)
#xi_NNO_max = xi_NNO[x_max_NNO]
#yi_NNO_max = yi_NNO[y_max_NNO]


#print("yi_NNO",yi_NNO_max)

#qx_Peak_NNO = -0.0319
#NNO_a_parameter = 0.3905*(1+qx_Peak_NNO-qx_Peak_STO)
#print('NNO_a_parameter',NNO_a_parameter)

### For tricontour ###
#xi = np.ndarray.flatten(xi)
#yi = np.ndarray.flatten(yi)
#####

```

```

    #plt.contourf(xi,yi,zi, levels = np.arange(zi_min+4,100+zi_min,0.1),cmap =
→ 'inferno',norm = matplotlib.colors.LogNorm(vmin=np.nanmin(counts)+1, vmax=np.
→ nanmax(counts), clip=False),linewidths = 0.1)
    plt.contourf(xi_NNO,yi_NNO,zi_NNO, levels = [3,5,10,15,20,30,33,35],cmap =
→ 'viridis',norm = matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1,
→ alpha = 1)
    #plt.tricontour(xi,yi,zi_array_one, levels = [3,5,10,15,20,35],cmap =
→ 'binary',norm = matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1,
→ alpha = 1)
    plt.title(r'SRO $[103]$ Plus',fontsize = 20, pad = 20)
    plt.ylabel(r'l (r.l.u)',fontsize =20, labelpad = 20)
    plt.xlabel("h (r.l.u) ",fontsize =20,labelpad = 20)
    #sm = plt.cm.ScalarMappable(cmap=cm,norm = matplotlib.colors.
→ LogNorm(vmin=np.nanmin(zi_min)+1, vmax=1000, clip=False))
    #cax = fig.add_axes([0.2, 0.65, 0.02, 0.20])
    #cbar = plt.colorbar(sm, cax=cax, shrink = 0.01, orientation='vertical',
→ extend = 'max')
    #cbar_scale=np.arange(np.nanmin(counts),np.nanmax(counts),np.nanmax(counts)/
→ 4)
    #norm = matplotlib.colors.LogNorm(vmin=1, vmax=35, clip=False)

    #plt.savefig(r"C:\Users\pblah\Data\XRD\FM317\RSM\103 Plus\hkl\FM318 103 Plus_
→ RSM hkl.png", bbox_inches = "tight")

    #counts = np.ma.masked_invalid(counts)
    #print(l)
    #print(h)
    #print(counts)
    #print('xi',xi)
    #print('yi',yi)
    #print('zi',zi)
    #print('zi_array_one',zi_array_one)
    #print(zi_min)
    #print(np.nanmin(counts))
    #print(np.nanmax(counts))

xi_NNO_plus = xi_NNO
yi_NNO_plus = yi_NNO

```

```
zi_NNO_plus = zi_NNO
```

```
x_max_index_NNO_plus = xi_NNO[z_max_NNO][0]
```

```
y_max_index_NNO_plus = yi_NNO[z_max_NNO][0]
```

```
i 0
```

```
data C:\Users\pblah\Data\XRD\FM332\Exfoliated\RSM\hkl\Analysed\SRO  
103+\Take_2_SRO_103+_hkl.txt
```

```
z_max_NNO (array([151], dtype=int64), array([166], dtype=int64))
```

```
y_max_index_NNO 151
```

```
y_max_NNO [2.94203242]
```

```
x_max_index_NNO (array([151], dtype=int64), array([166], dtype=int64))
```

```
x_max_NNO [1.02599307]
```


```
CPU times: total: 1.91 s
```

```
Wall time: 1.9 s
```

```
<timed exec>:103: UserWarning: Log scale: values of z <= 0 have been masked
```

```
<timed exec>:103: UserWarning: linewidths is ignored by contourf
```

SRO [103] Plus



0.5 Both

```
[9]: #fig, ax_left = plt.subplots()
#ax_left.contourf(xi_NNO,yi_NNO,zi_NNO, levels = [3,5,10,15,20,35],cmap =_
    ↳ 'viridis',norm = matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1,_
    ↳ alpha = 1)
#plt.ylabel(r'l (r.l.u)',fontsize =20, labelpad = 20)
#plt.xlabel("h (r.l.u) ",fontsize =20,labelpad = 20)

#ax_right = ax_left.twinx()
#ax_right.contourf(xi_STO,yi_STO,zi_STO, levels =_
    ↳ [5,10,50,100,500,1000,5000,10000,12000,13200,14000,14400],norm = matplotlib.
    ↳ colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths = 1, alpha_
    ↳ = 1)

fig, ax = plt.subplots(figsize=(12, 12), dpi = 500)

ax.contourf(xi_NNO,yi_NNO,zi_NNO, levels = [5,10,15,20,25,28,30,33,35],cmap =_
    ↳ 'viridis',norm = matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1,_
    ↳ alpha = 1)
ax.contourf(xi_STO,yi_STO,zi_STO, levels =_
    ↳ [10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =_
    ↳ matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths_
    ↳ = 1, alpha = 1)

ax.tick_params(axis = 'x', which='major', labels=30, length = 10, width = 2,_
    ↳ direction = 'in', pad = 10, top = True)
ax.tick_params(axis = 'y', which='major', labels=30, length = 10, width = 2,_
    ↳ direction = 'in', pad = 10, right = False)
ax.tick_params(axis = 'y', which='major', labels=30, length = 10, width = 2,_
    ↳ direction = 'in', pad = 10, right = True)

ax.spines["top"].set_linewidth(2.5)
ax.spines["bottom"].set_linewidth(2.5)
ax.spines["right"].set_linewidth(2.5)
ax.spines["left"].set_linewidth(2.5)

ax.set_ylim(2.9,3.04)
```

```

text = ax.text(0.25,0.78, ' ST0\n[103]+', size=30, color = 'black',transform =_
↳ax.transAxes )
text = ax.text(0.73,0.4, ' SRO\n[103]+', size=30, color = 'black',transform = ax.
↳transAxes )

#plt.vlines(xi_STO[z_max][0],2.9,3.04, color = "red", linestyle = 'dotted', lw =_
↳1)
#plt.vlines(xi_NNO[z_max_NNO][0],2.9,3.04, color = "red",linestyle = 'dotted',_
↳lw = 1)

x_difference = 1 - xi_NNO[z_max_NNO]
y_difference = 3-yi_NNO[z_max_NNO]

print('x_difference',x_difference)
print('y_difference',y_difference)

NNO_a_parameter = (3.905 * (-1+x_difference))
NNO_c_parameter = 3.905 * ((3+y_difference)/3)

print('SRO_a_parameter',NNO_a_parameter[0])
print('SRO_c_parameter',NNO_c_parameter[0])


#plt.title(r'$[103]+$ ST0 and SRO',fontsize = 20, pad = 20)
ax.set_ylabel(r'l (r.l.u)',fontsize=40,labelpad = 25)
ax.set_xlabel(r'h (r.l.u)',fontsize=40,labelpad = 25)
plt.savefig(r"C:\Users\pblah\Data\XRD\FM332\Figures\FM332_103_Plus_RSM_hkl.png",_
↳bbox_inches = "tight")
plt.savefig(r"C:\Users\pblah\Data\XRD\FM332\Figures\FM332_103_Plus_RSM_hkl.pdf",_
↳bbox_inches = "tight", format = "pdf")
plt.show()

```

C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\516850824.py:11: UserWarning:
Log scale: values of z <= 0 have been masked

```

ax.contourf(xi_NNO,yi_NNO,zi_NNO, levels = [5,10,15,20,25,28,30,33,35],cmap =
'viridis',norm = matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1,
alpha = 1)

```

C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\516850824.py:11: UserWarning:
linewidths is ignored by contourf

```

ax.contourf(xi_NNO,yi_NNO,zi_NNO, levels = [5,10,15,20,25,28,30,33,35],cmap =
'viridis',norm = matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1,


```

```

alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\516850824.py:12: UserWarning:
Log scale: values of z <= 0 have been masked
    ax.contourf(xi_ST0,yi_ST0,zi_ST0, levels =
[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\516850824.py:12: UserWarning:
linewidths is ignored by contourf
    ax.contourf(xi_ST0,yi_ST0,zi_ST0, levels =
[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)

x_difference [-0.02592743]
y_difference [0.05794321]
SR0_a_parameter -4.006246608116188
SR0_c_parameter 3.980422738591048

```



0.6 STO 103 Minus

```
[10]: %%time

import sys
np.set_printoptions(threshold=1000) # can change to sys.maxsize, default is 1000

fig = plt.figure(figsize=(8,6))
ax = fig.add_subplot(111)
cm = plt.get_cmap('inferno', 30)
```

```

#npts = 200
ngridx = 300
ngridy = 300

for i,data in enumerate(pathlist_ST0_103_minus):

    print("i",i)
    print("data",data)

    dataextracted = np.loadtxt(data,encoding="utf-8-sig", unpack = True)
    l = dataextracted[0]
    h = dataextracted[1]
    counts = dataextracted[2]

    l = np.ma.masked_invalid(l)
    h = np.ma.masked_invalid(h)

    print(len(h))

    x = np.linspace(-1.09348, -0.911055 , ngridx)
    y = np.linspace(3.04362,2.95828 , ngridy)
    xi_ST0, yi_ST0 = np.meshgrid(x, y)

    zi_ST0 = griddata((h,l), counts, (xi_ST0, yi_ST0), method='linear')
    zi_ST0 = np.ma.masked_invalid(zi_ST0)
    zi_array_ST0 = np.asarray(zi_ST0)
    zi_array_one_ST0 = np.ndarray.flatten(zi_array_ST0)

    print("max count value",np.nanmax(zi_ST0))
    print("max count value index",np.where(zi_ST0 == np.nanmax(zi_ST0)))
    z_max = np.where(zi_ST0 == np.nanmax(zi_ST0)) # The linear interpolation of
    ↳griddata is not perfect...Note: Say you get array[149],array[152]. This means
    ↳it's the 152nd element of the xi_ST0 array. The xi-ST0 array goes over a range
    ↳while yi_ST0 stays the same.
    print("z_max",z_max)
    y_max_index = z_max[0][0] # The yi_ST0 where we find the max count value,
    ↳where yi-ST0 is kept constant and you sweep through a range of values for xi_ST0.
    ↳SO the xi_ST0 and yi_ST0 indexes are the same.
    print("y_max index",y_max_index)
    print('y_max',yi_ST0[z_max])
    x_max_index = z_max
    print("x_max index",x_max_index)
    print('x_max',xi_ST0[z_max])

    y_correction = (3-yi_ST0[y_max_index])[0]
    x_correction = (-1-xi_ST0[x_max_index][0])

```



```

print(y_correction)
print(x_correction)

##### Showing what I explained in comment of z_max #####
#x_max_index = z_max[0][0]
#print("x_max index",x_max_index)
#print("zi_STO with x_max index", zi_STO[x_max_index])
#print("index of max value in 'zi_STO with x_max index'",np.
→where(zi_STO[x_max_index] == np.nanmax(zi_STO[x_max_index]))[0][0])
#print("x_max index actual",zi_STO[x_max_index][152])
#####

yi_STO = yi_STO + y_correction
xi_STO = xi_STO - x_correction

#zi_min = np.nanmin(zi_array_one)
#zi_max = np.nanmax(zi_array_one)

#STO Max value at (8.0998, 0.002905), found via excel
#STO Max value at (3.03326, 0.002905), found via excel after converting

#qx_Peak_STO = 0.0029

#NNO Max value at (8.3042,-0.0319), found via Excel

#qx_Peak_NNO = -0.0319
#NNO_a_parameter = 0.3905*(1+qx_Peak_NNO-qx_Peak_STO)
#print('NNO_a_parameter',NNO_a_parameter)

plt.contour(xi,yi,zi, levels = np.arange(zi_min+4,100+zi_min,0.01),cmap =
→'inferno',norm = matplotlib.colors.LogNorm(vmin=np.nanmin(counts)+1, vmax=np.
→nanmax(counts), clip=False),linewidths = 0.1)
plt.contourf(xi_STO,yi_STO,zi_STO, levels =
→[5,10,50,100,500,1000,5000,100000,120000,132000,140000,142000,143000,144500],norm=
→matplotlib.colors.LogNorm(vmin = 5, vmax = 144500),cmap =
→'viridis',linewidths = 1, alpha = 1)
plt.title(r'$[103]-$ STO',fontsize = 20, pad = 20)
plt.ylabel(r'l (r.l.u)',fontsize =20, labelpad = 20)

```

```

plt.xlabel("h (r.l.u) ", fontsize = 20, labelpad = 20)
plt.hlines(3, 0.9525, 1.05)
#sm = plt.cm.ScalarMappable(cmap=cm, norm = matplotlib.colors.
→LogNorm(vmin=np.nanmin(zi_min)+1, vmax=1000, clip=False))
#cax = fig.add_axes([0.2, 0.65, 0.02, 0.20])
#cbar = plt.colorbar(sm, cax=cax, shrink = 0.01, orientation='vertical',
→extend = 'max')
#cbar_scale=np.arange(np.nanmin(counts), np.nanmax(counts), np.nanmax(counts)/
→4)

plt.savefig(r"C:\Users\pblah\Data\XRD\FM317\RSM\103 Plus\hkl\FM318 103 Plus
→RSM hkl.png", bbox_inches = "tight")

#counts = np.ma.masked_invalid(counts)
#print(l)
#print(h)
#print(counts)
#print('xi', xi)
#print('yi', yi)
#print('zi', zi)
#print('zi_array_one', zi_array_one)
#print(zi_min)
#print(np.nanmin(counts))
#print(np.nanmax(counts))

xi_STO_minus = xi_STO
yi_STO_minus = yi_STO
zi_STO_minus = zi_STO

y_max_index_minus = yi_STO[z_max][0]
x_max_index_minus = xi_STO[z_max][0]

```

```

i 0
data C:\Users\pblah\Data\XRD\FM332\Exfoliated\RSM\hkl\Analysed\STO
103-\Take_2_STO_103-_hkl.txt
112200
max count value 978702.0958366791
max count value index (array([152], dtype=int64), array([152], dtype=int64))
z_max (array([152], dtype=int64), array([152], dtype=int64))
y_max index 152


```

```

y_max [3.00023645]
x_max index (array([152], dtype=int64), array([152], dtype=int64))
x_max [-1.00074221]
-0.00023645484949819107
0.00074220735785957
CPU times: total: 1.11 s
Wall time: 1.1 s

<timed exec>:91: UserWarning: Log scale: values of z <= 0 have been masked
<timed exec>:91: UserWarning: linewidths is ignored by contourf

```



0.7 SRO 103 Minus

```

[11]: %%time

import sys
np.set_printoptions(threshold=1000) # can change to sys.maxsize, default is 1000

fig = plt.figure(figsize=(8,6))

```

```

ax = fig.add_subplot(111)
cm = plt.get_cmap('inferno', 30)

npts = 200
ngridx = 300
ngridy = 300

for i,data in enumerate(pathlist_SRO_103_minus):

    print("i",i)
    print("data",data)

    dataextracted = np.loadtxt(data,encoding="utf-8-sig", unpack = True)
    l = (dataextracted[0])
    h = dataextracted[1]
    counts = dataextracted[2]

    l = np.ma.masked_invalid(l)
    h = np.ma.masked_invalid(h)

    x = np.linspace(-1.03875, -0.859542 , ngridx)
    y = np.linspace(3.00812,2.9227 , ngridy)
    xi_NNO, yi_NNO = np.meshgrid(x, y)

    zi_NNO = griddata((h,l), counts, (xi_NNO, yi_NNO), method='linear')
    zi_NNO = np.ma.masked_invalid(zi_NNO)

    zi_array_NNO = np.asarray(zi_NNO)
    zi_array_one_NNO = np.ndarray.flatten(zi_array_NNO)
    #zi_min = np.nanmin(zi_array_one)
    #zi_max = np.nanmax(zi_array_one)

    #yi_NNO = yi_NNO - (STO_max-3)

    #NNO Max value at (3.0798,0.986455), found via Excel

    #print(np.nanmax(zi_STO))

    #y_max = np.where(zi_STO == np.nanmax(zi_STO))[1][0]

    #print(y_max)
    #print((3-yi_STO[y_max]))

```

```

#xi_NNO_max = 0.9681
#yi_NNO = yi_NNO + y_correction # Taking into account the fact that
↪ interpolation of STO data not perfect, using STO correction can't get
↪ correction for NNO
#xi_NNO = xi_NNO + x_correction # Taking into account the fact that
↪ interpolation of STO data not perfect, using STO correction can't get
↪ correction for NNO

z_max_NNO = np.where(zi_NNO == np.nanmax(zi_NNO))
print("z_max_NNO", z_max_NNO)
y_max_index_NNO = z_max_NNO[0][0] # The yi_STO where we find the max count
↪ value, where yi-STO is kept constant and you sweep through a range of values for
↪ xi_STO. SO the xi_STO and yi_STO indexes are the same.
print("y_max index_NNO", y_max_index_NNO)
print('y_max_NNO', yi_NNO[z_max_NNO])
x_max_index_NNO = z_max_NNO
print("x_max index_NNO", x_max_index_NNO)
print('x_max_NNO', xi_NNO[z_max_NNO])

yi_NNO = yi_NNO + y_correction
xi_NNO = xi_NNO - x_correction


#x_max_index = z_max
#x_max_NNO = np.where(zi_NNO == np.nanmax(zi_NNO)) # The linear
↪ interpolation of griddata is not perfect...
#print(x_max_NNO)
#y_max_NNO = np.where(zi_NNO == np.nanmax(zi_NNO)) # The linear
↪ interpolation of griddata is not perfect...
#print(y_max_NNO)
#xi_NNO_max = xi_NNO[x_max_NNO]
#yi_NNO_max = yi_NNO[y_max_NNO]


#print("yi_NNO", yi_NNO_max)

#qx_Peak_NNO = -0.0319
#NNO_a_parameter = 0.3905*(1+qx_Peak_NNO-qx_Peak_STO)
#print('NNO_a_parameter', NNO_a_parameter)

### For tricontour ###
#xi = np.ndarray.flatten(xi)

```

```

#yi = np.ndarray.flatten(yi)
#####

plt.contourf(xi,yi,zi, levels = np.arange(zi_min+4,100+zi_min,0.1),cmap =
→ 'inferno',norm = matplotlib.colors.LogNorm(vmin=np.nanmin(counts)+1, vmax=np.
→ nanmax(counts), clip=False),linewidths = 0.1)
plt.contourf(xi_NNO,yi_NNO,zi_NNO, levels =
→ [3,5,10,15,20,30,33,35,50,80,120,135],cmap = 'viridis',norm = matplotlib.
→ colors.LogNorm(vmin = 5,vmax = 135),linewidths = 1, alpha = 1)
plt.tricontour(xi,yi,zi_array_one, levels = [3,5,10,15,20,35],cmap =
→ 'binary',norm = matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1,
→ alpha = 1)
plt.title(r'$[103]-$ SRO',fontsize = 20, pad = 20)
plt.ylabel(r'l (r.l.u)',fontsize =20, labelpad = 20)
plt.xlabel("h (r.l.u) ",fontsize =20,labelpad = 20)
#sm = plt.cm.ScalarMappable(cmap=cm,norm = matplotlib.colors.
→ LogNorm(vmin=np.nanmin(zi_min)+1, vmax=1000, clip=False))
#cax = fig.add_axes([0.2, 0.65, 0.02, 0.20])
#cbar = plt.colorbar(sm, cax=cax, shrink = 0.01, orientation='vertical',
→ extend = 'max')
#cbar_scale=np.arange(np.nanmin(counts),np.nanmax(counts),np.nanmax(counts)/
→ 4)
#norm = matplotlib.colors.LogNorm(vmin=1, vmax=35, clip=False)

plt.savefig(r"C:\Users\pblah\Data\XRD\FM317\RSM\103 Plus\hkl\FM318 103 Plus
→ RSM hkl.png", bbox_inches = "tight")

#counts = np.ma.masked_invalid(counts)
#print(l)
#print(h)
#print(counts)

```

```

# print('xi',xi)
# print('yi',yi)
# print('zi',zi)
# print('zi_array_one',zi_array_one)
# print(zi_min)
# print(np.nanmin(counts))
# print(np.nanmax(counts))

xi_NNO_minus = xi_NNO
yi_NNO_minus = yi_NNO
zi_NNO_minus = zi_NNO


y_max_index_NNO_minus = yi_NNO[z_max_NNO][0]
x_max_index_NNO_minus = xi_NNO[z_max_NNO][0]

i 0
data C:\Users\pblah\Data\XRD\FM332\Exfoliated\RSM\hkl\Analysed\SR0
103-\Take_2_SR0_103-_hkl.txt
z_max_NNO (array([150], dtype=int64), array([145], dtype=int64))
y_max_index_NNO 150
y_max_NNO [2.96526716]
x_max_index_NNO (array([150], dtype=int64), array([145], dtype=int64))
x_max_NNO [-0.95184311]
CPU times: total: 1.09 s
Wall time: 1.1 s

<timed exec>:103: UserWarning: Log scale: values of z <= 0 have been masked
<timed exec>:103: UserWarning: linewidths is ignored by contourf

```

[103] – SRO



0.8 Both

```
[12]: #fig, ax_left = plt.subplots()
#ax_left.contourf(xi_NNO,yi_NNO,zi_NNO, levels = [3,5,10,15,20,35],cmap =
→ 'viridis',norm = matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1,
→ alpha = 1)
#plt.ylabel(r'l (r.l.u)',fontsize =20, labelpad = 20)
#plt.xlabel("h (r.l.u) ",fontsize =20,labelpad = 20)

#ax_right = ax_left.twinx()
#ax_right.contourf(xi_STO,yi_STO,zi_STO, levels =
→ [5,10,50,100,500,1000,5000,10000,12000,13200,14000,14400],norm = matplotlib.
→ colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths = 1, alpha
→ = 1)

fig, ax = plt.subplots(figsize=(12, 12), dpi = 500)
```



```

ax.contourf(xi_NNO,yi_NNO,zi_NNO, levels =_
↳[12,15,20,25,28,30,33,35,50,80,120,135],cmap = 'viridis',norm = matplotlib.
↳colors.LogNorm(vmin = 12,vmax = 135),linewidths = 1, alpha = 1)
ax.contourf(xi_STO,yi_STO,zi_STO, levels =_
↳[20,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =_
↳matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths_
↳= 1, alpha = 1)

#plt.vlines(xi_STO_max,2.97,3.1, color = "red")
#plt.vlines(xi_NNO_max,2.97,3.1, color = "red")

ax.tick_params(axis = 'x', which='major', labels=30, length = 10, width = 2,_
↳direction = 'in', pad = 10, top = True)
ax.tick_params(axis = 'y', which='major', labels=30, length = 10, width = 2,_
↳direction = 'in', pad = 10, right = False)
ax.tick_params(axis = 'y', which='major', labels=30, length = 10, width = 2,_
↳direction = 'in', pad = 10, right = True)

ax.spines["top"].set_linewidth(2.5)
ax.spines["bottom"].set_linewidth(2.5)
ax.spines["right"].set_linewidth(2.5)
ax.spines["left"].set_linewidth(2.5)

ax.set_xlim(-1.1,-0.85)

text = ax.text(0.45,0.78, 'STO [103]-', size=30, color = 'black',transform = ax.
↳transAxes )
text = ax.text(0.2,0.13, 'SRO [103]-', size=30, color = 'black',transform = ax.
↳transAxes )

x_difference = -1 - xi_NNO[z_max_NNO]
y_difference = 3-yi_NNO[z_max_NNO]

print('x_difference',x_difference)
print('y_difference',y_difference)

NNO_a_parameter = 3.905 * (1-x_difference)
NNO_c_parameter = 3.905 * ((3 + y_difference)/3)

print('SRO_a_parameter',NNO_a_parameter[0])
print('SRO_c_parameter',NNO_c_parameter[0])

```

```

#plt.title(r'$[103]-$ STO and SRO',fontsize = 20, pad = 20)
ax.set_ylabel(r'l (r.l.u)',fontsize=40,labelpad = 25)
ax.set_xlabel(r'h (r.l.u)',fontsize=40,labelpad = 25)
plt.savefig(r"C:\Users\pblah\Data\XRD\FM332\Figures\FM332_103_Minus_RSM_hkl.
→png", bbox_inches = "tight")
plt.savefig(r"C:\Users\pblah\Data\XRD\FM332\Figures\FM332_103_Minus_RSM_hkl.
→pdf", bbox_inches = "tight", format = "pdf")
plt.show()


```

```

C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\2890475953.py:12: UserWarning:
Log scale: values of z <= 0 have been masked
  ax.contourf(xi_NNO,yi_NNO,zi_NNO, levels =
[12,15,20,25,28,30,33,35,50,80,120,135],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 12,vmax = 135),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\2890475953.py:12: UserWarning:
linewidths is ignored by contourf
  ax.contourf(xi_NNO,yi_NNO,zi_NNO, levels =
[12,15,20,25,28,30,33,35,50,80,120,135],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 12,vmax = 135),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\2890475953.py:13: UserWarning:
Log scale: values of z <= 0 have been masked
  ax.contourf(xi_STO,yi_STO,zi_STO, levels =
[20,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\2890475953.py:13: UserWarning:
linewidths is ignored by contourf
  ax.contourf(xi_STO,yi_STO,zi_STO, levels =
[20,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)

x_difference [-0.04741468]
y_difference [0.0349693]
SRO_a_parameter 4.0901543342809354
SRO_c_parameter 3.950518369119286

```



```
[20]: %%time

import sys
np.set_printoptions(threshold=1000) # can change to sys.maxsize, default is 1000

fig = plt.figure(figsize=(8,6))
ax = fig.add_subplot(111)
cm = plt.get_cmap('inferno', 30)

#npts = 200
ngridx = 300
ngridy = 300
```

```

for i,data in enumerate(pathlist_STO_103_minus):

    print("i",i)
    print("data",data)

    dataextracted = np.loadtxt(data,encoding="utf-8-sig", unpack = True)
    l = dataextracted[0]
    h = dataextracted[1]
    counts = dataextracted[2]

    l = np.ma.masked_invalid(l)
    h = np.ma.masked_invalid(h)

    print(len(h))

    x_minus = np.linspace(-1.09348, -0.911055 , ngridx)
    y_minus = np.linspace(3.04362,2.95828 , ngridy)
    xi_STO_minus, yi_STO_minus = np.meshgrid(x_minus, y_minus)

    zi_STO_minus = griddata((h,l), counts, (xi_STO_minus, yi_STO_minus),
↳method='linear')
    #print(zi_STO_minus)
    zi_STO_minus = np.ma.masked_invalid(zi_STO_minus)
    zi_array_STO_minus = np.asarray(zi_STO_minus)
    zi_array_one_STO_minus = np.ndarray.flatten(zi_array_STO_minus)

    ↳
    ↳#####
    print("max count value",np.nanmax(zi_STO_minus))
    print("max count value index",np.where(zi_STO_minus == np.
↳nanmax(zi_STO_minus)))
    z_max_minus = np.where(zi_STO_minus == np.nanmax(zi_STO_minus)) # The
↳linear interpolation of griddata is not perfect...Note: Say you get
↳array[149],array[152]. This means it's the 152nd element of the xi_STO array.
↳The xi-STO array goes over a range while yi_STO stays the same.
    print("z_max",z_max_minus)
    y_max_index_minus = z_max_minus[0][0] # The yi_STO where we find the max
↳count value, where yi-STO is kept constant and you sweep through a range of
↳values for xi-STO. SO the xi-STO and yi_STO indexes are the same.
    print("y_max index",y_max_index_minus)
    print('y_max',yi_STO_minus[z_max_minus])

```

```

x_max_index_minus = z_max_minus
print("x_max index",x_max_index_minus)
print('x_max',xi_STO_minus[z_max_minus])

y_correction_minus = (3-yi_STO_minus[y_max_index_minus])[0]
x_correction_minus = (1+xi_STO_minus[x_max_index_minus][0])
print('y_correction_minus',y_correction_minus)
print('x_correction_minus',x_correction_minus)

##### Showing what I explained in comment of z_max #####
#x_max_index = z_max[0][0]
#print("x_max index",x_max_index)
#print("zi_STO with x_max index", zi_STO[x_max_index])
#print("index of max value in 'zi_STO with x_max index'",np.
→where(zi_STO[x_max_index] == np.nanmax(zi_STO[x_max_index]))[0][0])
#print("x_max index actual",zi_STO[x_max_index][152])
#####

#####
yi_STO_minus = yi_STO_minus + y_correction_minus
xi_STO_minus = xi_STO_minus + x_correction_minus

zi_STO_minus = griddata((h,l), counts, (xi_STO_minus, yi_STO_minus),
→method='linear')
#print(zi_STO_minus)
zi_STO_minus = np.ma.masked_invalid(zi_STO_minus)
zi_array_STO_minus = np.asarray(zi_STO_minus)
zi_array_one_STO_minus = np.ndarray.flatten(zi_array_STO_minus)

#zi_min = np.nanmin(zi_array_one)
#zi_max = np.nanmax(zi_array_one)

#STO Max value at (8.0998, 0.002905), found via excel
#STO Max value at (3.03326, 0.002905), found via excel after converting

#qx_Peak_STO = 0.0029

#NNO Max value at (8.3042,-0.0319), found via Excel

#qx_Peak_NNO = -0.0319
#NNO_a_parameter = 0.3905*(1+qx_Peak_NNO-qx_Peak_STO)
#print('NNO_a_parameter',NNO_a_parameter)

```

```

#print(xi_STO)

#plt.contour(xi,yi,zi, levels = np.arange(zi_min+4,100+zi_min,0.01),cmap =
→ 'inferno',norm = matplotlib.colors.LogNorm(vmin=np.nanmin(counts)+1, vmax=np.
→ nanmax(counts), clip=False),linewidths = 0.1)
#####

plt.contourf(xi_STO_minus,yi_STO_minus,zi_STO_minus, levels =
→ [1,5,10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
→ matplotlib.colors.LogNorm(vmin = 1, vmax = 14400),cmap = 'viridis',linewidths
→ = 1, alpha = 1)
plt.title(r'$[103]-$ STO',fontsize = 20, pad = 20)
plt.ylabel(r'l (r.l.u)',fontsize =20, labelpad = 20)
plt.xlabel("h (r.l.u) ",fontsize =20,labelpad = 20)

#####
#plt.hlines(3,0.9525,1.05)
#sm = plt.cm.ScalarMappable(cmap=cm,norm = matplotlib.colors.
→ LogNorm(vmin=np.nanmin(zi_min)+1, vmax=1000, clip=False))
#cax = fig.add_axes([0.2, 0.65, 0.02, 0.20])
#cbar = plt.colorbar(sm, cax=cax, shrink = 0.01, orientation='vertical',
→ extend = 'max')
#cbar_scale=np.arange(np.nanmin(counts),np.nanmax(counts),np.nanmax(counts)/
→ 4)

#plt.savefig(r"C:\Users\pblah\Data\XRD\FM317\RSM\113 minus\Figures\Take 2_
→ Analysis\FM317_103_Minus_RSM_hkl.png", bbox_inches = "tight")
#plt.savefig(r"C:\Users\pblah\Data\XRD\FM317\RSM\113 minus\Figures\Take 2_
→ Analysis\FM317_103_Minus_RSM_hkl.pdf", bbox_inches = "tight", format = "pdf")

#counts = np.ma.masked_invalid(counts)
#print(l)
#print(h)


```

```
#print(counts)
#print('xi',xi)
#print('yi',yi)
#print('zi',zi)
#print('zi_array_one',zi_array_one)
#print(zi_min)
#print(np.nanmin(counts))
#print(np.nanmax(counts))
```

```
i 0
data C:\Users\pblah\Data\XRD\FM332\Exfoliated\RSM\hkl\Analysed\STO
103-\Take_2_STO_103-_hkl.txt
112200
max count value 978702.0958366791
max count value index (array([152], dtype=int64), array([152], dtype=int64))
z_max (array([152], dtype=int64), array([152], dtype=int64))
y_max index 152
y_max [3.00023645]
x_max index (array([152], dtype=int64), array([152], dtype=int64))
x_max [-1.00074221]
y_correction_minus -0.00023645484949819107
x_correction_minus -0.00074220735785957
CPU times: total: 2.09 s
Wall time: 2.11 s

<timed exec>:106: UserWarning: Log scale: values of z <= 0 have been masked
<timed exec>:106: UserWarning: linewidths is ignored by contourf
```

[103] – STO



```
[ ]: x = np.linspace(-1.09348, -0.911055 , ngridx)
      y = np.linspace(3.04362, 2.95828 , ngridy)
```

```
[ ]:
```

```
[19]: fig, ax = plt.subplots(figsize=(12, 12), dpi = 500)
      #ax2 = ax1.twinx()

      ax.tick_params(axis = 'x', which='major', labels=30, length = 10, width = 2,
        ↳ direction = 'in', pad = 10, top = True)
      ax.tick_params(axis = 'y', which='major', labels=30, length = 10, width = 2,
        ↳ direction = 'in', pad = 10, right = False)
      ax.tick_params(axis = 'y', which='major', labels=30, length = 10, width = 2,
        ↳ direction = 'in', pad = 10, right = False)

      ax.spines["top"].set_linewidth(2.5)
      ax.spines["bottom"].set_linewidth(2.5)
      ax.spines["right"].set_linewidth(2.5)
```



```

ax.spines["left"].set_linewidth(2.5)

ax.contourf(xi_NNO_plus,yi_NNO_plus,zi_NNO_plus, levels =_
    ↳ [5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm = matplotlib.colors.
    ↳ LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
ax.contourf(xi_STO_plus,yi_STO_plus,zi_STO_plus, levels =_
    ↳ [10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =_
    ↳ matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths_
    ↳ = 1, alpha = 1)
ax.contourf(xi_NNO_minus,yi_NNO_minus,zi_NNO_minus, levels =_
    ↳ [12,15,20,25,28,30,33,35,50,80,120,135],cmap = 'viridis',norm = matplotlib.
    ↳ colors.LogNorm(vmin = 12,vmax = 135),linewidths = 1, alpha = 1)
ax.contourf(xi_STO_minus,yi_STO_minus,zi_STO_minus, levels =_
    ↳ [20,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =_
    ↳ matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths_
    ↳ = 1, alpha = 1)
ax.vlines(0,2.92,3.05, lw = 3)
ax.hlines(3,-1,1, lw = 3)
ax.hlines(2.9536,x_max_index_NNO_minus-0.3,x_max_index_NNO_plus-0.052+0.3, color_
    ↳ = 'red',linestyle = 'dotted', lw = 3)

x_maxes_NNO = [x_max_index_NNO_minus,x_max_index_NNO_plus]
x_maxes_STO = [x_max_index_minus,x_max_index_minus]
y_maxes_NNO = [y_max_index_NNO_minus,y_max_index_NNO_plus]
y_maxes_STO = [y_max_index_minus,y_max_index_minus]

print(x_maxes_NNO,'x_maxes_NNO')
print(x_maxes_STO,'x_maxes_STO')
print(y_maxes_NNO,'y_maxes_NNO')
print(y_maxes_STO,'y_maxes_STO')

ax.plot(x_maxes_NNO,y_maxes_NNO, lw = 3)

a, b, = np.polynomial.polynomial.polyfit(x_maxes_NNO,y_maxes_NNO, 1)
print('a',a)
print('b',b)
fit = a + b*x_maxes_NNO[0] + b*x_maxes_NNO[1]
print('Polynomial Fit 1st Order', np.polynomial.polynomial.Polynomial([a,b]))

##### Left Triangle #####

```

```

left_edge_length = y_max_index_NNO_minus - a
bottom_edge_length = -x_max_index_NNO_minus - 0
hypo = np.sqrt(bottom_edge_length**2 + left_edge_length**2)

print('left_edge_length',left_edge_length)
print('bottom_edge_length',bottom_edge_length)

print('hypo',hypo)

ratios = left_edge_length/bottom_edge_length

print('ratios', ratios)

angle = np.arctan(ratios)*(180/np.pi) (Python trig functions use rads! Will_
    →keep it as rads as the rotation formula does)

print('angle',angle)

rotation_matrix_minus = [[np.cos(angle),-np.sin(angle)],[np.sin(angle),np.
    →cos(angle)]]

vector_minus = [[x_maxes_NNO[0]],[y_maxes_NNO[0]]]

print('rotation_matrix_minus',rotation_matrix_minus)
print('vector_minus',vector_minus)

#x_max_NNO_minus_rotated

#SRO_a_parameter_left = ((1+(1-hypo))*3.905)

#print('SRO_a_parameter_left',SRO_a_parameter_left)

#x_max_NNO_minus_rotated = np.cos(angle)*-hypo

vector_NNO_minus_rotated = np.matmul(rotation_matrix_minus,vector_minus)

print('vector_NNO_minus_rotated',vector_NNO_minus_rotated)

#SRO_a_parameter_left = ((1+(1+x_max_NNO_minus_rotated))*3.905)

#print('SRO_a_parameter_left',SRO_a_parameter_left)

##### Right Triangle #####

```

```

right_edge_length = y_max_index_NNO_plus - a
right_bottom_edge_length = x_max_index_NNO_plus - 0
hypo_right = np.sqrt(right_bottom_edge_length**2 + right_edge_length**2)

print('right_edge_length',left_edge_length)
print('right_bottom_edge_length',right_bottom_edge_length)

print('hypo_right',hypo_right)

ratios_right = left_edge_length/bottom_edge_length

print('ratios_right', ratios_right)

angle_right = np.tan(ratios_right)*(180/np.pi)

print('angle_right',angle_right)

#SRO_a_parameter_left = ((1+(1-hypo))*3.905)

#print('SRO_a_parameter_left',SRO_a_parameter_left)

rotation_matrix_plus = [[np.cos(angle),-np.sin(angle)],[np.sin(angle),np.
→cos(angle)]]

vector_plus = [[x_maxes_NNO[1]],[y_maxes_NNO[1]]]

print('rotation_matrix_plus',rotation_matrix_plus)
print('vector_plus',vector_plus)

vector_NNO_plus_rotated = np.matmul(rotation_matrix_plus,vector_plus)

#x_max_NNO_plus_rotated = np.cos(angle_right)*hypo_right

print('vector_NNO_plus_rotated',vector_NNO_plus_rotated)

#SRO_a_parameter_right = ((1+(1+x_max_NNO_plus_rotated))*3.905)

#print('SRO_a_parameter_right',SRO_a_parameter_right)

#SRO_a_lattice_parameter = (SRO_a_parameter_left + SRO_a_parameter_right)/2

#####

```

```

total_length = -vector_NNO_minus_rotated[0] + vector_NNO_plus_rotated[0]

#print('total_length',total_length)

#oo2_SRO_x_position = total_length/2

#print('oo2_SRO_x_position',oo2_SRO_x_position)

#correction = 1-oo2_SRO_x_position

#print('correction',correction)

#SRO_a_lattice_parameter_left = (1+(x_max_NNO_minus_rotated +
↳oo2_SRO_x_position - correction))*3.905

#print('SRO_a_lattice_parameter_left',SRO_a_lattice_parameter_left)

#SRO_a_lattice_parameter_right = (1+(x_max_NNO_plus_rotated - correction -
↳oo2_SRO_x_position - correction))*3.905

#print('SRO_a_lattice_parameter_right',SRO_a_lattice_parameter_right)

#SRO_a_lattice_parameter = (SRO_a_lattice_parameter_left +
↳SRO_a_lattice_parameter_right)/2

#print('SRO_a_lattice_parameter',SRO_a_lattice_parameter)

#####

test = (1+(2-total_length)/2) * 3.905

print('test',test)

test2 = ((3+(3-2.953))/3)*3.905

print('test2',test2)

text = ax.text(0.05,0.83, 'STO\n[103]-', size=30, color = 'black',transform = ax.
↳transAxes )
text = ax.text(0.08,0.22, 'SRO\n[103]-', size=30, color = 'black',transform = ax.
↳transAxes )

text = ax.text(0.75,0.85, ' STO\n[103]+', size=30, color = 'black',transform =
↳ax.transAxes )

```

```

text = ax.text(0.83,0.12, ' SRO\n[103]+', size=30, color = 'black',transform = ax.transAxes )

text = ax.text(0.26,0.405, r'$\theta$', size=30, color = 'black',transform = ax.transAxes )

text = ax.text(0.23,0.405, r'(', size=40, color = 'black',transform = ax.transAxes )

ax.set_ylabel(r'l (r.l.u)',fontsize=40,labelpad = 25)
ax.set_xlabel(r'h (r.l.u)',fontsize=40,labelpad = 25)

#plt.savefig(r"C:\Users\pblah\Data\XRD\FM332\Figures\Both_RSM_hkl.png",
↳bbox_inches = "tight")
#plt.savefig(r"C:\Users\pblah\Data\XRD\FM332\Figures\Both_RSM_hkl.pdf",
↳bbox_inches = "tight", format = "pdf")

```

```

[-0.9525853177257526, 1.0259274284548496] x_maxes_NNO
[-1.0014844147157191, -1.0014844147157191] x_maxes_STO
[2.9650307023411373, 2.942056794936455] y_maxes_NNO
[3.0, 3.0] y_maxes_STO
a 2.953969562135325
b -0.011611705534387786
Polynomial Fit 1st Order 2.95396956 - 0.01161171 x
left_edge_length 0.011061140205812503
bottom_edge_length 0.9525853177257526
hypo 0.9526495349126696
ratios 0.011611705534387612
angle 0.011611183701249419
rotation_matrix_minus [[0.9999325909638712, -0.011610922800509729],
[0.011610922800509729, 0.9999325909638712]]
vector_minus [[-0.9525853177257526], [2.9650307023411373]]
vector_NNO_minus_rotated [[-0.98694785]
[ 2.95377044]]
right_edge_length 0.011061140205812503
right_bottom_edge_length 1.0259274284548496
hypo_right 1.025996589896046
ratios_right 0.011611705534387612
angle_right 0.01161222743788862
rotation_matrix_plus [[0.9999325909638712, -0.011610922800509729],
[0.011610922800509729, 0.9999325909638712]]
vector_plus [[1.0259274284548496], [2.942056794936455]]
vector_NNO_plus_rotated [[0.99169828]
[2.95377044]]
test [3.94669344]
test2 3.966178333333333

```


C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\4135251183.py:17: UserWarning:
Log scale: values of z <= 0 have been masked

```

    ax.contourf(xi_NNO_plus,yi_NNO_plus,zi_NNO_plus, levels =
[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\4135251183.py:17: UserWarning:
linewidths is ignored by contourf
    ax.contourf(xi_NNO_plus,yi_NNO_plus,zi_NNO_plus, levels =
[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\4135251183.py:18: UserWarning:
Log scale: values of z <= 0 have been masked
    ax.contourf(xi_STO_plus,yi_STO_plus,zi_STO_plus, levels =
[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\4135251183.py:18: UserWarning:
linewidths is ignored by contourf
    ax.contourf(xi_STO_plus,yi_STO_plus,zi_STO_plus, levels =
[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\4135251183.py:19: UserWarning:
Log scale: values of z <= 0 have been masked
    ax.contourf(xi_NNO_minus,yi_NNO_minus,zi_NNO_minus, levels =
[12,15,20,25,28,30,33,35,50,80,120,135],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 12,vmax = 135),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\4135251183.py:19: UserWarning:
linewidths is ignored by contourf
    ax.contourf(xi_NNO_minus,yi_NNO_minus,zi_NNO_minus, levels =
[12,15,20,25,28,30,33,35,50,80,120,135],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 12,vmax = 135),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\4135251183.py:20: UserWarning:
Log scale: values of z <= 0 have been masked
    ax.contourf(xi_STO_minus,yi_STO_minus,zi_STO_minus, levels =
[20,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_14560\4135251183.py:20: UserWarning:
linewidths is ignored by contourf
    ax.contourf(xi_STO_minus,yi_STO_minus,zi_STO_minus, levels =
[20,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)

```

```
[19]: Text(0.5, 0, 'h (r.l.u)')
```



0.8.1 Breaking x axis

```
[181]: fig, (ax1,ax2) = plt.subplots(1,2,figsize=(12, 12), dpi = 500)
#ax2 = ax1.twinx()

ax1.tick_params(axis = 'x', which='major', labelsize=30, length = 10, width = 2,
↳direction = 'in', pad = 10, top = True)
ax1.tick_params(axis = 'y', which='major', labelsize=30, length = 10, width = 2,
↳direction = 'in', pad = 10, right = False)
ax1.tick_params(axis = 'y', which='major', labelsize=30, length = 10, width = 2,
↳direction = 'in', pad = 10, right = False)

ax1.spines["top"].set_linewidth(2.5)
ax1.spines["bottom"].set_linewidth(2.5)
ax1.spines["right"].set_linewidth(2.5)
```

```

ax1.spines["left"].set_linewidth(2.5)

ax2.tick_params(axis = 'x', which='major', labels=30, length = 10, width = 2,
    ↳direction = 'in', pad = 10, top = True)
ax2.tick_params(axis = 'y', which='major', labels=30, length = 10, width = 2,
    ↳direction = 'in', pad = 10, right = False)
ax2.tick_params(axis = 'y', which='major', labels=30, length = 10, width = 2,
    ↳direction = 'in', pad = 10, right = False)

ax2.spines["top"].set_linewidth(2.5)
ax2.spines["bottom"].set_linewidth(2.5)
ax2.spines["right"].set_linewidth(2.5)
ax2.spines["left"].set_linewidth(2.5)

ax1.contourf(xi_NNO_plus,yi_NNO_plus,zi_NNO_plus, levels =
    ↳[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm = matplotlib.colors.
    ↳LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
ax1.contourf(xi_STO_plus,yi_STO_plus,zi_STO_plus, levels =
    ↳[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
    ↳matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths
    ↳= 1, alpha = 1)
ax1.contourf(xi_NNO_minus,yi_NNO_minus,zi_NNO_minus, levels =
    ↳[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm = matplotlib.colors.
    ↳LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
ax1.contourf(xi_STO_minus,yi_STO_minus,zi_STO_minus, levels =
    ↳[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
    ↳matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths
    ↳= 1, alpha = 1)
ax1.vlines(0,2.92,3.05)
ax1.hlines(3,-1,1)
ax1.hlines(2.9536,x_max_index_NNO_minus-0.3,x_max_index_NNO_plus-0.052+0.3,
    ↳color = 'red',linestyle = 'dotted')

ax1.set_ylim(2.9, 3.05)
ax1.set_xlim(-1.1, -0.8)

ax2.contourf(xi_NNO_plus,yi_NNO_plus,zi_NNO_plus, levels =
    ↳[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm = matplotlib.colors.
    ↳LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)

```



```

ax2.contourf(xi_STO_plus,yi_STO_plus,zi_STO_plus, levels =_
↳[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =_
↳matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths_
↳= 1, alpha = 1)
ax2.contourf(xi_NNO_minus,yi_NNO_minus,zi_NNO_minus, levels =_
↳[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm = matplotlib.colors.
↳LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
ax2.contourf(xi_STO_minus,yi_STO_minus,zi_STO_minus, levels =_
↳[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =_
↳matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths_
↳= 1, alpha = 1)
ax2.vlines(0,2.92,3.05)
ax2.hlines(3,-1,1)
ax2.hlines(2.9536,x_max_index_NNO_minus-0.3,x_max_index_NNO_plus-0.052+0.3,_
↳color = 'red',linestyle = 'dotted')

ax2.set_ylim(2.9, 3.05)
ax2.set_xlim(0.95, 1.1)

ax1.spines['right'].set_visible(False)
ax2.spines['left'].set_visible(False)
#ax1.yaxis.tick_left()
ax1.tick_params(labelright='off')
#ax2.yaxis.tick_right()
ax2.tick_params(labelright='off')
ax2.tick_params(labelleft='off')

x_maxes_NNO = [x_max_index_NNO_minus,x_max_index_NNO_plus]
x_maxes_STO = [x_max_index_minus,x_max_index_minus]
y_maxes_NNO = [y_max_index_NNO_minus,y_max_index_NNO_plus]
y_maxes_STO = [y_max_index_minus,y_max_index_minus]

print(x_maxes_NNO,'x_maxes_NNO')
print(x_maxes_STO,'x_maxes_STO')
print(y_maxes_NNO,'y_maxes_NNO')
print(y_maxes_STO,'y_maxes_STO')

ax.plot(x_maxes_NNO,y_maxes_NNO)

a, b, = np.polynomial.polynomial.polyfit(x_maxes_NNO,y_maxes_NNO, 1)
print('a',a)

```

```

print('b',b)
fit = a + b*x_maxes_NNO[0] + b*x_maxes_NNO[1]
print('Polynomial Fit 1st Order', np.polynomial.polynomial.Polynomial([a,b]))

##### Left Triangle #####

left_edge_length = y_max_index_NNO_minus - a
bottom_edge_length = -x_max_index_NNO_minus - 0
hypo = np.sqrt(bottom_edge_length**2 + left_edge_length**2)

print('left_edge_length',left_edge_length)
print('bottom_edge_length',bottom_edge_length)

print('hypo',hypo)

ratios = left_edge_length/bottom_edge_length

print('ratios', ratios)

angle = np.tan(ratios)*(180/np.pi)

print('angle',angle)

#SRO_a_parameter_left = ((1+(1-hypo))*3.905)

#print('SRO_a_parameter_left',SRO_a_parameter_left)

x_max_NNO_minus_rotated = np.cos(angle)*-hypo

print('x_max_NNO_minus_rotated',x_max_NNO_minus_rotated)

#SRO_a_parameter_left = ((1+(1+x_max_NNO_minus_rotated))*3.905)

#print('SRO_a_parameter_left',SRO_a_parameter_left)

##### Right Triangle #####

right_edge_length = y_max_index_NNO_plus - a
right_bottom_edge_length = x_max_index_NNO_plus - 0
hypo_right = np.sqrt(right_bottom_edge_length**2 + right_edge_length**2)

print('right_edge_length',left_edge_length)
print('right_bottom_edge_length',right_bottom_edge_length)

print('hypo_right',hypo_right)

```

```

ratios_right = left_edge_length/bottom_edge_length

print('ratios_right', ratios_right)

angle_right = np.tan(ratios_right)*(180/np.pi)

print('angle_right',angle_right)

#SRO_a_parameter_left = ((1+(1-hypo))*3.905)

#print('SRO_a_parameter_left',SRO_a_parameter_left)

x_max_NNO_plus_rotated = np.cos(angle_right)*hypo_right

print('x_max_NNO_plus_rotated',x_max_NNO_plus_rotated)

#SRO_a_parameter_right = ((1+(1+x_max_NNO_plus_rotated))*3.905)

#print('SRO_a_parameter_right',SRO_a_parameter_right)

#SRO_a_lattice_parameter = (SRO_a_parameter_left + SRO_a_parameter_right)/2

#####

total_length = -x_max_NNO_minus_rotated + x_max_NNO_plus_rotated

print('total_length',total_length)

oo2_SRO_x_position = total_length/2

print(oo2_SRO_x_position)

correction = 1-oo2_SRO_x_position

print('correction',correction)

SRO_a_lattice_parameter_left = (1+(x_max_NNO_minus_rotated - correction +
↪oo2_SRO_x_position - correction))*3.905

print('SRO_a_lattice_parameter_left',SRO_a_lattice_parameter_left)

SRO_a_lattice_parameter_right = (1+(x_max_NNO_plus_rotated - correction -
↪oo2_SRO_x_position - correction))*3.905

```

```

print('SR0_a_lattice_parameter_right',SR0_a_lattice_parameter_right)

SR0_a_lattice_parameter = (SR0_a_lattice_parameter_left +
    ↪SR0_a_lattice_parameter_right)/2

print('SR0_a_lattice_parameter',SR0_a_lattice_parameter)

#####

test = (1+(2-total_length)) * 3.905

print(test)

test2 = ((3+(3-2.953))/3)*3.905

print(test2)

```

```

C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:26: UserWarning:
Log scale: values of z <= 0 have been masked
  ax1.contourf(xi_NNO_plus,yi_NNO_plus,zi_NNO_plus, levels =
[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:26: UserWarning:
linewidths is ignored by contourf

```

```

ax1.contourf(xi_NNO_plus,yi_NNO_plus,zi_NNO_plus, levels =
[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:27: UserWarning:
Log scale: values of z <= 0 have been masked
ax1.contourf(xi_STO_plus,yi_STO_plus,zi_STO_plus, levels =
[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:27: UserWarning:
linewidths is ignored by contourf
ax1.contourf(xi_STO_plus,yi_STO_plus,zi_STO_plus, levels =
[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:28: UserWarning:
Log scale: values of z <= 0 have been masked
ax1.contourf(xi_NNO_minus,yi_NNO_minus,zi_NNO_minus, levels =
[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:28: UserWarning:
linewidths is ignored by contourf
ax1.contourf(xi_NNO_minus,yi_NNO_minus,zi_NNO_minus, levels =
[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:29: UserWarning:
Log scale: values of z <= 0 have been masked
ax1.contourf(xi_STO_minus,yi_STO_minus,zi_STO_minus, levels =
[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:29: UserWarning:
linewidths is ignored by contourf
ax1.contourf(xi_STO_minus,yi_STO_minus,zi_STO_minus, levels =
[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:39: UserWarning:
Log scale: values of z <= 0 have been masked
ax2.contourf(xi_NNO_plus,yi_NNO_plus,zi_NNO_plus, levels =
[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:39: UserWarning:
linewidths is ignored by contourf
ax2.contourf(xi_NNO_plus,yi_NNO_plus,zi_NNO_plus, levels =
[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:40: UserWarning:

```

```

Log scale: values of z <= 0 have been masked
    ax2.contourf(xi_STO_plus,yi_STO_plus,zi_STO_plus, levels =
[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:40: UserWarning:
linewidths is ignored by contourf
    ax2.contourf(xi_STO_plus,yi_STO_plus,zi_STO_plus, levels =
[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:41: UserWarning:
Log scale: values of z <= 0 have been masked
    ax2.contourf(xi_NNO_minus,yi_NNO_minus,zi_NNO_minus, levels =
[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:41: UserWarning:
linewidths is ignored by contourf
    ax2.contourf(xi_NNO_minus,yi_NNO_minus,zi_NNO_minus, levels =
[5,10,15,20,25,28,30,33,35],cmap = 'viridis',norm =
matplotlib.colors.LogNorm(vmin = 5,vmax = 35),linewidths = 1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:42: UserWarning:
Log scale: values of z <= 0 have been masked
    ax2.contourf(xi_STO_minus,yi_STO_minus,zi_STO_minus, levels =
[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)
C:\Users\pblah\AppData\Local\Temp\ipykernel_4448\3960664250.py:42: UserWarning:
linewidths is ignored by contourf
    ax2.contourf(xi_STO_minus,yi_STO_minus,zi_STO_minus, levels =
[10,50,100,500,1000,5000,10000,12000,13200,14000,14200,14400],norm =
matplotlib.colors.LogNorm(vmin = 5, vmax = 14400),cmap = 'viridis',linewidths =
1, alpha = 1)


[-0.9525853177257526, 1.0259274284548496] x_maxes_NNO
[-1.0014844147157191, -1.0014844147157191] x_maxes_STO
[2.9650307023411373, 2.942056794936455] y_maxes_NNO
[3.0, 3.0] y_maxes_STO
a 2.953969562135325
b -0.011611705534387786
Polynomial Fit 1st Order 2.95396956 - 0.01161171 x
left_edge_length 0.011061140205812503
bottom_edge_length 0.9525853177257526
hypo 0.9526495349126696
ratios 0.011611705534387612
angle 0.01161222743788862
x_max_NNO_minus_rotated -0.9525853061803163
right_edge_length 0.011061140205812503

```

```

right_bottom_edge_length 1.0259274284548496
hypo_right 1.025996589896046
ratios_right 0.011611705534387612
angle_right 0.01161222743788862
x_max_NN0_plus_rotated 1.0259274160204992
total_length 1.9785127222008154
0.9892563611004077
correction 0.01074363889959229
SR0_a_lattice_parameter_left 3.9642926496571405
SR0_a_lattice_parameter_right 3.9642926496571413
SR0_a_lattice_parameter 3.964292649657141
3.9889078198058154
3.966178333333333

```



```
[1]: !export PATH=/Library/TeX/texbin:$PATH
```

'export' is not recognized as an internal or external command,
operable program or batch file.

[]: