

GM Chevrolet Silverado 2024 Service Manual

Model Year: 2024 | Make: GM | Model: Silverado 1500

Table of Contents

1. Engine - 6.2L V8 EcoTec3
2. Trailering & Towing
3. Safety Systems

Engine - 6.2L V8 EcoTec3

The 6.2L EcoTec3 V8 uses Dynamic Fuel Management (DFM) to deactivate up to 7 cylinders under light load. A slight vibration or drone at 1,400-1,800 RPM is normal DFM operation.

Oil: Dexos1 Gen3 full synthetic 0W-20. Oil life monitor tracks engine load, temperature, and idle time.

Code P0521 (Oil Pressure Sensor Performance) - verify oil level before condemning the sensor.

Trailer & Towing

Maximum tow rating: 13,300 lbs (with Duramax diesel and Max Trailering Package).

Trailer Sway Control automatically applies individual wheel brakes if trailer oscillation is detected.

Integrated Trailer Brake Controller supports electric trailer brakes up to 4 axles.

Fault P0878 (Transmission Fluid Pressure Sensor B Circuit High) may appear when towing near max capacity

in high ambient temperatures - allow transmission to cool before resuming.

Safety Systems

Super Cruise hands-free driver assistance works on 200,000+ miles of compatible divided highways.

The driver attention camera monitors eye gaze and head position. Green light = hands-free mode active.

Forward Collision Alert and Automatic Emergency Braking are standard on all 2024 Silverado trims.

Calibration is required if the front bumper, grille, or windshield is replaced.