# Rajalakshmi Engineering College

Name: Padma Priya D

Email: 240701377@rajalakshmi.edu.in

Roll no: 240701377 Phone: 8668123104

Branch: REC

Department: I CSE FD

Batch: 2028

Degree: B.E - CSE



## NeoColab\_REC\_CS23221\_Python Programming

REC\_Python\_Week 1\_CY

Attempt : 1 Total Mark : 40 Marks Obtained : 40

Section 1: Coding

#### 1. Problem Statement

Liam and his friends are sharing the cost of a group purchase. The total cost of the purchase is subject to a 10% discount. One of the friends receives a 35% bonus, which means they will pay a larger portion of the discounted cost. The remaining cost is then divided equally among the other friends.

## Write a program to:

Calculate the total cost after applying a 10% discount. Determine the amount paid by the friend who receives a 35% bonus. Calculate the amount each of the other friends will pay.

## **Input Format**

The first line of input consists of a float value f, representing the total cost.

The second line contains an integer value n, representing the total number of friends.

### **Output Format**

The first line of output displays "Cost after a 10% discount: " followed by the discounted cost of the ticket package as a float value formatted to two decimal places.

The second line displays "Friend with a 35% bonus pays: " followed by the amount paid by the friend with the bonus as a float value formatted to two decimal places.

The third line displays "Each of the other friends pays: " followed by the individual share of the remaining cost as a float value formatted to two decimal places.

Refer to the sample output for the formatting specifications.

#### Sample Test Case

Input: 10000.0

5

Output: Cost after a 10% discount: 9000.00 Friend with a 35% bonus pays: 3150.00 Each of the other friends pays: 1462.50

#### Answer

# You are using Python
f=float(input())
n=int(input())
discounted\_cost=f\*0.9
bonus=discounted\_cost\*0.35
remaining=discounted\_cost-bonus
share=remaining/(n-1)
print("Cost after a 10% discount:","{:.2f}".format(discounted\_cost))
print("Friend with a 35% bonus pays:","{:.2f}".format(bonus))
print("Each of the other friends pays:","{:.2f}".format(share))

Status: Correct Marks: 10/10

## 2. Problem Statement

John is developing a financial application to help users manage their investment portfolios. As part of the application, he needs to write a program that receives the portfolio's main value and the values of two specific investments as inputs. The program should then display these values in reverse order for clear visualization.

Help John achieve this functionality by writing the required program.

#### **Input Format**

The first line of input consists of a float, representing the first investment value.

The second line of input consists of a float, representing the second investment value.

The third line of input consists of an integer, representing the portfolio ID.

#### **Output Format**

The first line of output prints "The values in the reverse order:".

The second line prints the integer, representing the portfolio ID.

The third line prints the second float, representing the second investment value.

The fourth line prints the first float, representing the first investment value.

Refer to the sample output for the formatting specifications.

### Sample Test Case

Input: 35.29 9374.11 48

Output: The values in the reverse order:

48 9374.11 35.29

#### Answer

```
# You are using Python
a=float(input())
b=float(input())
c=int(input())
temp=c
c=b
b=a
print("The values in the reverse order:")
print(temp)
print(c)
print(b)
```

Status: Correct Marks: 10/10

#### 3. Problem Statement

Nina is working on a project involving multiple sensors. Each sensor provides a data point that needs to be processed to compute an aggregated value.

Given data points from three sensors, write a program to calculate the aggregated value using specific bitwise operations and arithmetic manipulations. The final result should be the aggregated value modulo 1000.

Example:

Input:

1 //sensor 1 data

2 //sensor 2 data

3 //sensor 3 data

Output

q

Explanation

240701311

2,010131

Calculate the bitwise AND of sensor 1 data and sensor 2 data: 0

Calculate the XOR of the result from step 1 and sensor 3 data: 3

Multiply the result from step 2 by 3: 9

Compute the final aggregated value by taking the result from step 3 modulo 1000: 9

So, the aggregated value is 9.

#### **Input Format**

The first line of input consists of an integer S1, representing sensor1 data.

The second line of input consists of an integer S2, representing sensor2 data.

The third line of input consists of an integer S3, representing sensor3 data.

### **Output Format**

The output displays an integer representing the aggregated value.

Refer to the sample output for the formatting specifications.

### Sample Test Case

```
Input: 1
```

Output: 9

#### Answer

```
# You are using Python
S1=int(input())
S2=int(input())
S3=int(input())
a=S1&S2
b=a^S3
c=b*3
agg=c%1000
print(agg)
```

V.

0,40101311

Status: Correct Marks: 10/10

#### 4. Problem Statement

Emily is organizing a taco party and needs to determine the total number of tacos required and the total cost. Each attendee at the party will consume 2 tacos. To ensure there are enough tacos:

If there are 10 or more attendees, Emily will need to provide an additional 5 tacos. If there are fewer than 10 attendees, Emily must ensure a minimum of 20 tacos are provided.

The cost of each taco is \$25. Write a program that calculates both the total number of tacos required and the total cost based on the number of attendees.

#### **Input Format**

The input consists of an integer n, representing the number of attendees.

#### **Output Format**

The first line prints "Number of tacos needed: " followed by an integer representing the number of tacos needed for n attendees.

The second line prints "Total cost: " followed by an integer representing the total cost

Refer to the sample output for the formatting specifications.

### Sample Test Case

Input: 10

Output: Number of tacos needed: 25

Total cost: 625

#### Answer

# You are using Python
n=int(input())
if(n>=10):

240701377 240701377 print("Number of tacos needed:",tacos)
print("Total cost:",tacos\*25)
else: else: tacos=20 print("Number of tacos needed:",tacos) print("Total cost:",tacos\*25) Marks: 10/10 Status: Correct 240701377 240701377 240701377

240701317

240701377

240701377

240701377