

# SPORTY SHOES E-COMMERCE WEBSITE

## SOURCE CODE:

```
CommonController.java
package com.springapps.Controller;

import java.io.PrintWriter;
import java.sql.Date;
import java.util.List;
import com.springapps.entity.Cart;
import com.springapps.entity.Order;
import com.springapps.entity.Products;
import com.springapps.entity.Users;
import com.springapps.service.CartService;
import com.springapps.service.OrderService;
import com.springapps.service.ProductsService;
import com.springapps.service.UserService;
import com.springapps.entity.Users;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Controller;
import org.springframework.ui.ModelMap;
import org.springframework.validation.BindingResult;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RequestMethod;
import org.springframework.web.bind.annotation.RequestParam;

@Controller
@RequestMapping("/account")
public class CommonController {

    @Autowired
    ProductsService productsService;

    @Autowired
    UserService userService;

    @Autowired
    CartService cartService;

    @Autowired
    OrderService orderService;
```

```

@RequestMapping("/productsboy")
public String showproductsboy(ModelMap model)
{
    List<Products> products=productsService.getProducts();
    model.addAttribute("products",products);
    return "productsboy";
}

@RequestMapping("/productsgirl")
public String showproductsgirl(ModelMap model) {
    List<Products> productsg=productsService.getProducts();
    model.addAttribute("productsg",productsg);
    return "productsgirl";
}

@RequestMapping(value="/login",method = RequestMethod.GET)
public String login(ModelMap mm)
{
    mm.put("user",new Users());
    return "login";
}

@RequestMapping(value="/login",method = RequestMethod.POST)
public String login(@ModelAttribute(value="user") Users user,ModelMap mm)
{
    if(user.getUsername().equals("tek")&& user.getPassword().equals("123"))
        return "home";
    else if(user.getUsername().equals("admin")&&
user.getPassword().equals("admin"))
        return "adminhome";
    else
    {
        PrintWriter out = new PrintWriter(System.out);
        mm.put("message","Login Failed,Invalid Credentials");
        out.println("InValid Credentials");
        return "login";
    }
}

@RequestMapping("/home")
public String home()
{
    return "home";
}

@RequestMapping("/homes")
public String homes()
{

```

```

        return "home";
    }
    @RequestMapping("/products")
    public String products(ModelMap model)
    {
        List<Products> products=productsService.getProducts();
        model.addAttribute("products",products);
        return "products";
    }
    @RequestMapping("/orders")
    public String orders(ModelMap model)
    {
        List<Order> order=orderService.getOrder();
        model.addAttribute("order",order);
        return "orders";
    }
    @RequestMapping("/cart")
    public String showcart(ModelMap model)
    {
        List<Cart> cart=cartService.getCart();
        model.addAttribute("cart",cart);
        return "cart";
    }
    @RequestMapping(value="/addtocart",method=RequestMethod.POST)
    public String cart(@ModelAttribute("cart")Cart cart,ModelMap model)
    {
        int result=cartService.save(cart);
        List<Cart> cartitems=cartService.getCart();
        model.addAttribute("cart", cartitems);
        return "cart";
    }
    @RequestMapping("/buy")
    public String userdetails(ModelMap model)
    {
        List<Cart> cart=cartService.getCart();
        model.addAttribute("cart", cart);
        return "userdetails";
    }
    @RequestMapping(value="/ordersuccess",method=RequestMethod.POST)
    public String cart(@ModelAttribute("order")Order order,ModelMap model)
    {
        List<Cart> cart=cartService.getCart();
        Cart cartitem=new Cart();

```

```

        for(Cart item:cart)
        {
            order.setPrice(item.getMrp());
            order.setPcode(item.getId());
            order.setCategory(item.getCategory());
            order.setBrand(item.getBrand());
            order.setImage(item.getImage());
            orderService.save(order);
            cartitem.setId(item.getId());
            cartService.delete(cartitem);
        }
        model.addAttribute("orders", order);
        return "orders";
    }
    @RequestMapping("/logout")
    public String login()
    {
        return "login";
    }
    @RequestMapping("/adminhomes")
    public String adminhomes()
    {
        return "adminhome";
    }
    @RequestMapping("/change_password")
    public String change()
    {
        return "change_password";
    }
    @RequestMapping(value="/change_password",method=RequestMethod.POST)
    public String changed(@ModelAttribute("user") Users user, ModelMap
model,BindingResult res)
    {
        user.setId(1);
        usersService.update(user);
        model.addAttribute("res","Password changed successfully");
        return "change_password";
    }
    @RequestMapping("/manage_products")
    public String manage()
    {
        return "manage_products";
    }

```

```

@RequestMapping("/addproduct")
public String add()
{
    return "addproduct";
}

@RequestMapping(value="/add_product", method=RequestMethod.POST)
public String addProduct(@ModelAttribute("product") Products product, ModelMap
model, BindingResult res) {
    int result = productsService.save(product);
    String message = "Product added successfully";
    model.addAttribute("result", message);
    return "addproduct";
}

@RequestMapping("/deleteproduct")
public String delete()
{
    return "deleteproduct";
}

@RequestMapping(value="/delete_product", method=RequestMethod.POST)
public String deleteProduct(@ModelAttribute("product") Products product, ModelMap
model, BindingResult res) {
    productsService.delete(product);
    String message = "Product deleted successfully";
    model.addAttribute("result", message);
    return "deleteproduct";
}

@RequestMapping("/users_list")
public String userslist(ModelMap model)
{
    List<Users> users=usersService.getUsers();
    model.addAttribute("users",users);
    return "users_list";
}

@RequestMapping("/add_user")
public String adduser()
{
    return "add_user";
}

@RequestMapping(value="/registeruser", method=RequestMethod.POST)
public String registerUser(@ModelAttribute("user") Users user, ModelMap
model, BindingResult res) {
    int result = usersService.save(user);
    String message = "User added successfully";

```

```

        model.addAttribute("result", message);
        return "add_user";
    }
    @RequestMapping("/search_user")
    public String searchuser()
    {
        return "search_user";
    }
    @RequestMapping(value="/search_user",method=RequestMethod.POST)
    public String searchuser(@ModelAttribute("user") Users user,ModelMap
model,BindingResult result)
    {
        Users users=userService.getUser(user.getId());
        model.addAttribute("result","User Found");
        model.addAttribute("users",users);
        return "search_result";
    }
    @RequestMapping("/purchase_reports")
    public String reports()
    {
        return "purchase_reports";
    }
    @RequestMapping(value="/filter",method=RequestMethod.GET)
    public String filterbydate(@RequestParam Date date,@RequestParam String
category,@ModelAttribute("order") Order order,ModelMap model)
    {
        Order o=new Order();
        o.setDate(date);
        o.setCategory(category);
        model.addAttribute("date", date);
        model.addAttribute("category", category);
        List<Order> orders=orderService.getOrder();
        model.addAttribute("result","User Found");
        model.addAttribute("orders",orders);
        return "purchase_result";
    }
    @RequestMapping("/adminhome")
    public String adminhome()
    {
        return "adminhome";
    }
    @RequestMapping("/adminproducts")
    public String adminproducts(ModelMap model)

```

```

    {
        List<Products> products=productsService.getProducts();
        model.addAttribute("products",products);
        return "adminproducts";
    }
    @RequestMapping("/adminproductsboy")
    public String adminproductsboy(ModelMap model)
    {
        List<Products> products=productsService.getProducts();
        model.addAttribute("products_boy",products);
        return "adminproductsboy";
    }
    @RequestMapping("/adminproductsgirl")
    public String adminproductsgirl(ModelMap model)
    {
        List<Products> products=productsService.getProducts();
        model.addAttribute("products_girl",products);
        return "adminproductsgirl";
    }
    @RequestMapping(value="/view_products",method=RequestMethod.POST)
    public String viewproducts(@ModelAttribute("Products") Products products,ModelMap
model,BindingResult result)
    {
        Products products1=productsService.getProduct(products.getId());
        model.addAttribute("products",products1);
        return "view_products";
    }
    @RequestMapping("/adminorders")
    public String adminorders(ModelMap model)
    {
        List<Order> order=orderService.getOrder();
        model.addAttribute("order",order);
        return "adminorders";
    }
    @RequestMapping("/admincart")
    public String admmincart(ModelMap model)
    {
        List<Cart> cart=cartService.getCart();
        model.addAttribute("cart",cart);
        return "admincart";
    }
}

```

CartDao.java

```
package com.springapps.dao;
```

```
import java.util.List;
```

```
import com.springapps.entity.Cart;
```

```
public interface CartDao {  
    int create(Cart cart);  
    List<Cart> findCart();  
    Cart getCart(int id);  
    void delete(Cart cartitem);  
}
```

OrderDao.java

```
package com.springapps.dao;
```

```
import java.util.List;
```

```
import com.springapps.entity.Order;
```

```
public interface OrderDao {  
    int create(Order order);  
    List<Order> findOrder();  
    Order getOrder(int id);  
    void delete(Order order);  
}
```

ProductsDao.java

```
package com.springapps.dao;
```

```
import java.util.List;
```

```
import com.springapps.entity.Cart;  
import com.springapps.entity.Products;  
import com.springapps.entity.Users;
```

```
public interface ProductsDao {  
    int create(Products pd);  
    List<Products> findProducts();  
    Products getProduct(int id);  
}
```



```
        void delete(Products product);
    }
```

UsersDao.java

```
package com.springapps.dao;
```

```
import java.util.List;
```

```
import com.springapps.entity.Users;
```

```
public interface UsersDao {
    int create(Users users);
    void delete(int id);
    List<Users> findUsers();
    Users getUser(int id);
    void update(Users users);
}
```

CartDaoImpl.java

```
package com.springapps.dao.impl;
```

```
import java.util.List;
```

```
import com.springapps.dao.CartDao;
```

```
import com.springapps.entity.Cart;
```

```
import org.springframework.beans.factory.annotation.Autowired;
```

```
import org.springframework.orm.hibernate5.HibernateTemplate;
```

```
import org.springframework.stereotype.Repository;
```

```
@Repository
```

```
public class CartDaoImpl implements CartDao{
```

```
    @Autowired
```

```
    private HibernateTemplate hibernateTemplate;
```

```
    @Override
```

```
    public int create(Cart cart) {
        return (int) hibernateTemplate.save(cart);
    }
```

```
    @Override
```

```
    public List<Cart> findCart() {
        return hibernateTemplate.loadAll(Cart.class);
    }
```

```

@Override
public Cart getCart(int id) {
    return (Cart) hibernateTemplate.get(Cart.class,id);
}
@Override
public void delete(Cart cartitem) {

    hibernateTemplate.delete(cartitem);

}
}

```

OrderDao.java

```
package com.springapps.dao.impl;
```

```
import java.util.List;
```

```
import com.springapps.dao.OrderDao;
```

```
import com.springapps.entity.Cart;
```

```
import com.springapps.entity.Order;
```

```
import org.springframework.beans.factory.annotation.Autowired;
```

```
import org.springframework.orm.hibernate5.HibernateTemplate;
```

```
import org.springframework.stereotype.Repository;
```

```
@Repository
```

```
public class OrderDaoImpl implements OrderDao{
```

```
    @Autowired
```

```
    private HibernateTemplate hibernateTemplate;
```

```
    @Override
```

```
    public int create(Order order) {
```

```
        return (int) hibernateTemplate.save(order);
```

```
    }
```

```
    @Override
```

```
    public List<Order> findOrder() {
```

```
        return hibernateTemplate.loadAll(Order.class);
```

```
    }
```

```
    @Override
```

```
    public Order getOrder(int id) {
```

```
        return (Order) hibernateTemplate.get(Order.class,id);
```

```

    }

    @Override
    public void delete(Order order) {
        hibernateTemplate.delete(order);
    }
}

```

## ProductsDaoImpl.java

```

package com.springapps.dao.impl;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.orm.hibernate5.HibernateTemplate;
import org.springframework.stereotype.Repository;

import java.util.List;

import com.springapps.dao.ProductsDao;
import com.springapps.entity.Products;
import com.springapps.entity.Users;

@Repository
public class ProductsDaoImpl implements ProductsDao {

    @Autowired
    private HibernateTemplate hibernateTemplate;

    @Override
    public int create(Products pb) {
        return (int) hibernateTemplate.save(pb);
    }

    @Override
    public List<Products> findProducts() {
        return hibernateTemplate.loadAll(Products.class);
    }

    @Override
    public Products getProduct(int id) {
        return (Products) hibernateTemplate.get(Products.class, id);
    }

    @Override
    public void delete(Products product) {

```

```

        hibernateTemplate.delete(product);
    }
}

```

UsersDaoImpl.java

```
package com.springapps.dao.impl;
```

```
import java.util.List;
```

```
import com.springapps.dao.ProductsDao;
import com.springapps.dao.UsersDao;
import com.springapps.entity.Products;
import com.springapps.entity.Users;
```

```
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.orm.hibernate5.HibernateTemplate;
import org.springframework.stereotype.Repository;
```

```
@Repository
```

```
public class UsersDaoImpl implements UsersDao {
```

```
    @Autowired
```

```
    private HibernateTemplate hibernateTemplate;
```

```
    @Override
```

```
    public int create(Users users) {
        return (int) hibernateTemplate.save(users);
    }

```

```
    @Override
```

```
    public List<Users> findUsers() {
        return hibernateTemplate.loadAll(Users.class);
    }

```

```
    @Override
```

```
    public void delete(int id) {
        hibernateTemplate.delete(id);
    }

```

```
    @Override
```

```
    public Users getUser(int id) {
        return (Users) hibernateTemplate.get(Users.class,id);
    }

```

```
    @Override
```

```
    public void update(Users users) {
```

```
        hibernateTemplate.update(users);
    }

}
```

Cart.java

```
package com.springapps.entity;

import javax.persistence.Entity;
import javax.persistence.Id;
import javax.persistence.Table;

@Entity
@Table(name="cart")
public class Cart {
    @Id
    private int Id;
    private String Brand;
    private int Mrp;
    private String Category;
    private String Description;
    private String Image;
    public int getId() {
        return Id;
    }
    public void setId(int id) {
        Id = id;
    }
    public String getBrand() {
        return Brand;
    }
    public void setBrand(String brand) {
        Brand = brand;
    }
    public int getMrp() {
        return Mrp;
    }
    public void setMrp(int mrp) {
        Mrp = mrp;
    }
    public String getDescription() {
        return Description;
    }
}
```

```

    }
    public void setDescription(String description) {
        Description = description;
    }
    public String getImage() {
        return Image;
    }
    public void setImage(String image) {
        Image = image;
    }

    public String getCategory() {
        return Category;
    }
    public void setCategory(String category) {
        Category = category;
    }
    @Override
    public String toString() {
        return "Cart [Id=" + Id + ", Brand=" + Brand + ", Mrp=" + Mrp + ", Category=" +
Category + ", Description="
        + Description + ", Image=" + Image + "]";
    }
}

```

Order.java

```
package com.springapps.entity;
```

```
import java.sql.Date;
```

```
import javax.persistence.Entity;
```

```
import javax.persistence.Id;
```

```
import javax.persistence.Table;
```

```
@Entity
```

```
@Table(name="orders")
```

```
public class Order {
```

```
    @Id
```

```
    private int orderid;
```

```
    private int pcode;
```

```
    private String username;
```

```
    private String email;
```

```
private String mobile;
private int price;
private String location;
private Date date;
private String category;
private String brand;
private String image;
public int getOrderid() {
    return orderid;
}
public void setOrderid(int orderid) {
    this.orderid = orderid;
}
public int getPcode() {
    return pcode;
}
public void setPcode(int pcode) {
    this.pcode = pcode;
}
public String getUsername() {
    return username;
}
public void setUsername(String username) {
    this.username = username;
}
public String getEmail() {
    return email;
}
public void setEmail(String email) {
    this.email = email;
}
public String getMobile() {
    return mobile;
}
public void setMobile(String mobile) {
    this.mobile = mobile;
}
public int getPrice() {
    return price;
}
public void setPrice(int price) {
    this.price = price;
}
```

```

    public String getLocation() {
        return location;
    }
    public void setLocation(String location) {
        this.location = location;
    }

    public Date getDate() {
        return date;
    }
    public void setDate(Date date) {
        this.date = date;
    }
    public String getCategory() {
        return category;
    }
    public void setCategory(String category) {
        this.category = category;
    }
    public String getBrand() {
        return brand;
    }
    public void setBrand(String brand) {
        this.brand = brand;
    }
    public String getImage() {
        return image;
    }
    public void setImage(String image) {
        this.image = image;
    }
}

```

Products.java

```

package com.springapps.entity;

import javax.persistence.Entity;
import javax.persistence.Table;
import javax.persistence.Id;

```

```

@Entity
@Table(name="products")

```



```

public class Products {
    @Id
    private int Id;
    private String Brand;
    private int Mrp;
    private String Category;
    private String Description;
    private String Image;
    public int getId() {
        return Id;
    }
    public void setId(int id) {
        Id = id;
    }
    public String getBrand() {
        return Brand;
    }
    public void setBrand(String brand) {
        Brand = brand;
    }
    public int getMrp() {
        return Mrp;
    }
    public void setMrp(int mrp) {
        Mrp = mrp;
    }
    public String getDescription() {
        return Description;
    }
    public void setDescription(String description) {
        Description = description;
    }
    public String getImage() {
        return Image;
    }
    public void setImage(String image) {
        Image = image;
    }
    public String getCategory() {
        return Category;
    }
    public void setCategory(String category) {

```

```

        Category = category;
    }
    @Override
    public String toString() {
        return "Products [Id=" + Id + ", Brand=" + Brand + ", Mrp=" + Mrp + ",
Category=" + Category + ", Description="
        + Description + ", Image=" + Image + "]";
    }
}

```

Users.java

```

package com.springapps.entity;
import javax.persistence.Entity;
import javax.persistence.Id;
import javax.persistence.Table;

@Entity
@Table(name="Users")
public class Users {
    @Id
    private int Id;
    private String username;
    private String password;
    public int getId() {
        return Id;
    }
    public void setId(int id) {
        Id = id;
    }
    public String getUsername() {
        return username;
    }
    public void setUsername(String username) {
        this.username = username;
    }
    public String getPassword() {
        return password;
    }
    public void setPassword(String password) {
        this.password = password;
    }
}

```

CartService.java

```
package com.springapps.service;

import java.util.List;

import com.springapps.entity.Cart;

public interface CartService {
    int save(Cart cart);

    List<Cart> getCart();
    Cart getCart(int id);

    void delete(Cart cartitem);
}
```

OrderService.java

```
package com.springapps.service;

import java.util.List;
import com.springapps.entity.Order;

public interface OrderService {
    int save(Order order);

    List<Order> getOrder();
    Order getOrder(int id);

    void delete(Order order);
}
```

ProductsService.java

```
package com.springapps.service;

import java.util.List;

import com.springapps.entity.Cart;
import com.springapps.entity.Products;
import com.springapps.entity.Users;
```

```

public interface ProductService {

    int save(Products pb);

    List<Products> getProducts();
    Products getProduct(int id);
    void delete(Products product);
}

```

UserService.java

```

package com.springapps.service;

import java.util.List;
import com.springapps.entity.Users;

public interface UserService {
    int save(Users users);
    void delete(int id);
    List<Users> getUsers();
    Users getUser(int id);
    void update(Users user);
}

```

CartServiceImpl.java

```

package com.springapps.service.impl;

import java.util.List;

import com.springapps.dao.CartDao;
import com.springapps.dao.ProductsDao;
import com.springapps.entity.Cart;
import com.springapps.service.CartService;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;
import org.springframework.transaction.annotation.Transactional;

@Service
public class CartServiceImpl implements CartService{
    @Autowired
    private CartDao cartDao;
}

```

```

@Override
@Transactional
public int save(Cart cart) {
    return cartDao.create(cart);
}
@Override
public List<Cart> getCart() {
    List<Cart> cart = cartDao.findCart();
    return cart;
}
@Override
@Transactional
public Cart getCart(int id) {
    return cartDao.getCart(id);
}
@Override
@Transactional
public void delete(Cart cartitem) {
    cartDao.delete(cartitem);
}
}

```

OrderServiceImpl.java

```

package com.springapps.service.impl;

import java.util.List;
import com.springapps.dao.OrderDao;
import com.springapps.entity.Order;
import com.springapps.service.OrderService;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;
import org.springframework.transaction.annotation.Transactional;

```

```

@Service
public class OrderServiceImpl implements OrderService{

    @Autowired
    private OrderDao orderDao;

    @Override
    @Transactional

```

```

    public int save(Order order) {
        return orderDao.create(order);
    }

    @Override
    public List<Order> getOrder() {
        List<Order> order = orderDao.findOrder();
        return order;
    }

    @Override
    @Transactional
    public Order getOrder(int id) {
        return orderDao.getOrder(id);
    }

    @Override
    @Transactional
    public void delete(Order order) {
        orderDao.delete(order);
    }
}

```

ProductsServiceImpl.java

```

package com.springapps.service.impl;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;
import org.springframework.transaction.annotation.Transactional;

import java.util.List;

import com.springapps.dao.ProductsDao;
import com.springapps.entity.Cart;
import com.springapps.entity.Products;
import com.springapps.entity.Users;
import com.springapps.service.ProductsService;

@Service
public class ProductsServiceImpl implements ProductsService{

```

```

    @Autowired
    private ProductsDao productsDao;

    @Override
    @Transactional
    public int save(Products pb) {
        return productsDao.create(pb);
    }
    @Override
    public List<Products> getProducts() {
        List<Products> pb = productsDao.findProducts();
        return pb;
    }
    @Override
    @Transactional
    public Products getProduct(int id) {
        return productsDao.getProduct(id);
    }
    @Override
    @Transactional
    public void delete(Products product) {
        productsDao.delete(product);
    }
}

```

UserServiceImpl.java

```

package com.springapps.service.impl;

import java.util.List;

import com.springapps.dao.UsersDao;
import com.springapps.entity.Users;
import com.springapps.service.UserService;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;
import org.springframework.transaction.annotation.Transactional;

@Service
public class UserServiceImpl implements UserService{
    @Autowired
    private UsersDao usersDao;

```

```

@Override
@Transactional
public int save(Users users) {
    return usersDao.create(users);
}

@Override
public List<Users> getUsers() {
    List<Users> users = usersDao.findUsers();
    return users;
}

@Override
@Transactional
public void delete(int id) {
    usersDao.delete(id);
}

@Override
@Transactional
public Users getUser(int id) {
    return usersDao.getUser(id);
}

@Override
@Transactional
public void update(Users users) {
    usersDao.update(users);
}
}

```

redirect.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<% response.sendRedirect("account/login"); %>

```

Login.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>

```



```

<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>
<%@ taglib prefix="spring" uri="http://www.springframework.org/tags/form" %>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Sign In</title>
<style>
    button {
        justify-content: center;
        background-color:black;
        width: 100%;
        color: white;
        padding: 10px;
        margin: 10px 0px;
        border: none;
        cursor: pointer;
        font-size:25px;
        font-family:normal;
    }
form {
        border: 2px solid black;
        width: 45%;
        margin: 0 auto;
    }

input[type=text], input[type=password] {
        justify-content: center;
        width: 100%;
        margin: 8px 0;
        padding: 12px 20px;
        display: inline-block;
        border: 2px solid black;
        box-sizing: border-box;
    }

button:hover {
        opacity: 0.7;
    }

.container {
        justify-content: center;
        padding: 15px;
        background-color: #F8F8F8;
    }
</style>

```

```

</head>
<body style="background-color: #F8F8F8">
    <h1 style="color:red;text-align:center">${message}</h1>
    <br>
    <br>
    <h1 align="center" style="font-size: 40px;">Sporty Shoes</h1>
    <spring:form action="login" method="POST" commandName="account">
        <div class="container">
            <label>Username : </label> <br /> <input type="text"
                placeholder="Enter Username" name="username"> <br />
            <label>Password : </label> <br /> <input type="password"
                placeholder="Enter Password" name="password"> <br />
            <button type="submit" style="font-style: normal;">Sign In</button>
        </div>
    </spring:form>
</body>
</html>

```

header.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Header</title>
<style>
    th
    {
        background-color: black;
        color:white;
    }
    a{
        color:white;
        text-decoration: none;
    }
    th:hover{
        background-color: white;
        color:black;
    }
    a:hover{
        color:black;
    }

```

```

.container {
    display: flex;
    align-items: center;
    justify-content: center;
}
.search-bar {
    width: 100%;
    max-width: 800px;
    background: rgba(255, 255, 255, 0.2);
    display: flex;
    align-items: center;
    border-radius: 10px;
    padding: 3px 5px 3px 5px;
    backdrop-filter: blur(4px) saturate(180%);
}
.search-bar input {
    background: transparent;
    flex: 1;
    border: 0;
    outline: none;
    padding: 5px 10px 5px 3px;
    font-size: 20px;
    color: white;
}
::placeholder {
    color: white;
}
.search-bar button {
    border: 0;
    border-radius: 50%;
    height: 32px;
    width: 32px;
    background: transparent;
    cursor: pointer;
}
</style>
</head>
<body>
    <table style="background-color: black; width: 100%; height: 300" >
        <tr>
            <th style="text-decoration: none; font-size: 40px; padding: 10px 0px 10px 0px; text-align: left; color: white; background-color: black;">
                Sporty Shoes
            </th>
            <th style="background-color: black;">
                <div class="container">

```

```

        <form action="" class="search-bar">
        <input type="text" placeholder="Search.." name="search">
        <button type="submit">" width="25px" height="25px"/></button>
        </form></div>
        </th>
        <th style="text-decoration: none;padding: 10px 0px 10px 0px;text-align:
center">
                <a href="homes" target=_top style="font-size: 30px;">Home</a>
        </th>
        <th style="padding: 10px 0px 10px 0px; text-align: center">
                <a href="products" target=_top style="font-size:
30px;">Products</a>
        </th>
        <th style="padding: 10px 0px 10px 0px; text-align: center">
                <a href="orders" target=_top style="font-size:
30px;">Orders</a>
        </th>
        <th style="padding: 10px 0px 10px 0px; text-align: center">
                <a href="cart" target=_top style="font-size: 30px;">Cart</a>
        </th>
        <th style="padding: 10px 0px 10px 0px; text-align:center">
                <a href="logout" target=_top style="font-size: 30px;">Sign
out</a>
        </th>
    </tr>
</table>
</body>
</html>

```

home.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Home Page</title>
</head>
<body>
    <jsp:include page="header.jsp"/>
    <br><br>
    <center style="font-size:40px">Welcome!!</center>
</body>
</html>

```

## Products.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false" import="java.util.*"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Products</title>
<style>
.col1 {
    float:left;
    margin-left:0px;
    padding: 10px;
    width:40%;
    height:40%;
}

.col2 {
    position:absolute;
    margin-left: 350px;
    padding:10px;
    width:40%;
    height:80%;
}
.col3 {
    position:right;
    margin-left: 750px;
    padding: 10px;
    width:40%;
    height:50%;
}

.button{
    border:none;
    font-size: 16px;
    background-color: black;
    padding: 5px 15px;
    border-radius: 25px;
    color:white;
}
.button:hover{
    box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
```

```

        }
        b{
            font-size:20px;
        }
    </style>
</head>
<body align="center">
    <jsp:include page="header.jsp"/>
    <a href="productsboy" style="text-decoration:none;font-size:30px;color:Black">Men</a>&emsp;
    <a href="productsgirl" style="text-decoration:none;font-size:30px;color:Black">Women</a><br><br>
    <c:forEach items="${products}" var="pb" varStatus="status" step="1" begin="0">
        <div class="col${status.index % 3 + 1}">
            <a href="" style="color:Black">" style="width: 50%; height: 50%; border: 1px solid"/>
            <br><b>Brand: ${pb.brand}<br>Category:
${pb.category}<br>Mrp: ${pb.mrp}</b><br><br></a>
            <form action="addtocart" method="post">
                <input type="hidden" id="id" name="id"
value="${pb.id}"/>
                <input type="hidden" id="brand" name="brand"
value="${pb.brand}"/>
                <input type="hidden" id="mrp" name="mrp"
value="${pb.mrp}"/>
                <input type="hidden" id="category" name="category"
value="${pb.category}"/>
                <input type="hidden" id="description" name="description"
value="${pb.description}"/>
                <input type="hidden" id="image" name="image"
value="${pb.image}"/>
                <button class="button" type="submit">Add to
Cart</button>
            </form>
            <br><br><br>
        </div>
    </c:forEach>
</body>
</html>

```

Productsboy.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false" import="java.util.*"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>
<!DOCTYPE html>

```

```

<html>
<head>
<meta charset="ISO-8859-1">
<title>Men Shoes</title>
<style>
.col1 {
    float:left;
    margin-left:0px;
    padding: 10px;
    width:40%;
    height:40%;
}

.col2 {
    position:absolute;
    margin-left: 350px;
    padding:10px;
    width:40%;
    height:80%;
}
.col3 {
    position:right;
    margin-left: 750px;
    padding: 10px;
    width:40%;
    height:50%;
}
.button{
    border:none;
    font-size: 16px;
    background-color: black;
    padding: 5px 15px;
    border-radius: 25px;
    color:white;
}
.button:hover{
    box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
}
b{
    font-size:20px;
}
</style>
</head>
<body align="center">
<jsp:include page="header.jsp" />
<a href="productsboy"

```

```

                style="text-decoration: none; font-size: 30px; color: Black">Men</a>&emsp;
<a href="productsgirl"
    style="text-decoration: none; font-size: 30px; color: Black">Women</a>
<br><br>
<c:forEach items="${products}" var="pb" varStatus="status" step="1" begin="0">
    <div class="col${status.index % 3 + 1}">
        <c:if test="${pb.category=='men'}">
            <a href="" style="color:Black">" style="width: 50%; height: 50%; border: 1px solid"/>
            <br><b>Brand: ${pb.brand}<br>Category:
${pb.category}<br>Mrp: ${pb.mrp}</b><br><br><br></a>
            <form action="addtocart" method="post">
                <input type="hidden" id="id" name="id"
value="${pb.id}"/>
                <input type="hidden" id="brand" name="brand"
value="${pb.brand}"/>
                <input type="hidden" id="mrp" name="mrp"
value="${pb.mrp}"/>
                <input type="hidden" id="category" name="category"
value="${pb.category}"/>
                <input type="hidden" id="description" name="description"
value="${pb.description}"/>
                <input type="hidden" id="image" name="image"
value="${pb.image}"/>
                <button class="button" type="submit">Add to
Cart</button>
            </form>
            <br><br>
        </c:if>
    </div>
</c:forEach>
</body>
</html>

```

Productsgirl.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false" import="java.util.*"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Women Shoes</title>
<style>

```



```

.col1 {
    position: absolute;
    margin-left: 10px;
    padding: 5px;
    width: 40%;
    height: 40%;
}

.col2 {
    position: absolute;
    margin-left: 400px;
    width: 40%;
    height: 80%;
}

.col3 {
    position: absolute;
    margin-left: 800px;
    padding: 10px;
    width: 40%;
    height: 50%;
}

.button {
    border: none;
    font-size: 16px;
    background-color: black;
    padding: 5px 15px;
    border-radius: 25px;
    color: white;
}

.button:hover {
    box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
}

b {
    font-size: 20px;
}
</style>
</head>
<body align="center">
    <jsp:include page="header.jsp"/>
    <a href="productsboy" style="text-decoration: none; font-size: 30px; color: Black">Men</a> &emsp;
    <a href="productsgirl" style="text-decoration: none; font-size: 30px; color: Black">Women</a>
    <c:forEach items="${productsg}" var="pg" varStatus="status" step="1" begin="0">
        <div class="col${status.index % 3 + 1}">

```

```

                <c:if test="\${pg.category=='women'}">
                    <a href="" style="color:Black">" style="width: 40%; height: 60%; border: 1px solid"/>
                    <br><b>Brand: \${pg.brand}<br>Category:
\${pg.category}<br><b>Mrp: \${pg.mrp}</b><br><br></a>
                    <form action="addtocart" method="post">
                        <input type="hidden" id="id" name="id"
value="\${pg.id}"/>
                        <input type="hidden" id="brand" name="brand"
value="\${pg.brand}"/>
                        <input type="hidden" id="mrp" name="mrp"
value="\${pg.mrp}"/>
                        <input type="hidden" id="category" name="category"
value="\${pg.category}"/>
                        <input type="hidden" id="description" name="description"
value="\${pg.description}"/>
                        <input type="hidden" id="image" name="image"
value="\${pg.image}"/>
                        <button class="button" type="submit">Add to
Cart</button>
                    </form>
                    <br><br><br>
                </c:if>
            </div>
        </c:forEach>
    </body>
</html>

```

## Orders.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Orders</title>
<style>
    .coll {
        float:left;
        margin-left:0px;
        padding: 10px;
        width:40%;
        height:40%;
    }

```

```

    }

.col2 {
    position: absolute;
    margin-left: 380px;
    padding: 10px;
    width: 40%;
    height: 80%;
}
.col3 {
    position: right;
    margin-left: 780px;
    padding: 10px;
    width: 40%;
    height: 50%;
}
b {
    font-size: 20px;
}
</style>
</head>
<body align="center">
    <jsp:include page="header.jsp"/>
    <br>
    <h1>Your Orders</h1>
    <c:forEach items="${orders}" var="order" varStatus="status" step="1" begin="0">
        <div class="col${status.index % 3 + 1}">
            " style="width: 50%;
height: 50%; border: 1px solid"/>
            <br><b>Brand: ${order.brand}<br>Category:
${order.category}<br>Mrp: ${order.price}</b><br><br>
        </div>
    </c:forEach>
</body>
</html>

```

Cart.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">

```

```

<title>Cart</title>
<style>
    .col1 {
        float:left;
        margin-left:0px;
        padding: 10px;
        width:40%;
        height:40%;
    }

    .col2 {
        position:absolute;
        margin-left: 380px;
        padding:10px;
        width:40%;
        height:80%;
    }
    .col3 {
        position:right;
        margin-left: 780px;
        padding: 10px;
        width:40%;
        height:50%;
    }
    b{
        font-size:20px;
    }
    .button{
        border:none;
        font-size: 16px;
        background-color: black;
        padding: 5px 15px;
        border-radius: 25px;
        color:white;
        bottom: 10px;
        position:center;
    }
    .button:hover{
        box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
    }
</style>
</head>
<body align="center">
    <jsp:include page="header.jsp"/>
    <br>
    <c:forEach items="\${cart}" var="cart" varStatus="status" step="1" begin="0">

```

```

        <div class="col${status.index % 3 + 1}">
            " style="width: 50%;
height: 50%; border: 1px solid"/>
            <br><b>Brand: ${cart.brand}<br>Category:
${cart.category}<br>Mrp: ${cart.mrp}</b><br><br>
        </div>
    </c:forEach><br><br><br><br><br>
    <a class="button" href="buy" style="color:white;align="center">Buy</a>
</body>
</html>

```

Userdetails.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>User Details</title>
<style>
    td{
        font-size:20px;
    }
    .button{
        border:none;
        font-size: 16px;
        background-color: black;
        padding: 5px 15px;
        border-radius: 25px;
        color:white;
    }
    .button:hover{
        box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
    }
    b{
        font-size:20px;
    }
</style>
</head>
<body align="center">
    <jsp:include page="header.jsp"/>
    <c:set var="total" value="${0}" />
    <c:forEach items="${cart}" var="cart" varStatus="status" step="1"
        begin="0">

```

```

        <c:set var="total" value="\${total + cart.mrp}" />
    </c:forEach>
    <form action="ordersuccess" method="post">
        <table align="center">
            <tr>
                <td colspan="2"><h2>Payee Details</h2></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px ">Name:</td>
                <td><input type="text" name="username" /></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px ">Email:</td>
                <td><input type="text" name="email" /></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px ">Mobile:</td>
                <td><input type="text" name="mobile" /></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px ">Location:</td>
                <td><input type="text" name="location" /></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px ">Date:</td>
                <td><input id="date" type="date" name="date" ></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px ">Price:</td>
                <td><input type="text" value="\${total}" name="price" readonly
            /></td>
            </tr>
        </table>
        <br>
        <input type="submit" value="Proceed to Pay" class="button">
    </form>
</body>
</html>

adduser.sp

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>
<!DOCTYPE html>

```

```
<html>
<head>
<meta charset="ISO-8859-1">
<title>Add user</title>
<style>
    td{
        font-size:20px;
    }

    button:hover{
        box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
    }
    b{
        font-size:20px;
    }
</style>
</head>
<body align="center">
    <jsp:include page="adminheader.jsp"></jsp:include>
    <form action="registeruser" method="post">
        <h1>Add User</h1>
        <table align="center">
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px "><b>ID:</b>
            </td>
                <td align="left"><input type="text" name="id"/></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px
"><b>Username:</b></td>
                <td align="left"><input type="text" name="username"/></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px
"><b>Password</b></td>
                <td align="left"><input type="password"
name="password"/></td>
            </tr>
            <tr>
                <td colspan=2>
                    <button type="submit" style="border:none;
font-size: 16px;
background-color: black;
padding: 5px 15px;
border-radius: 25px;
color:white;">Add</button>&ensp;
                </td>
            </tr>
        </table><br><br>
    </form>
</body>
</html>
```

```

        <button type="reset" style="border:none;
        font-size: 16px;
        background-color: black;
        padding: 5px 15px;
        border-radius: 25px;
        color:white;">Reset</button>
    </form><br><br>
    <b>${result}</b>
</body>
</html>

```

addproduct.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>

<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Add Product</title>
<style>
    td{
        font-size:20px;
    }
    .button{
        border:none;
        font-size: 16px;
        background-color: black;
        padding: 5px 15px;
        border-radius: 25px;
        color:white;
    }
    .button:hover{
        box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
    }
    b{
        font-size:20px;
    }
</style>
</head>
<body align="center">
    <jsp:include page="adminheader.jsp"/>
    <form action="add_product" method="post">
        <h1>Add Product</h1>

```



```

        <table align="center">
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px "><b>ID:</b>
            </td>
                <td align="left"><input type="text" name="id"/></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px
            "><b>Brand:</b></td>
                <td align="left"><input type="text" name="brand"/></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px
            "><b>MRP</b></td>
                <td align="left"><input type="text" name="mrp"/></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px
            "><b>Category:</b></td>
                <td align="left"><input type="text" name="category"/></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px
            "><b>Description:</b></td>
                <td align="left"><input type="text" name="description"/></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px
            "><b>Image</b></td>
                <td align="left"><input type="text" name="image"/>
            </tr>
        </table><br><br>
        <button type="submit" class="button">Add</button>&ensp;
        <button type="reset" class="button">Reset</button>
    </form><br><br>
    <b>${result}</b>
</body>
</html>

```

admincart.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>

```

```

<!DOCTYPE html>

```

```

<html>
<head>
<meta charset="ISO-8859-1">
<title>Admin Cart</title>
<style>
.col1 {
    float:left;
    margin-left:0px;
    padding: 10px;
    width:40%;
    height:40%;
}

.col2 {
    position:absolute;
    margin-left: 380px;
    padding:10px;
    width:40%;
    height:80%;
}
.col3 {
    position:right;
    margin-left: 780px;
    padding: 10px;
    width:40%;
    height:50%;
}
b{
    font-size:20px;
}
.button{
    border:none;
    font-size: 16px;
    background-color: black;
    padding: 5px 15px;
    border-radius: 25px;
    color:white;
    bottom: 10px;
    position:center;
}
.button:hover{
    box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
}
</style>
</head>
<body align="center">

```

```

<jsp:include page="adminheader.jsp"/>
<br>
<c:forEach items="${cart}" var="cart" varStatus="status" step="1" begin="0">
    <div class="col${status.index % 3 + 1}">
        " style="width: 50%;
height: 50%; border: 1px solid"/>
        <br><b>Brand: ${cart.brand}<br>Category:
${cart.category}<br>Mrp: ${cart.mrp}</b><br><br>
    </div>
</c:forEach><br><br><br><br><br>
<a class="button" href="buy" style="color:white;align="center">Buy</a>
</body>
</html>

```

adminheader.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>

```

```

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Header</title>
<style>
    th
    {
        background-color: black;
        color:white;
    }
    a{
        color:white;
        text-decoration: none;
    }
    th:hover{
        background-color: white;
        color:black;
    }
    a:hover{
        color:black;
    }
    .container {
        display:flex;
        align-items:center;
        justify-content:center;
    }

```

```

}
.search-bar{
    width:100%;
    max-width:800px;
    background:rgba(255,255,255,0.2);
    display:flex;
    align-items:center;
    border-radius:10px;
    padding:3px 5px 3px 5px;
    backdrop-filter:blur(4px) saturate(180%);
}
.search-bar input{
    background:transparent;
    flex:1;
    border:0;
    outline:none;
    padding:5px 10px 5px 3px;
    font-size:20px;
    color:white;
}
::placeholder{
    color:white;
}
.search-bar button{
    border:0;
    border-radius:50%;
    height:32px;
    width:32px;
    background:transparent;
    cursor:pointer;
}
</style>
</head>
<body>
    <table style="background-color: black; width:100%;height:300" >
        <tr>
            <th style="text-decoration: none; font-size: 40px; padding: 10px 0px 10px 0px; text-align: left;color:white;background-color: black;">
                Sporty Shoes
            </th>
            <th style="background-color: black;">
                <div class="container">
                    <form action="" class="search-bar">
                        <input type="text" placeholder="Search.." name="search">
                        <button type="submit">" width="25px" height="25px"/></button>

```

```

        </form></div>
        </th>
        <th style="text-decoration: none;padding: 10px 0px 10px 0px;text-align:
center">
            <a href="adminhomes" target=_top style="font-size:
30px;">Home</a>
        </th>
        <th style="padding: 10px 0px 10px 0px; text-align: center">
            <a href="adminproducts" target=_top style="font-size:
30px;">Products</a>
        </th>
        <th style="padding: 10px 0px 10px 0px; text-align: center">
            <a href="adminorders" target=_top style="font-size:
30px;">Orders</a>
        </th>
        <th style="padding: 10px 0px 10px 0px; text-align: center">
            <a href="admincart" target=_top style="font-size:
30px;">Cart</a>
        </th>
        <th style="padding: 10px 0px 10px 0px; text-align:center">
            <a href="logout" target=_top style="font-size: 30px;">Sign
out</a>
        </th>
    </tr>
</table>
</body>
</html>

```

adminhome.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Admin Home</title>
<style>
</style>
</head>
<body>
    <jsp:include page="adminheader.jsp"/>
    <br><br><br>
    <ul>
        <li><a href="change_password" style="color:black;font-size:30px">Change
password</a><br></li><br>
    </ul>

```

```

        <li><a href="manage_products" style="color:black;font-size:30px;">Manage
Products</a><br></li><br>
        <li><a href="users_list" style="color:black;font-size:30px">List of
users</a><br></li><br>
        <li><a href="search_user" style="color:black;font-size:30px">Search
User</a><br></li><br>
        <li><a href="purchase_reports" style="color:black;font-size:30px">Purchase
Reports</a><br></li>
    </ul>
</body>
</html>

```

adminorders.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>

```

```

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Admin Orders</title>
<style>
    .col1 {
        float:left;
        margin-left:0px;
        padding: 10px;
        width:40%;
        height:40%;
    }

    .col2 {
        position:absolute;
        margin-left: 380px;
        padding:10px;
        width:40%;
        height:80%;
    }

    .col3 {
        position:right;
        margin-left: 780px;
        padding: 10px;
        width:40%;
        height:50%;
    }

```

```

        b{
            font-size:20px;
        }
</style>
</head>
<body align="center">
    <jsp:include page="adminheader.jsp"/>
    <br>
    <h1>Your Orders</h1>
    <c:forEach items="${order}" var="order" varStatus="status" step="1" begin="0">
        <div class="col${status.index % 3 + 1}">
            " style="width: 50%;
height: 50%; border: 1px solid"/>
            <br><b>Brand: ${order.brand}<br>Category:
${order.category}<br>Mrp: ${order.price}</b><br><br>
        </div>
    </c:forEach>
</body>
</html>

```

adminproducts.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Products</title>
<style>

</style>
</head>
<body align="center">
    <jsp:include page="adminheader.jsp"/>
    <a href="adminproductsboy" style="text-decoration:none;font-
size:30px;color:Black">Men</a>&nbsp;
    <a href="adminproductsgirl" style="text-decoration:none;font-
size:30px;color:Black">Women</a><br><br>
</body>
</html>

```

adminproductsboy.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false" import="java.util.*"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Men Shoes</title>
<style>
    .col1 {
        float:left;
        margin-left:0px;
        padding: 10px;
        width:40%;
        height:40%;
    }

    .col2 {
        position:absolute;
        margin-left: 380px;
        padding:10px;
        width:40%;
        height:80%;
    }
    .col3 {
        position:right;
        margin-left: 780px;
        padding: 10px;
        width:40%;
        height:50%;
    }
    .button{
        border:none;
        font-size: 16px;
        background-color: black;
        padding: 5px 15px;
        border-radius: 25px;
        color:white;
    }
    .button:hover{
        box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
    }
    b{
        font-size:20px;
    }
</style>

```



```

</head>
<body align="center">
    <jsp:include page="adminheader.jsp" />
    <a href="adminproductsboy"
        style="text-decoration: none; font-size: 30px; color: Black">Men</a>&emsp;
    <a href="adminproductsgirl"
        style="text-decoration: none; font-size: 30px; color: Black">Women</a>
    <br><br>
    <c:forEach items="${products_boy}" var="pb" varStatus="status" step="1" begin="0">
        <div class="col${status.index % 3 + 1}">
            <c:if test="${pb.category=='men'}">
                <a href="view_product" style="color:Black">" style="width: 50%; height: 50%; border: 1px solid"/>
                <br><b>Brand: ${pb.brand}<br>Category:
${pb.category}<br>Mrp: ${pb.mrp}</b><br><br></a>
                <form action="addtocart" method="post">
                    <input type="hidden" id="id" name="id"
value="${pb.id}"/>
                    <input type="hidden" id="brand" name="brand"
value="${pb.brand}"/>
                    <input type="hidden" id="mrp" name="mrp"
value="${pb.mrp}"/>
                    <input type="hidden" id="category" name="category"
value="${pb.category}"/>
                    <input type="hidden" id="description" name="description"
value="${pb.description}"/>
                    <input type="hidden" id="image" name="image"
value="${pb.image}"/>
                    <button class="button" type="submit" class="button">Add
to Cart</button>
                </form>
                <br><br>
            </c:if>
        </div>
    </c:forEach>
</body>
</html>

```

adminproductsgirl.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false" import="java.util.*"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>

<!DOCTYPE html>

```

```

<html>
<head>
<meta charset="ISO-8859-1">
<title>Women Shoes</title>
<style>
    .col1 {
        position: absolute;
        margin-left: 10px;
        padding: 5px;
        width: 40%;
        height: 40%;
    }

    .col2 {
        position: absolute;
        margin-left: 400px;
        width: 40%;
        height: 80%;
    }

    .col3 {
        position: absolute;
        margin-left: 800px;
        padding: 10px;
        width: 40%;
        height: 50%;
    }

    .button {
        border: none;
        font-size: 16px;
        background-color: black;
        padding: 5px 15px;
        border-radius: 25px;
        color: white;
    }

    .button:hover {
        box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
    }

    b {
        font-size: 20px;
    }
</style>
</head>
<body align="center">
    <jsp:include page="adminheader.jsp"/>

```

```

        <a href="adminproductsboy" style="text-decoration:none;font-
size:30px;color:Black">Men</a>&emsp;
        <a href="adminproductsgirl" style="text-decoration:none;font-
size:30px;color:Black">Women</a>
        <c:forEach items="\${products_girl}" var="pg" varStatus="status" step="1" begin="0">
            <div class="col\${status.index % 3 + 1}">
                <c:if test="\${pg.category=='women'}">
                    <a href="" style="color:Black">" style="width: 40%; height: 60%; border: 1px solid"/>
                    <br><b>Brand: \${pg.brand}<br>Category:
\${pg.category}<br>Mrp: \${pg.mrp}</b><br><br></a>
                    <form action="addtocart" method="post">
                        <input type="hidden" id="id" name="id"
value="\${pg.id}"/>
                        <input type="hidden" id="brand" name="brand"
value="\${pg.brand}"/>
                        <input type="hidden" id="mrp" name="mrp"
value="\${pg.mrp}"/>
                        <input type="hidden" id="category" name="category"
value="\${pg.category}"/>
                        <input type="hidden" id="description" name="description"
value="\${pg.description}"/>
                        <input type="hidden" id="image" name="image"
value="\${pg.image}"/>
                        <button class="button" type="submit">Add to
Cart</button>
                    </form>
                    <br><br><br>
                </c:if>
            </div>
        </c:forEach>
</body>
</html>

```

Change\_password.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Change Password</title>
<style>
    td{
        font-size:20px;

```

```

    }
    .button{
        border:none;
        font-size: 16px;
        background-color: black;
        padding: 5px 15px;
        border-radius: 25px;
        color:white;
    }
    .button:hover{
        box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
    }
    b{
        font-size:20px;
    }
</style>
</head>
<body align="center">
    <jsp:include page="adminheader.jsp"/>
    <center><h1>Change Password</h1></center>
    <form action="change_password" method="post">
        <br><br>
        <table align="center">
            <tr>
                <td><input type="hidden" name="username"
value="admin"/></td>
                <td align="left" style="padding:10px 20px 10px 5px ">Current
Password</td>
                <td align="left" style="padding:10px 20px 10px 5px "><input
type="password" name="cp" required/></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px ">New
Password</td>
                <td align="left" style="padding:10px 20px 10px 5px "><input
type="password" name="password" required/></td>
            </tr>
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px">Confirm
Password</td>
                <td align="left" style="padding:10px 20px 10px 5px"><input
type="password" name="np" required/></td>
            </tr>
        </table><br>
        <button type="submit" class="button">Change</button>
    </form>
</body>
</html>

```

```

        </form><br><br>
        <b>${res}</b>
    </body>
</html>

```

deleteproduct.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Delete Product</title>
<style>
    td{
        font-size:20px;
    }
    .button{
        border:none;
        font-size: 16px;
        background-color: black;
        padding: 5px 15px;
        border-radius: 25px;
        color:white;
    }
    .button:hover{
        box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
    }
    b{
        font-size:20px;
    }
</style>
</head>
<body align="center">
    <jsp:include page="adminheader.jsp"/>
    <h1>Delete Product</h1>
    <br>
    <form action="delete_product" method="post">
        <table align="center">
            <tr>
                <td align="left" style="padding:10px 20px 10px 5px ">Id</td>
                <td align="left" style="padding:10px 20px 10px 5px "><input
type="text" name="id"/></td>

```

```

        </tr>
    </table><br><br>
    <button type="submit" class="button">Delete</button>
</form>
<br><b>${result}</b>
</body>
</html>

```

Manage\_products.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false" import="java.util.*"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Manage Products</title>
<style>
    .button {
        border: none;
        font-size: 20px;
        background-color: black;
        padding: 5px 15px;
        border-radius: 25px;
        color: white;
    }

    .button:hover {
        box-shadow: 0 8px 16px 0 rgba(0, 0, 0, 0.2), 0 6px 20px 0
            rgba(0, 0, 0, 0.19);
    }

    b {
        font-size: 20px;
    }
</style>
</head>
<body align="center">
    <jsp:include page="adminheader.jsp" />
    <h1>Manage Products</h1>
    <br><br>
    <a href="addproduct" class="button" style="color:white">Add Product</a>
    <br><br><br>
    <a href="deleteproduct" class="button" style="color:white">Delete Product</a>
</body>

```

</html>

Purchase\_reports.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Purchase Reports</title>
<style>
    .button {
        border: none;
        font-size: 20px;
        background-color: black;
        padding: 5px 15px;
        border-radius: 25px;
        color: white;
    }

    .button:hover {
        box-shadow: 0 8px 16px 0 rgba(0, 0, 0, 0.2), 0 6px 20px 0
            rgba(0, 0, 0, 0.19);
    }

    td {
        font-size: 20px;
    }
</style>
</head>
<body align="center">
    <jsp:include page="adminheader.jsp"/>
    <h1>Purchase Reports</h1>
    <br><br>
    <form action="filter">
        <table align="center">
            <tr>
                <td align="left" style="padding: 10px 20px 10px 5px ">Date</td>
                <td align="left" style="padding: 10px 20px 10px 5px "><input
type="date" name="date"/></td>
            </tr>
            <tr>
                <td align="left" style="padding: 10px 20px 10px 5px
">Category</td>
                <td align="left" style="padding: 10px 20px 10px 5px ">
```

```

                                <select name="category">
                                    <option selected>Select</option>
                                    <option value="men">men</option>
                                    <option value="women">women</option>
                                </select>
                            </td>
                        </tr>
                    </table><br><br>
                    <button type="submit" class="button">Filter</button>
                </form>
</body>
</html>

```

Purchase\_result.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Reports</title>
<style>
    .col1 {
        position:left;
        margin-left:10px;
        padding: 10px;
        width:40%;
        height:40%;
    }

    .col2 {
        position:right;
        margin-left: 380px;
        padding:10px;
        width:40%;
        height:80%;
    }
    .col3 {
        position:left;
        margin-left: 10px;
        padding: 0px;
        width:40%;
        height:50%;
    }

```



```

    }
    b{
        font-size:20px;
    }
</style>
</head>
<body align="center">
    <jsp:include page="adminheader.jsp"/>
    <h1>Your Orders</h1>
    <c:forEach items="${orders}" var="order" varStatus="status" step="1" begin="0">
        <div class="col${status.index % 3 + 1}">
            <c:if test="${order.date == param.date && order.category ==
param.category}">
                
                <br><b>Brand: ${order.brand}<br>Category:
${order.category}<br>Mrp: ${order.price}<br>Date: ${order.date}</b><br>
            </c:if>
        </div>
    </c:forEach>
</body>
</html>

```

Search\_result.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Search Result</title>
<style>
    b{
        font-size:20px;
    }
</style>
</head>
<body align="center">
    <jsp:include page="adminheader.jsp"/>
    <h1>Search Result</h1>
    <table align="center" width=600 height=100>
        <tr>
            <th style="background-color:black;color:white;">ID</th>
            <th style="background-color:black;color:white;">Username</th>
            <th style="background-color:black;color:white;">Password</th>

```

```

        </tr>
        <tr>
            <td>${users.id}</td>
            <td>${users.username}</td>
            <td>${users.password}</td>
        </tr>
    </table><br><br>
    <b>${result}</b>
</body>
</html>

```

Search\_user.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Search User</title>
<style>
    td{
        font-size:20px;
    }
    .button{
        border:none;
        font-size: 16px;
        background-color: black;
        padding: 5px 15px;
        border-radius: 25px;
        color:white;
    }
    .button:hover{
        box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
    }
</style>
</head>
<body align="center">
    <jsp:include page="adminheader.jsp"/>
    <center><h1>Search User</h1></center>
    <br>
    <form action="search_user" method="post">
        <table align="center">

```

```

        <tr>
            <td align="left" style="padding:10px 20px 10px 5px ">Id</td>
            <td align="left" style="padding:10px 20px 10px 5px "><input
type="text" name="id"/></td>
        </tr>
    </table><br><br>
    <button type="submit" class="button">Search</button>
</form>
</body>
</html>

```

Users\_list.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1" isELIgnored="false"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Users List</title>
<style>
    tr:nth-child(odd) {
        background-color: #F0F0F0;
    }
    th {
        background-color:black;
        color:white;
    }
    th,td {
        padding:5px 5px 5px 5px;
    }

    button:hover {
        box-shadow: 0 8px 16px 0 rgba(0,0,0,0.2), 0 6px 20px 0 rgba(0,0,0,0.19);
    }
</style>
</head>
<body align="center">
    <jsp:include page="adminheader.jsp"/>
    <h1>Users List</h1>
    <table align="center" width=600 height=100>
        <tr>
            <th style="background-color:black;color:white;">ID</th>

```

```

        <th style="background-color: black; color: white;">Username</th>
        <th style="background-color: black; color: white;">Password</th>
    </tr>
    <c:forEach var="user" items="\${users}">
        <tr>
            <td>\${user.id}</td>
            <td>\${user.username}</td>
            <td>\${user.password}</td>
        </tr>
    </c:forEach>
</table><br><br>
<a href="add_user"><button style="border: none;
    font-size: 16px;
    background-color: black;
    padding: 10px 20px;
    border-radius: 25px;
    color: white;">Add User</button></a>
</body>
</html>

```

dispatcher-servlet.jsp

```

<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:context="http://www.springframework.org/schema/context"
    xmlns:p="http://www.springframework.org/schema/p"
    xmlns:tx="http://www.springframework.org/schema/tx"
    xmlns:mvc="http://www.springframework.org/schema/mvc"
    xsi:schemaLocation="http://www.springframework.org/schema/beans
        http://www.springframework.org/schema/beans/spring-beans.xsd
        http://www.springframework.org/schema/context
        http://www.springframework.org/schema/context/spring-context.xsd
        http://www.springframework.org/schema/mvc
        http://www.springframework.org/schema/mvc/spring-mvc.xsd
        http://www.springframework.org/schema/tx
        http://www.springframework.org/schema/tx/spring-tx.xsd">

    <context:component-scan
        base-package="com.springapps" />

    <mvc:annotation-driven/>
    <mvc:resources location="/resources/" mapping="/resources/**"/>

    <bean name="viewResolver"

```

```

        class="org.springframework.web.servlet.view.InternalResourceViewResolver">
        <property name="prefix">
            <value>/WEB-INF/views/</value>
        </property>
        <property name="suffix">
            <value>.jsp</value>
        </property>
    </bean>
    <bean name="datasource"
        class="org.springframework.jdbc.datasource.DriverManagerDataSource"
        p:driverClassName="com.mysql.jdbc.Driver"
        p:url="jdbc:mysql://localhost:3306/sporty_shoes" p:username="root"
        p:password="*Paddu@18" />

    <bean name="sessionfactory"
        class="org.springframework.orm.hibernate5.LocalSessionFactoryBean">
        <property name="dataSource" ref="datasource" />
        <property name="hibernateProperties">
            <props>
                <prop
key="hibernate.dialect">org.hibernate.dialect.MySQL57Dialect</prop>
                <prop key="hibernate.show_sql">true</prop>
            </props>
        </property>
        <property name="annotatedClasses">
            <list>
                <value>com.springapps.entity.Users</value>
                <value>com.springapps.entity.Products</value>
                <value>com.springapps.entity.Cart</value>
                <value>com.springapps.entity.Order</value>
            </list>
        </property>
    </bean>

    <bean name="hibernateTemplate"
        class="org.springframework.orm.hibernate5.HibernateTemplate"
        p:sessionFactory-ref="sessionfactory" />

    <bean name="transactionManager"
        class="org.springframework.orm.hibernate5.HibernateTransactionManager"
        p:sessionFactory-ref="sessionfactory" />

    <tx:annotation-driven />

</beans>

```

Web.xml

```
<!DOCTYPE web-app PUBLIC
"-//Sun Microsystems, Inc.//DTD Web Application 2.3//EN"
"http://java.sun.com/dtd/web-app_2_3.dtd" >

<web-app>
  <display-name>Archetype Created Web Application</display-name>
  <servlet>
    <servlet-name>dispatcher</servlet-name>
    <servlet-class>org.springframework.web.servlet.DispatcherServlet</servlet-
class>
    </servlet>
    <servlet-mapping>
      <servlet-name>dispatcher</servlet-name>
      <url-pattern>/</url-pattern>
    </servlet-mapping>
    <welcome-file-list>
      <welcome-file>redirect.jsp</welcome-file>
    </welcome-file-list>
  </web-app>
```