## →Creating queue-templete

developer-production-q1ltkz0tkmp-solace-primary-0> enable

developer-production-q1ltkz0tkmp-solace-primary-0# configure

developer-production-q1ltkz0tkmp-solace-primary-0(configure)# message-spool message-vpn testing-sample-01

developer-production-q1ltkz0tkmp-solace-primary-0(configure/message-spool)# create queue-template queue01

developer-production-q1ltkz0tkmp-solace-primary-0(configure/message-spool/queue-template)# permission all consume

developer-production-q1ltkz0tkmp-solace-primary-0(configure/message-spool/queue-template)# name-filter partice/wed

developer-production-q1ltkz0tkmp-solace-primary-0(configure/message-spool/queue-template)# max-spool-usage 50

developer-production-q1ltkz0tkmp-solace-primary-0(configure/message-spool/queue-template)# show queue-template queue01 detail

Name : queue01

Message VPN : testing-sample-01

Name Filter : partice/wed
Durability Override : none
Access Type : Exclusive

All Others Permission : Consume (1100)

Quota (MB) : 50

Respect Message Priority : No Respect TTL : No

Max TTL (Seconds) : 0 (Disabled)
Reject Msg to Sender on Discard : Yes
Including When Shutdown : No

Max Delivered Unacked Msgs Per Flow: 10000

Redelivery : Enabled Max Redelivery : 0

Redelivery Delay : Disabled

Multiplier : 2.00
Initial Interval (ms) : 1000
Max Interval (ms) : 64000
Delivery Delay (Seconds) : 0
Consumer Ack Propagation : Yes
Reject Low-Priority-Msg : No
Reject Low-Priority-Msg Limit : 0

Max Msg Size Allowed (B) : 10000000

Max Bind Count : 1000

Dead Message Queue : #DEAD MSG QUEUE

Event Threshold Set Value Clear Value

\_\_\_\_\_\_

 Bind count
 80%(800)
 60%(600)

 Spool usage (MB)
 25%(12)
 18%(9)

 Reject Low-Priority-Msg Limit
 80%(0)
 60%(0)

---Press any key to continue, or `q' to quit---

developer-production-q1ltkz0tkmp-solace-primary-0(configure/message-spool/queue-template)#