Experiment 3: DML Commands Using INSERT and SELECT

AIM

To insert records into a table and retrieve all or selected records using INSERT and SELECT commands.

Outputs:

```
mysql> CREATE TABLE Employee ( emp_id INT PRIMARY KEY,emp_name VARCHAR(50),salary DECIMAL(10,2), department VARCHAR(30));
Query OK, 0 rows affected (0.06 sec)

mysql> INSERT INTO Employee
    -> VALUES (101, 'Bhavya', 30000, 'IT'),(102, 'Ravi', 35000, 'HR'),(103, 'Priya', 40000, 'IT'),(104, 'Arun', 28000, 'Sales');
Query OK, 4 rows affected (0.02 sec)
Records: 4  Duplicates: 0  Warnings: 0
```

```
mysql> SELECT * FROM Employee;
+--------+----------+----------+------------+
| emp_id | emp_name | salary   | department |
+--------+----------+----------+------------+
|    101 | Bhavya   | 30000.00 | IT         |
|    102 | Ravi     | 35000.00 | HR         |
|    103 | Priya    | 40000.00 | IT         |
|    104 | Arun     | 28000.00 | Sales      |
+--------+----------+----------+------------+
4 rows in set (0.00 sec)
```

```
mysql> SELECT emp_name, salary
    -> FROM Employee;
+----------+----------+
| emp_name | salary   |
+----------+----------+
| Bhavya   | 30000.00 |
| Ravi     | 35000.00 |
| Priya    | 40000.00 |
| Arun     | 28000.00 |
+----------+----------+
4 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM Employee
    -> WHERE department = 'IT';
+--------+----------+----------+------------+
| emp_id | emp_name | salary   | department |
+--------+----------+----------+------------+
|    101 | Bhavya   | 30000.00 | IT         |
|    103 | Priya    | 40000.00 | IT         |
+--------+----------+----------+------------+
2 rows in set (0.01 sec)
```

```
mysql> SELECT * FROM Employee
    -> WHERE salary > 30000;
+--------+----------+----------+------------+
| emp_id | emp_name | salary   | department |
+--------+----------+----------+------------+
|    102 | Ravi     | 35000.00 | HR         |
|    103 | Priya    | 40000.00 | IT         |
+--------+----------+----------+------------+
2 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM Employee
    -> ORDER BY salary DESC;
+--------+----------+----------+------------+
| emp_id | emp_name | salary   | department |
+--------+----------+----------+------------+
|    103 | Priya    | 40000.00 | IT         |
|    102 | Ravi     | 35000.00 | HR         |
|    101 | Bhavya   | 30000.00 | IT         |
|    104 | Arun     | 28000.00 | Sales      |
+--------+----------+----------+------------+
4 rows in set (0.00 sec)
```

RESULT

Thus, INSERT and SELECT commands were executed to add employee records and retrieve all records, selected columns, filtered results, and records sorted by salary.