Experiment 4: DML Commands Using UPDATE and DELETE

AIM

To modify existing records using UPDATE and remove selected records using DELETE in MySQL.

Output:

```
mysql> CREATE TABLE Employee ( emp_id INT PRIMARY KEY,emp_name VARCHAR(50),salary DECIMAL(10,2), department VARCHAR(30));
Query OK, 0 rows affected (0.05 sec)

mysql>  INSERT INTO Employee
    ->  VALUES (101, 'Bhavya', 30000, 'IT'),(102, 'pavani', 35000, 'HR'),(103, 'anitha', 40000, 'IT'),(104, 'kumari', 28000, 'Sales');
Query OK, 4 rows affected (0.01 sec)
Records: 4  Duplicates: 0  Warnings: 0
```

```
mysql> SELECT * FROM Employee;
+--------+----------+----------+------------+
| emp_id | emp_name | salary   | department |
+--------+----------+----------+------------+
|    101 | Bhavya   | 30000.00 | IT         |
|    102 | pavani   | 35000.00 | HR         |
|    103 | anitha   | 40000.00 | IT         |
|    104 | kumari   | 28000.00 | Sales      |
+--------+----------+----------+------------+
4 rows in set (0.00 sec)
```

```
mysql> UPDATE Employee
    -> SET salary = 45000
    -> WHERE emp_id = 101;
Query OK, 1 row affected (0.02 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> SELECT * FROM Employee;
+--------+----------+----------+------------+
| emp_id | emp_name | salary   | department |
+--------+----------+----------+------------+
|    101 | Bhavya   | 45000.00 | IT         |
|    102 | pavani   | 35000.00 | HR         |
|    103 | anitha   | 40000.00 | IT         |
|    104 | kumari   | 28000.00 | Sales      |
+--------+----------+----------+------------+
4 rows in set (0.00 sec)
```

```
mysql> UPDATE Employee
    -> SET department = 'Finance'
    -> WHERE emp_id = 102;
Query OK, 1 row affected (0.01 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> SELECT * FROM Employee;
+--------+----------+----------+------------+
| emp_id | emp_name | salary   | department |
+--------+----------+----------+------------+
|    101 | Bhavya   | 45000.00 | IT         |
|    102 | pavani   | 35000.00 | Finance    |
|    103 | anitha   | 40000.00 | IT         |
|    104 | kumari   | 28000.00 | Sales      |
+--------+----------+----------+------------+
4 rows in set (0.00 sec)
```

```
mysql> DELETE FROM Employee
    -> WHERE emp_id = 104;
Query OK, 1 row affected (0.01 sec)

mysql> SELECT * FROM Employee;
+--------+----------+----------+------------+
| emp_id | emp_name | salary   | department |
+--------+----------+----------+------------+
|    101 | Bhavya   | 45000.00 | IT         |
|    102 | pavani   | 35000.00 | Finance    |
|    103 | anitha   | 40000.00 | IT         |
+--------+----------+----------+------------+
3 rows in set (0.00 sec)
```

RESULT

Thus, UPDATE and DELETE commands were executed successfully to modify employee details and remove a selected employee record. The table structure remained unchanged.