

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 7.11 Revision Date 02.07.2024 Print Date 27.08.2024

GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifiers

Product name : Methanol for liquid chromatography

LiChrosolv®

: 1.06018 **Product Number** Catalogue No. : 106018 Brand : Millipore Index-No.

: 603-001-00-X

REACH No. 01-2119433307-44-XXXX

CAS-No. 67-56-1

Relevant identified uses of the substance or mixture and uses advised against 1.2

Identified uses : Reagent for analysis, Solvent, Analytical and preparative

chromatography

Details of the supplier of the safety data sheet

Sigma-Aldrich Chemical Pvt Limited Company

Industrial Area, Anekal Taluka

Plot No 12,

12 Bommasandra - Jigani Link Road

560100 BANGALORE

INDIA

Emergency telephone 1.4

Emergency Phone # : 000 800 1007 141 (CHEMTREC)

SECTION 2: Hazards identification

Classification of the substance or mixture

H225: Highly flammable liquid and vapor. Flammable liquids, (Category 2)

Acute toxicity, (Category 3) H301: Toxic if swallowed.

H331: Toxic if inhaled. Acute toxicity, (Category 3)

Acute toxicity, (Category 3) H311: Toxic in contact with skin.

Millipore- 1.06018 Page 1 of 16



Specific target organ toxicity single exposure, (Category 1), Eyes, Central nervous system H370: Causes damage to organs.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal Word Danger

Hazard Statements

H225 Highly flammable liquid and vapor.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.

H370 Causes damage to organs (Eyes, Central nervous system).

Precautionary Statements

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P233 Keep container tightly closed.

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water.

P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER/ doctor.

Supplemental Hazard

Statements

none

Reduced Labeling (<= 125 ml)

Pictogram

Signal Word Danger

Hazard Statements

H370 Causes damage to organs.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.

Precautionary Statements

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER/ doctor.

Supplemental Hazard none

Statements

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Millipore- 1.06018 Page 2 of 16



Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Toxicological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula : CH40

Molecular weight : 32,04 g/mol

CAS-No. : 67-56-1

EC-No. : 200-659-6

Index-No. : 603-001-00-X

Component		Classification	Concentration
Methanol			
CAS-No. EC-No. Index-No.	67-56-1 200-659-6 603-001-00-X	Flam. Liq. 2; Acute Tox. 3; STOT SE 1; H225, H301, H331, H311, H370 Concentration limits: >= 10 %: STOT SE 1, H370; 3 - < 10 %: STOT SE 2, H371;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

Millipore- 1.06018 Page 3 of 16

M

If swallowed

After swallowing: fresh air. Make victim drink ethanol (e.g. 1 drinking glass of a 40% alcoholic beverage). Call a doctor immediately (mention methanol ingestion). Only in exceptional cases, if no medical care is available within one hour, induce vomiting (only in fully conscious persons) and make victim drink ethanol again (approx. 0.3 ml of a 40% alcoholic beverage/kg body weight/hour).

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

Millipore- 1.06018 Page 4 of 16

A

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Derived No Effect Level (DNEL)

	· · · (- · · -)		
Application Area	Routes of exposure	Health effect	Value
Worker DNEL, acute	dermal	Systemic effects	
Worker DNEL, acute	inhalation	Systemic effects	260 mg/m3
Worker DNEL, acute	inhalation	Local effects	260 mg/m3

Millipore- 1.06018 Page 5 of 16



Worker DNEL, longterm	dermal	Systemic effects	
Worker DNEL, longterm	inhalation	Systemic effects	260 mg/m3
Worker DNEL, longterm	inhalation	Local effects	260 mg/m3
Consumer DNEL, acute	dermal	Systemic effects	
Consumer DNEL, acute	inhalation	Systemic effects	50 mg/m3
Consumer DNEL, acute	oral	Systemic effects	
Consumer DNEL, acute	inhalation	Local effects	50 mg/m3
Consumer DNEL, longterm	dermal	Systemic effects	
Consumer DNEL, longterm	inhalation	Systemic effects	50 mg/m3
Consumer DNEL, longterm	oral	Systemic effects	
Consumer DNEL, longterm	inhalation	Local effects	50 mg/m3

Predicted No Effect Concentration (PNEC)

· · · · · · · · · · · · · · · · · · ·		
Compartment	Value	
Fresh water	154 mg/l	
Fresh water sediment	570,4 mg/kg	
Sea water	15,4 mg/l	
Soil	23,5 mg/kg	
Sewage treatment plant	100 mg/l	

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

ntact

Material: butyl-rubber

Minimum layer thickness: 0,7 mm Break through time: 480 min

Material tested:Butoject® (KCL 898)

Millipore- 1.06018 Page 6 of 16

M

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact Material: Viton®

Minimum layer thickness: 0,7 mm Break through time: 120 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system. Recommended Filter type: Filter type AX

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

a) Physical state liquid

b) Color

c) Odor characteristic

d) Melting Melting point: -97,8 °C - (ECHA)

colorless

point/freezing point

e) Initial boiling point and boiling range

64,7 °C at 1.013 hPa - (ECHA)

Flammability (solid,

gas)

No data available

g) Upper/lower Upper explosion limit: 44 %(V) flammability or Lower explosion limit: 5,5 %(V)

explosive limits

9,7 °C - closed cup - Regulation (EC) No. 440/2008, Annex, A.9 h) Flash point

Autoignition 455.0 °C

> at 1.013 hPa - DIN 51794 temperature

Decomposition Distillable in an undecomposed state at normal pressure. i) temperature

Millipore- 1.06018 Page 7 of 16



k) pH No data available

I) Viscosity Viscosity, kinematic: 0,54 - 0,59 mm2/s at 20 °C

Viscosity, dynamic: > 0,544 - < 0,59 mPa.s at 25 °C

m) Water solubility 1.000 g/l at 20 °C - completely miscible

n) Partition coefficient: log Pow: -0,77 at 25 °C - (HSDB), Bioaccumulation is not

n-octanol/water expected.

o) Vapor pressure 169,27 hPa at 25 °C p) Density 0,79 g/cm3 at 20 °C

Relative density 0,79 - 0,8 at 20 °C

q) Relative vapor

density

1,11

r) Particle

characteristics

No data available

s) Explosive properties No data available

t) Oxidizing properties none

9.2 Other safety information

Minimum ignition 0,14 mJ

energy

Conductivity $< 1 \mu S/cm$

Relative vapor

density

1,11

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion with:

Oxidizing agents

perchloric acid

perchlorates

salts of oxyhalogenic acids

chromium(VI) oxide

halogen oxides

nitrogen oxides

nonmetallic oxides

chromosulfuric acid

chlorates

hydrides

Millipore- 1.06018 Page 8 of 16



zinc diethyl halogens

powdered magnesium

hydrogen peroxide

Nitric acid

sulfuric acid

permanganic acid

sodium hypochlorite

Exothermic reaction with:

acid halides

Acid anhydrides

Reducing agents

acids

Bromine

Chlorine

Chloroform

magnesium

tetrachloromethane

Risk of ignition or formation of inflammable gases or vapours with:

Fluorine

Oxides of phosphorus

Raney-nickel

Generates dangerous gases or fumes in contact with:

Alkaline earth metals

Alkali metals

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity estimate Oral - 100,1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Nausea, Vomiting

Acute toxicity estimate Inhalation - 4 h - 3,1 mg/l - vapor

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300,1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Millipore- 1.06018 Page 9 of 16



Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

Remarks: (ECHA)

Remarks: Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation Remarks: (ECHA)

Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

Did not show carcinogenic effects in animal experiments.

Reproductive toxicity

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Causes damage to organs. - Eyes, Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Millipore- 1.06018 Page 10 of 16

11.2 Additional Information

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain

components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Acute effects:, Headache, Dizziness, Drowsiness, narcosis, Blindness, Impairment of vision, irritant effects, Nausea, Vomiting, agitation, spasms, inebriation, Coma

Drying-out effect resulting in rough and chapped skin.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

acidosis
drop in blood pressure
agitation, spasms
inebriation
Dizziness
Drowsiness
Headache
Impairment of vision
Blindness
narcosis
Coma

Symptoms may be delayed.

Damage to:

Liver Kidney Cardiac

Irreversible damage of the optical nerve.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish flow-through test LC50 - Lepomis macrochirus (Bluegill) - 15.400,0

mg/l - 96 h (US-EPA)

Millipore- 1.06018 Page 11 of 16



Toxicity to daphnia semi-static test EC50 - Daphnia magna (Water flea) - 18.260 mg/l -

and other aquatic

invertebrates (OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata (green algae) - ca.

> 22.000,0 mg/l - 96 h (OECD Test Guideline 201)

Toxicity to bacteria static test IC50 - activated sludge - > 1.000 mg/l - 3 h

(OECD Test Guideline 209)

NOEC - Oryzias latipes (Orange-red killifish) - 7.900 mg/l - 200 h Toxicity to

Remarks: (External MSDS) fish(Chronic toxicity)

12.2 Persistence and degradability

Biodegradability Result: 99 % - Readily biodegradable.

(OECD Test Guideline 301D)

Biochemical Oxygen 600 - 1.120 mg/g Demand (BOD) Remarks: (IUCLID)

Chemical Oxygen 1.420 mg/g

Remarks: (IUCLID) Demand (COD)

Theoretical oxygen $1.500 \, \text{mg/g}$ demand Remarks: (Lit.)

Ratio BOD/ThBOD 76 %

Remarks: Closed Bottle test(IUCLID)

12.3 Bioaccumulative potential

Bioaccumulation Cyprinus carpio (Carp) - 72 d

at 20 °C - 5 mg/l(Methanol)

Bioconcentration factor (BCF): 1,0

12.4 Mobility in soil

Will not adsorb on soil.

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

> considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Additional ecological Avoid release to the environment. information

Millipore- 1.06018 Page 12 of 16

Stability in water at 19 °C83 - 91 % - 72 h

Remarks: Hydrolyzes on contact with water. Hydrolyzes readily.

- 2,2 yr

Remarks: reaction with hydroxyl radicals(IUCLID)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1230 IMDG: 1230 IATA: 1230

14.2 UN proper shipping name

ADR/RID: METHANOL IMDG: METHANOL IATA: Methanol

14.3 Transport hazard class(es)

ADR/RID: 3 (6.1) IMDG: 3 (6.1) IATA: 3 (6.1)

14.4 Packaging group

ADR/RID: II IMDG: II IATA: II

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

Tunnel restriction code : (D/E)

Further information : No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Authorisations and/or restrictions on use

REACH - Restrictions on the manufacture, : Methanol placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

National legislation

Millipore- 1.06018 Page 13 of 16



Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

H2 ACUTE TOXIC

P5c FLAMMABLE LIQUIDS

22 Methanol

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of H-Statements

H225	Highly flammable liquid and vapor
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.

Millipore- 1.06018 Page 14 of 16



Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM -American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS -Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Millipore- 1.06018 Page 15 of 16

M

Millipore- 1.06018 Page 16 of 16

