

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 7.5  
Revision Date 16.04.2024  
Print Date 23.06.2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifiers

Product name : Methyl Alcohol (3 x 1.5 mL)

Product Number : 1424109

Brand : US Pharmacopeia

Index-No. : 603-001-00-X

REACH No. : 01-2119433307-44-XXXX

CAS-No. : 67-56-1

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

### 1.3 Details of the supplier of the safety data sheet

Company : Merck Life Science UK Limited  
New Road  
The Old Brickyard  
GILLINGHAM  
Dorset  
SP8 4XT  
UNITED KINGDOM

Telephone : +44 (0)1747 833-000

Fax : +44 (0)1747 833-313

E-mail address : TechnicalService@merckgroup.com

### 1.4 Emergency telephone

Emergency Phone # : +44 (0)870 8200418 (CHEMTREC)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567**

Flammable liquids, (Category 2) H225: Highly flammable liquid and vapor.

Acute toxicity, (Category 3) H301: Toxic if swallowed.

Acute toxicity, (Category 3) H331: Toxic if inhaled.

Acute toxicity, (Category 3) H311: Toxic in contact with skin.



Specific target organ toxicity -  
single exposure, (Category 1),  
Eyes, Central nervous system

H370: Causes damage to organs.

## 2.2 Label elements

### Labelling according Regulation (EC) No 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567

Pictogram



Signal Word

Danger

Hazard Statements

H225

Highly flammable liquid and vapor.

H301 + H311 + H331

Toxic if swallowed, in contact with skin or if inhaled.

H370

Causes damage to organs (Eyes, Central nervous system).

Precautionary Statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233

Keep container tightly closed.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P310

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P311

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.

Supplemental Hazard  
Statements

none

### Reduced Labeling (<= 125 ml)

Pictogram



Signal Word

Danger

Hazard Statements

H370

Causes damage to organs.

H301 + H311 + H331

Toxic if swallowed, in contact with skin or if inhaled.

Precautionary Statements

P301 + P310

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P304 + P340 + P311

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.

Supplemental Hazard  
Statements

none



### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Formula : CH<sub>4</sub>O  
Molecular weight : 32.04 g/mol  
CAS-No. : 67-56-1  
EC-No. : 200-659-6  
Index-No. : 603-001-00-X

Component		Classification	Concentration
<b>Methanol</b>			
CAS-No.	67-56-1	Flam. Liq. 2; Acute Tox. 3; STOT SE 1; H225, H301, H331, H311, H370 Concentration limits: >= 10 %: STOT SE 1, H370; 3 - < 10 %: STOT SE 2, H371;	<= 100 %
EC-No.	200-659-6		
Index-No.	603-001-00-X		

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

No data available

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available



---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

No data available

### 5.2 Special hazards arising from the substance or mixture

Carbon oxides  
Combustible.

### 5.3 Advice for firefighters

No data available

### 5.4 Further information

No data available

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For personal protection see section 8.

### 6.2 Environmental precautions

No data available

### 6.3 Methods and materials for containment and cleaning up

No data available

### 6.4 Reference to other sections

For disposal see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

No data available

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with workplace control parameters

Component	CAS-No.	Control parameters	Value	Basis
Methanol	67-56-1	TWA	200 ppm 260 mg/m <sup>3</sup>	Europe. Indicative occupational exposure limit values
	Remarks	Indicative Identifies the possibility of significant uptake through the		



		skin		
		TWA	200 ppm 266 mg/m3	UK. EH40 WEL - Workplace Exposure Limits
		Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	250 ppm 333 mg/m3	UK. EH40 WEL - Workplace Exposure Limits
		Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		

## 8.2 Exposure controls

### Personal protective equipment

#### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 120 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

#### Control of environmental exposure

Prevent product from entering drains.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- a) Physical state                      liquid
- b) Color                                      colorless



c) Odor	characteristic
d) Melting point/freezing point	Melting point: -97.8 °C - (ECHA)
e) Initial boiling point and boiling range	64.7 °C at 1,013 hPa - (ECHA)
f) Flammability (solid, gas)	No data available
g) Upper/lower flammability or explosive limits	Upper explosion limit: 44 %(V) Lower explosion limit: 5.5 %(V)
h) Flash point	9.7 °C - closed cup - Regulation (EC) No. 440/2008, Annex, A.9
i) Autoignition temperature	455.0 °C at 1,013 hPa - DIN 51794
j) Decomposition temperature	Distillable in an undecomposed state at normal pressure.
k) pH	No data available
l) Viscosity	Viscosity, kinematic: 0.54 - 0.59 mm <sup>2</sup> /s at 20 °C  Viscosity, dynamic: > 0.544 - < 0.59 mPa.s at 25 °C
m) Water solubility	1,000 g/l at 20 °C - completely miscible
n) Partition coefficient: n-octanol/water	log Pow: -0.77 at 25 °C - (HSDB), Bioaccumulation is not expected.
o) Vapor pressure	169.27 hPa at 25 °C
p) Density	0.79 g/cm <sup>3</sup> at 20 °C
Relative density	0.79 - 0.8 at 20 °C
q) Relative vapor density	1.11
r) Particle characteristics	No data available
s) Explosive properties	Not classified as explosive.
t) Oxidizing properties	none

## 9.2 Other safety information

Minimum ignition energy	0.14 mJ
Conductivity	< 1 µS/cm
Relative vapor density	1.11



---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available

### 10.2 Chemical stability

No data available

### 10.3 Possibility of hazardous reactions

Risk of explosion with:

Oxidizing agents  
perchloric acid  
perchlorates  
salts of oxyhalogenic acids  
chromium(VI) oxide  
halogen oxides  
nitrogen oxides  
nonmetallic oxides  
chromosulfuric acid  
chlorates  
hydrides  
zinc diethyl  
halogens  
powdered magnesium  
hydrogen peroxide  
Nitric acid  
sulfuric acid  
permanganic acid  
sodium hypochlorite  
Exothermic reaction with:  
acid halides  
Acid anhydrides  
Reducing agents  
acids  
Bromine  
Chlorine  
Chloroform  
magnesium  
tetrachloromethane  
Risk of ignition or formation of inflammable gases or vapours with:  
Fluorine  
Oxides of phosphorus  
Raney-nickel  
Generates dangerous gases or fumes in contact with:  
Alkaline earth metals  
Alkali metals

### 10.4 Conditions to avoid

No data available

### 10.5 Incompatible materials

No data available



## 10.6 Hazardous decomposition products

In the event of fire: see section 5

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Acute toxicity estimate Oral - 100.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Nausea, Vomiting

Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l - vapor

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

Remarks: (ECHA)

Remarks: Drying-out effect resulting in rough and chapped skin.

#### Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

Remarks: (ECHA)

#### Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative

(OECD Test Guideline 406)

#### Germ cell mutagenicity

Based on available data the classification criteria are not met.

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow





Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

### **Carcinogenicity**

Did not show carcinogenic effects in animal experiments.

### **Reproductive toxicity**

Based on available data the classification criteria are not met.

### **Specific target organ toxicity - single exposure**

Causes damage to organs. - Eyes, Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

### **Specific target organ toxicity - repeated exposure**

No data available

### **Aspiration hazard**

No data available

## **11.2 Additional Information**

### **Endocrine disrupting properties**

#### **Product:**

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Acute effects:, Headache, Dizziness, Drowsiness, narcosis, Blindness, Impairment of vision, irritant effects, Nausea, Vomiting, agitation, spasms, inebriation, Coma

Drying-out effect resulting in rough and chapped skin.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

acidosis  
drop in blood pressure  
agitation, spasms  
inebriation  
Dizziness  
Drowsiness  
Headache  
Impairment of vision  
Blindness  
narcosis  
Coma

Symptoms may be delayed.

Damage to:

Liver



Kidney  
Cardiac  
Irreversible damage of the optical nerve.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish	flow-through test LC50 - <i>Lepomis macrochirus</i> (Bluegill) - 15,400.0 mg/l - 96 h (US-EPA)
Toxicity to daphnia and other aquatic invertebrates	semi-static test EC50 - <i>Daphnia magna</i> (Water flea) - 18,260 mg/l - 96 h (OECD Test Guideline 202)
Toxicity to algae	static test ErC50 - <i>Pseudokirchneriella subcapitata</i> (green algae) - ca. 22,000.0 mg/l - 96 h (OECD Test Guideline 201)
Toxicity to bacteria	static test IC50 - activated sludge - > 1,000 mg/l - 3 h (OECD Test Guideline 209)
Toxicity to fish(Chronic toxicity)	NOEC - <i>Oryzias latipes</i> (Orange-red killifish) - 7,900 mg/l - 200 h Remarks: (External MSDS)

### 12.2 Persistence and degradability

Biodegradability	Result: 99 % - Readily biodegradable. (OECD Test Guideline 301D)
Biochemical Oxygen Demand (BOD)	600 - 1,120 mg/g Remarks: (IUCLID)
Chemical Oxygen Demand (COD)	1,420 mg/g Remarks: (IUCLID)
Theoretical oxygen demand	1,500 mg/g Remarks: (Lit.)
Ratio BOD/ThBOD	76 % Remarks: Closed Bottle test(IUCLID)

### 12.3 Bioaccumulative potential

Bioaccumulation	Cyprinus carpio (Carp) - 72 d at 20 °C - 5 mg/l(Methanol)
	Bioconcentration factor (BCF): 1.0

### 12.4 Mobility in soil

Will not adsorb on soil.



## 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

Additional ecological information Avoid release to the environment.

Stability in water at 19 °C 83 - 91 % - 72 h  
Remarks: Hydrolyzes on contact with water. Hydrolyzes readily.  
- 2.2 yr  
Remarks: reaction with hydroxyl radicals(IUCLID)

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

No data available

---

## SECTION 14: Transport information

### 14.1 UN number

ADR/RID: 1230                      IMDG: 1230                      IATA: 1230

### 14.2 UN proper shipping name

ADR/RID: METHANOL  
IMDG: METHANOL  
IATA: Methanol

### 14.3 Transport hazard class(es)

ADR/RID: 3 (6.1)                      IMDG: 3 (6.1)                      IATA: 3 (6.1)

### 14.4 Packaging group

ADR/RID: II                      IMDG: II                      IATA: II

### 14.5 Environmental hazards

ADR/RID: no                      IMDG Marine pollutant: no                      IATA: no

### 14.6 Special precautions for user

Tunnel restriction code : (D/E)



Further information : No data available

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

#### Authorisations and/or restrictions on use

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Methanol

#### National legislation

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. H2 ACUTE TOXIC

P5c FLAMMABLE LIQUIDS

22 Methanol

### 15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

---

## SECTION 16: Other information

### Full text of H-Statements

H225	Highly flammable liquid and vapor.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.



## Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).

