SECURITY ACCESS CONTROL
EQUIPMENT & DEVICES SCHEDULE

1- REVISION 0 - REVIEW IN QUANTITIES

TAG	STATUS	EQUIPMENT NAME	TYPE	MANUFACTURER	MODEL	CAPACITY	DIMENSIONS (mm)	MATERIAL	REMARKS	QUANTITY	REFERENCE DRAWING
BUILDING 7A											
ACU-A1001-01 ACU-A1011-01 ACU-A1011-02 ACU-A1015-01 ACU-A1017-01 ACU-A1020-01 ACU-A1021-01 ACU-A1026-01 ACU-A1034-01 ACU-A1039-01 ACU-A1041-01 ACU-A1049-01 ACU-A2005-01 ACU-A2026-01 ACU-A2027-01 ACU-A2030-01 ACU-A2031-01 ACU-A2032-01 ACU-A2034-01 ACU-A2035-01 ACU-A2038-01 ACU-A2039-01 ACU-A2046-01 ACU-A2049-01 ACU-A2049-02 ACU-A3002-01 ACU-A3003-01 ACU-A3009-01 ACU-A3005-01 ACU-A3006-01 ACU-A2010-01 ACU-A2011-01 ACU-A2013-01 ACU-A2014-01 ACU-A2015-01 ACU-A2017-01 ACU-A2019-01 ACU-A1043-01 ACU-A1035-01 ACU-A1040-01 ACU-A1038-01 ACU-A1037-01 ACU-A1025-01 ACU-C1001-01 ACU-C1003-01 ACU-A2021-01 ACU-A1039-02	NEW	ACCESS CONTROL UNIT (ACU) WITH INTERLOCK OPTION	37-BIT WIEGAND FORMAT	PCSC	IQ-6-P6-L-12-X-LAN	6 ID CARDS READERS	292 mm W x 457 mm H x 152 mm D 11.5" W x 18"H x 6" D	16 AWG Cold Rolled Steel (CRS) enclosure with Tamper, Lock, and Key	PCSC Access controler for 6 readers, 6 relays, 30 DI, 12 TTL Outputs, Onboard LAN port installed in Large Enclosure cabinet UL (21.8" H x 16.1" W x 5.7" D), 220VAC to 12VDC@6,5A operating voltage	48	7A-I-0-3-02 7A-I-1-3-12 7A-I-2-3-22 7A-I-3-3-32
-	NEW	PROXIMITY READERS - CR	37-BIT WIEGAND FORMAT	PCSC	PR732	Weigand 125KHz	137 mm (HEIGHT) x 44 mm (WIDHT) x 27.5 mm (DEPTH)	-	Reader 125K	121	
-	NEW	CONTACT DOOR - ZS	MAGNETIC	Honeywell	7940WH	SINGLE POLE SINGLE THROW	6.35 mm x 9.5 mm x 50.8 mm	-	Universal Door contact screw mount, adhesive mount or recess. Super wide gap of 2" (51mm) is standard or 1" (25mm) end-to-end recessed	132	
-	NEW	ELECTRIC STRIKE - ES	ELECTRIC	PCSC	ES-125-SS	1000 LBS	165mm x 44mm x 38mm	-	Fail Secure Stainless door strike	116	

TAG	STATUS	EQUIPMENT NAME	TYPE	MANUFACTURER	MODEL	CAPACITY	DIMENSIONS (mm)	MATERIAL	REMARKS	QUANTITY	REFERENCE DRAWING
-	NEW	MAG LOCK - ML	MAGNETIC	PCSC	ML600DS	600 LBS	L- 9.8in (250mm) W- 1.7in (42mm) D- 1.0in (26mm	Stainless Steel	600 LBS Maglock,12/24 VDC, w/door sense, Heavy duty design	5	
-	NEW	EMERGENCY BUTTON - P	WALL MOUNT	Assa Abloy	CP-32G	SINGLE OR DOUBLE DOOR USE	89mm H x 89MM W x 63.5"D	ABS 757 plastic construction	Emergency overwrite 2stage button, with NO and NC contacts	53	
-	NEW	ID CARDS	PVC PLASTIC CARD	PCSC	PC-73	CARDS WITH CHIP EMBEDDED AND FREQUENCY OF 13.56 MHZ	-	Plastic	PCSC Standard 125KHz HID Proximit card ID in 37 Bit CORP1000 format	100	-

TAG	STATUS	EQUIPMENT NAME	TYPE	MANUFACTURER	MODEL	CAPACITY	DIMENSIONS (mm)	MATERIAL	REMARKS	QUANTITY	REFERENCE DRAWING
BUILDING 7B											
ACU-B1001-01 ACU-B1001-02 ACU-B1013-01 ACU-B1013-02 ACU-B1013-03 ACU-B1016-01 ACU-B1016-01 ACU-B1022-01 ACU-B1024-01 ACU-B1025-01 ACU-B1028-01 ACU-B1032-01 ACU-B1033-01 ACU-B1034-01 ACU-B2011-01 ACU-B2012-01 ACU-B2013-01 ACU-B2014-01 ACU-B2018-01 ACU-B2019-01 ACU-B2020-01 ACU-B2022-01 ACU-B2023-01 ACU-B2024-01 ACU-B2024-02 ACU-B2025-01 ACU-B2025-02 ACU-B2026-01 ACU-B2027-01 ACU-B2030-01 ACU-B2033-01 ACU-B2034-01 ACU-B2035-01 ACU-B2036-01 ACU-B2040-01 ACU-B2041-01 ACU-B2042-01 ACU-B2043-01 ACU-B3010-01 ACU-B3011-01 ACU-B3012-01 ACU-B2029-01 ACS-B2056-01 ACS-B2056-02 ACS-B2056-03 ACS-B2056-04 ACS-B3001-01 ACS-B3001-02 ACS-B3007-01	NEW	ACCESS CONTROL UNIT (ACU) WITH INTERLOCK OPTION	37-BIT WIEGAND FORMAT	PCSC	IQ-6-P6-L-12-X-LAN	6 ID CARDS READERS	292 mm W x 457 mm H x 152 mm D 11.5" W x 18"H x 6" D	16 AWG Cold Rolled Steel (CRS) enclosure with Tamper, Lock, and Key	PCSC Access controler for 6 readers, 6 relays, 30 DI, 12 TTL Outputs, Onboard LAN port installed in Large Enclosure cabinet UL (21.8" H x 16.1" W x 5.7" D), 220VAC to 12VDC@6,5A operating voltage	49	7B-I-0-3-02 7B-I-1-3-12 7B-I-2-3-22 7B-I-3-3-32

TAG	STATUS	EQUIPMENT NAME	TYPE	MANUFACTURER	MODEL	CAPACITY	DIMENSIONS (mm)	MATERIAL	REMARKS	QUANTITY	REFERENCE DRAWING
-	NEW	PROXIMITY READERS - CR	37-BIT WIEGAND FORMAT	PCSC	PR732	Weigand 125KHz	137 mm (HEIGHT) x 44 mm (WIDHT) x 27.5 mm (DEPTH)	-	Reader 125K	119	
-	NEW	CONTACT DOOR - ZS	MAGNETIC	Honeywell	7940WH	SINGLE POLE SINGLE THROW	6.35 mm x 9.5 mm x 50.8 mm	-	Universal Door contact screw mount, adhesive mount or recess. Super wide gap of 2" (51mm) is standard or 1" (25mm) end-to-end recessed	133	
-	NEW	ELECTRIC STRIKE - ES	ELECTRIC	PCSC	ES-125-SS	1000 LBS	165mm x 44mm x 38mm	-	Fail Secure Stainless door strike	45	
-	NEW	MAG LOCK - ML	MAGNETIC	PCSC	ML600DS	600 LBS	L- 9.8in (250mm) W- 1.7in (42mm) D- 1.0in (26mm	Stainless Steel	600 LBS Maglock,12/24 VDC, w/door sense, Heavy duty design	80	
-	NEW	EMERGENCY BUTTON - P	WALL MOUNT	Assa Abloy	CP-32G	SINGLE OR DOUBLE DOOR USE	89mm H x 89MM W x 63.5"D	ABS 757 plastic construction	Emergency overwrite 2stage button, with NO and NC contacts	54	
-	NEW	ID CARDS	PVC PLASTIC CARD	PCSC	PC-73	CARDS WITH CHIP EMBEDDED AND FREQUENCY OF 13.56 MHZ	-	Plastic	PCSC Standard 125KHz HID Proximit card ID in 37 Bit CORP1000 format	100	-

BUILDING 7C

TAG	STATUS	EQUIPMENT NAME	TYPE	MANUFACTURER	MODEL	CAPACITY	DIMENSIONS (mm)	MATERIAL	REMARKS	QUANTITY	REFERENCE DRAWING
ACU-C1001-01 ACU-C1002-01 ACU-C1002-02 ACU-C1003-01	NEW	ACCESS CONTROL UNIT (ACU) WITH INTERLOCK OPTION	37-BIT WIEGAND FORMAT	PCSC	IQ-6-P6-L-12-X-LAN	6 ID CARDS READERS	292 mm W x 457 mm H x 152 mm D 11.5" W x 18"H x 6" D	16 AWG Cold Rolled Steel (CRS) enclosure with Tamper, Lock, and Key	PCSC Access controler for 6 readers, 6 relays, 30 DI, 12 TTL Outputs, Onboard LAN port installed in Large Enclosure cabinet UL (21.8" H x 16.1" W x 5.7" D), 220VAC to 12VDC@6,5A operating voltage	4	
-	NEW	PROXIMITY READERS	37-BIT WIEGAND FORMAT	PCSC	PR732	Weigand 125KHz	137 mm (HEIGHT) x 44 mm (WIDHT) x 27.5 mm (DEPTH)	-	Reader 125K	6	7C-I-1-3-12
-	NEW	CONTACT DOOR	MAGNETIC	Honeywell	7940WH	SINGLE POLE SINGLE THROW	6.35 mm x 9.5 mm x 50.8 mm	-	Universal Door contact screw mount, adhesive mount or recess. Super wide gap of 2" (51mm) is standard or 1" (25mm) end-to-end recessed	4	
-	NEW	MAG LOCK	MAGNETIC	PCSC	ML600DS	600 LBS	L- 9.8in (250mm) W- 1.7in (42mm) D- 1.0in (26mm	Stainless Steel	600 LBS Maglock,12/24 VDC, w/door sense, Heavy duty design	4	
-	NEW	EMERGENCY BUTTON	WALL MOUNT	Assa Abloy	CP-32G	SINGLE OR DOUBLE DOOR USE	89mm H x 89MM W x 63.5"D	ABS 757 plastic construction	Emergency overwrite 2stage button, with NO and NC contacts	3	

TAG	STATUS	EQUIPMENT NAME	TYPE	MANUFACTURER	MODEL	CAPACITY	DIMENSIONS (mm)	MATERIAL	REMARKS	QUANTITY	REFERENCE DRAWING
BUILDING 7F											
ACU-F1001-01 ACU-F1002-01	NEW	ACCESS CONTROL UNIT (ACU) WITH INTERLOCK OPTION	37-BIT WIEGAND FORMAT	PCSC	IQ-6-P6-L-12-X-LAN	6 ID CARDS READERS	292 mm W x 457 mm H x 152 mm D 11.5" W x 18"H x 6" D	16 AWG Cold Rolled Steel (CRS) enclosure with Tamper, Lock, and Key	PCSC Access controler for 6 readers, 6 relays, 30 DI, 12 TTL Outputs, Onboard LAN port installed in Large Enclosure cabinet UL (21.8" H x 16.1" W x 5.7" D), 220VAC to 12VDC@6,5A operating voltage	2	7F-I-1-3-12
-	NEW	PROXIMITY READERS	37-BIT WIEGAND FORMAT	PCSC	PR732	Weigand 125KHz	137 mm (HEIGHT) x 44 mm (WIDHT) x 27.5 mm (DEPTH)	-	Reader 125K	4	
-	NEW	CONTACT DOOR	MAGNETIC	Honeywell	7940WH	SINGLE POLE SINGLE THROW	6.35 mm x 9.5 mm x 50.8 mm	-	Universal Door contact screw mount, adhesive mount or recess. Super wide gap of 2" (51mm) is standard or 1" (25mm) end-to-end recessed	2	
-	NEW	MAG LOCK	MAGNETIC	PCSC	ML600DS	600 LBS	L- 9.8in (250mm) W- 1.7in (42mm) D- 1.0in (26mm)	Stainless Steel	600 LBS Maglock,12/24 VDC, w/door sense, Heavy duty design	2	
-	NEW	EMERGENCY BUTTON	WALL MOUNT	Assa Abloy	CP-32G	SINGLE OR DOUBLE DOOR USE	89mm H x 89MM W x 63.5"D	ABS 757 plastic construction	Emergency overwrite 2stage button, with NO and NC contacts,	2	