

From causal salads to causal inference

Francisco Rodríguez-Sánchez


<https://frodriguezsanchez.net>



Self-learnt stuff ahead



Larger flowers produce more seeds



Larger flowers produce more seeds

```
lm(seeds ~ flower.size)
```

| <i>Variable</i> | <i>Beta</i> | <i>SE</i> | <i>p.value</i> |
|-----------------|-------------|-----------|----------------|
| (Intercept) | 57 | 10.1 | <0.001 |
| flower.size | 11 | 0.978 | <0.001 |

Does flower size
really **cause**
increased seed production?

Shall we select plants with large flowers
to increase seed production?


Shall we select plants with large flowers
to increase seed production?

We tried but didn't get the expected benefits

Maybe large plants (e.g. growing on better soil)
have large flowers AND produce more seeds?



Maybe plant size is a **CONFOUNDER**?



Adjusting for plant size (confounding)

```
lm(seeds ~ flower.size + plant.size)
```

| <i>Variable</i> | <i>Beta</i> | <i>SE</i> | <i>p.value</i> |
|--------------------|-------------|-------------|------------------|
| (Intercept) | 12 | 12.9 | 0.4 |
| flower.size | 6.6 | 1.18 | <0.001 |
| plant.size | 0.82 | 0.168 | <0.001 |

Including pollinators (bees)




Including pollinators (bees)

```
lm(seeds ~ flower.size + plant.size + bees)
```

| <i>Variable</i> | <i>Beta</i> | <i>SE</i> | <i>p.value</i> |
|--------------------|-------------|-------------|----------------|
| (Intercept) | 5.2 | 12.1 | 0.7 |
| flower.size | 2.1 | 1.56 | 0.2 |
| plant.size | 0.90 | 0.157 | <0.001 |
| bees | 8.8 | 2.14 | <0.001 |

Pollinators are a **MEDIATOR**




Including beetles (pollen & seed predators)

```
lm(seeds ~ flower.size + plant.size + bees +  
beetles)
```


| <i>Variable</i> | <i>Beta</i> | <i>SE</i> | <i>p.value</i> |
|--------------------|-------------|-------------|----------------|
| (Intercept) | -11 | 8.67 | 0.2 |
| flower.size | -3.8 | 1.25 | 0.003 |
| plant.size | 0.47 | 0.118 | <0.001 |
| bees | 4.8 | 1.56 | 0.003 |
| beetles | 5.2 | 0.529 | <0.001 |

Now flower.size has negative coefficient!!


Beetles are a COLLIDER




Colliders induce negative relation between treatment (flower.size) and outcome (seeds)



What is the real causal effect of flower size?




What is the real causal effect of flower size?




| Variable | Beta | SE | p.value |
|--------------------|-------------|-------------|--------------|
| (Intercept) | -11 | 8.67 | 0.2 |
| flower.size | -3.8 | 1.25 | 0.003 |
| plant.size | 0.47 | 0.118 | <0.001 |
| bees | 4.8 | 1.56 | 0.003 |
| beetles | 5.2 | 0.529 | <0.001 |

What is the real causal effect of flower size?




AVOID COLLIDERS!

What is the real causal effect of flower size?




| Variable | Beta | SE | p.value |
|--------------------|------------|-------------|------------|
| (Intercept) | 5.2 | 12.1 | 0.7 |
| flower.size | 2.1 | 1.56 | 0.2 |
| plant.size | 0.90 | 0.157 | <0.001 |
| bees | 8.8 | 2.14 | <0.001 |

What is the real causal effect of flower size?




MEDIATORS split **total effect** into **direct** and **indirect** effects

What is the real causal effect of flower size?



| <i>Variable</i> | <i>Beta</i> | <i>SE</i> | <i>p.value</i> |
|--------------------|-------------|-------------|------------------|
| (Intercept) | 12 | 12.9 | 0.4 |
| flower.size | 6.6 | 1.18 | <0.001 |
| plant.size | 0.82 | 0.168 | <0.001 |


What is the real causal effect of flower size?



Include **CONFOUNDERS** to avoid bias (backdoor criterion)

Tools to identify correct causal structure

```
dagify(  
  seeds ~ plant.size + flower.size + bees,  
  flower.size ~ plant.size,  
  bees ~ flower.size,  
  beetles ~ flower.size + seeds,  
  coords = coords  
) |>  
ggdag_collider(size = 2) + theme_dag_blank()
```



Causal salads

Causal salads

You put everything into a regression equation, toss with some creative story-telling, and hope the reviewers eat it

R. McElreath



Jerry Pank

*Throwing predictor variables into a statistical model
hoping this will improve the analysis is a dreadful idea*

Jan Vanhove

Predictive criteria don't help for
causal inference

Predictive criteria don't help to choose correct causal model

Making good predictions doesn't require accurate causal model

| Model | AIC | R2 |
|-----------------------------|-------|-----|
| m.flower | 933.3 | 0.5 |
| m.flower.plant | 913.2 | 0.6 |
| m.flower.plant.bees | 899.1 | 0.7 |
| m.flower.plant.bees.beetles | 829.9 | 0.8 |

“Best model” (based on AIC or R2) not good for causal inference

Simpler (best) model provides biased causal estimates

Simulate response depending on two correlated variables (Hartig 2022)

```
x1 = runif(100)
x2 = 0.8*x1 + 0.2*runif(100)
y = x1 + x2 + rnorm(100)
```

| y | x1 | x2 |
|------|-----|-----|
| -0.1 | 0.3 | 0.4 |
| 1.7 | 0.8 | 0.7 |
| 0.6 | 0.4 | 0.4 |
| 1.4 | 0.9 | 0.9 |
| 0.8 | 0.9 | 0.8 |
| 0.2 | 0.0 | 0.2 |

Simpler (best) model provides biased causal estimates

Simulate response depending on two correlated variables (Hartig 2022)

```
fullmodel = lm(y ~ x1 + x2)
```

Call:

```
lm(formula = y ~ x1 + x2)
```

Residuals:

| Min | 1Q | Median | 3Q | Max |
|---------|---------|---------|--------|--------|
| -1.8994 | -0.6821 | -0.1086 | 0.5749 | 3.3663 |

Coefficients:

| | Estimate | Std. Error | t value | Pr(> t) |
|-------------|----------|------------|---------|----------|
| (Intercept) | -0.1408 | 0.2862 | -0.492 | 0.624 |
| x1 | 1.2158 | 1.5037 | 0.809 | 0.421 |
| x2 | 0.8518 | 1.8674 | 0.456 | 0.649 |

Residual standard error: 0.9765 on 97 degrees of freedom

Multiple R-squared: 0.237, Adjusted R-squared: 0.2212

F-statistic: 15.06 on 2 and 97 DF, p-value: 2.009e-06

Simpler (best) model provides biased causal estimates

```
simplemodel = MASS::stepAIC(fullmodel, trace = 0)
```

Call:

```
lm(formula = y ~ x1)
```

Residuals:

| Min | 1Q | Median | 3Q | Max |
|---------|---------|---------|--------|--------|
| -1.9047 | -0.6292 | -0.1019 | 0.6077 | 3.3394 |

Coefficients:

| | Estimate | Std. Error | t value | Pr(> t) |
|-------------|----------|------------|---------|--------------|
| (Intercept) | -0.04633 | 0.19670 | -0.236 | 0.814 |
| x1 | 1.88350 | 0.34295 | 5.492 | 3.13e-07 *** |

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 0.9725 on 98 degrees of freedom

Multiple R-squared: 0.2353, Adjusted R-squared: 0.2275

F-statistic: 30.16 on 1 and 98 DF, p-value: 3.134e-07

Automated model selection (dredge)

Simulating data with 10 random predictors

```
dat <- data.frame(y = rnorm(100),  
                  x = matrix(runif(1000), ncol = 10))
```

| y | x.1 | x.2 | x.3 | x.4 | x.5 | x.6 | x.7 | x.8 | x.9 | x.10 |
|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| -0.1 | 0.6 | 0.6 | 0.3 | 0.8 | 0.2 | 0.0 | 0.4 | 0.4 | 0.3 | 0.2 |
| 0.8 | 0.4 | 0.4 | 0.9 | 0.2 | 0.5 | 0.1 | 0.6 | 0.2 | 0.0 | 0.0 |
| -0.5 | 0.0 | 0.3 | 0.4 | 0.3 | 0.1 | 0.1 | 0.9 | 0.9 | 0.5 | 0.8 |
| -0.6 | 0.7 | 0.7 | 0.4 | 0.5 | 0.2 | 0.7 | 0.7 | 0.8 | 0.5 | 0.3 |
| 0.7 | 0.0 | 0.6 | 0.9 | 0.1 | 0.2 | 0.4 | 0.8 | 0.6 | 0.6 | 0.1 |
| -0.1 | 0.4 | 0.2 | 0.9 | 0.4 | 0.6 | 0.5 | 0.9 | 0.1 | 0.8 | 0.8 |

Automated model selection

Running `MuMIn::dredge` with 10 random predictors

```
full.model <- lm(y ~ ., data = dat)
dd <- MuMIn::dredge(full.model)
```

Best model:

| Parameter | Coefficient | SE | p |
|-------------|-------------|------|------|
| (Intercept) | -1.50 | 0.36 | 0.00 |
| x.2 | 0.78 | 0.36 | 0.03 |
| x.5 | 0.59 | 0.32 | 0.07 |
| x.6 | 0.61 | 0.35 | 0.09 |
| x.9 | 0.87 | 0.34 | 0.01 |


“Let the computer find out” is a poor strategy and usually reflects the fact that the researcher did not bother to think clearly about the problem of interest and its scientific setting

Burnham and Anderson 2002

Variable importance in machine learning


Random forest on 100 random predictors

```
dat <- data.frame(x = matrix(runif(50000), ncol = 100), y = runif(500))  
rfm <- randomForest::randomForest(y ~ ., data = dat)  
varImpPlot(rfm)
```




Simpson's paradox as a causal problem

Simpson's paradox



| <i>Variable</i> | <i>Beta</i> | <i>SE</i> | <i>p.value</i> |
|-----------------|-------------|-----------|----------------|
| (Intercept) | 344 | 10.7 | <0.001 |
| flower.size | -1.8 | 0.486 | <0.001 |


Simpson's paradox



| <i>Variable</i> | <i>Beta</i> | <i>SE</i> | <i>p.value</i> |
|--------------------|-------------|--------------|------------------|
| (Intercept) | 308 | 6.50 | <0.001 |
| flower.size | 5.7 | 0.500 | <0.001 |
| site | | | |
| 1 | — | — | |

Simpson's paradox

Site is a confounder!



From causal salads to causal inference

Causal interpretation requires external knowledge

To estimate causal effects accurately we require more information than can be gleaned from statistical tools alone

D'Agostino et al

Causal interpretation requires external knowledge

To estimate causal effects accurately we require more information than can be gleaned from statistical tools alone

D'Agostino et al

No amount of data reliably turns salad into sense

R. McElreath

From causal salad to causal inference

- Draw the **causal graph** (DAG) beforehand

From causal salad to causal inference

- Draw the **causal graph** (DAG) beforehand
- Control for **confounders**

From causal salad to causal inference

- Draw the **causal graph** (DAG) beforehand
- Control for **confounders**
- Avoid conditioning on **post-treatment variables**

From causal salad to causal inference

- Draw the **causal graph** (DAG) beforehand
- Control for **confounders**
- Avoid conditioning on **post-treatment variables**
 - Treatment -> Covariate -> Outcome

From causal salad to causal inference

- Draw the **causal graph** (DAG) beforehand
- Control for **confounders**
- Avoid conditioning on **post-treatment variables**
 - Treatment -> Covariate -> Outcome
- Beware of **collider bias**

From causal salad to causal inference

- Draw the **causal graph** (DAG) beforehand
- Control for **confounders**
- Avoid conditioning on **post-treatment variables**
 - Treatment -> Covariate -> Outcome
- Beware of **collider bias**
- **Predictive criteria** not fit for causal inference

To learn more

Suchinta Arif's papers

McElreath's workshop on causal inference

<https://www.r-causal.org>

<https://theeffectbook.net>