



Chulalongkorn University

# What Name ?

Pakapim E., Pasin P., Sarit P.

template from KACTL

2025-07-20

- 1 Template
- 2 Mathematics
- 3 Combinatorial
- 4 Data Structures
- 5 Number Theory
- 6 Graph
- 7 Tree
- 8 Strings
- 9 Geometry
- 10 Dynamic Programming
- 11 Polynomials
- 12 Convolutions
- 13 Various
- 14 Competitive Programming Topics

# Template (1)

```
template.cpp31 lines

#pragma once
#include <bits/stdc++.h>
#define sz(x) (int)(x).size()
#define all(x) (x).begin(), (x).end()

using namespace std;

typedef long long ll;
typedef double db;
typedef long double ld;
typedef pair<int, int> pii;
typedef pair<ll, ll> pll;

template<typename T> bool ckmin(T &a, const T &b) { return b < a ? a = b, 1 : 0; }
template<typename T> bool ckmax(T &a, const T &b) { return a < b ? a = b, 1 : 0; }

mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());

const char nl = '\n';
const int INF = 0x3fffffff;
const int MOD=1000000007;
// const int MOD = 998244353;
const ll LINF = 0xffffffffffffffff;
const db DINF = numeric_limits<db>::infinity();
```

```
1const db EPS = 1e-9;
1const db PI = acos(db(-1));
1
1signed main(){
1    ios_base::sync_with_stdio(0); cin.tie(NULL);
1    return 0;
1}
2c.sh
2
2g++ -std=gnu++2a -Wall $1 -o a.out
2./a.out
```

## Mathematics (2)

### 2.1 Goldbatch’s Conjecture

- Even number can be written in sum of two primes (Up to 1e12)
- Range of  $N^{th}$  prime and  $N + 1^{th}$  prime will be less than or equal to 300 (Up to 1e12)

### 2.2 Divisibility

Number of divisors of  $N$  is given by  $\prod_{i=1}^k (a_i + 1)$  where  $N = \prod_{i=1}^k p_i^{a_i}$  and  $p_i$  are prime factors of  $N$ .

## Combinatorial (3)

### 3.1 Permutations

#### 3.1.1 Factorial

$n$	1	2	3	4	5	6	7	8	9	10
$n!$	1	2	6	24	120	720	5040	40320	362880	3628800
$n$	11	12	13	14	15	16	17			
$n!$	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14			
$n$	20	25	30	40	50	100	150	171		
$n!$	2e18	2e25	3e32	8e47	3e64	9e157	6e262	>DBL_MAX		

IntPerm.h

#### 3.1.2 Cycles

Let  $g_S(n)$  be the number of  $n$ -permutations whose cycle lengths all belong to the set  $S$ . Then

$$\sum_{n=0}^{\infty} g_S(n) \frac{x^n}{n!} = \exp \left( \sum_{n \in S} \frac{x^n}{n} \right)$$

#### 3.1.3 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n - 1)(D(n - 1) + D(n - 2)) = nD(n - 1) + (-1)^n = \left\lfloor \frac{n!}{e} \right\rfloor$$

### 3.1.4 Burnside’s lemma

Given a group  $G$  of symmetries and a set  $X$ , the number of elements of  $X$  up to symmetry equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|,$$

where  $X^g$  are the elements fixed by  $g$  ( $g.x = x$ ).

If  $f(n)$  counts “configurations” (of some sort) of length  $n$ , we can ignore rotational symmetry using  $G = \mathbb{Z}_n$  to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(\gcd(n, k)) = \frac{1}{n} \sum_{k|n} f(k) \phi(n/k).$$

## 3.2 Partitions and subsets

### 3.2.1 Partition function

Number of ways of writing  $n$  as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1, \quad p(n) = \sum_{k \in \mathbb{Z} \setminus \{0\}} (-1)^{k+1} p(n - k(3k - 1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

$n$	0	1	2	3	4	5	6	7	8	9	20	50	100
$p(n)$	1	1	2	3	5	7	11	15	22	30	627	$\sim 2e5$	$\sim 2e8$

### 3.2.2 Lucas’ Theorem

Let  $n, m$  be non-negative integers and  $p$  a prime. Write  $n = n_k p^k + \dots + n_1 p + n_0$  and  $m = m_k p^k + \dots + m_1 p + m_0$ . Then  $\binom{n}{m} \equiv \prod_{i=0}^k \binom{n_i}{m_i} \pmod{p}$ .

### 3.2.3 Binomials

multinomial.h

## 3.3 General purpose numbers

### 3.3.1 Bernoulli numbers

EGF of Bernoulli numbers is  $B(t) = \frac{t}{e^t - 1}$  (FFT-able).

$$B[0, \dots] = [1, -\frac{1}{2}, \frac{1}{6}, 0, -\frac{1}{30}, 0, \frac{1}{42}, \dots]$$

Sums of powers:

$$\sum_{i=1}^n n^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k \cdot (n+1)^{m+1-k}$$

Euler-Maclaurin formula for infinite sums:

$$\begin{aligned} \sum_{i=m}^{\infty} f(i) &= \int_m^{\infty} f(x) dx - \sum_{k=1}^{\infty} \frac{B_k}{k!} f^{(k-1)}(m) \\ &\approx \int_m^{\infty} f(x) dx + \frac{f(m)}{2} - \frac{f'(m)}{12} + \frac{f'''(m)}{720} + O(f^{(5)}(m)) \end{aligned}$$

### 3.3.2 Stirling numbers of the first kind

Number of permutations on  $n$  items with  $k$  cycles.

$$c(n,k)=c(n-1,k-1)+(n-1)c(n-1,k),\; c(0,0)=1$$
$$\sum_{k=0}^nc(n,k)x^k=x(x+1)\ldots(x+n-1)$$

$$c(8,k)=8,0,5040,13068,13132,6769,1960,322,28,1$$
$$c(n,2)=0,0,1,3,11,50,274,1764,13068,109584,\ldots$$

### 3.3.3 Eulerian numbers

Number of permutations  $\pi\in S_n$  in which exactly  $k$  elements are greater than the previous element.  $k\;j$ :s s.t.  $\pi(j)>\pi(j+1)$ ,  $k+1\;j$ :s s.t.  $\pi(j)\geq j$ ,  $k\;j$ :s s.t.  $\pi(j)>j$ .

$$E(n,k)=(n-k)E(n-1,k-1)+(k+1)E(n-1,k)$$
$$E(n,0)=E(n,n-1)=1$$
$$E(n,k)=\sum_{j=0}^k(-1)^j\binom{n+1}{j}(k+1-j)^n$$

### 3.3.4 Stirling numbers of the second kind

Partitions of  $n$  distinct elements into exactly  $k$  groups.

$$S(n,k)=S(n-1,k-1)+kS(n-1,k)$$
$$S(n,1)=S(n,n)=1$$
$$S(n,k)=\frac{1}{k!}\sum_{j=0}^k(-1)^{k-j}\binom{k}{j}j^n$$

### 3.3.5 Bell numbers

Total number of partitions of  $n$  distinct elements.  $B(n)=1,1,2,5,15,52,203,877,4140,21147,\ldots$ . For  $p$  prime,

$$B(p^m+n)\equiv mB(n)+B(n+1)\pmod{p}$$

### 3.3.6 Labeled unrooted trees

# on  $n$  vertices:  $n^{n-2}$   
# on  $k$  existing trees of size  $n_i$ :  $n_1n_2\cdots n_kn^{k-2}$   
# with degrees  $d_i$ :  $(n-2)!/((d_1-1)!\cdots(d_n-1)!)$

### 3.3.7 Catalan numbers

$$C_n=\frac{1}{n+1}\binom{2n}{n}=\binom{2n}{n}-\binom{2n}{n+1}=\frac{(2n)!}{(n+1)!n!}$$
$$C_0=1,\; C_{n+1}=\frac{2(2n+1)}{n+2}C_n,\; C_{n+1}=\sum C_iC_{n-i}$$
$$C_n=1,1,2,5,14,42,132,429,1430,4862,16796,58786,\ldots$$

- sub-diagonal monotone paths in an  $n\times n$  grid.
- strings with  $n$  pairs of parenthesis, correctly nested.
- binary trees with with  $n+1$  leaves (0 or 2 children).

- ordered trees with  $n+1$  vertices.
- ways a convex polygon with  $n+2$  sides can be cut into triangles by connecting vertices with straight lines.
- permutations of  $[n]$  with no 3-term increasing subseq.

## Data Structures (4)

OrderedSet.hpp

SparseTable.hpp

FenwickTree.hpp

2DFenwickTree.hpp

SegmentTree.hpp

LazySegmentTree.hpp

DynamicSegmentTree.hpp

PersistentSegmentTree.hpp

LiChaoTree.hpp

BinaryTrie.hpp

MO.hpp

StaticTopTree.hpp

Treap.hpp

## Number Theory (5)

ExtendedEuclid.hpp

euclid.h

CRT.hpp

phiFunction.hpp

FloorSum.hpp

### 5.1 Prime Numbers

MillerRabin.hpp

LinearSieve.hpp

FastEratosthenes.hpp

GolbatchConjecture.hpp

### 5.2 Modulo

ModArith.hpp

ModGen.hpp

ModInverse.hpp

ModLog.hpp

ModMulLL.hpp

ModPow.hpp

ModSqrt.hpp

ModSum.hpp

ModArithmetic.hpp

## Graph (6)

SCC.hpp

ArticulationPoint.hpp

Bridge.hpp

Hierholzer.hpp

### 6.1 Matching

HopcroftKarp.hpp

Kuhn.hpp

WeightedMatching.hpp

### 6.2 Network Flow

Dinic.hpp

MinCostFlow.hpp

## Tree (7)

LCA.hpp

CartesianTree.hpp

VirtualTree.hpp

HLD.hpp

CentroidDecom.hpp

RootedTreeIsomorphism.hpp

UnrootedTreeIsomorphism.hpp

## Strings (8)

KMP.hpp

ZAlgo.hpp

AhoCorasick.hpp

Ukkonen.hpp

SuffixArray.hpp

PrefixFunction.hpp

SuffixAutomaton.hpp

## Geometry (9)

### 9.1 Geometric primitives

Point.h

lineDistance.h

SegmentDistance.h

SegmentIntersection.h

lineIntersection.h

sideOf.h

OnSegment.h

linearTransformation.h

LineProjectionReflection.h

Angle.h

### 9.2 Circles

CircleIntersection.h

CircleTangents.h

CircleLine.h

CirclePolygonIntersection.h

circumcircle.h

MinimumEnclosingCircle.h

### 9.3 Polygons

InsidePolygon.h

PolygonArea.h

PolygonCenter.h

PolygonCut.h

ConvexHull.h

HullDiameter.h

PointInsideHull.h

LineHullIntersection.h

### 9.4 Misc. Point Set Problems

ClosestPair.h

ManhattanMST.h

kdTree.h

DelaunayTriangulation.h

FastDelaunay.h

### 9.5 3D

PolyhedronVolume.h

Point3D.h

3dHull.h

sphericalDistance.h

ComplexGeometry.hpp

DefiniteIntegral.hpp

## Dynamic Programming (10)

CHT.hpp

Knuth.hpp

DVC.hpp

SlopeTrick.hpp

AlienTrick.hpp

## Polynomials (11)

### 11.1 Newton’s Method

if  $F(Q) = 0$ , then  $Q_{2n} \equiv Q_n - \frac{F(Q_n)}{F'(Q_n)} \pmod{x^{2n}}$

$$Q = P^{-1} : Q_{2n} \equiv Q_n \cdot (2 - P \cdot Q_n^2) \pmod{x^{2n}}$$

$$Q = \ln P = \int \frac{P'}{P} dx$$

$$Q = e^P : Q_{2n} \equiv Q_n(1 + P - \ln Q_n) \pmod{x^{2n}}$$

$$Q = \sqrt{P} : Q_{2n} \equiv \frac{1}{2}(Q_n + P \cdot Q_n^{-1}) \pmod{x^{2n}}$$

$$Q = P^k = \alpha^k x^{kt} e^{k \ln T}; P = \alpha \cdot x^t \cdot T, T(0) = 1$$

Interpolation.hpp

FormalPowerSeries.hpp

FFT.hpp

NTT.hpp

## Convolutions (12)

AndConvolution.hpp

GCDCConvolution.hpp

LCMConvolution.hpp

ORConvolution.hpp

XORConvolution.hpp

MaxPlusConvolution.hpp

## Various (13)

GaussianElimination.hpp

XORBasis.hpp

RangeXor.hpp

### 13.1 Optimization tricks

`__builtin_ia32_ldmxcsr(40896);` disables denormals (which make floats 20x slower near their minimum value).

#### 13.1.1 Bit hacks

- `x & -x` is the least bit in `x`.
- `for (int x = m; x; ) { --x &= m; ... }` loops over all subset masks of `m` (except `m` itself).
- `c = x&-x, r = x+c; (((r^x) >> 2)/c) | r` is the next number after `x` with the same number of bits set.
- `rep(b,0,K) rep(i,0,(1 << K)) if (i & 1 << b) D[i] += D[i^(1 << b)];` computes all sums of subsets.

#### 13.1.2 Pragmas

- `#pragma GCC optimize ("Ofast")` will make GCC auto-vectorize loops and optimizes floating points better.
- `#pragma GCC target ("avx2")` can double performance of vectorized code, but causes crashes on old machines.
- `#pragma GCC optimize ("trapv")` kills the program on integer overflows (but is really slow).

## Competitive Programming Topics (14)

topics.txt	159 lines
Recursion	
Divide and conquer	
Finding interesting points in N log N	
Algorithm analysis	
Master theorem	
Amortized time complexity	
Greedy algorithm	
Scheduling	
Max contiguous subvector sum	
Invariants	
Huffman encoding	
Graph theory	
Dynamic graphs (extra book-keeping)	
Breadth first search	
Depth first search	
* Normal trees / DFS trees	
Dijkstra's algorithm	
MST: Prim's algorithm	
Bellman-Ford	
Konig's theorem and vertex cover	
Min-cost max flow	
Lovasz toggle	
Matrix tree theorem	
Maximal matching, general graphs	
Hopcroft-Karp	
Hall's marriage theorem	
Graphical sequences	
Floyd-Warshall	
Euler cycles	
Flow networks	
* Augmenting paths	
* Edmonds-Karp	
Bipartite matching	
Min. path cover	
Topological sorting	
Strongly connected components	
2-SAT	
Cut vertices, cut-edges and biconnected components	
Edge coloring	
* Trees	
Vertex coloring	
* Bipartite graphs (=> trees)	
* 3^n (special case of set cover)	
Diameter and centroid	
K'th shortest path	
Shortest cycle	
Dynamic programming	
Knapsack	
Coin change	
Longest common subsequence	
Longest increasing subsequence	
Number of paths in a dag	
Shortest path in a dag	
Dynprog over intervals	
Dynprog over subsets	
Dynprog over probabilities	
Dynprog over trees	
3^n set cover	
Divide and conquer	
Knuth optimization	
Convex hull optimizations	
RMQ (sparse table a.k.a 2^k-jumps)	
Bitonic cycle	
Log partitioning (loop over most restricted)	
Combinatorics	
Computation of binomial coefficients	
Pigeon-hole principle	

Inclusion/exclusion	
Catalan number	
Pick's theorem	
Number theory	
Integer parts	
Divisibility	
Euclidean algorithm	
Modular arithmetic	
* Modular multiplication	
* Modular inverses	
* Modular exponentiation by squaring	
Chinese remainder theorem	
Fermat's little theorem	
Euler's theorem	
Phi function	
Frobenius number	
Quadratic reciprocity	
Pollard-Rho	
Miller-Rabin	
Hensel lifting	
Vieta root jumping	
Game theory	
Combinatorial games	
Game trees	
Mini-max	
Nim	
Games on graphs	
Games on graphs with loops	
Grundy numbers	
Bipartite games without repetition	
General games without repetition	
Alpha-beta pruning	
Probability theory	
Optimization	
Binary search	
Ternary search	
Unimodality and convex functions	
Binary search on derivative	
Numerical methods	
Numeric integration	
Newton's method	
Root-finding with binary/ternary search	
Golden section search	
Matrices	
Gaussian elimination	
Exponentiation by squaring	
Sorting	
Radix sort	
Geometry	
Coordinates and vectors	
* Cross product	
* Scalar product	
Convex hull	
Polygon cut	
Closest pair	
Coordinate-compression	
Quadtrees	
KD-trees	
All segment-segment intersection	
Sweeping	
Discretization (convert to events and sweep)	
Angle sweeping	
Line sweeping	
Discrete second derivatives	
Strings	
Longest common substring	
Palindrome subsequences	
Knuth-Morris-Pratt	
Tries	

Rolling polynomial hashes	
Suffix array	
Suffix tree	
Aho-Corasick	
Manacher's algorithm	
Letter position lists	
Combinatorial search	
Meet in the middle	
Brute-force with pruning	
Best-first (A*)	
Bidirectional search	
Iterative deepening DFS / A*	
Data structures	
LCA (2^k-jumps in trees in general)	
Pull/push-technique on trees	
Heavy-light decomposition	
Centroid decomposition	
Lazy propagation	
Self-balancing trees	
Convex hull trick (wcipeg.com/wiki/Convex_hull_trick)	
Monotone queues / monotone stacks / sliding queues	
Sliding queue using 2 stacks	
Persistent segment tree	

troubleshooting.txt	52 lines
Pre-submit:	
Write a few simple test cases if sample is not enough.	
Are time limits close? If so, generate max cases.	
Is the memory usage fine?	
Could anything overflow?	
Make sure to submit the right file.	
Wrong answer:	
Print your solution! Print debug output, as well.	
Are you clearing all data structures between test cases?	
Can your algorithm handle the whole range of input?	
Read the full problem statement again.	
Do you handle all corner cases correctly?	
Have you understood the problem correctly?	
Any uninitialized variables?	
Any overflows?	
Confusing N and M, i and j, etc.?	
Are you sure your algorithm works?	
What special cases have you not thought of?	
Are you sure the STL functions you use work as you think?	
Add some assertions, maybe resubmit.	
Create some testcases to run your algorithm on.	
Go through the algorithm for a simple case.	
Go through this list again.	
Explain your algorithm to a teammate.	
Ask the teammate to look at your code.	
Go for a small walk, e.g. to the toilet.	
Is your output format correct? (including whitespace)	
Rewrite your solution from the start or let a teammate do it.	
Runtime error:	
Have you tested all corner cases locally?	
Any uninitialized variables?	
Are you reading or writing outside the range of any vector?	
Any assertions that might fail?	
Any possible division by 0? (mod 0 for example)	
Any possible infinite recursion?	
Invalidated pointers or iterators?	
Are you using too much memory?	
Debug with resubmits (e.g. remapped signals, see Various).	
Time limit exceeded:	
Do you have any possible infinite loops?	

What is the complexity of your algorithm?  
Are you copying a lot of unnecessary data? (References)  
How big is the input and output? (consider scanf)  
Avoid vector, map. (use arrays/unordered\_map)  
What do your teammates think about your algorithm?

Memory limit exceeded:  
What is the max amount of memory your algorithm should need?  
Are you clearing all data structures between test cases?