

# Segmentation and Clustering (Part 3)

## This Lecture

- Segmentation and grouping
  - Gestalt principles
  - Image segmentation
- Segmentation as clustering
  - k-Means
  - Feature spaces
- Probabilistic clustering
  - Mixture of Gaussians, EM
- Model-free clustering
  - Mean-Shift clustering
- Graph theoretic segmentation
  - Normalised cuts

# Mean-Shift Segmentation

- An advanced and versatile technique for clustering-based segmentation

Segmented "landscape 1"




Segmented "landscape 2"



D. Comaniciu and P. Meer, [Mean Shift: A Robust Approach toward Feature Space Analysis](#), PAMI 2002.


# Finding Modes in a Histogram



## ● How many modes are there?

- *Mode* = local maximum of the density of a given distribution
- Easy to see, hard to compute


# Finding Modes in a Histogram



## ● How many modes are there?

- *Mode* = local maximum of the density of a given distribution
- Easy to see, hard to compute


# Mean-Shift Algorithm



## ● Iterative Mode Search

1. Initialise random seed, and window  $W$
2. Calculate centre of gravity (the “mean”) of  $W$ :  $\sum_{x \in W} xH(x)$
3. Shift the search window to the “mean”
4. Repeat Step 2 until convergence

# Mean-Shift and mode finding




One-dimensional visualization of kernel density estimate, its derivative, and a mean shift.

## Further details:


- Parzen window or kernel approach to probability density estimation:
  - Duda, Hart, and Stork 2001, section 4.3
  - Bishop 2006, section 2.5.1
- D. Comaniciu and P. Meer, [Mean Shift: A Robust Approach toward Feature Space Analysis](#), PAMI 2002 (*copy on blackboard*)

# Mean-Shift







# Mean-Shift




# Mean-Shift




# Mean-Shift




# Mean-Shift




# Mean-Shift




# Mean-Shift



# Mean-Shift




# Mean-Shift







# Mean-Shift




# Mean-Shift




# Mean-Shift




# Mean-Shift




# Mean-Shift




# Mean-Shift



# Mean-Shift




# Real Modality Analysis






# Real Modality Analysis




Run the procedure in parallel

# Real Modality Analysis




Run the procedure in parallel

# Real Modality Analysis



The blue data points were traversed by the windows towards the mode.


# Real Modality Analysis



The blue data points were traversed by the windows towards the mode.


# Mean-Shift Clustering

- **Cluster:** all data points in the attraction basin of a mode
- **Attraction basin:** the region for which all trajectories lead to the same mode




# Mean-Shift Clustering/Segmentation


- Find features (colour, gradients, texture, etc)
- Initialize windows at individual pixel locations
- Perform mean shift for each window until convergence
- Merge windows that end up near the same “peak” or mode




(a)



(b)



# Mean-Shift Segmentation Results



D. Comaniciu and P. Meer, [Mean Shift: A Robust Approach toward Feature Space Analysis](#), PAMI 2002.

# Summary Mean-Shift

## ● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters



# Summary Mean-Shift

## ● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size  $h$ )

# Summary Mean-Shift

## ● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size  $h$ )
- Finds variable number of modes

# Summary Mean-Shift

## ● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size  $h$ )
- Finds variable number of modes
- Robust to outliers

# Summary Mean-Shift

## ● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size  $h$ )
- Finds variable number of modes
- Robust to outliers

## ● Cons

# Summary Mean-Shift

## ● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size  $h$ )
- Finds variable number of modes
- Robust to outliers

## ● Cons

- Output depends on window size

# Summary Mean-Shift

## ● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size  $h$ )
- Finds variable number of modes
- Robust to outliers

## ● Cons

- Output depends on window size
- Window size (bandwidth) selection is not trivial

# Summary Mean-Shift

## ● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size  $h$ )
- Finds variable number of modes
- Robust to outliers

## ● Cons

- Output depends on window size
- Window size (bandwidth) selection is not trivial
- Computationally (relatively) expensive ( $\sim 2s/\text{image}$ )

# Summary Mean-Shift

## ● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size  $h$ )
- Finds variable number of modes
- Robust to outliers

## ● Cons

- Output depends on window size
- Window size (bandwidth) selection is not trivial
- Computationally (relatively) expensive ( $\sim 2s/\text{image}$ )
- Does not scale well with dimension of feature space



## Today's Lecture

- Segmentation and grouping
  - Gestalt principles
  - Image segmentation
- Segmentation as clustering
  - k-Means
  - Feature spaces
- Probabilistic clustering
  - Mixture of Gaussians, EM
- Model-free clustering
  - Mean-Shift clustering
- Graph theoretic segmentation
  - Normalised cuts

# Reading

## Reading

- **Forsyth, Ponce: Chapter 14**

# Reading

- Forsyth, Ponce: Chapter 14
- D. Comaniciu and P. Meer, Mean Shift: A Robust Approach toward Feature Space Analysis, PAMI 2002 (copy on blackboard)