

Segmentation and Clustering (part 1)

Segmentation Lectures (parts 1, 2, 3 and 4)

● Segmentation and grouping

- Gestalt principles
- Image segmentation

● Segmentation as clustering

- k-Means
- Feature spaces

● Probabilistic clustering

- Mixture of Gaussians, EM

● Model-free clustering

- Mean-Shift clustering

● Graph theoretic segmentation

- Normalised cuts

This lecture:

- **Segmentation and grouping**


- Gestalt principles
- Image segmentation

- **Segmentation as clustering**

- k-Means
- Feature spaces

Grouping in vision

- **Goal:** Gather features that belong together



- Obtain an intermediate representation that compactly describes key image or video parts

Examples of Grouping in Computer Vision



Determining
image regions



Grouping video frames into shots



Figure-ground






Image Segmentation



Examples of Grouping in Computer Vision



Determining
image regions



Grouping video frames into shots



Figure-ground





Image Segmentation



Examples of Grouping in Computer Vision



Determining
image regions



Grouping video frames into shots



Figure-ground






Image Segmentation




Basic ideas of grouping in human vision

- We want to group together pixels that “belong together”
- Psychologists also thought of studying this (Gestalt school)

The Gestalt School

- Grouping is key to visual perception
- Elements in a collection can have properties that result from relationships
 - “The whole is greater than the sum of its parts”



Gestalt Factors



Not grouped




Proximity




Similarity




Similarity




Common Fate




Common Region




Parallelism



Symmetry



Continuity



Closure

Gestalt

- Psychologists identified series of factors that predispose set of elements to be grouped (by the human visual system)
- Inspiring observations/explanations; challenge remains how to best map to algorithms.

Grouping in computer vision

- **Goals:**

- Gather features that belong together
- Obtain an intermediate representation that compactly describes key image (video) parts

- **Top down vs. bottom up segmentation**

Grouping in computer vision

● Goals:

- Gather features that belong together
- Obtain an intermediate representation that compactly describes key image (video) parts

● Top down vs. bottom up segmentation

- Top down: pixels belong together because they are from the same object

Grouping in computer vision

● Goals:

- Gather features that belong together
- Obtain an intermediate representation that compactly describes key image (video) parts

● Top down vs. bottom up segmentation

- Top down: pixels belong together because they are from the same object
- Bottom up: pixels belong together because they look ‘similar’

Grouping in computer vision

● Goals:

- Gather features that belong together
- Obtain an intermediate representation that compactly describes key image (video) parts

● Top down vs. bottom up segmentation

- Top down: pixels belong together because they are from the same object
- Bottom up: pixels belong together because they look ‘similar’

● Hard to measure success

- What is interesting depends on the app.




The Goals of Segmentation

- Separate image into coherent “objects”

Image



Human segmentation




Berkeley Segmentation dataset

The Goals of Segmentation



Original Image




Human segmentation



User 1



User 2




User 3

The Goals of Segmentation

- Group together similar-looking pixels for efficiency of further processing

The Goals of Segmentation

- Group together similar-looking pixels for efficiency of further processing




X. Ren and J. Malik. [Learning a classification model for segmentation.](#) ICCV 2003.


Today's Lecture

- Segmentation and grouping
 - Gestalt principles
 - Image segmentation
- Segmentation as clustering
 - k-Means
 - Feature spaces

Image Segmentation: Toy Example




input image




intensity

Image Segmentation: Toy Example




input image



intensity

Image Segmentation: Toy Example



input image





Image Segmentation: Toy Example



input image





Image Segmentation: Toy Example



input image





Image Segmentation: Toy Example



input image





Image Segmentation: Toy Example



input image






Image Segmentation: Toy Example




input image




intensity

- These intensities define the three groups.

Image Segmentation: Toy Example




input image




intensity

- These intensities define the three groups.
- We could label every pixel in the image according to which of these primary intensities it is.
 - i.e., segment the image based on the intensity feature.

Image Segmentation: Toy Example




input image





intensity


- These intensities define the three groups.
- We could label every pixel in the image according to which of these primary intensities it is.
 - i.e., segment the image based on the intensity feature.
- What if the image isn't quite so simple?





Input image




Input image




Input image




Input image







Input image





- Now how to determine the three main intensities that define our groups?
- We need to cluster



- Goal: choose three “centers” as the representative intensities, and label every pixel according to which of these centers it is nearest to.
- Best cluster centers are those that minimize SSD between all points and their nearest cluster center c_i :



- Goal: choose three “centers” as the representative intensities, and label every pixel according to which of these centers it is nearest to.
 - Best cluster centers are those that minimize SSD between all points and their nearest cluster center c_j :




- Goal: choose three “centers” as the representative intensities, and label every pixel according to which of these centers it is nearest to.
- Best cluster centers are those that minimize SSD between all points and their nearest cluster center c_i :

$$\sum_{\text{clusters } i} \sum_{\text{points } p \text{ in cluster } i} \|p - c_i\|^2$$

Clustering




Clustering




Clustering

- With this objective, it is a “chicken and egg” problem:

- If we knew the *cluster centers*, we could allocate points to groups by assigning each to its closest center.




- If we knew the *group memberships*, we could get the centers by computing the mean per group.




Clustering

- With this objective, it is a “chicken and egg” problem:

- If we knew the *cluster centers*, we could allocate points to groups by assigning each to its closest center.



- If we knew the *group memberships*, we could get the centers by computing the mean per group.



K-Means Clustering

- **Basic idea: randomly initialize the k cluster centers, and iterate between the two steps we just saw.**

K-Means Clustering

- **Basic idea: randomly initialize the k cluster centers, and iterate between the two steps we just saw.**
 1. Randomly initialize the cluster centers, c_1, \dots, c_K

K-Means Clustering

- **Basic idea: randomly initialize the k cluster centers, and iterate between the two steps we just saw.**

1. Randomly initialize the cluster centers, c_1, \dots, c_K
2. Given cluster centers, determine points in each cluster
 - For each point p , find the closest c_i . Put p into cluster i

K-Means Clustering


- **Basic idea: randomly initialize the k cluster centers, and iterate between the two steps we just saw.**

1. Randomly initialize the cluster centers, c_1, \dots, c_K
2. Given cluster centers, determine points in each cluster
 - For each point p , find the closest c_i . Put p into cluster i
3. Given points in each cluster, solve for c_i
 - Set c_i to be the mean of points in cluster i

K-Means Clustering

- **Basic idea: randomly initialize the k cluster centers, and iterate between the two steps we just saw.**


1. Randomly initialize the cluster centers, c_1, \dots, c_K
2. Given cluster centers, determine points in each cluster
 - For each point p , find the closest c_i . Put p into cluster i
3. Given points in each cluster, solve for c_i
 - Set c_i to be the mean of points in cluster i
4. If c_i have changed, repeat Step 2



K-Means Clustering

- Basic idea: randomly initialize the k cluster centers, and iterate between the two steps we just saw.

1. Randomly initialize the cluster centers, c_1, \dots, c_K
2. Given cluster centers, determine points in each cluster
 - For each point p , find the closest c_i . Put p into cluster i
3. Given points in each cluster, solve for c_i
 - Set c_i to be the mean of points in cluster i
4. If c_i have changed, repeat Step 2



- Properties

- Will always converge to some solution
- Can be a “local minimum”
 - Does not always find the global minimum of objective function:

$$\sum_{\text{clusters } i} \sum_{\text{points } p \text{ in cluster } i} \|p - c_i\|^2$$

Feature Space

Feature Space

- Depending on what we choose as the *feature space*, we can group pixels in different ways.
- Grouping pixels based on **intensity** similarity



- Feature space: intensity value (1D)

Segmentation as Clustering



K=2




Segmentation as Clustering



K=2




K=3





Feature Space



Feature Space



Feature Space





Feature Space



Feature Space


- Depending on what we choose as the feature space, we can group pixels in different ways.
- Grouping pixels based on colour similarity



- Feature space: colour value (3D)

K-Means Clustering Results

- K-means clustering based on intensity or color is essentially vector quantization of the image attributes
 - Clusters don't have to be spatially coherent



We can cluster (r,g,b,x,y) values to enforce more spatial coherence
⇒ Way to encode both *similarity* and *proximity*.

Summary K-Means

● Pros

- Simple, fast to compute
- Converges to local minimum of within-cluster squared error

Summary K-Means

● Pros

- Simple, fast to compute
- Converges to local minimum of within-cluster squared error

● Cons/issues

- Setting k?

Summary K-Means

● Pros

- Simple, fast to compute
- Converges to local minimum of within-cluster squared error

● Cons/issues

- Setting k?
- Sensitive to initial centers


Summary K-Means

● Pros


- Simple, fast to compute
- Converges to local minimum of within-cluster squared error

● Cons/issues

- Setting k?
- Sensitive to initial centers
- Sensitive to outliers



(A): Undesirable clusters



(B): Ideal clusters


Summary K-Means

● Pros

- Simple, fast to compute
- Converges to local minimum of within-cluster squared error

● Cons/issues


- Setting k?
- Sensitive to initial centers
- Sensitive to outliers
- Detects spherical clusters only




(A): Undesirable clusters



(B): Ideal clusters



(A): Two natural clusters



(B): k -means clusters

Next Lecture

- Segmentation and grouping
 - Gestalt principles
 - Image segmentation
- Segmentation as clustering
 - k-Means
 - Feature spaces
- Probabilistic clustering
 - Gaussian and Multivariate Gaussian distributions
 - Mixture of Gaussians
 - Expectation-Maximization (EM)
- Model-free clustering
 - Mean-Shift clustering
- Graph theoretic segmentation
 - Normalised cuts