

FLOOR MARKING TAPE

PRODUCT CODE

PVC COATED WITH RUBBER ADHESIVE

41860



Description

DEON<sup>®</sup> 41860 - FLOOR MARKING TAPE

PVC floor marking tape with high-performance rubber adhesive, designed for consistent marking and zoning across industrial and commercial floor applications.

- Features
- High Initial Tack for Immediate Bonding
  - High Visibility Colours for Safety Marking

- Clean Removal without Residue
  - Durable PVC Backing for Industrial Use

- Application
- Area Demarcation
  - Safety & Hazard Zone Identification

- Aisle & Floor Marking
  - Lane Marking for Traffic Management

Technical Properties

| Product Characteristics  |                | UOM     | Typical Values    | Test Method |
|--------------------------|----------------|---------|-------------------|-------------|
| Backing Material         |                | -       | PVC Film          | -           |
| Thickness (Customizable) |                | mm      | 0.130 - 0.140     | ASTM D1000  |
| Width                    | (Customizable) | mm      | 24/48/72 ± 1      | ASTM D1000  |
| Length                   | (Customizable) | m       | 15/20/25/28/30/33 | -           |
| Adhesive                 |                | -       | Rubber Adhesive   | -           |
| Adhesion to Steel        |                | kg/inch | 0.400 - 0.450     | ASTM D1000  |
| Tensile Strength         |                | kg/inch | 5.0 - 6.0         | ASTM D1000  |
| Elongation at Break      |                | %       | 170 - 190         | ASTM D1000  |

Available Colours

Yellow

Blue

Red

Green

Black

Orange

Yellow/Black

Yellow/Red

Green/White

Black/White

Storage & Usage Conditions

Store at room temperature, away from direct sunlight.

Ensure the application surface is clean, dry, and free from oil and dust.

A trial application is recommended to confirm suitability for the intended use.

Available Formats

Standard cut rolls and log roll formats for slitting and conversion

