

WIRE HARNESS TAPE

PVC FILM WITH RUBBER ADHESIVE

PRODUCT CODE

50W13



Description

DEON® 50W13 - WIRE HARNESS TAPE

PVC wire harnessing tape with rubber adhesive, designed for secure bundling, insulation, and protection of wire assemblies in automotive and electrical applications.

- Features
- Strong Adhesion for Secure Bundling

• Flame Retardant

• Good Dielectric Strength for Electrical Insulation

• General-Purpose Industrial Harnessing

- Application
- Wire Harness Bundling in Automotive Systems

• Insulation of Low-Voltage Wiring

• Cable Management in Electrical Assemblies

• General-Purpose Use in Industrial Applications

Technical Properties	Product Characteristics	UOM	Typical Values	Test Method
	Backing Material	-	PVC film	-
	Thickness (Customizable)	mm	0.104 - 0.112	ASTM D1000
	Width (Customizable)	mm	18/19	ASTM D1000
	Length (Customizable)	m	22/25	-
	Adhesive	-	Rubber Adhesive	-
	Adhesion to Steel	N/ 10mm width	1.8 - 1.9	ASTM D1000
	Adhesion to Backing	N/ 10mm width	1.6 - 1.8	ASTM D1000
	Tensile Strength	N/ 10mm width	160 - 180	ASTM D1000
	Elongation at Break	%	170 - 190	ASTM D1000
	Breakdown Voltage	kV	5.0 - 5.6	ASTM D1000
	Unwind Force	kg/ width	0.500 - 0.550	ASTM D1000
	Flammability	-	Self Extinguishing	ASTM D1000

Available Colours

Black

Red

Blue

Yellow

Green

White

Storage & Usage Conditions

Store at room temperature, away from direct sunlight.

Shelf life is 12 months from the date of manufacture.

Ensure the application surface is clean, dry, and free from oil and dust before use.

A trial application is recommended to confirm suitability for the intended application.

Available Formats

Standard cut rolls and log roll formats for slitting and conversion