



Description

DEON® DT1111 - CLASS B POLYESTER INSULATION TAPE
Polyester film tape with thermosetting rubber adhesive, rated Class B for continuous electrical insulation up to 130°C.

- Features
- Class B Thermal Rating (up to 130°C)
 - Reliable Adhesion (≈ 2.5 N/cm)

- High Dielectric Strength (≥ 5 kV)
 - Thermosetting Rubber Adhesive for Temperature Stability

- Application
- Motor Winding & Coil Insulation
 - Capacitor Wrapping (Cast Resin & Film/Foil)

- Transformer Layer & Barrier Insulation
 - Telecommunication Cable Insulation

Technical Properties	Product Characteristics	UOM	Typical Values	Test Method
	Backing Material	-	Polyester Film	-
	Thickness (Customizable)	mm	0.058 ± 0.002	ASTM D1000
	Width (Customizable)	mm	25	ASTM D1000
	Length (Customizable)	m	50 / 65	-
	Adhesive	-	Synthetic Rubber Thermosetting	-
	Adhesive Coating	-	Single - sided	-
	Adhesion to Steel (min)	N/cm	2.5	ASTM D1000
	Tensile Strength (min)	N/cm	40	ASTM D1000
	Temperature Operating Range	-	Class B (130°C)	ASTM D1000
	Elongation at Break	%	70	ASTM D1000
	Dielectric Strength- BDV (min)	V	5000	ASTM D1000

Available Colours

Transparent

Red

Blue

Yellow

Green

Storage & Usage Conditions

Store at room temperature, away from direct sunlight, heat, and moisture.
Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH).
Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.

Available Formats

Standard cut rolls and jumbo roll formats for slitting and conversion.

