



Description

DEON[®] DT1113 CLASS B POLYESTER FLEECE INSULATION TAPE
Polyester fleece tape with thermosetting rubber adhesive, engineered for electrical insulation in varnish-impregnated coil applications. Rated Class B for continuous operation up to 130°C.

- Features
- Fleece Construction for Varnish Impregnation
 - High Adhesion (≈ 5.0 N/cm)

- Class B Thermal Rating (up to 130°C)
 - High Dielectric Strength (≥ 5 kV)

- Application
- Motor Coil Winding with Varnish Impregnation
 - General Electrical Equipment Insulation

Technical Properties	Product Characteristics	UOM	Typical Values	Test Method
	Backing Material	-	Polyester Reinforced Fleece	-
	Thickness (Customizable)	mm	0.18 ± 0.005	ASTM D1000
	Width (Customizable)	mm	24	ASTM D1000
	Length (Customizable)	m	55	-
	Adhesive	-	Thermosetting Rubber	-
	Adhesive Coating	-	Single - sided	-
	Adhesion to Steel (min)	N/cm	5.0	ASTM D1000
	Tensile Strength (min)	N/cm	45	ASTM D1000
	Temperature Operating Range	-	Class B 130°C	ASTM D1000
	Elongation at Break	%	80	ASTM D1000
	Dielectric Strength- BDV (min)	V	5000	ASTM D1000

Available Colours

Natural (Translucent)

Storage & Usage Conditions

Store at room temperature, away from direct sunlight, heat, and moisture.
Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH).
Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.

Available Formats

Standard cut rolls and jumbo roll formats for slitting and conversion

