

CLASS F POLYESTER FLEECE INSULATION TAPE

POLYESTER FLEECE / ACRYLIC ADHESIVE

PRODUCT CODE

DT1123



Description	DEON[®] DT1123 - CLASS F POLYESTER FLEECE INSULATION TAPE Polyester fleece tape with thermosetting acrylic adhesive, designed for electrical insulation in varnish-impregnated coil applications. Rated Class F for continuous operation up to 155°C.																																																		
Features	• Fleece Construction for Varnish Impregnation • High Adhesion to Metal Surfaces (≈ 5.0 N/cm) • Class F Thermal Rating (up to 155°C) • High Dielectric Strength (≥ 5 kV)																																																		
Application	• Motor Coil Winding with Varnish Impregnation • Transformer Coil Layer Insulation • Slot Liner & Phase Separation Insulation • High-Temperature Electrical Equipment Insulation																																																		
Technical Properties	<table><tr><th>Product Characteristics</th><th>UOM</th><th>Typical Values</th><th>Test Method</th></tr><tr><td>Backing Material</td><td>-</td><td>Polyester reinforced fleece</td><td>-</td></tr><tr><td>Thickness (Customizable)</td><td>mm</td><td>0.18 ± 0.005</td><td>ASTM D1000</td></tr><tr><td>Width (Customizable)</td><td>mm</td><td>24</td><td>ASTM D1000</td></tr><tr><td>Length (Customizable)</td><td>m</td><td>50</td><td>-</td></tr><tr><td>Adhesive</td><td>-</td><td>Thermosetting acrylic</td><td>-</td></tr><tr><td>Adhesive Coating</td><td>-</td><td>Single - sided</td><td>-</td></tr><tr><td>Adhesion to Steel (min)</td><td>N/cm</td><td>5.0</td><td>ASTM D1000</td></tr><tr><td>Tensile Strength (min)</td><td>N/cm</td><td>45</td><td>ASTM D1000</td></tr><tr><td>Temperature Operating Range</td><td>-</td><td>Class F (150°C)</td><td>ASTM D1000</td></tr><tr><td>Elongation at Break</td><td>%</td><td>80</td><td>ASTM D1000</td></tr><tr><td>Dielectric Strength- BDV (min)</td><td>V</td><td>5000</td><td>ASTM D1000</td></tr></table>			Product Characteristics	UOM	Typical Values	Test Method	Backing Material	-	Polyester reinforced fleece	-	Thickness (Customizable)	mm	0.18 ± 0.005	ASTM D1000	Width (Customizable)	mm	24	ASTM D1000	Length (Customizable)	m	50	-	Adhesive	-	Thermosetting acrylic	-	Adhesive Coating	-	Single - sided	-	Adhesion to Steel (min)	N/cm	5.0	ASTM D1000	Tensile Strength (min)	N/cm	45	ASTM D1000	Temperature Operating Range	-	Class F (150°C)	ASTM D1000	Elongation at Break	%	80	ASTM D1000	Dielectric Strength- BDV (min)	V	5000	ASTM D1000
Product Characteristics	UOM	Typical Values	Test Method																																																
Backing Material	-	Polyester reinforced fleece	-																																																
Thickness (Customizable)	mm	0.18 ± 0.005	ASTM D1000																																																
Width (Customizable)	mm	24	ASTM D1000																																																
Length (Customizable)	m	50	-																																																
Adhesive	-	Thermosetting acrylic	-																																																
Adhesive Coating	-	Single - sided	-																																																
Adhesion to Steel (min)	N/cm	5.0	ASTM D1000																																																
Tensile Strength (min)	N/cm	45	ASTM D1000																																																
Temperature Operating Range	-	Class F (150°C)	ASTM D1000																																																
Elongation at Break	%	80	ASTM D1000																																																
Dielectric Strength- BDV (min)	V	5000	ASTM D1000																																																
Available Colours	Natural (Translucent)																																																		
Storage & Usage Conditions	Store at room temperature, away from direct sunlight, heat, and moisture. Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH). Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.																																																		
Available Formats	Standard cut rolls and jumbo roll formats for slitting and conversion																																																		

