

DOUBLE-SIDED POLYESTER BONDING TAPE

POLYESTER FILM / HOT MELT ADHESIVE

PRODUCT CODE

DT1142



Description	DEON® DT1142 - DOUBLE-SIDED POLYESTER BONDING TAPE Polyester film tape with hot melt adhesive, designed for high-performance bonding across a wide range of industrial substrates, including low surface energy materials.	
Features	- Compatible with Low Surface Energy Substrates (PP, PE & Similar) - Double-Coated Construction for Dual-Surface Bonding - High Adhesion Strength (≈ 12 N/cm on Steel) - High Initial Tack for Immediate Bond Formation	
Application	- Label Fixing & Component Mounting (Appliances) - Holding & Sealing in Packaging & Container Assembly - Film & Fabric Splicing in Converting Operations - Bonding on Plastics & Low Surface Energy Substrates	

Technical Properties	Product Characteristics	UOM	Typical Values	Test Method
	Backing Material	-	Polyester Film	-
	Thickness (Customizable)	µm	90 ± 5	ASTM D1000
	Width (Customizable)	mm	25	ASTM D1000
	Length (Customizable)	m	50	-
	Adhesive	-	Synthetic hot melt	-
	Adhesive Coating	-	Double -sided	-
	Adhesion to Steel (min)	N/cm	12	ASTM D1000
	Tensile Strength (min)	N/cm	45	ASTM D1000
	Release Liner	-	Double side release paper	ASTM D1000
	Elongation at Break	%	70	ASTM D1000
	Release Liner Thickness	µm	60 ± 5	ASTM D1000

Available Colours

Transparent

Storage & Usage Conditions

Store at room temperature, away from direct sunlight, heat, and moisture.
Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH).
Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.

Available Formats

Standard cut rolls and jumbo roll formats for slitting and conversion

