

POLYESTER HOLDING & SPLICING TAPE

POLYESTER FILM / ACRYLIC ADHESIVE

PRODUCT CODE

DT1221H



Description

DEON® DT1221H - POLYESTER HOLDING & SPLICING TAPE

Polyester film tape with thermosetting acrylic adhesive, designed for reliable performance in holding and splicing applications across industrial processes.

- Features
- High Cohesive Strength for Clean Removal
 - High Tensile Strength (≈ 45 N/cm)

- Multi-Surface Adhesion (Plastics, Metals & Composites)
 - Translucent Blue Film for Visual Identification

- Application
- Component Holding in Home Appliances During Transit
 - Splicing in Synthetic Leather & Fabric Manufacturing

- Glass & Panel Fixation During Assembly & Dispatch
 - Temporary Process Holding in Electronics Assembly

Technical Properties	Product Characteristics	UOM	Typical Values	Test Method
	Backing Material	-	Polyester Film	-
	Thickness (Customizable)	mm	0.055 ± 0.005	ASTM D1000
	Width (Customizable)	mm	25	ASTM D1000
	Length (Customizable)	m	50 / 65	-
	Adhesive	-	Synthetic Thermosetting Acrylic	-
	Adhesive Coating	-	Single - sided	-
	Adhesion to Steel (min)	N/cm	2.0	ASTM D1000
	Tensile Strength (min)	N/cm	45	ASTM D1000
	Elongation at Break	%	80	ASTM D1000

Available Colours

Blue (Translucent)

Storage & Usage Conditions

Store at room temperature, away from direct sunlight, heat, and moisture.

Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH).

Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.

Available Formats

Standard cut rolls and jumbo roll formats for slitting and conversion

