

HIGH-TEMPERATURE POLYESTER MASKING TAPE

POLYESTER FILM / SILICONE ADHESIVE

PRODUCT CODE

DT1231



Description	DEON® DT1231 - HIGH-TEMPERATURE POLYESTER MASKING TAPE Polyester film tape with thermosetting polysiloxane adhesive, designed for high-temperature masking applications. Suitable for continuous service from -40°C to 200°C with short-term resistance up to 250°C.																																																		
Features	- Silicone Adhesive for Clean, Residue-Free Removal - Stable Adhesion to Metal Surfaces (≈ 2.0 N/cm) - Wide Service Temperature Range																																																		
Application	- Wave Soldering Masking on PCBs - Masking for Surface Protection During Heat Treatment & Curing - High-Temperature Masking in Powder Coating - Masking During Thermal Spray & Paint Baking Processes																																																		
Technical Properties	<table><tr><th>Product Characteristics</th><th>UOM</th><th>Typical Values</th><th>Test Method</th></tr><tr><td>Backing Material</td><td>-</td><td>Polyester Film</td><td>-</td></tr><tr><td>Thickness (Customizable)</td><td>mm</td><td>0.055 / 0.075 ± 0.005</td><td>ASTM D1000</td></tr><tr><td>Width (Customizable)</td><td>mm</td><td>25</td><td>ASTM D1000</td></tr><tr><td>Length (Customizable)</td><td>m</td><td>50</td><td>-</td></tr><tr><td>Adhesive</td><td>-</td><td>Thermosetting Polysiloxane</td><td>-</td></tr><tr><td>Adhesive Coating</td><td>-</td><td>Single - sided</td><td>-</td></tr><tr><td>Adhesion to Steel (min)</td><td>N/cm</td><td>2.0</td><td>ASTM D1000</td></tr><tr><td>Tensile Strength (min)</td><td>N/cm</td><td>40 / 70</td><td>ASTM D1000</td></tr><tr><td>Temperature Operating Range</td><td>-</td><td>-40°C to 200°C</td><td>ASTM D1000</td></tr><tr><td>Elongation at Break</td><td>%</td><td>80</td><td>ASTM D1000</td></tr><tr><td>Service Temperature</td><td>°C</td><td>-40 to 200</td><td>ASTM D1000</td></tr></table>			Product Characteristics	UOM	Typical Values	Test Method	Backing Material	-	Polyester Film	-	Thickness (Customizable)	mm	0.055 / 0.075 ± 0.005	ASTM D1000	Width (Customizable)	mm	25	ASTM D1000	Length (Customizable)	m	50	-	Adhesive	-	Thermosetting Polysiloxane	-	Adhesive Coating	-	Single - sided	-	Adhesion to Steel (min)	N/cm	2.0	ASTM D1000	Tensile Strength (min)	N/cm	40 / 70	ASTM D1000	Temperature Operating Range	-	-40°C to 200°C	ASTM D1000	Elongation at Break	%	80	ASTM D1000	Service Temperature	°C	-40 to 200	ASTM D1000
Product Characteristics	UOM	Typical Values	Test Method																																																
Backing Material	-	Polyester Film	-																																																
Thickness (Customizable)	mm	0.055 / 0.075 ± 0.005	ASTM D1000																																																
Width (Customizable)	mm	25	ASTM D1000																																																
Length (Customizable)	m	50	-																																																
Adhesive	-	Thermosetting Polysiloxane	-																																																
Adhesive Coating	-	Single - sided	-																																																
Adhesion to Steel (min)	N/cm	2.0	ASTM D1000																																																
Tensile Strength (min)	N/cm	40 / 70	ASTM D1000																																																
Temperature Operating Range	-	-40°C to 200°C	ASTM D1000																																																
Elongation at Break	%	80	ASTM D1000																																																
Service Temperature	°C	-40 to 200	ASTM D1000																																																
Available Colours	Green (Translucent)																																																		
Storage & Usage Conditions	Store at room temperature, away from direct sunlight, heat, and moisture. Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH). Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.																																																		
Available Formats	Standard cut rolls and jumbo roll formats for slitting and conversion																																																		

