

CLASS H POLYIMIDE INSULATION TAPE

POLYIMIDE FILM / SILICONE ADHESIVE

PRODUCT CODE

DT2131



Description

DEON® DT2131 - CLASS H POLYIMIDE INSULATION TAPE

Polyimide film tape with thermosetting polysiloxane adhesive, engineered for high-temperature electrical insulation and masking applications. Rated Class H for continuous operation up to 180°C.

- Features
- Class H Thermal Rating (up to 180°C)
 - High Dielectric Strength (≥ 5 kV)

- Flame Retardant Performance (Internally Tested)
 - Silicone Adhesive for Clean, Residue-Free Removal

- Application
- Coil Insulation in Traction & High-Voltage Motors
 - High-Stress Electrical Insulation Applications

- Wave Soldering Masking on PCBs
 - High-Temperature Masking in Electronics & PCB Processing

Technical Properties	Product Characteristics		UOM	Typical Values	Test Method
	Backing Material		-	Polyimide Film	-
	Thickness (Customizable)		mm	0.055 ± 0.005	ASTM D1000
	Width (Customizable)		mm	25	ASTM D1000
	Length (Customizable)		m	33	-
	Adhesive		-	Thermosetting Polysiloxane	-
	Adhesive Coating		-	Single - sided	-
	Adhesion to Steel (min)		N/cm	2.5	ASTM D1000
	Tensile Strength (min)		N/cm	45	ASTM D1000
	Temperature Operating Range		-	Class H (180°C)	ASTM D1000
	Elongation at Break		%	60	ASTM D1000
	Dielectric strength- BDV (min)		V	5000	ASTM D1000
	Flammability Rating		-	Self Extinguishing	ASTM D1000

Available Colours

Amber

Storage & Usage Conditions

Store at room temperature, away from direct sunlight, heat, and moisture.
Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH).
Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.

Available Formats

Standard cut rolls and jumbo roll formats for slitting and conversion

