

CLASS F GLASS CLOTH INSULATION TAPE

WOVEN GLASS FABRIC / ACRYLIC ADHESIVE

PRODUCT CODE

DT3121L



Description

DEON® DT3121L - CLASS F GLASS CLOTH INSULATION TAPE

Woven glass fabric tape with thermosetting acrylic adhesive, designed for electrical insulation and mechanical protection in high-temperature applications.

- Features
- Class F Thermal Rating (-20°C to 155°C)
 - Excellent Abrasion Resistance for Mechanical Protection

- High Tensile Strength (≈ 150 N/cm)
 - Siliconized PET Release Liner for Controlled Application in Winding Processes

- Application
- Transformer & Rectifier Coil Winding
 - Terminal Insulation in Electrical Motors

- High-Temperature Wire Harnessing

Technical Properties	Product Characteristics		UOM	Typical Values	Test Method
	Backing Material		-	Woven Glass Fabric	-
	Thickness (Customizable)		µm	180 ± 5	ASTM D1000
	Width (Customizable)		mm	-25	ASTM D1000
	Length (Customizable)		m	20/30	-
	Adhesive		-	Thermosetting Acrylic	-
	Adhesive Coating		-	Single - sided	-
	Adhesion to Steel (min)		N/cm	2.5	ASTM D1000
	Tensile Strength (min)		N/cm	150	ASTM D1000
	Temperature Operating Range		-	-20°C to +155°C	ASTM D1000
	Elongation at Break		%	9	ASTM D1000
	Breakdown Voltage (min)		V	2000	ASTM D1000
	Release Liner		µm	30 ± 2	ASTM D1000
	* One side siliconized polyester film				

Available Colours

Off-white

Storage & Usage Conditions

Store at room temperature, away from direct sunlight, heat, and moisture.
Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH).
Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.

Available Formats

Standard cut rolls and jumbo roll formats for slitting and conversion

