

POLYGLASS WATERPROOFING TAPE
GLASS FABRIC / ACRYLIC ADHESIVE

PRODUCT CODE
DT3124L



Description	DEON® DT3124L – POLYGLASS WATERPROOFING TAPE LDPE-coated glass fabric tape with thermosetting acrylic adhesive, built for demanding outdoor environments with resistance to weather, moisture, oil, and alkali exposure.	
Features	• High Tensile Strength (≈ 120 N/cm) • Excellent Weather Resistance (200 hrs Xenon Arc Exposure) • Waterproof Barrier (≤ 2 Drops After 2 Hours) • Strong Adhesion to Metal Surfaces (≈ 12 N/cm)	
Application	• Water Ingress Protection for Locomotive Rooftops • Seam Sealing & Waterproofing in Buses & Passenger Vehicles • Weatherproof Sealing in Outdoor Industrial Equipment • Protective Sealing in High-Exposure Environments	

Technical Properties	Product Characteristics	UOM	Typical Values	Test Method
	Backing Material	-	Polycoated Glass Fabric	-
	Thickness (Customizable)	µm	300 ± 30	ASTM D1000
	Width (Customizable)	mm	50	-
	Length (Customizable)	m	20	ASTM D1000
	Adhesive	-	Thermosetting Acrylic	-
	Adhesive Coating	-	Single - sided	-
	Adhesion to Steel (min)	N/cm	12	ASTM D1000
	Tensile Strength (min)	N/cm	120	ASTM D1000
	Elongation at Break	%	5	ASTM D1000
	Weather Resistance	No cracking should be observed on surface when exposed for 200 hrs in standard xenon arc weathrometer		
	Water Permeability	Not more than 2 drops after 2 hrs when used as water barrier.		
	Oil Resistance	No cracking or blistering should be observed on surface when exposed to oil for 6 hrs		
	Alkali Resistance	No cracking or blistering should be observed on surface when exposed to 0.1 N NaOH for 6 hrs		

Available Colours	Black
-------------------	-----------------------------

Storage & Usage Conditions	Store at room temperature, away from direct sunlight, heat, and moisture. Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH). Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.
----------------------------	--

Available Formats	Standard cut rolls and jumbo roll formats for slitting and conversion
-------------------	---

