

HDPE FABRIC TAPE

WOVEN HDPE FABRIC / HOT MELT ADHESIVE

PRODUCT CODE

DT3741L



Description

DEON® DT3741L - HDPE FABRIC TAPE

Laminated woven HDPE fabric tape with synthetic hot melt adhesive, offering durable adhesion across standard and low surface energy substrates.

- Features
- High Adhesion to LSE Surfaces (≈ 10 N/cm)

• Excellent Abrasion Resistance for Rough Handling

• High Tensile Strength (≈ 80 N/cm)

• Woven HDPE for Durability & Moisture Resistance

- Application
- Steel Coil & Metal Sheet Packing

• Container Liner Bonding & Fixation

• Greenhouse Film Fixation & Securing

• Heavy-Duty Industrial Packaging & Bundling

Technical Properties	Product Characteristics	UOM	Typical Values	Test Method
	Backing Material	-	Woven HDPE Fabric	-
	Thickness (Customizable)	µm	140 ± 5	ASTM D1000
	Width (Customizable)	mm	48	ASTM D1000
	Length (Customizable)	m	50/100	-
	Adhesive	-	Synthetic Hot Melt	-
	Adhesive Coating	-	Single - sided	-
	Adhesion to Steel (min)	N/cm	10	ASTM D1000
	Tensile Strength (min)	N/cm	80	ASTM D1000
	Elongation at Break	%	20	ASTM D1000
	Release Liner Thickness	µm	50 ± 5	ASTM D1000
	Release Liner	-	Single side silicone coated paper	-

Available Colours

Black

White

Blue

Yellow

Storage & Usage Conditions

Store at room temperature, away from direct sunlight, heat, and moisture.

Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH).

Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.

Available Formats

Standard cut rolls and jumbo roll formats for slitting and conversion

