

ALUMINIUM FOIL TAPE
ACRYLIC SERIES
SOFT ALUMINIUM FOIL / ACRYLIC ADHESIVE

PRODUCT CODE
DT4021 / DT4021L
DT4121 / DT4121L



Description

DEON® DT4021 / DT4021L / DT4121 / DT4121L ALUMINIUM FOIL TAPE - ACRYLIC SERIES

Soft aluminium foil tapes with modified and thermosetting acrylic adhesive, available in multiple thicknesses and liner options, designed for HVAC sealing, insulation, and general-purpose industrial applications.

- Features
- High Initial Tack for Immediate Bonding
 - Good Adhesion on Metal Surfaces (≈ 5 N/cm)

- Thermosetting Variant for Elevated Temperature (up to 150°C)
 - Available with or without Release Liner

- Application
- HVAC Duct Seaming & Insulation Seam Sealing
 - Glass Wool & Rock Wool Vapour Barrier Sealing

- Refrigerator & Freezer Coil Mounting
 - Insulation Puncture Repair & Mending

Technical Properties	Product Characteristics	UOM	Typical Values		Test Method
			DT4021 / DT4021L	DT4121 / DT4121L	
	Backing Material	-	Soft Aluminium Foil	Soft Aluminium Foil	-
	Thickness (Customizable)	µm	50 ± 5	80 ± 5	ASTM D1000
	Width (Customizable)	mm	48	48	ASTM D1000
	Length (Customizable)	m	20/50	50	-
	Adhesive	-	Modified Acrylic	Thermosetting Acrylic	-
	Adhesive Coating	-	Single - sided	Single - sided	-
	Adhesion to Steel (min)	N/cm	5.0	5.0	ASTM D1000
	Tensile Strength (min)	N/cm	10	50	ASTM D1000
	Elongation at Break	%	6	6	ASTM D1000
	Temperature Operating Range	-	Ambient	Up to 150	ASTM D1000
	Release Liner	-	Optional	Optional	-

Available Colours

Metallic

Storage & Usage Conditions

Store at room temperature, away from direct sunlight, heat, and moisture.
Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH).
Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.

Available Formats

Standard cut rolls and jumbo roll formats for slitting and conversion

