

ALUMINIUM FOIL TAPE
HOT MELT SERIES
SOFT ALUMINIUM FOIL / HOT MELT ADHESIVE

PRODUCT CODE
DT4041 / DT4041L
DT4141 / DT4141L



Description	DEON® DT4041 / DT4041L / DT4141 / DT4141L ALUMINIUM FOIL TAPE - HOT MELT SERIES Soft aluminium foil tape with hot melt adhesive, available in multiple thicknesses and liner options, designed for HVAC sealing and general-purpose applications requiring high initial tack and fast bonding.	
Features	• High Initial Tack for Immediate Bonding • Good Adhesion on Metal Surfaces (≈ 8–10 N/cm)	• Conformable Aluminium Foil for Sealing Irregular Surfaces • Available with or without Release Liner
Application	• HVAC Duct Seaming & Insulation Seam Sealing • Glass Wool & Rock Wool Vapour Barrier Sealing	• Refrigerator & Freezer Coil Mounting • Insulation Puncture Repair & Mending

Technical Properties	Product Characteristics	UOM	Typical Values		Test Method
			DT4041 / DT4041L	DT4141 / DT4141L	
	Backing Material	-	Soft Aluminium Foil	Soft Aluminium Foil	-
	Thickness (Customizable)	µm	50 ± 5	80 ± 5	ASTM D1000
	Width (Customizable)	mm	48	48	ASTM D1000
	Length (Customizable)	m	20/50	20/50	-
	Adhesive	-	Synthetic Hot Melt	Synthetic Hot Melt	-
	Adhesive Coating	-	Single - sided	Single - sided	-
	Adhesion to Steel (min)	N/cm	10	10 - 20	ASTM D1000
	Tensile Strength (min)	N/cm	10	20 - 50	ASTM D1000
	Elongation at Break	%	6	6	ASTM D1000
	Temperature Operating Range	-	Ambient	Ambient	ASTM D1000
	Release Liner	-	None / Single side paper	None / Single side paper	-

Available Colours

 Metallic

Storage & Usage Conditions

Store at room temperature, away from direct sunlight, heat, and moisture.
Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH).
Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.

Available Formats Standard cut rolls and jumbo roll formats for slitting and conversion

