

DOUBLE-SIDED PE FOAM BONDING TAPE

PE FOAM / HOT MELT ADHESIVE

PRODUCT CODE

DT5142



Description

DEON® DT5142 - DOUBLE-SIDED PE FOAM BONDING TAPE

Double-sided PE foam tape with hot melt adhesive, designed for high-strength bonding and mounting applications requiring conformability and adhesion across a wide range of surfaces, including low surface energy materials.

- Features
- High Adhesion to Steel (≈ 15 N/cm)
 - Double-Coated for Reliable Two-Surface Bonding

- High Elongation (≈ 150%) for Conformable Bonding
 - Good Performance on LSE Surfaces

- Application
- Metal-to-Metal Structural Bonding & Assembly
 - Photovoltaic Cell & Panel Bonding

- Auto & Electronic Component Mounting & Fixation
 - Label & Nameplate Fixing in Appliances

Technical Properties	Product Characteristics	UOM	Typical Values	Test Method
	Backing Material	-	PE Foam	-
	Thickness (Customizable)	mm	1.2 ± 0.005	ASTM D1000
	Width (Customizable)	mm	25	ASTM D1000
	Length (Customizable)	m	10	-
	Adhesive	-	Synthetic Hot Melt	-
	Adhesive Coating	-	Both - sided	-
	Adhesion to Steel (min)	N/cm	15.0	ASTM D1000
	Tensile Strength (min)	N/cm	8.0	ASTM D1000
	Elongation at Break	%	150	ASTM D1000
	Release Liner Thickness	µm	60	ASTM D1000
	Release Liner	-	PE Film Liner	-

Available Colours

Black

Storage & Usage Conditions

Store at room temperature, away from direct sunlight, heat, and moisture.
Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH).
Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.

Available Formats

Standard cut rolls and jumbo roll formats for slitting and conversion

