

ADHESIVE TRANSFER TAPE

CARRIERLESS / HOT MELT ADHESIVE

PRODUCT CODE

DT6041



Description

DEON® DT6041 - ADHESIVE TRANSFER TAPE

Carrierless adhesive transfer tape comprising high-performance synthetic hot melt adhesive coated directly onto release paper, designed for ultra-thin bonding and high conformability across a wide range of industrial substrates.

- Features
- Good Adhesion to Steel (≥ 12 N/cm)

• Carrierless Adhesive for Ultra-Thin Bond Lines (~50 µm)

• Excellent Conformability on Irregular Surfaces

• Effective Bonding on LSE Surfaces

- Application
- Metal-to-Metal Bonding & Assembly Support

• Label & Nameplate Fixing in Appliances

• Foam Lamination for Gasket Manufacturing

• Low-Profile Bonding of Thin Substrates

| Technical Properties | Product Characteristics  | UOM  | Typical Values             | Test Method |
|----------------------|--------------------------|------|----------------------------|-------------|
|                      | Backing Material         | -    | -                          | -           |
|                      | Thickness (Customizable) | µm   | 50 ± 5                     | ASTM D1000  |
|                      | Width (Customizable)     | mm   | 25                         | ASTM D1000  |
|                      | Length (Customizable)    | m    | 50                         | -           |
|                      | Adhesive                 | -    | Synthetic Hot Melt         | -           |
|                      | Adhesive Coating         | -    | Single - sided             | -           |
|                      | Adhesion to Steel (min)  | N/cm | 12.0                       | ASTM D1000  |
|                      | Tensile Strength (min)   | N/cm | -                          | -           |
|                      | Elongation at Break      | %    | -                          | -           |
|                      | Release Liner Thickness  | µm   | 60 ± 5                     | ASTM D1000  |
|                      | Release Liner            | -    | Double sided release paper | -           |

Available Colours

White

Storage & Usage Conditions

Store at room temperature, away from direct sunlight, heat, and moisture.  
Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH).  
Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.

Available Formats

Standard cut rolls and jumbo roll formats for slitting and conversion

