

DOUBLE-SIDED TISSUE BONDING TAPE

TISSUE / ACRYLIC & HOT MELT ADHESIVE

PRODUCT CODE

DT6122 /

DT6142



Description

DEON® DT6122 / DT6142 - DOUBLE-SIDED TISSUE BONDING TAPE

Ultra-thin double-sided tissue tapes, each double-coated with a distinct adhesive system - cross-linked solvent acrylic (DT6122) or synthetic hot melt (DT6142) — offering application-specific selection for precision, low-profile bonding across industrial substrates.

Features

- Ultra-Thin Construction (≈ 70 µm Total Thickness)
 - High Initial Tack for Fast Bond Formation
- Good Adhesion on Metal & LSE Surfaces
 - Low Elongation (≈ 5%) for Dimensional Stability

Application

- Metal-to-Metal Bonding & Assembly Support
 - Label & Nameplate Fixing in Appliances
- Foam Lamination for Gasket Manufacturing
 - Bonding in Sanitary & Industrial Components

Technical Properties

Product Characteristics	UOM	Typical Values		Test Method
		DT6122	DT6142	
Backing Material	-	Tissue Paper	Tissue Paper	-
Thickness (Customizable)	µm	70 ± 5	70 ± 5	ASTM D1000
Width (Customizable)	mm	25	25	ASTM D1000
Length (Customizable)	m	50	50	-
Adhesive	-	Cross-linked Solvent Acrylic	Synthetic Hot Melt	-
Adhesive Coating	-	Double - sided	Double - sided	-
Adhesion to Steel (min)	N/cm	8.0	10.0	ASTM D1000
Tensile Strength (min)	N/cm	2.0	2.0	ASTM D1000
Elongation at Break	%	5	5	ASTM D1000
Release Liner Thickness	µm	60	60	ASTM D1000
Release Liner	-	Double side release paper	Double side release paper	-

Available Colours

White

Storage & Usage Conditions

Store at room temperature, away from direct sunlight, heat, and moisture.
Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH).
Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.

Available Formats

Standard cut rolls and jumbo roll formats for slitting and conversion

