

CROSS FILAMENT REINFORCED PACKAGING TAPE

PET-GLASS FIBRE LAMINATE / HOT MELT ADHESIVE

PRODUCT CODE

DT7243



Description	DEON® DT7243 - CROSS FILAMENT REINFORCED PACKAGING TAPE Cross-filament reinforced tape with polyester film and glass fibre filaments in both directions, coated with hot melt adhesive, engineered for heavy-duty bundling and packaging where bidirectional tear resistance and dimensional stability under load are required.		
Features	• High Tensile Strength (≥ 120 N/cm) • Good Adhesion to Metal, Carton & Plastic Surfaces • Low Elongation (≤ 5%) for Stable Load Holding • Cross Filament Reinforcement for Multi-Directional Strength		
Application	• Steel Coil & Metal Bundle Wrapping • Appliance & Equipment Securing for Transit • Heavy-Duty Export Carton Reinforcement • Container Cover Sealing & Load Unitising		

Technical Properties	Product Characteristics	UOM	Typical Values	Test Method
	Backing Material	-	PET / Cross-woven Glass Fibre Laminate	-
	Thickness (Customizable)	µm	130 ± 0.005	ASTM -D1000
	Width (Customizable)	mm	-	ASTM -D1000
	Length (Customizable)	m	50	-
	Adhesive	-	Synthetic Hot Melt	-
	Adhesive Coating	-	Single - sided	-
	Adhesion to Steel (min)	N/cm	8.0	ASTM -D1000
	Tensile Strength (min)	N/cm	120	ASTM -D1000
	Elongation at Break	%	5	ASTM -D1000

Available Colours

Yellowish

Storage & Usage Conditions

Store at room temperature, away from direct sunlight, heat, and moisture.
Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH).
Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.

Available Formats

Standard cut rolls and jumbo roll formats for slitting and conversion

