

BOPP PACKAGING TAPE

BOPP FILM / WATER-BASED ACRYLIC ADHESIVE

PRODUCT CODE

DT9151



Description

DEON® DT9151 - BOPP PACKAGING TAPE

The DT9151 series are single-sided BOPP packaging tapes coated with water-based acrylic adhesive, enabling precise specification matching for light, standard, and heavy-duty carton sealing and packaging line requirements.

- Features
- Solvent-free, water-based acrylic adhesive system — compliant with industrial hygiene standards and suitable for food-adjacent secondary packaging environments.
 - Available in a wide range of standard thickness grades with full customisation of thickness, width, and roll length - enabling precise specification matching for any packaging line or buyer requirement.
 - Strong peel adhesion combined with sustained shear resistance ensures long-term carton seal integrity from point of packing through final delivery.
 - Consistent bond performance on corrugated fibreboard, kraft, recycled board, and plastic substrates under standard machine and hand-application pressures.

- Application
- Carton sealing and box closure on automated and manual packaging lines
 - Flap-closure sealing and reinforcement in secondary and transit packaging
 - Securing corrugated shipping boxes for e-commerce, industrial distribution, and export logistics
 - Custom-printed branded packaging tape - customer logo printing available on request

Technical Properties

Product Characteristics	UOM	Typical Values	Test Method
Backing Material	-	BOPP Film	-
Thickness (Customizable)	µm	38 - 55	ASTM D1000
Width (Customizable)	mm	-	ASTM D1000
Length (Customizable)	m	66	-
Adhesive	-	Water-based Acrylic	-
Adhesive Coating	-	Single - sided	-
Adhesion to Steel (min)	N/25mm	4.1 - 5.5	ASTM D1000
Tensile Strength, MD (min)	N/25mm	70 - 80	ASTM D1000
Elongation at Break MD (min)	%	100	ASTM D1000
Initial Tack - Rolling Ball (max)	cm	8	ASTM D1000
Shear Strength on Steel (min)	hrs	>24	ASTM D1000

Available Colours

Brown

Red

Blue

Yellow

Green

White

Black

Yellow (Translucent)

Orange (Translucent)

Storage & Usage Conditions

Store at 21°C / 50% RH, away from direct sunlight and moisture sources.

Ensure carton surfaces are clean and dry; avoid application below 10°C for optimal initial tack.

- Available Formats
- Standard roll length: 66 m (custom lengths available).
 - Core: 76 mm ID, paper.
 - Standard slit widths: 12 / 18 / 24 / 36 / 48 / 60 / 72 / 96 mm.
 - Custom widths, lengths, and thickness grades available on request.

