



Description	DEON® PW6001 – PVC PIPE WRAPPING TAPE PVC pipe wrapping tape with rubber adhesive, designed for corrosion protection, moisture sealing, and insulation applications on pipes and ducts.																																														
Features	• Good Peel Strength for Secure Wrapping • Flexible PVC Backing for Conformable Application • Moisture & Corrosion Resistance • Suitable for Outdoor & Industrial Use																																														
Application	• Pipeline Protection & Wrapping • Moisture Sealing & Insulation • Air Conditioning Duct Wrapping																																														
Technical Properties	<table><tr><th>Product Characteristics</th><th>UOM</th><th>Typical Values</th><th>Test Method</th></tr><tr><td>Backing Material</td><td>-</td><td>PVC Flim</td><td>-</td></tr><tr><td>Thickness (Customizable)</td><td>µm</td><td>0.130 ± 0.01</td><td>ASTM D1000</td></tr><tr><td>Width (Customizable)</td><td>mm</td><td>48</td><td>ASTM D1000</td></tr><tr><td>Length (Customizable)</td><td>m</td><td>65 / 100</td><td>-</td></tr><tr><td>Adhesive</td><td>-</td><td>Rubber Adhesive</td><td>-</td></tr><tr><td>Adhesive Coating</td><td>-</td><td>Single - sided</td><td>-</td></tr><tr><td>Adhesion to Steel (min)</td><td>N/cm</td><td>≥ 0.8</td><td>ASTM D1000</td></tr><tr><td>Tensile Strength (min)</td><td>N/cm</td><td>≥ 8</td><td>ASTM D1000</td></tr><tr><td>Temperature Operating Range</td><td>-</td><td>up to 55°C</td><td>ASTM D1000</td></tr><tr><td>Initial Tack - Rolling Ball (max)</td><td>mm</td><td>≥ 100</td><td>ASTM D1000</td></tr></table>			Product Characteristics	UOM	Typical Values	Test Method	Backing Material	-	PVC Flim	-	Thickness (Customizable)	µm	0.130 ± 0.01	ASTM D1000	Width (Customizable)	mm	48	ASTM D1000	Length (Customizable)	m	65 / 100	-	Adhesive	-	Rubber Adhesive	-	Adhesive Coating	-	Single - sided	-	Adhesion to Steel (min)	N/cm	≥ 0.8	ASTM D1000	Tensile Strength (min)	N/cm	≥ 8	ASTM D1000	Temperature Operating Range	-	up to 55°C	ASTM D1000	Initial Tack - Rolling Ball (max)	mm	≥ 100	ASTM D1000
Product Characteristics	UOM	Typical Values	Test Method																																												
Backing Material	-	PVC Flim	-																																												
Thickness (Customizable)	µm	0.130 ± 0.01	ASTM D1000																																												
Width (Customizable)	mm	48	ASTM D1000																																												
Length (Customizable)	m	65 / 100	-																																												
Adhesive	-	Rubber Adhesive	-																																												
Adhesive Coating	-	Single - sided	-																																												
Adhesion to Steel (min)	N/cm	≥ 0.8	ASTM D1000																																												
Tensile Strength (min)	N/cm	≥ 8	ASTM D1000																																												
Temperature Operating Range	-	up to 55°C	ASTM D1000																																												
Initial Tack - Rolling Ball (max)	mm	≥ 100	ASTM D1000																																												
* Max 70°C up to 30°C																																															
Available Colours	Black																																														
Storage & Usage Conditions	Store at room temperature, away from direct sunlight, heat, and moisture. Shelf life is six months from the date of shipment when stored under standard conditions (21°C, 50% RH). Ensure the application surface is clean, dry, and free from grease and oil. A trial application is recommended to confirm suitability for the intended use.																																														
Available Formats	Standard cut rolls and log roll formats for slitting and conversion																																														

