

WE HAVE BETTER SOLUTIONS

VIDEO LARYNGOSCOPE VIDEO STYLET LIGHTED STYLET

DISPOSABLE VIDEO LARYNGOSCOPE

Anti-Fog medical-grade polycarbonate



Blade parameter size

Item Number: BD-DP

Blade	MilO	MAC1	MAC3	MAC4
Application	Neonate	Pediatric	Adult	Large Adult
Intubation Inner Diameter	2.5-4.0mm	4.0-6.0mm	6.0-9.0mm	7.5-10.0mm
Length (cm)	8.31	10.15	13.69	16.08
Sterilize Method	2.0%Glutaral fully soak for 10 minutes Or 0.5%-0.6% Cidex OPA for more than 5 minutes.			

Technical Specification

Parts	Description	Technical Index	
Machine	Display	3inch LCD	
	Resolution Ratio	640*480 (RGB)	
	Viewing angle	≥60°	
	Power	<2W	
	Display front and back rotation Angle	0°~130°	
	Weight	225g	
Camera	Illuminance	≥150 LUX	
	Resolution Ratio	1280*720 px	
Image/Video function	Image/ Video function	Yes	
	Outrot	USB output,	
	Output	Easy to storage and establish image/video	
	Memory type	Micro SD card 8GB	
Batterty	Battery Type	Rechargable lithium battery	
	Capacity	1350mAh	
	Cycle life of battery	>500 times	
	Battery working time	>240min	
	Charging time	<2(hrs)	
	Charging Port	Micro USB	
Power Adapter	Input	100-250V, 50 Hz.	
	Output	5V1A	
Working Condition	Temperature	-5 °C~+50 °C	
	Humidity	10%~90%	
	Air Pressure	860~1060hpa	
Transport / Storage Condition	Temperature	-10°C~50°C	
	Humidity	≤93%	
	Air Pressure	500~1060hpa	

BESDATA® VIDEO Larryngoscope make it better prepared for unexpected tracheal intubations.

- Confidence MAC-style video laryngoscope blades for a wide range of clinical preferences
- Simplicity One-button operation, Automatic power off
- Convenience —Anti-Fog Camera, 3.0inch screen reduces blind spot,250 minutes battery with screen low battery alarming notice

Compared to traditional MAC-style laryngoscopy Blades, Besdata®Video Laryngoscope articulated tip have a bigger angle that allows to raise the epiglottis equal to or greater than 60 $^{\circ}$.



BESDATA TECHNOLOGY CO.,LTD

Add:2 / F, Building C, Hongyi Industrial Park,
No.4010 Banxuegang Road, Shenzhen, 518129, China
Tel: +86-755-84416070 Fax: +86-755-23039200
support@besdatatech.com www.besdatatech.com