



# Azure Transit VNet Deployment Guide

How to deploy a Transit VNet solution in Azure

<http://www.paloaltonetworks.com>

## Table of Contents

---

<b>Version History.....</b>	<b>3</b>
<b>1. About.....</b>	<b>4</b>
<b>2. Topology .....</b>	<b>4</b>
<b>3. Support Policy.....</b>	<b>6</b>
<b>4. Prerequisites .....</b>	<b>6</b>
<b>5. Launch the Transit VNet Hub Template.....</b>	<b>7</b>
<b>6. Launch the Transit VNet Spoke Template .....</b>	<b>17</b>
<b>7. VNet Peering Verification.....</b>	<b>24</b>
<b>8. Inbound and Outbound Traffic Tests .....</b>	<b>26</b>
<b>9. Cleanup .....</b>	<b>31</b>

## Version History

Version number	Comments
1.0	Initial GitHub check-in

## **1. About**

This document will guideline how to deploy a Transit VNet solution in Azure. For more details about the advantages of the hub and spoke topology please refer to this link:

<https://docs.microsoft.com/en-us/azure/architecture/reference-architectures/hybrid-networking/hub-spoke>

**Note:** The Azure Transit VNet solution is considered advanced. It requires familiarity with Azure and Palo alto Networks. For a more entry level solution please refer to the following Azure Two Tier solution.

<https://github.com/PaloAltoNetworks/azure/tree/master/two-tier-sample>

## **2. Topology**

The transit VNet solution deploys a classic hub-and-spoke. The Hub is deployed in a separate VNet, and each spoke is deployed in a separate VNet as well.


### **VNet Peering**

For the different virtual networks to talk to each other, they must be peered in both the directions. VNet Peering works under the assumption that the peering networks **do not have overlapping subnets**. In this topology, when a VNet spoke is deployed, we will dynamically peer the spoke's VNet and the hub's VNet enabling traffic to flow between them.

For additional information on VNet Peering please reference the link below

<https://docs.microsoft.com/en-us/azure/virtual-network/virtual-network-peering-overview>

## Palo Alto Networks Azure Transit VNet Deployment Guide



**Figure 1**

### Hub Topology

In Figure 1 **PAN** represents the Hub VNet. The Hub VNet consists of Mgmt , Untrust and Trust subnets. An Azure internal LB[Outbound-LB] used for outbound traffic and a pair of VM Series FWs in an availability set. The Hub topology serves as the exit point of all non-return traffic for the Hub and Spoke topology.

### Spoke Topology

In Figure 1 **APP1** represents the Spoke VNet. The spoke VNet allows an ingress point for all traffic destined to public facing resources. The subnets consist of Mgmt, Untrust, Trust and Backend Subnets for the application servers. An Application Gateway doubles as a public facing load balancer and sits on the front end. A pair of VM Series FWs in an availability set receive traffic from the public facing LB. An Internal LB sits behind the firewalls and sends traffic to the backend application servers. All return traffic egresses this same path. When a spoke subscribes to a hub, a UDR is also defined which has a default route to the Hub's

Internal Load Balancer. This is so all packets that are not destined to the spoke's virtual network gets forwarded to the Hub Internal LB for routing.

## **3. Support Policy**

This solution is released under an as-is, best effort, support policy. These scripts should be seen as community supported and Palo Alto Networks will contribute our expertise as and when possible. We do not provide technical support or help in using or troubleshooting the components of the project through our normal support options such as Palo Alto Networks support teams, or ASC (Authorized Support Centers) partners and backline support options. The underlying product used (the VM-Series firewall) by the scripts or templates are still supported, but the support is only for the product functionality and not for help in deploying or using the template or script itself.

## **4. Prerequisites**


Here are the prerequisites required to successfully launch this template:

1. AZURE account with appropriate permissions.
2. Clone or download the files from the following GitHub repository on to your local machine:  
<https://github.com/PaloAltoNetworks/Azure-transit-VNet>
3. If the GitHub Repository has a deploy button you can deploy your templates using the button.



## 5. Launch the Transit VNet Hub Template

In the Azure Resource Manager console you can launch the `azureDeployInfra.json` file directly from the Azure Portal. To do this click “**New**” then search “**Template Deployment**”, click the Template Deployment icon and select “**Create**”.



The screenshot shows the Microsoft Azure portal interface. On the left, there's a sidebar with options like New, Dashboard, All resources, Resource groups, App Services, and SQL databases. The main area is titled "Marketplace" and has a search bar at the top right with the placeholder "Search resources, services and docs". Below the search bar, there's a filter section with a dropdown set to "Everything" and a search input for "Template Deployment". The results table has columns for NAME, PUBLISHER, and CATEGORY. One result is listed: "Template deployment" by Microsoft, categorized under Compute.

NAME	PUBLISHER	CATEGORY
Template deployment	Microsoft	Compute

In the next screen click “**Build your own template in the editor**”

## Palo Alto Networks Azure Transit VNet Deployment Guide

The screenshot shows the Microsoft Azure portal interface. The top navigation bar includes 'New > Marketplace > Everything > Template deployment > Custom deployment'. On the left sidebar, under the 'New' section, there are links for 'Dashboard', 'All resources', 'Resource groups', 'App Services', 'SQL databases', 'SQL data warehouses', 'Azure Cosmos DB', and 'Virtual machines'. The main content area is titled 'Custom deployment' with the sub-instruction 'Deploy from a custom template'. Below this, a section titled 'Learn about template deployment' contains two items: 'Read the docs' and 'Build your own template in the editor', with the second item having a red arrow pointing to it. Another section titled 'Common templates' lists four options: 'Create a Linux virtual machine', 'Create a Windows virtual machine', 'Create a web app', and 'Create a SQL database'.

Select “Load File”


The screenshot shows the 'Edit template' page within the Azure portal. The top navigation bar is identical to the previous screenshot. The main content area is titled 'Edit template' with the sub-instruction 'Edit your Azure Resource Manager template'. Below this, there are buttons for '+ Add resource', 'Quickstart template', 'Load file' (which is highlighted with a red box), and 'Download'. To the right, there are sections for 'Parameters (0)', 'Variables (0)', and 'Resources (0)'. A code editor window displays the beginning of an ARM template:

```
1 {
2     "$schema": "https://schema.management.azure.com/schemas/2015-01-01/deploymentTemplate.json#",
3     "contentVersion": "1.0.0.0",
4     "parameters": {},
5     "resources": []
6 }
```

## Palo Alto Networks Azure Transit VNet Deployment Guide

Select “**azureDeployInfra.json**” file from the Azure-Transit-VNet/azure-pan-hub directory that you cloned from GitHub, then click “**Save**” to bring up the parameters.

## Palo Alto Networks Azure Transit VNet Deployment Guide



## Palo Alto Networks Azure Transit VNet Deployment Guide

- a. Most of the **parameters** are self-explanatory and should be left at the defaults
- b. **Resource Group** – Always create a new resource Group. The hub template does not work in an existing resource group
- c. **Location** – Use a location where Standard Load Balancer Preview feature is enabled. List of regions is found here - <https://docs.microsoft.com/en-us/azure/load-balancer/load-balancer-standard-overview#region-availability>
- d. **Hub Load Balancer Sku** – Use the **Standard** SKU type which will load balance all outbound TCP traffic.
- e. **Network Security Group Name** is the NSG that is attached to the Firewall's Management subnet
- f. **Network Security Group Inbound Src IP** – This is the IP you will allow explicit access to the management interface of the virtual machines.
- g. **Virtual Network Name** – Use a unique name which will not be used in the spoke VNet deployment. Remember this name since it is an input parameter for the spoke template.
- h. For security purposes be sure to set **Security Group Inbound IP** for mgmt access to the firewall.
- i. **Virtual Network Address Prefix** – Use a network address which will not be used in the spoke deployment.
- j. **Virtual Network Name** – Use a unique name which will not be used in the spoke VNet deployment. Remember this name since it is an input parameter for the spoke template.
- k. **Virtual Network Address Prefix** – Use a network address which will not be used in the spoke deployment.
- l. **Load Balancer IP** – Use a static IP for Load Balancer in the Trust network. Remember this address since it is used as an input parameter for the spoke template.
- m. **Firewall Model** – The template default will work unless a larger size is required.
- n. It could take up to 5 minutes to complete the launch or It could take longer depending on Azure.
- o. **Username** and **password** that is entered by default for the devices is

**user:pandemo password:Dem0pa\$\$w0rd**

## Palo Alto Networks Azure Transit VNet Deployment Guide

**Custom deployment**  
Deploy from a custom template

---

**TEMPLATE**

Customized template  
5 resources

Edit template Edit parameters Learn more

---

**BASICS**

\* Subscription: AzureTME

\* Resource group: Create new (radio button selected) Use existing  
Create a resource group

\* Location: Central US

---

**SETTINGS**

Hub Load Balancer Sku: Standard

Storage Name: Enter a globally unique name

Mgmt Public IP Dns: Enter a globally unique name

Network Security Group Name: nsg

Network Security Group Inbound IP: 0.0.0.0/0 

Av Set Name: outbound-avset

Storage Type: Standard\_LRS

Virtual Network Name: vnet

Virtual Network Address Prefix: 10.0.0.0/16

Mgmt Subnet Name: Mgmt

Mgmt Subnet Prefix: 10.0.0.0/24

## Palo Alto Networks Azure Transit VNet Deployment Guide

Acknowledge the terms and conditions and click “Purchase”

Untrusted Subnet Name <small> ⓘ</small>	Untrust
Untrusted Subnet Prefix <small> ⓘ</small>	10.0.1.0/24
Trusted Subnet Name <small> ⓘ</small>	Trust
Trusted Subnet Prefix <small> ⓘ</small>	10.0.2.0/24
Mgmt Public IP Name <small> ⓘ</small>	mgmt-pip
Load Balancer Name <small> ⓘ</small>	outbound-lb
Load Balancer IP <small> ⓘ</small>	10.0.2.4
Firewall Model <small> ⓘ</small>	byol
Firewall Vm Name <small> ⓘ</small>	outbound-vm-series
Firewall Vm Size <small> ⓘ</small>	Standard_D3_v2
Authentication Type <small> ⓘ</small>	password
Username <small> ⓘ</small>	pandemo
Password <small> ⓘ</small>	*****
Ssh Public Key <small> ⓘ</small>	

### TERMS AND CONDITIONS

this template. Prices and associated legal terms for any Marketplace offerings can be found in the [Azure Marketplace](#); both are subject to change at any time prior to deployment.

Neither subscription credits nor monetary commitment funds may be used to purchase non-Microsoft offerings. These purchases are billed separately.

If any Microsoft products are included in a Marketplace offering (e.g. Windows Server or SQL Server), such products are licensed by Microsoft and not by any third party.

I agree to the terms and conditions stated above

Pin to dashboard

**Purchase**

## Palo Alto Networks Azure Transit VNet Deployment Guide

Once the firewalls have launched, locate the **Management** interface public IP address in Azure.

outbound-vm-series0-std - Networking

Virtual machine

Search (Ctrl+ /)

Overview

Activity log

Access control (IAM)

Tags

Diagnose and solve problems

SETTINGS

Networking

Attach network interface    Detach network interface

outbound-vm-series0-nic1-std    outbound-vm-series0-nic0    outbound-vm-series0-nic2

**Network Interface:** outbound-vm-series0-nic0

Virtual network/subnet: vnet/Mgmt    Public IP: 40.67.191.216    Private IP: 10.0.0.5

**INBOUND PORT RULES**

Network security group nsg-mgmt (attached to subnet: Mgmt)  
Impacts 1 subnets, 0 network interfaces

PRIORITY	NAME	PORT	PROTOCOL	SOURCE
----------	------	------	----------	--------

Log into the hub firewalls using **HTTPS**. Locate the **working\_hub\_config.xml** configuration snapshot and import this configuration into both firewalls. This is in the Hub directory that you exported from GitHub.

Dashboard ACC Monitor Policies Objects Network Device

Management Operations Services Interfaces Telemetry Content-ID WildFire Session HSM

Configuration Management

Revert: Revert to last saved configuration  
Revert to running configuration  
Save: Save named configuration snapshot  
Save candidate configuration  
Load: Load named configuration snapshot  
Load configuration version  
Export: Export named configuration snapshot  
Export configuration version  
Export device state  
Import: Import named configuration snapshot  
Import device state

Import Named Configurator

Import File: Select a file    Browse...    OK    Cancel

File name: working\_hub\_config.xml    Open    Cancel

## Palo Alto Networks Azure Transit VNet Deployment Guide

Once you load the configuration and commit the changes make sure your ethernet1/1 and Ethernet1/2 interfaces now show green.

Interface	Interface Type	Management Profile	Link State	IP Address	Virtual Router	Tag	VLAN / Virtual-Wire	Security Zone	Features	Comment
ethernet1/1	Layer3	ILBHealthCheck	<span style="color: green;">online</span>	Dynamic-DHCP Client	default	Untagged	none	untrust		
ethernet1/2	Layer3	ILBHealthCheck	<span style="color: green;">online</span>	Dynamic-DHCP Client	default	Untagged	none	trust		
ethernet1/3			<span style="color: grey;">offline</span>	none	none	Untagged	none	none		
ethernet1/4			<span style="color: grey;">offline</span>	none	none	Untagged	none	none		
ethernet1/5			<span style="color: grey;">offline</span>	none	none	Untagged	none	none		
ethernet1/6			<span style="color: grey;">offline</span>	none	none	Untagged	none	none		
ethernet1/7			<span style="color: grey;">offline</span>	none	none	Untagged	none	none		

Verify the **virtual router** has the following configuration.

Name	Interfaces	Configuration	RIP	OSPF	OSPFv3	BGP
default	ethernet1/1 ethernet1/2	Static Routes: 3 ECMP status: Disabled				

**Virtual Router - default**

**Router Settings**

- Static Routes
- Redistribution Profile
- RIP
- OSPF
- OSPFv3
- BGP
- Multicast

**IPv4** **IPv6**

**Next Hop**

Name	Destination	Interface	Type	Value	Admin Distance	Metric	BFD	Route Table
defaultRoute	0.0.0.0/0	ethernet1/1	ip-address	10.20.1.1	default	10	None	unicast
SpokeRoute	192.168.0.0/24	ethernet1/2	ip-address	10.20.2.1	default	10	None	unicast
HealthProbe	168.63.129.0/24	ethernet1/2	ip-address	10.20.2.1	default	10	None	unicast

**Add** **Delete** **Clone**

**OK** **Cancel**

**DefaultRoute:** is to forward all outbound traffic to the untrust interface so that it egresses out of the Azure network.

## Palo Alto Networks Azure Transit VNet Deployment Guide

**SpokeRoute:** is to forward all the inbound traffic and inter-spoke traffic back to the Trust interface so that it reaches the appropriate Spoke (application server). Note that the Network address of the all the spokes VNets should be part of this network address. If a new spoke is added whose network address is not part of this network address, then a new route needs to be added in the config to forward that traffic to the Trust interface.

**HealthProbe:** is to respond to the health probe packets generated by the Internal Load Balancer. For this lab the health check is configured to port 22 on the firewall Trust interface.

An **allow-all** security policy is created to forward all traffic. This should be modified to accommodate your policy preferences.

Name	Tags	Type	Source				Destination				Application	Service	Action	Profile	Options
1	allow_all	none	universal	any	any	any	any	any	any	any	any	any	any	none	none
2	intrazone-default	none	intrazone	any	any	any	any	(intrazone)	any	any	any	any	any	none	none
3	interzone-default	none	interzone	any	any	any	any	any	any	any	any	any	any	Deny	none

Verify that you have a **NAT rule** on the hub firewall for outbound traffic

	Name	Tags	Original Packet						Translated Packet	
	Name	Tags	Source Zone	Destination Zone	Destination Interface	Source Address	Destination Address	Service	Source Translation	Destination Translation
1	hubNatRule	none	trust	untrust	ethernet1/1	any	any	any	dynamic-ip-and-port ethernet1/1	none


## 6. Launch the Transit VNet Spoke Template

There are two flavors of the spoke template.

**Azuredeploy.json** – This launches the spoke template with VM-Series firewalls sandwiched between an external and internal load balancer. This provides secured external access to public facing workloads with return traffic egressing the spoke VNet. All internal originating traffic will be forwarded to the Hub VNet as the exit route to provide secure outbound access.

**Azuredeploy-no-firewall.json** – Launches the spoke template with no firewalls but still launches application servers. This scenario would NOT provide security using the VM-Series for public facing workloads. All internal originating traffic will be forwarded to the Hub VNet as the exit route to provide secure outbound access.

From the Azure-Transit-VNet/azure-pan-spoke GitHub repository that you cloned, launch the **azuredeploy.json** file directly from the Azure Portal. You may need to bring up two azure portal browsers in order to locate information needed to fill out the parameters when launching this template. To do this click “**New**” then search “**Template Deployment**”, click the Template Deployment icon and select “**Create**”.



## Palo Alto Networks Azure Transit VNet Deployment Guide

In the next screen click “Build your own template in the editor”

Microsoft Azure New > Marketplace > Everything > Template deployment > Custom deployment

Custom deployment  
Deploy from a custom template

New

Dashboard

All resources

Resource groups

App Services

SQL databases

SQL data warehouses

Azure Cosmos DB

Virtual machines

Learn about template deployment

Read the docs

Build your own template in the editor

Common templates

Create a Linux virtual machine

Create a Windows virtual machine

Create a web app

Create a SQL database

Select “Load File”

Microsoft Azure New > Marketplace > Everything > Template deployment > Custom deployment > Edit template

Search resources, services and docs

New

Dashboard

All resources

Resource groups

Edit template  
Edit your Azure Resource Manager template

Add resource Quickstart template Load file Download

Parameters (0)


Variables (0)

Resources (0)

```
1 {  
2   "$schema": "https://schema.management.azure.com/schemas/2015-01-01/deploymentTemplate.json#",  
3   "contentVersion": "1.0.0.0",  
4   "parameters": {},  
5   "resources": []  
6 }
```

Select “azuredetect.json” file from the Azure-Transit-VNet/azure-pan-spoke directory that you cloned from GitHub, then click “Save” to bring up the parameters.

## Palo Alto Networks Azure Transit VNet Deployment Guide



- a. Most of the **parameters** are self-explanatory and should be left at the defaults
- b. **Resource Group** – Create a new Resource Group. This template does not work with existing resource groups.
- c. **Location** – It should be the same location as the hub since VNet peering does not work well across regions.
- d. **Hub Resource Group Name** – Give the Resource Group name of the hub created resource group.
- e. **Hub VNet Name** – Use the exact VNet name of the hub created earlier.
- f. **Hub Load Balancer IP** – Use the static IP given to the Load Balancer in the created in the hub template. You can find this information in the load balancer settings
- g. **Network Security Group Name** – The security group name for mgmt access
- h. **Network Security Group Inbound Src IP** – This is the IP you will allow explicit access to the management interface of the virtual machines.
- i. **Virtual Network Address Prefix** – This network address should be the subnet of the network address given in the “**SpokeRoute**” in the hub’s firewall configuration.

## Palo Alto Networks Azure Transit VNet Deployment Guide

- j. **Mgmt, Trust and Untrust** subnets should be subnets of the VNet subnet created in the previous step.
- k. **Firewall VM Size** - Choose the Firewall Model and Size based on requirements. Use Standard D3 or D3 v2.
- l. **SSH Public Key** – If using a password then leave this section blank.

## Palo Alto Networks Azure Transit VNet Deployment Guide

**Custom deployment**  
Deploy from a custom template

---

**BASICS**

\* Subscription: AzureTME

\* Resource group: Create new (selected) / Use existing  
Create a resource group

\* Location: Central US

---

**SETTINGS**

\* Hub Resource Group Name: hubrg ✓

Hub Vnet Name: hubvnet

\* Hub Load Balancer IP: 10.0.2.4 ✓

Network Security Group Name: nsg-mgmt

Network Security Group Inbound Src IP: 0.0.0.0/0

Virtual Network Name: spoke-vnet

Virtual Network Address Prefix: 192.168.0.0/16

Mgmt Subnet Name: Mgmt

Mgmt Subnet Prefix: 192.168.0.0/24

Untrusted Subnet Name: Untrust

Untrusted Subnet Prefix: 192.168.1.0/24

Trusted Subnet Name: Trust

Trusted Subnet Prefix: 192.168.2.0/24

App Gateway Name: myAppGw

\* App Gateway Dns Name:

## Palo Alto Networks Azure Transit VNet Deployment Guide

App Gateway Subnet Name <small> ⓘ</small>	AppGWSUBNET
App Gateway Subnet Prefix <small> ⓘ</small>	192.168.3.0/24
Internal Load Balancer Name <small> ⓘ</small>	myPrivateLB
Backend Subnet Name <small> ⓘ</small>	backendSubnet
Backend Subnet Prefix <small> ⓘ</small>	192.168.4.0/24
Backend Vm Size <small> ⓘ</small>	Standard_D1
Firewall Model <small> ⓘ</small>	byol
Firewall Vm Name <small> ⓘ</small>	VM-Series
Firewall Vm Size <small> ⓘ</small>	Standard_D3
* Mgmt Public IP Address Name <small> ⓘ</small>	
* Storage Account Name <small> ⓘ</small>	
Storage Account Type <small> ⓘ</small>	Standard_LRS
* Username <small> ⓘ</small>	
Authentication Type <small> ⓘ</small>	password
Password <small> ⓘ</small>	
Ssh Public Key <small> ⓘ</small>	

### TERMS AND CONDITIONS

[Azure Marketplace Terms](#) | [Azure Marketplace](#)

By clicking "Purchase," I (a) agree to the applicable legal terms associated with the offering; (b) authorize Microsoft to charge or bill my current payment method for the fees associated the offering(s), including applicable taxes, with the same billing frequency as my Azure subscription, until I discontinue use of the offering(s); and (c) agree that, if the deployment involves 3rd party offerings, Microsoft may share my contact information and other details of such deployment with the publisher of that offering.


I agree to the terms and conditions stated above

Pin to dashboard


**Purchase**

## Palo Alto Networks Azure Transit VNet Deployment Guide

Once the Spoke template has successfully launched you will see Deployment Succeeded.



Log into the spoke firewalls using **HTTPS**. Locate the **appgw-sample.xml** configuration snapshot and import this configuration into both firewalls. This is in the Spoke directory that you exported from GitHub.



## Palo Alto Networks Azure Transit VNet Deployment Guide

Once you load the configuration and commit the changes. Once you have committed the changes make sure your ethernet1/1 and Ethernet1/2 interfaces now show green

Interface	Interface Type	Management Profile	Link State	IP Address	Virtual Router	Tag	VLAN / Virtual-Wire	Security Zone	Features	Comment
ethernet1/1	Layer3		Up	Dynamic-DHCP Client	default	Untagged	none	untrust		
ethernet1/2	Layer3		Up	Dynamic-DHCP Client	default	Untagged	none	trust		
ethernet1/3			Up	none	none	Untagged	none	none		
ethernet1/4			Up	none	none	Untagged	none	none		
ethernet1/5			Up	none	none	Untagged	none	none		
ethernet1/6			Up	none	none	Untagged	none	none		
ethernet1/7			Up	none	none	Untagged	none	none		

Verify the spoke firewall **virtual router** has the following configuration.

Name	Destination	Interface	Type	Value	Admin Distance	Metric	BFD	Route Table
appgw	0.0.0.0/0	ethernet1/1	ip-address	192.168.1.1	default	10	None	unicast

**appgw:** is to forward all traffic originating from the firewall to the untrust interface. Traffic originating from spoke resources behind the firewall will egress through the Hub VNet.

## Palo Alto Networks Azure Transit VNet Deployment Guide

An **allow-all** security policy on the firewall is created to receive all traffic although the application gateway load balancer only listens for port 80. This should be modified to accommodate your policy preferences.

Name	Tags	Type	Source				Destination			Application	Service	Action	Profile	Options
			Zone	Address	User	HIP Profile	Zone	Address						
1 allow_all	none	universal	any	any	any	any	any	any	any	application-d...	Allow	none	none	none
2 intrazone-default	none	intrazone	any	any	any	any	(intrazone)	any	any	any	Allow	none	none	none
3 interzone-default	none	interzone	any	any	any	any	any	any	any	any	Deny	none	none	none

Verify that you have a **NAT rule** on the spoke firewall for inbound traffic

Dashboard	ACC	Monitor	Policies	Objects	Network	Device
Name	Tags	Source Zone	Destination Zone	Destination Interface	Source Address	Destination Address
1 ilb	none	any	p2p untrust	any	any	firewall-untrust... any
Service	Source Translation	Translated Packet	Destination Translation			
	dynamic-ip-and-port	ethernet1/2	address: internal-load-balancer-IP			

## 7. VNet Peering Verification

Within Azure Portal verify that **VNet Peering** has been configured automatically between the Hub VNet and Spoke VNet. To check this in Azure navigate to Virtual Networks > select the virtual network **name**.

Virtual networks	
Palo Alto Networks	
	Add
	Columns
... More	
Filter by name...	
2 items	
NAME	↑↓
	spoke-vnet
	vnet

## Palo Alto Networks Azure Transit VNet Deployment Guide

Then select **Peerings**

The screenshot shows the 'vnet - Peerings' blade in the Azure portal. At the top, there's a search bar labeled 'Search (Ctrl+ /)'. Below it is a navigation menu with the following items:

- Overview
- Activity log
- Access control (IAM)
- Tags
- Diagnose and solve problems

Below the navigation menu is a section titled 'SETTINGS' with the following options:

- Address space
- Connected devices
- Subnets
- DNS servers
- Peerings

The 'Peerings' option is highlighted with a light blue background.

Here you should see the name of the peer **VNet** with a status of **connected**. **Gateway Transit** should be disabled. Check this on both the hub and spoke VNet.


NAME	PEERING STATUS	PEER	GATEWAY TRANSIT	...
vnet-spoke-vnetvnet-peering	Connected	spoke-vnet	Disabled	...

## 8. Inbound and Outbound Traffic Tests

Once you have confirmed that both the Hub and Spoke templates were successfully deployed, you have imported and loaded the firewall configuration and confirmed VNet Peering, you will want to test your proof of concept with live traffic.

### Outbound Traffic Test

As per the diagram all traffic originating from within the Azure virtual networks will exit through the Hub VNet.



One way to test this setup is to originate traffic from a backend Linux VM deployed in the spoke to [www.google.com](http://www.google.com) by using wget [www.google.com](http://www.google.com). From there check the traffic logs of the Hub firewalls

## Palo Alto Networks Azure Transit VNet Deployment Guide

for [www.google.com](http://www.google.com) traffic or web-browsing traffic if using another port 80 based website for wget tests. You will need a license to see logs in the traffic logs or you can edit the template to use PAYG1 or PAYG2.

By default you will not be able to access the Linux servers in the spoke. To access the Linux devices you will need to add a public IP address to one of the Spoke backend Linux servers. Then add a route on the UDR named “**defaultBackendUDR**” for mgmt traffic, that will allow your public IP address with a next hop of “**Internet**”


+ Add			
Search routes			
NAME	ADDRESS PREFIX	NEXT HOP	...
defaultRoute	0.0.0.0/0	10.0.2.4	...
mgmt-traffic	.0.0/16	Internet 	...

Another way to accomplish this would be to install a **Bastion Host** or **Jump Box** into the Backend Subnet and SSH from that device.

## Inbound Traffic Test

When launching the spoke template with firewalls, the spoke VNet will have an Application Gateway (External LB), A set of firewalls and an internal Load balancer. This allows the spoke to host its own public facing workloads. Once you have launched the Spoke template with firewalls you can test access to the public facing workload by

Navigating to “**Application gateways**” within the Azure Portal



## Palo Alto Networks Azure Transit VNet Deployment Guide


Selecting the name of your **Application Gateway** that was created when you launched the Transit VNet Spoke template. You can find the name of your **Resource Group** to help you differentiate from any other Application Gateways.

<input type="checkbox"/>	NAME	PUBLIC IP ADDR...	PRIVATE IP ADD...	RESOURCE GROUP
<input type="checkbox"/>	js-waf-appgw1	13.93.203.139	-	js-waf-appgw1
<input type="checkbox"/>	myAppGw	52.165.180.7	-	spokerg
<input type="checkbox"/>	myAppGw-jstestuuid1	104.45.230.21	-	jstestuuid1

Locate the **Public IP address** for your Application Gateway.

<input type="checkbox"/>	NAME	PUBLIC IP ADDR...	PRIVATE IP ADD...	RESOURCE GROUP
<input type="checkbox"/>	js-waf-appgw1	13.93.203.139	-	js-waf-appgw1
<input type="checkbox"/>	myAppGw	52.165.180.7	-	spokerg
<input type="checkbox"/>	myAppGw-jstestuuid1	104.45.230.21	-	jstestuuid1

Place the **Public IP address** in your web browser. This IP address is the public facing IP of the Application Gateway Load Balancer. You will see the default Ubuntu Page.



The screenshot shows a web browser window displaying the Apache2 Ubuntu Default Page. The URL in the address bar is 52.165.180.7. The page features the Ubuntu logo and the title "Apache2 Ubuntu Default Page". A red banner at the top right says "It works!". Below the banner, text explains that this is the default welcome page for testing the Apache2 server. It mentions that the configuration is based on Debian and includes a note about replacing the index file. A "Configuration Overview" section details the Apache2 configuration layout, showing a tree structure of files under /etc/apache2/. At the bottom, a list of bullet points describes the components of the configuration layout.

① 52.165.180.7

**Apache2 Ubuntu Default Page**

**It works!**

This is the default welcome page used to test the correct operation of the Apache2 server after installation on Ubuntu systems. It is based on the equivalent page on Debian, from which the Ubuntu Apache packaging is derived. If you can read this page, it means that the Apache HTTP server installed at this site is working properly. You should **replace this file** (located at `/var/www/html/index.html`) before continuing to operate your HTTP server.

If you are a normal user of this web site and don't know what this page is about, this probably means that the site is currently unavailable due to maintenance. If the problem persists, please contact the site's administrator.

**Configuration Overview**

Ubuntu's Apache2 default configuration is different from the upstream default configuration, and split into several files optimized for interaction with Ubuntu tools. The configuration system is **fully documented in `/usr/share/doc/apache2/README.Debian.gz`**. Refer to this for the full documentation. Documentation for the web server itself can be found by accessing the **manual** if the `apache2-doc` package was installed on this server.

The configuration layout for an Apache2 web server installation on Ubuntu systems is as follows:

```
/etc/apache2/
|-- apache2.conf
|   '-- ports.conf
|-- mods-enabled
|   '-- *.Load
|   '-- *.conf
|-- conf-enabled
|   '-- *.conf
|-- sites-enabled
|   '-- *.conf
```

- `apache2.conf` is the main configuration file. It puts the pieces together by including all remaining configuration files when starting up the web server.
- `ports.conf` is always included from the main configuration file. It is used to determine the listening ports for incoming connections, and this file can be customized anytime.
- Configuration files in the `mods-enabled/`, `conf-enabled/` and `sites-enabled/` directories contain particular configuration snippets which manage modules, global configuration fragments, or virtual host configurations, respectively.
- They are activated by symlinking available configuration files from their respective `*-available/` counterparts. These should be managed by using our helpers `a2enmod`, `a2dismod`, `a2ensite`, `a2dissite`, and `a2enconf`, `a2disconf`. See their respective man pages for detailed information.
- The binary is called `apache2`. Due to the use of environment variables, in the default configuration, `apache2` needs to be started/stopped with `/etc/init.d/apache2` or `apache2ctl`.

## 9. Cleanup

You can clean up the setup by deleting the **resource groups** for both the hub and spoke deployments. Once you have deleted the resource groups for both the hub and spoke you will have successfully deleted all resources created in this deployment.