SwissSign Adaptable CA

The purpose of this document is to provide information regarding the configuration of `SwissSign Managed PKI` for integration with Venafi Trust Protection Platform (TPP).

The information provided in this document is considered proprietary and confidential.

> This integration guide, as well as the software and/or products described in it, are furnished under agreement with `SwissSign AG` and may be used only in accordance with the terms of such agreement. Except as permitted by such agreement, no part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, recording, or otherwise, without prior written permission of SwissSign AG.

TABLE OF CONTENTS

- Prerequisites
- Installation and Configuration

Prerequisites

Before following the steps in this integration guide, the following prerequisite items must be installed and configured:

- Venafi Trust Protection Platform
- SwissSign Managed PKI [link]

Installation and Configuration

To enable Trust Protection Platform integration, the following must be completed:

Step 1: Username Credential

Create a "Username Credential", using an API key from your SwissSign account. Either:

- Use the "Service API Key" from your SwissSign account: https://ra.swisssign.ch/account/my/SAAPIKeys (columns: "Service Account", "API Key")
    - User Name: `<service-account>` (e.g. `MPKI5000042.AutoRA0`)
    - Password: `<api-key>`
- Or create a "Account API Key" in your SwissSign account: https://ra.swisssign.ch/account/my/keys (columns: "API Key")
    - User Name: `<account-username>` (e.g. `my-email@example.com`)
    - Password: `<api-key>`

Step 2: Adaptable CA Template

At the time of writing, the following products (called `policy-name` in this document) are available for SwissSign Managed PKI Service:

- Domain Validation (DV)
  - `SwissSign DV SSL Silver Single-Domain`
  - `SwissSign DV SSL Silver Multi-Domain`
  - `SwissSign DV SSL Silver Wildcard`
- Organisation Validation (OV)
  - `SwissSign OV SSL Gold Single-Domain`
  - `SwissSign OV SSL Gold Multi-Domain`
  - `SwissSign OV SSL Gold Wildcard`
- Extended Validation (EV)
  - `SwissSign EV SSL Gold Single-Domain`
  - `SwissSign EV SSL Gold Multi-Domain`
- E-Mail (S/MIME)
  - `SwissSign Pro S/MIME E-Mail ID Gold`
  - `SwissSign Pro S/MIME E-Mail ID Gold with Auth`
  - `SwissSign Pro S/MIME E-Mail ID Gold RSASSA-PSS`

Note that not all customers have all products available. Customers of SwissSign Private Managed PKI also have customized products. For a complete product listing refer to your SwissSign account:

- https://ra.swisssign.ch/issue for production, or
- https://ra.pre.swisssign.ch/issue for pre-production (testing) environment.

Set up a "CA Template":

- Set "CA Name" (e.g. `MPKI5000042 - SwissSign EV SSL Gold Single-Domain`).
- Pick "Username Credential" from step 1.
- Set "Service Address", either:
  - Service Address: **`https://api.ra.swisssign.ch`** for production, or
  - Service Address: `https://api.ra.pre.swisssign.ch` for pre-production (testing)
- Set "Profile String". The issuing CA (more precisely: the "product reference") is defined by `client-name` ("MPKIxxx - Client Name") and `policy-name` ("SwissSign EV SSL Gold Single-Domain", ...).

Pick a client and policy from your SwissSign account: https://ra.swisssign.ch/issue (columns: "Client", "Policy Name")

- Profile String: **`policy-name [client-name]`** (e.g. `SwissSign EV SSL Gold Single-Domain [MPKI5000042 - Firma Muster AG]`). Both client-name and policy-name are required values, there is no default.

Step 3: Server Certificate

- Set "Certificate Name" (e.g. `my.example.com - SwissSign EV`).
- In "Subject DN", specify at least a "**Common Name**" (CN). Values pre-set from the SwissSign policy are not required (such as Organization for OV and EV), and will silently be overwritten with correct SwissSign validated values.
- For multi-domain policies, also set "Subject Alt Name(s)" (SAN) of type DNS.
- Pick the "CA Template" created in step 2.