

21/08/2026

1) FROG JUMP:

```
import java.util.Scanner;

public class FrogJump {

    public static void main(String[] args) {

        Scanner scanner = new Scanner(System.in);

        if (!scanner.hasNextInt()) return;

        int n = scanner.nextInt();

        int[] heights = new int[n];

        for (int i = 0; i < n; i++) {

            heights[i] = scanner.nextInt();

        }

        scanner.close();

        if (n == 1) {

            System.out.println(0);

            return;

        }

        int prev2 = 0;

        int prev1 = Math.abs(heights[1] - heights[0]);

        for (int i = 2; i < n; i++) {

            int jumpOne = prev1 + Math.abs(heights[i] - heights[i - 1]);

            int jumpTwo = prev2 + Math.abs(heights[i] - heights[i - 2]);

            int current = Math.min(jumpOne, jumpTwo);

            prev2 = prev1;

            prev1 = current;

        }

        System.out.println(prev1);

    }

}
```

SQL

1. Select e.emp_id, e.emp_name, d.dept_name, d.location from employee e inner join departments d on e.dept_id=d.dept_id;
2. Select e.emp_id, e.emp_name, d.dept_name from employees e left join departments d on e.dept_id=d.dept_id;
3. Select d.dept_id, d.dept_name, d.location from departments d left join employees e on d.dept_id=e.dept_id where e.emp_id is null;
4. Select e.emp_name , p.project_name, d.dept_name, ep.hours from employee_project ep inner join employees e on ep.emp_id=e.emp_id inner join projects p on ep.project_id =p.project_id left join departments d on e.dept_id =d.dept_id;
5. Select p.project_id , p.project_name , e.emp_id, e.emp_name from projects p left join employee_project ep on p.project_id =ep.project_id left join employees e on ep.emp_id=e.emp_id;