

Honors Discrete Mathematics: Extra Problems

Due on Friday, April 28 at 11:59pm

Professor Gerandy Brito Spring 2023

Sarthak Mohanty

Instructions

Each semester, we release a challenge problem. It's ungraded, but your submission/discussion of this problem will be considered if you ever apply to be a TA for this course. You can find the previous years' problems [here](#).

IMPORTANT: For these problems, you may NOT collaborate with other students.

The Problem

In the Homework 5 Supplement, we wished to find a solution to the Task Scheduling problem, which we restate here:

We are given a partially ordered set of tasks $T = T_1, T_2, \dots, T_n$, where each task T_i takes 1 unit of time to complete. The tasks are partially ordered by a binary relation $<$, which specifies the dependencies between the tasks. Specifically, if $T_i < T_j$, then T_i must be completed before T_j can be started.

We also have k processors P_1, P_2, \dots, P_k available to perform the tasks. A **schedule** for T assigns each task T_i to a processor P_j and a start time t_i for P_j to begin working on T_i . If a processor starts working on T_i at time t_i , then T_i will be completed at time $t_i + 1$.

A schedule is **feasible** if it satisfies the following conditions:

- 1 No single processor performs multiple tasks at the same time. In other words, if a processor is assigned to both T_i and T_j , where $i \neq j$, then the start times for the two tasks must be different.
- 2 For every pair of tasks T_i and T_j such that $T_i < T_j$, the start time for T_j is later than or equal to the completion time for T_i . In other words, if T_i must be completed before T_j can start, then the start time for T_j must be after or at the same time as the completion time for T_i .

The **latency** of a schedule is defined as the time between the earliest start time for any task and the latest completion time for any task. Our goal is to find a feasible schedule with the smallest possible latency.

A possible **solution** was presented for this problem, but it was fairly inefficient. Your task is as follows: **Find an efficient solution for the Task Scheduling problem.**

A few notes:

- Consider how to best represent the input data, including possibly using external data structures.
- What is the Big- O time complexity of your solution? What about Big- Ω ?

Extra Problem [Spring 2022]

No one solved this problem last year, so we are posing it again.

Consider the grid shown below in Figure 1.

```

      S
    S A S
  S A R A S
S A R T R A S
S A R T H T R A S
S A R T H A H T R A S
S A R T H A K A H T R A S
S A R T H A H T R A S
S A R T H T R A S
S A R T R A S
S A R A S
S A S
    S
  
```

Figure 1: A diamond-shaped, narcissistic grid of letters.

Suppose you start at any S, and can move only left, right, down, or up to adjacent letters. In how many ways can the palindrome SARTHAKAHTRAS be read if the same letter cannot be used more than one in each sequence? **Prove your answer.**

(Hint): You can program a script to get your answer, and then work backwards to prove it.