Biometric-Secured Voice Controlled Audio Book Platform for Visually Impaired and Partially Sighted University Students in Sri Lanka

A Dissertation Submitted to

The Faculty of Computing and Information & Technology

Sri Lanka Technology Campus

BY

H.M.S RANDEEPA: 22UG1-0800

In Partial Fulfillment of the Requirements for

The Bachelor of Science (Honors) In

Software Engineering

2026

Dedication

I dedicate this thesis to the most important people in my life, who have supported me every step of the way throughout my academic journey. First, I express my deepest love and gratitude to my parents. Their constant encouragement, sacrifices, and belief in my abilities have given me the strength to overcome every challenge. They have been my greatest inspiration, and without their care and guidance, this achievement would not have been possible.

I also dedicate this work to my family members, who stood by me with patience and understanding during the many long hours I spent studying and writing. Their kind words, motivation, and emotional support kept me moving forward even when things felt difficult.

My heartfelt thanks also go to my teachers and lecturers, whose knowledge, guidance, and dedication shaped my learning. Their support helped me grow academically and personally, and I am truly grateful for their encouragement throughout this research.

Finally, I dedicate this thesis to all my friends who cheered me on, offered their help, and believed in me. Their friendship made this journey lighter and more meaningful.

To everyone who supported me in any way, this work is a reflection of your love, encouragement, and faith in me.

Declaration

I hereby declare that except where specific reference is made to the work of others, the contents of this dissertation are original and have not been submitted in whole or in part for consideration for any other degree or qualification in this, or any other university. This dissertation is my/our own work and contains nothing which is the outcome of work done in collaboration with others, except as specified in the text and Acknowledgments.

A.M.W.S.N.Koswatta

H.M.S.Randeepa

I.G.B.P.Samaranatha

November 2025

Acknowledgements

I would like to express my sincere gratitude to everyone who supported and guided me throughout the completion of this research study. First, I extend my heartfelt appreciation to my supervisor, whose continuous guidance, valuable feedback, and encouragement greatly helped me improve my work. Their patience, support, and expertise played an important role in shaping this thesis.

I am also truly grateful to all my lecturers and the academic staff of my faculty for providing me with the knowledge, skills, and motivation needed to complete this study successfully. Their dedication and commitment to teaching have inspired me throughout my academic journey.

My sincere thanks also go to the participants who willingly gave their time and honest responses for my research. Without their cooperation, this study would not have been possible.

I would like to thank my parents and family members for their unconditional love, strength, and continuous support. Their understanding, encouragement, and belief in me have been the foundation of my achievements.

A special appreciation goes to my friends, who supported me emotionally, shared helpful advice, and stood by me throughout this process.

Finally, I thank everyone who contributed in any way to the completion of this research. Your support and kindness mean a great deal to me.

Abstract

Visually impaired and partially sighted university students in Sri Lanka encounter significant academic barriers, primarily due to the chronic scarcity of accessible learning materials, particularly audiobooks. This limited availability, coupled with inefficient recommendation and access systems, hinders their academic equity and independence. The core aim of this project was to pioneer the "Biometric-Secured Voice Controlled Audio Book Platform" to provide these students with a highly secure, convenient, and user-friendly solution for accessing educational resources.

The methodology employed a user-centered, iterative design approach, focused on building a multi-module system. Key development focused on integrating advanced biometric authentication, including voice and face recognition, to secure user access and automatically create personalized profiles. Furthermore, a highly customizable user interface (UI) was developed based on color-based accessibility principles to cater specifically to partially sighted and colorblind users. Findings from internal testing and structured user feedback confirmed the robustness of the biometric security features across diverse vocal patterns. The validation process successfully demonstrated the platform's high usability and confirmed that the customizable UI effectively addresses the specific accessibility needs of the target audience, particularly in the Sri Lankan context. In conclusion, the project successfully delivered a secure and fully functional prototype, achieving its objectives by enhancing academic accessibility. Future efforts will focus on implementing full Sinhala voice recognition and scaling the personalized recommendation system to provide an even more tailored user experience.

Table of contents

List of tables **11**

Nomenclature **12**

1.1 Background: The Need for Digital Access in Higher Education 14

1.1.1 Understanding Visual Impairment and Assistive Technology **14**

1.1.2 The Power of Technology in Academic Life **15**

1.1.3 Local Challenges: Sri Lankan University Context **16**

1.2.1 Linguistic Isolation: The Sinhala Voice Recognition Gap **17**

1.2.2 Interface Exclusion: Ignoring Partially Sighted Needs **18**

1.2.3 Security and Management Failures in Resource Systems **19**

1.3.1 Sinhala Natural Language Processing for Voice Control **20**

1.3.2 Customizable and Adaptive User Interfaces **21**

1.3.3 Security with Advanced Biometric Authentication **21**

1.3.4 Personalized Learning via Recommendation Systems **22**

1.4.1 Primary Aim of the Project **23**

1.4.2 Specific Objectives (S.M.A.R.T. Objectives) **23**

1.5.1 Target User Group and Geographic Scope **24**

1.5.2 Technical Boundaries and Constraints **24**

1.5.3 Inherent Limitations **25**

1.6.1 Tangible Deliverables **25**

1.6.2 Project Timeline and Milestones **26**

2.1 Introduction and Context of Accessibility Research 28

2.1.1 The Importance of Assistive Technology in Education **28**

2.1.2 Defining the Localized Research Gap in Sri Lanka **29**

2.2 Review of Sinhala Voice Control and Natural Language Processing (NLP) 30

2.2.1 Evolution and Technical Challenges of ASR Systems 30

2.2.2 ASR Performance in Low-Resource Languages 30

2.2.3 The Sinhala Voice Control Gap 31

2.3 Accessible User Interface Design for Partial Visual Impairment (PVI) 32

2.3.1 Foundational Principles and Universal Design 32

2.3.2 Addressing the Needs of Partially Sighted Users (PVI) 33

2.3.3 The Limitation of Standard High-Contrast Modes 33

2.4 Security and Biometric Authentication in Accessible Systems 34

2.4.1 Inadequacy of Traditional Authentication 34

2.4.2 Biometric Modalities for Enhanced Security 35

2.4.3 Usability Challenges of Biometrics for Disabled Users 35

2.5 Machine Learning Models for Personalized Audiobook Recommendations 36

2.5.1 Architectures of Recommendation Systems in E-Learning 36

2.5.2 Limitations of Collaborative Filtering in Niche Environments 37

2.5.3 The Need for Hybrid Recommendation Models 38

2.6 Synthesis of Literature and Definition of the Research Gap 38

2.6.1 Summary of Existing Limitations 38

2.6.2 The Unified Research Gap 39

3.1 Research Strategy and Development Approach 41

3.1.1 Overarching Research Paradigm: Design Science Research (DSR) 41

3.1.2 Agile and Iterative Development Lifecycle 42

3.1.3 Requirement Elicitation and User Research Protocol 42

3.2 Conceptual System Architecture and Design 43

3.2.1 High-Level Architectural View 43

3.2.2 Technology Stack Selection and Justification 44

3.2.3 Data Flow and Interaction Protocol 46

3.3 Methodological Implementation of Core Objectives 47

3.3.1 Methodology for Secure Biometric Authentication (Objective 3)..... 47

3.3.2 Methodology for Sinhala Voice Control and NLP (Objective 1)..... 50

3.3.3 Methodology for Adaptive User Interface (Adaptive HCI) (Objective 2) 51

3.3.4 Methodology for Machine Learning Recommendation System (Objective 4) . 53

3.4 System Deployment Environment and Infrastructure..... 55

3.4.1 Backend Architecture and Database Design 55

3.4.2 Cloud Hosting Strategy and Scalability..... 55

3.5 Validation and Evaluation Protocols..... 56

3.5.1 Functional and Non-Functional Testing..... 56

3.5.2 Usability Testing Methodology with Target Users..... 56

3.5.3 Security Audit and Compliance Checks for Biometric Data 57

3.6 Assumptions, Limitations, and Workarounds..... 58

3.6.1 Assumptions and Constraints..... 58

3.6.2 Foreseeable Difficulties and Engineered Workarounds 58

4.1 Development and Deployment Environment Configuration 60

4.1.1 Prototype Instruments and Core Technology Stack..... 60

4.1.2 Hardware and Network Prerequisites..... 61

4.2 Implementation of Sinhala Voice Control and NLP (Objective 1) 62

Hybrid ASR Pipeline Architecture 62

4.2.2 Constrained Lexicon and Grammar Model Deployment 63

4.3 Implementation of Adaptive Human-Computer Interaction (Objective 2)..... 63

4.3.1 Dual-Interface Model Implementation 64

4.3.2 Dynamic Color Filtering System for PVI Users 65

4.3.3 Real-time Hand Gesture Control Protocol (MediaPipe Integration)..... 66

4.4 Implementation of Multi-Modal Biometric Security (Objective 3)..... 67

4.4.1 Facial Recognition Enrollment and Verification Pipeline 67

4.4.2 Voice Biometric Template and Anti-Spoofing Protocol 68

4.4.3 Data Layer Security and Defensive Programming..... 69

4.5 Implementation of the Machine Learning Recommendation System (Objective 4)... 69

4.5.1 Hybrid Recommendation Model Architecture 70
4.6 Experimental Design and Validation Instruments..... 72

4.6.1 Data Acquisition and Corpus Augmentation..... 72

4.6.2 Experimental Metrics and Measurement Protocols 72
4.7 Implementation Challenges (Pitfalls) and Engineered Workarounds 73
5.1 Introduction..... 76
5.2 Quantitative Performance Results..... 77

5.2.1 Summary of Key Performance Indicators..... 77

5.2.2 Usability Validation via System Usability Scale (SUS)..... 78

5.2.3 Sinhala ASR Performance: Command Execution Success Rate (CESR) 80

5.2.4 Biometric System Performance and False Rejection Rate (FRR) 81

5.2.5 Machine Learning Recommendation Accuracy 82

5.2.6 User-Reported Experience Ratings 82
5.3 Analysis and Discussion of Core Objectives 84

5.3.1 Efficacy of Sinhala Voice Control in a Low-Resource Context (Objective 1)... 84

5.3.2 Analysis of the Adaptive HCI and Usability (Objective 2) 85

5.3.3 Multi-Modal Biometrics and Accessibility Assurance (Objective 3) 86

5.3.4 Validation of the Hybrid Recommendation Model (Objective 4) 87
5.4 Critical Discussion of Inherent System Limitations..... 88

5.4.1 Infrastructure Dependency and Operational Cost 88

5.4.2 Latency and Network Performance Under Variable Load 89

5.4.3 Functional Constraints of ASR Lexicon 89
5.5 Chapter Summary and Conclusion 90
6.1 Project Synthesis and Thesis Confirmation 92

6.1.1 Summary of Achievement Against S.M.A.R.T. Objectives..... 92
6.2 Critical Discussion of Accomplishments..... 93

6.2.1 Achievement of Objective 2: Setting a New Standard for PVI Inclusivity 93

6.2.2 Achievement of Objective 3: Guaranteed Hands-Free Access via Multi-

Modality **94**

6.2.3 Status of Objective 1: Operationalizing Low-Resource Sinhala ASR **95**

6.2.4 Achievement of Objective 4: Contextual Relevance in Niche Academics **97**

6.3 Analysis of Foundational Limitations and Institutional Challenges 98

6.3.1 The Performance Plateau in Sinhala ASR **98**

6.3.2 The Unsustainable Economic Model: The OPEX Barrier of Cloud Dependency **99**

6.3.3 The Perpetual Burden of Biometric Data Governance **99**

6.4 Future Works: Strategic Research Roadmap for Next-Generation Accessibility 100

6.4.1 Phase 1: Next-Generation Natural Language Understanding (NLU) **100**

6.4.2 Phase 2: Architectural Evolution for Economic and Energy Sustainability **102**

6.4.3 Phase 3: Strategic Linguistic and Academic Expansion **103**

6.5 Concluding Statement 105

References **107**

List of tables

Table 1.1: the problems found and the four technical solutions

Table 1.2: S.M.A.R.T.

Table 2.1: Critical Limitation Found in Literature

Table 3.1: Core Technical Stack Selection and Justification

Table 3.2: Hybrid Recommendation Model Structure

Table 4.6: Critical Implementation Pitfalls and Engineered Workarounds Table

Table 5.1: Overall Performance Metrics Against S.M.A.R.T. Objectives

Table 5.2: Comparative System Usability Scale (SUS) Scores by User Cohort

Table 5.3: Command Execution Success Rate (CESR) Analysis Table

Table 5.4: User Experience Ratings (Realism, Memory, Latency) by User Cohort Table

Table 6.2: Comparative Usability and Latency Metrics by User Cohort

Nomenclature

Acronyms / Abbreviations

CVI	Completely Visually Impaired
PVI	Partially Sighted
AI	Artificial Intelligence
ML	Machine Learning
NLP	Natural Language Processing
ASR	Automatic Speech Recognition
UCD	User-Centric Design
CF	Collaborative Filtering
RS	recommendation systems
VID	visual disabilities
HCI	Human-Computer Interaction
PINs	Personal Identification Numbers
CVI	Completely Visually Impaired
WCAG	Web Content Accessibility Guidelines
ASR	Automatic Speech Recognition
S.M.A.R.T.	Specific, Measurable, Achievable, Realistic, and Time-constrained
UI	User Interface
APIs	Application Programming Interfaces
CESR	Command Execution Success Rate
CSS	Cascading Style Sheets
DSR	Design Science Research
CBF	Content-Based Filtering

CESR	Command Execution Success Rate
ASR	Automatic Speech Recognition
HMM	Hidden Markov Model
CNN	Convolutional Neural Network
DNN	Deep Neural Network

Chapter 1

Introduction

1.1 Background: The Need for Digital Access in Higher Education

A good education is a basic right for every student. This right should be available regardless of a person's physical abilities. Many universities around the world are now using digital platforms. This shift is meant to make education easier to access. It offers many new ways to learn and share information.

However, this move to digital spaces also creates huge problems for students with visual impairments. These problems happen if the right kind of technology is not used. Visually impaired university students in Sri Lanka have a lot of trouble using modern learning materials. These difficulties come from system designs that only focus on students who can see well. The unique needs of students with disabilities are often ignored.

We must change this approach. Our focus must be on creating digital learning environments that are truly fair and accessible for all students.

1.1.1 Understanding Visual Impairment and Assistive Technology

The group of people known as "visually impaired" is very diverse. It is not just one type of condition. This group includes individuals who are Completely Visually Impaired (CVI), meaning they have no light perception. It also includes people who are Partially Sighted (PVI), who have a range of mild to severe vision loss.[1]

Students who are fully blind rely completely on sound or touch to get information. They use auditory feedback or tactile mechanisms. But partially sighted users have some remaining vision. This residual vision can be very useful. However, the digital interface must be carefully adjusted to their specific needs.

When specialized assistive technology is missing, students struggle to make academic progress. They also lose their independence when they try to access study materials. Standard accessibility tools are often not enough. Simple screen readers or generic audiobook libraries cannot meet the complex and different needs of this student population.

For any platform to work well, it must handle the full range of visual impairment. This project uses a design approach that focuses on multiple senses. This is very important. The success of a learning resource depends on matching the interface to the student's unique vision capability.[1]

The system must support CVI students. They need audio guidance and hands-on control. It must also support PVI students. They need highly adaptable visual settings. Examples include changing font sizes, using high-contrast modes, and customizing color schemes. Designing a system for this wide range of visual capability is difficult. This complexity is the main reason why this comprehensive research and development project is necessary.

1.1.2 The Power of Technology in Academic Life

Modern technology can lead to true independence and empowerment for students. This is especially true when we use advanced computing and Artificial Intelligence (AI). Technology can automate tasks that were once difficult. It can replace tasks that needed manual help. This automation greatly increases a student's self-reliance.

For visually impaired students accessing school content, achieving independence depends on three main pillars of technology:

1. **Navigation:** The ability to move around the system easily.
2. **Security:** Safe and simple authentication to protect private data.
3. **Resource Discovery:** Finding the right academic content quickly and effectively.

Advanced systems allow for hands-free control. Students can use voice commands for navigation. This removes the physical struggle of using traditional input like a mouse or keyboard. Secure access to personal educational records is essential. The system must achieve this without making students type complicated passwords. This task is nearly impossible for many CVI users. Finally, smart technology ensures students can quickly find

relevant academic content. They are not overwhelmed by scattered or irrelevant results.[2]

The issues faced by these students are complicated. No single technology can solve everything. Our project achieves high automation and customization by combining four distinct technologies.

- **Voice Control** handles input and command execution.
- **Biometric Technology** manages secure identity verification.
- **Machine Learning (ML)** handles smart data filtering and resource recommendations.[2]

These four functions input, identity, intelligence, and a flexible interface must work together. By combining them into one platform, the system offers a level of accessibility that simple, manual systems cannot achieve. The convergence of these advanced components is the main technical contribution of this research. It is the reason for the complexity of the final system design.

1.1.3 Local Challenges: Sri Lankan University Context

Global efforts to improve accessibility are important. However, local realities create unique and tough problems. These realities include local languages and infrastructure limitations. In Sri Lanka, Sinhala is the language used for teaching in many university courses.

This linguistic reality creates a massive problem when students try to use global assistive technologies. Most international software is made for English or other major languages. They simply cannot support Sinhala voice commands, text-to-speech output, or detailed Natural Language Processing (NLP). [3]

Because of this lack of local language support, students cannot interact easily with the system. They are forced into learning environments that require constant linguistic effort. This heavily impacts their success and independence in academics.

On top of this, the systems used in Sri Lankan universities for managing resources are often manual and slow. These old systems usually do not meet modern accessibility standards. This means educational content is disorganized, scattered, and often lacks proper security. The Sinhala language itself presents a technical hurdle. Within the field of NLP, Sinhala is seen as a low-resource language. This means it lacks the necessary components to build sophisticated AI systems.[4] These missing resources include:

- Comprehensive, labeled data sets.
- Strong acoustic models for accurate speech recognition.
- Large text collections for linguistic analysis.

Developing an accurate Sinhala voice recognition module is a huge technical challenge. It places this project in an advanced research area where few strong solutions exist. Overcoming this low-resource language barrier is a major research gap. Our project is specifically designed to fill this gap.

1.2 The Problem: Main Barriers to Resource Access

The current university environment in Sri Lanka gives visually impaired students a major, systematic disadvantage. This research focuses on fixing three crucial barriers. These barriers together limit their educational progress and access to learning materials. These specific problems are the core justification for this entire project.

1.2.1 Linguistic Isolation: The Sinhala Voice Recognition Gap

The lack of accurate Sinhala voice recognition is the most immediate problem. For a student with complete visual impairment, typing on a keyboard is not practical. Voice command is the most intuitive and efficient way to use a digital system.

Without strong support for Sinhala Automatic Speech Recognition (ASR), this primary way of interaction becomes frustrating. It is clumsy and often leads to errors. This severely limits a user's ability to navigate the platform smoothly.

Previous studies on Sinhala speech recognition have had some success. For instance, one early study showed that recognition rates could reach over 87% in a quiet environment.[3] This is promising. However, a university is not a quiet environment. Real-world settings are noisy and acoustically varied. This noise greatly reduces system performance.

Academic work requires the system to do more than recognize a few words. It needs to handle a huge, diverse vocabulary. It must understand complex commands. Examples include specific search queries or multi-step navigation requests. The system needs to be capable of complex Natural Language Understanding (NLU). Basic audio transcription is

not enough.

Also, Sinhala digital material is scarce. This makes finding content hard, even if a basic ASR system is working. Because Sinhala is a low-resource language, we must use complex deep learning models for NLU and ASR.[4] This requires using specialized, flexible, open-source tools. We cannot use simple, ready-made Application Programming Interfaces (APIs). This means the project must build the necessary, high-performance linguistic structure from the ground up.

1.2.2 Interface Exclusion: Ignoring Partially Sighted Needs

The needs of the partially visually impaired (PVI) vary widely. They have a large spectrum of residual vision. A conventional interface that looks the same for everyone cannot serve all PVI students well.

A high-contrast interface (like black text on white) is helpful for many people. But some color combinations can be bad. They can cause discomfort for users with light sensitivity or specific types of color blindness.

Current accessibility features do not offer the detailed customization that PVI users require. Custom settings are essential for usability.[1] These must include:

- User-defined background colors.
- Adjustable, large font sizes.
- Personalized color palettes.

When these features are missing, students must rely on sighted people for help. They need help with navigating the interface and setting it up. This lack of features severely limits their independence. It prevents them from achieving the goal of learning autonomously.

To solve the problem of interface exclusion, the platform must offer deep, individual personalization.[1] We must move beyond simple checks for contrast ratios. The research must focus on an interface that can change dynamically based on the user's specific visual needs.

We plan to implement a Dual Interface option. This allows users to choose between touch control or voice control at the start. This makes the system inclusive. It supports CVI students who use only voice. It also supports PVI students who may use a mix of touch and residual vision. The system must also include specialized color modification. It can use the principles of the Ishihara Test to adjust the entire color scheme based on the user's condition. This actively prevents exclusion caused by subtle visual differences. This

commitment to detailed customization needs complex modern front-end engineering.

1.2.3 Security and Management Failures in Resource Systems

Existing educational systems often use simple login methods. This causes a major problem for visually impaired students. Typing long, complex passwords is very difficult. Using simple passwords makes the system less secure and risks private data. This difficulty means students often need someone else to enter their details. This sacrifices their privacy and personalization.

Furthermore, managing academic resources is often done manually. This makes finding and accessing content time-consuming. It is prone to administrative errors and is very inefficient.

The perfect solution needs to balance easy access with strong security. Biometric technologies are a great answer.[4] They use unique physical characteristics like face or voice patterns to confirm identity. This allows for hands-free authentication. It makes the login process much easier for visually impaired students.

However, using biometrics creates a new technical challenge. We must securely manage and store highly sensitive personal data. If biometric data is compromised permanently, the user's long-term security is at risk. Therefore, implementing a biometric system puts a high responsibility on the developers. They must use strict security protocols and cryptographic modules.[4]

The project's goal is not just to use biometric features. It is to show that the security design includes necessary checks. This means conducting security audits and using robust protection mechanisms during setup and daily use. The security part of this project has two goals: maximizing user independence with hands-free login and ensuring the complete privacy of the student's personal data.

1.3 The Proposed Solution: A Secure, Multi-Modal Audiobook Platform

This final year project proposes the development of the Biometric-Secured Voice-Controlled Audiobook Platform. This platform is a new solution built to directly fix the critical educational problems faced by visually impaired students in Sri Lanka. The platform's innovation is in successfully combining four advanced technologies into one

unified system. It is also localized for the Sri Lankan context.

The design overcomes local and language barriers by focusing on Sinhala support and flexible interface features. At the same time, it ensures security and personalized learning through smart AI use.

The following table summarizes the problems we found and the four technical solutions that make up the project.

Table 1.1 : the problems found and the four technical solutions

Identified Challenge (Problem)	**Current Limitation/Gap**	**Proposed Solution Component**
Linguistic Barrier to Access	No strong Sinhala voice recognition support.	Sinhala Voice Control System for hands-free navigation (Objective 1).
Non-Inclusive Interfaces	Solutions lack adaptive features for partially sighted users (PVI).	Customizable User Interface (UI) with high-contrast color schemes and adjustable fonts (Objective 2).
Inefficient and Insecure Access	Basic authentication methods compromise data privacy and user independence.	Advanced Biometric Authentication (Facial and Voice Recognition) for secure, personalized login (Objective 3).
Non-Personalized Learning	Resources are scattered or too generic for individual needs.	Machine Learning (ML)-Powered Audiobook Recommendation System (Objective 4).

1.3.1 Sinhala Natural Language Processing for Voice Control

Using Sinhala NLP is the critical first step. It changes the platform from a simple digital library into an essential, culturally sensitive assistive tool. The voice-controlled system is specifically designed to overcome the common language barriers found in current systems. The main function is to let users navigate and interact with the platform using simple voice

commands in their native language.

To handle the complexity of Sinhala ASR in a low-resource setting, the solution must use specialized, flexible, open-source tools such as Kaldi. We need this strategic choice. Commercial ASR solutions do not offer the flexibility needed to train effective language models for less common languages. Successfully developing this part of the system gives students a key level of independence. It allows for smooth, hands-free operation. They no longer need to rely on a keyboard for input. Also, a permanent Voice Assistant will be on every page. It will give constant spoken guidance and immediate feedback to the user. This acts as a vital support tool throughout the learning process.

1.3.2 Customizable and Adaptive User Interfaces

The User Interface (UI) design is based on the idea that customization equals control and inclusivity. We recognize the broad range of partial visual impairment. Therefore, the platform moves away from fixed designs. It offers highly adaptable features.[1]
These features include adjustable font sizes, easy-to-use navigation menus, and high-contrast color schemes. All of these are specifically designed for partially sighted individuals. A significant feature is the **"Dual Interface"** option. The user can choose between touch or voice control at the very beginning. This ensures maximum inclusivity. It supports CVI students who rely purely on voice. It also supports PVI students who might use touch alongside their residual vision.
The system will include intelligent adaptive logic. For example, it can use concepts from color-blindness tests to dynamically change the whole color environment. This actively prevents the interface from excluding users based on subtle visual differences. This commitment to detailed customization requires complex modern front-end engineering.

1.3.3 Security with Advanced Biometric Authentication

The integration of advanced biometric technologies directly solves the dual problems of insecurity and dependence caused by traditional passwords. We will use facial recognition and voice recognition. Biometrics offer a simple, hands-free way to securely log in. This makes accessing the system instantaneous for visually impaired students. This focus on

maximizing user independence at the entry point is a core accessibility benefit.

The technical complexity involves running advanced computer vision algorithms for facial recognition. It also means running sophisticated audio processing algorithms for voice recognition. We will use powerful, flexible open-source frameworks like TensorFlow and OpenCV for these biometric algorithms. The final system gives highly secure and personalized access. This is vital for protecting student data, like private learning histories. However, the implementation must be managed carefully. We must prioritize security measures. This includes documented security audits. We must employ strong protection mechanisms to safeguard the highly sensitive biometric template data from any compromise.[4]

1.3.4 Personalized Learning via Recommendation Systems

For visually impaired students, navigating huge academic content libraries is difficult. They cannot easily browse digital or physical shelves. The use of a Machine Learning (ML)-based recommendation system acts as an automated, smart librarian.[2] This system will use collaborative filtering models. It will analyze user preferences, past listening history, and overall interaction patterns.

This feature ensures that educational resources are no longer generic or scattered. The platform will automatically curate content. It will deliver tailored audiobook suggestions that are highly relevant to the student's needs and current syllabus. This strategic use of ML significantly cuts down the time students spend searching for materials. It turns the resource management system into a highly organized, user-centered knowledge platform. This personalization is a key step in improving the quality of the learning process. It helps foster greater academic success.

1.4 Project Aim and Objectives

We now formally define the project's purpose. We also list the measurable steps needed for its success. These objectives are designed to be Specific, Measurable, Achievable, Realistic, and Time-constrained (S.M.A.R.T.).

1.4.1 Primary Aim of the Project

The main goal of this project is to design, develop, and deploy an accessible audiobook platform. This platform is specifically for visually impaired and partially sighted university students in Sri Lanka. It will ensure they have equal access to vital educational resources. The access will be secure, easy to use, and highly tailored to local language needs.

1.4.2 Specific Objectives (S.M.A.R.T. Objectives)

The project aim will be met only if these four S.M.A.R.T. objectives are successfully completed. They define the main technical goals and deliverables of the research.

Table 1.2: S.M.A.R.T.

Objective	**Component Focus**	**Action (Specific)**	**Metric (Measurable)**
O1	Sinhala Voice Control	Design and implement a highly functional Sinhala ASR module.	Achieve a defined command execution success rate (e.g., greater than 90%) validated by user testing.
O2	Adaptive User Interface	Develop customizable UI features (contrast, font size, color adaptation) for PVI users.	Achieve a high user satisfaction rating (e.g., 4/5 or higher) during formal usability tests.
O3	Biometric Security	Implement secure facial and voice recognition for access control.	Validate security performance through required security audits and compliance checks.[4]
O4	Personalized Learning	Build and integrate an ML-based audiobook recommendation system.	Achieve defined accuracy metrics for content suggestions validated

			against user preference data.[2]

Completing and validating each of these four objectives will prove that the project's main aim has been fulfilled. Each objective is directly connected to a measurable output. This output can be tested against fixed performance standards.

1.5 Scope and Limitations

The scope of this research sets clear boundaries for the system we are developing. It also acknowledges the limits that influenced our methods and final results. Defining these boundaries ensures the research stays focused and is achievable within the time and resource limits.

1.5.1 Target User Group and Geographic Scope

The system is narrowly focused on providing specialized academic support. The Target Population is strictly defined as university students who are visually impaired or partially sighted. This focus means we must build specialized interfaces and content. The Geographic Focus is only Sri Lanka. This is necessary because it forces us to prioritize and develop the Sinhala language support module.

The system is designed to be scalable and usable. This includes adapting to the needs of users in rural areas. Some rural areas may have limited internet access. This is a functional constraint. The system architecture must be efficient in how it uses bandwidth. It may need to use local data processing or efficient compression techniques. This will ensure performance remains good even with poor internet stability.

1.5.2 Technical Boundaries and Constraints

The Core Technical Systems are limited to integrating and deploying the four main technology modules: Sinhala ASR, the multi-modal Biometrics system, the Adaptive UI, and the ML Recommendation Engine. These systems define where the innovation happens in this project.

The tools chosen also define the technical boundary. We must use specific, flexible frameworks. We are mandated to use TensorFlow and OpenCV for biometrics. We also need adaptable open-source tools like Kaldi or CMU Sphinx for Sinhala NLP. This reliance on specialized frameworks is a direct result of the low-resource nature of the Sinhala language. Commercial solutions cannot solve this problem effectively.

However, this choice creates a significant technical constraint: the Data Set Reliance. The accuracy of the ASR and ML recommendation systems depends heavily on the availability and quality of Sinhala training data. This data is known to be scarce. The project's success is therefore partly limited by how well we can gather data and train our models.

1.5.3 Inherent Limitations

We must formally acknowledge several limits to this project. First, Language Specificity limits the current system to the Sinhala language only. The need is critical, but the platform does not currently support other regional languages, such as Tamil.

Second, the system's performance is subject to Infrastructure differences. The architecture is designed to be efficient. Despite this, performance metrics will change based on local internet connectivity. This is especially true in rural areas. The system relies on cloud hosting solutions (like AWS or Google Cloud). The remote performance will always be limited by the speed of the user's internet connection.

Finally, using advanced biometrics brings a major limitation related to Biometric Data Sensitivity. Storing and processing highly sensitive user data carries a permanent risk. To manage this risk, the project requires constant security monitoring. It must follow strict data protection standards and undergo regular security audits.[5] This ongoing requirement is a necessary operational burden that comes with the security approach we chose.

1.6 Deliverables and Milestones

This section summarizes the concrete outputs of the research. It confirms the project’s feasibility using the time plan set out in the project proposal.

1.6.1 Tangible Deliverables

The successful completion of this research and development project will result in these measurable outputs:

1. **Biometric-Secured Voice-Controlled Audiobook Platform:** A fully working application that integrates all four core technology modules.
2. **Sinhala ASR Module:** A validated software component that can process complex Sinhala voice commands for system navigation and content search.
3. **Adaptive UI Module:** Customizable interface software engineered specifically for the needs of partially sighted and fully visually impaired users.
4. **Secure Biometric Module:** The integrated facial and voice authentication system. It will come with documented security performance reports and data privacy protocols.[5]
5. **ML Recommender Engine:** A trained and validated machine learning model for personalized audiobook suggestions.[2]
6. **Technical and User Documentation:** Complete technical reports detailing the system architecture, implementation details, testing results, and user guides for students and administrators.

1.6.2 Project Timeline and Milestones

The project will follow a structured timeline. It starts in December and ends in September with the final thesis submission. This schedule ensures the complex development and testing requirements are met within the institutional deadlines. The timeline is broken into seven clear phases:

The first phase, Project Initiation, happens in December. It focuses on defining the scope and assigning roles.

The Research and Requirements phase is in January and February. We will gather user needs through interviews. We will also complete the literature review to define all technical specifications.

System Design is completed by March. This involves detailed planning of the system architecture. It includes creating accessible UI/UX prototypes. The most important phase is the Development Phase. It runs for five months, from March to July. This time is for the complex, simultaneous implementation of the Sinhala recognition module, the biometric features, the recommendation system, and the adaptive UI features.

The Testing Phase runs through July and August. This includes tough usability and functionality testing with visually impaired users in different regions. It also includes mandatory security audits for handling biometric data. Deployment and Training is scheduled for August. This involves launching the system in partner universities. We will

provide necessary training for both students and faculty. The project ends in September with Project Closure. This involves a final review and the submission of all required thesis documents.

1.7 Outline of the Thesis Report

The following chapters of this thesis will document the research process, technical implementation, and validation of the platform.

Chapter 2: Related Work will provide a careful, in-depth review of existing academic research. We will focus on the current status and limits of Sinhala NLP, the recognized standards for accessible UI design[1], the difficulties in using multi-modal biometrics for security[4], and the effectiveness of current ML recommendation systems in education.[2] This detailed analysis will formally conclude by establishing the specific research gap that our project is designed to fill.

Chapter 3: Methodology will explain the theoretical framework and procedures used for this research. This chapter details the protocols for requirement analysis (surveys and interviews). It justifies why we chose a modular system architecture. It also explains the choice of specific machine learning and NLP algorithms (like Kaldi for ASR) over other options.

Chapter 4: Experimental Setup and Implementation documents the practical building of the system. This chapter focuses only on the innovative or non-standard technical parts. Examples include how we adapted open-source NLP tools for Sinhala, the techniques used to combine the multi-modal biometric system, and the logic for the adaptive UI. It will also document any technical problems we faced during development and the workarounds we engineered to fix them.

Chapter 5: Results and Analysis presents the findings from the testing and validation phases. We will report on key performance indicators. These include the success rate of Sinhala voice commands, the accuracy of the biometric authentication, and user satisfaction scores for the adaptive UI. The results will be fully analyzed against the measurable S.M.A.R.T. objectives set in Chapter 1.

Chapter 6: Conclusion and Future Works will summarize the main achievements and contributions of the project. It will formally confirm that the primary aim was achieved. This final chapter will also acknowledge the limits we encountered. It will suggest strategic areas for future expansion, such as adding support for other regional languages.

Chapter 2 Related work

2.1 Introduction and Context of Accessibility Research

Access to good educational resources is a basic need for all university students. Visually impaired students around the world face serious obstacles in getting this access.[6] These problems happen because current technologies and systems are not adequate for their needs. [6]

The goal of this literature review is to look at existing scientific and technical solutions.[6] This helps us see the gaps and limitations in what is currently available. By understanding these gaps, this project can define its own unique contribution to accessible computing.[6] The focus is on creating assistive technology. This technology is essential for ensuring equal learning opportunities.[6]

2.1.1 The Importance of Assistive Technology in Education

Assistive technology is very important for students with visual impairments. This is especially true now because learning increasingly moves to digital platforms.[6] Many digital learning tools are designed based on the capabilities of resource-rich countries.[6] While digital learning offers many benefits, it often causes new challenges for users.[6] This is particularly true for students who use low-resource languages or need special interface designs. [6]

Existing research shows that standard methods are not enough. Relying on generic audiobook libraries or manual processes fails to address the unique needs of students.[6] These traditional approaches can lead to struggles in academic progress.[6] They also cause a loss of independence for the student.[6]

This failure often comes from a lack of tailored solutions. For example, a global platform built primarily for English speakers will not support Sinhala voice commands.[6] A system made for people with perfect vision will not offer customizable contrast for someone who is

partially sighted.[6] The problem should not be left to the user to solve. New research must focus on developing specific, localized solutions. These solutions should integrate all necessary features into a single, cohesive platform.

2.1.2 Defining the Localized Research Gap in Sri Lanka

The need for accessible systems that are culturally and linguistically relevant is clear in Sri Lanka. Sinhala is the primary language in this region.[6] Visually impaired university students in Sri Lanka face specific barriers to their education.[6]

First, there is limited local language support.[6] Educational materials in Sinhala are scarce in digital formats compatible with assistive technologies.[6] Existing systems fail to offer comprehensive support for Sinhala voice recognition.[6] This lack of language support severely restricts how easily local students can interact with learning platforms.[6] It makes seamless, hands-free navigation almost impossible.[6]

Second, there is a lack of inclusive and adaptive interfaces.[6] Current solutions often ignore the needs of partially sighted users.[6] This group requires customizable and color-based interfaces for better usability.[6] When navigation is difficult or relies on visual complexity, users need assistance from others.[6] This greatly reduces their independence.[6]

Third, security and management practices are often inefficient. Manual processes for accessing educational materials take too much time. They are also prone to error. Furthermore, many systems use basic authentication methods. These methods lack the security and personalization needed to protect user data. They cannot ensure unique, tailored user experiences.[6]

These three areas language, interface inclusivity, and secure access form the critical gaps in current research. The proposed Biometric-Secured Voice-Controlled Audiobook Platform aims to solve these problems. It does this by integrating four key technologies: Sinhala voice control, customizable color-based user interfaces, biometric security, and a machine learning recommendation system. The following sections review the literature related to each of these four core technological areas.[6]

2.2 Review of Sinhala Voice Control and Natural Language Processing (NLP)

Automatic Speech Recognition (ASR) systems are vital for creating truly hands-free interfaces.[10] These systems provide essential accessibility for visually impaired users.[10] A review of ASR and Natural Language Processing (NLP) is necessary. It helps us understand the technical challenges involved, especially for low-resource languages like Sinhala.

2.2.1 Evolution and Technical Challenges of ASR Systems

ASR technology has improved dramatically over time. Early systems used basic statistical models.[5] Modern ASR relies heavily on complex deep learning architectures.[5] In languages that have many resources, like English, modern models are highly accurate. This is because developers have access to massive, high-quality speech datasets.[5]

The performance of any ASR system is directly dependent on the quality of its underlying NLP tools. Developers often use open-source frameworks like CMU Sphinx or Kaldi to build new ASR systems.[5] However, even in ideal language environments, ASR faces several challenges. These include capturing variations in speaker accents.[8] Systems also struggle to filter out background noise.[8] Processing different emotional tones in speech is another common difficulty.

In resource-rich languages, these issues are usually minimized. This happens through continuous data collection and model retraining. When developing for low-resource languages, these challenges become much harder to overcome.[9]

2.2.2 ASR Performance in Low-Resource Languages

The development of effective ASR for languages outside of Europe or North America, especially South Asian languages, presents distinct difficulties.[8] These hurdles must be addressed through specific, localized research.[9]

A major difficulty is the linguistic complexity of the target language itself. Sinhala is a

morphologically rich language.[11] It is also known as an agglutinative language.[11] Agglutinative languages build words by adding many suffixes and prefixes to a base word. This means a single Sinhala word can carry the meaning of a whole sentence in a language like English.[11]

This complex structure makes standard NLP tasks difficult.[11] It complicates processes such as morphological analysis and part-of-speech tagging.[11] Standard ASR systems depend on pre-defined lexicons or word sequences. Because Sinhala words can be heavily modified, the required dictionary size and the complexity of grammatical modeling increases greatly.[11] This linguistic complexity makes achieving high accuracy in voice command interpretation much more challenging.[9]

A critical obstacle in low-resource environments is the severe lack of high-quality, annotated speech datasets specifically for Sinhala.[8] This scarcity is widespread in the development of ASR for less-common languages.[9] Even when speech data initiatives exist, the audio quality, speaker representation, and recording conditions can be variable.[8] This limits the ability of ASR models to accurately generalize across different speech contexts and demographics.[8]

Studies confirm that the overall accuracy of South Asian scripts, which include Sinhala, lags significantly behind Latin-based scripts.[5] While research has shown some success in text-based Sinhala NLP, such as achieving over 90% accuracy for known words in tagging, these systems are not sufficient for a complex, real-time, voice-controlled platform.[11] High-accuracy, real-time command recognition with varied vocabulary is needed for education.[11] In an educational context, low error rates are essential for visually impaired users to trust and control the platform.

2.2.3 The Sinhala Voice Control Gap

A review of current accessible systems reveals a major operational deficit. There is a widespread lack of comprehensive Sinhala language support. This problem is the main reason why local students have restricted independence. It forces them to use less natural input methods. They often have to rely on assistance from a sighted person.

Previous Sinhala NLP research has shown moderate success in certain areas. For example, a system for Word Sense Disambiguation achieved a precision of 63%.[11] This level of success is often insufficient for the critical tasks of real-time voice navigation and functional operability in a hands-free learning platform.

The challenge is not just to convert speech to text. It is to develop an NLP engine that can accurately interpret the specific voice *commands* necessary for navigation, chapter selection, and content interaction. This functional gap establishes the need for this project. It requires a voice-controlled system specifically designed and carefully tuned for command interpretation in the Sinhala language.

Integrating Sinhala voice recognition is a mandatory feature. It will enhance accessibility and provide intuitive navigation. This directly solves the core linguistic barrier that currently prevents visually impaired students from achieving full independence.

2.3 Accessible User Interface Design for Partial Visual Impairment (PVI)

Designing user interfaces (UIs) requires following established global standards.[10] However, developers must also recognize that a standardized approach often fails to address the unique and diverse needs of all users.[12]

2.3.1 Foundational Principles and Universal Design

The Web Content Accessibility Guidelines (WCAG) are the global standard for digital accessibility.[7] WCAG is based on four main principles, summarized by the acronym POUR: Perceivable, Operable, Understandable, and Robust.[7] These principles guide developers. They ensure that content can be accessed by all users, regardless of their disability.[7]

Localized research into e-learning accessibility for visually impaired students in Sri Lanka confirms the importance of these standards. One study found that the Perceivable and Understandable factors had a significant and positive effect on learner satisfaction. However, the same research showed that the Operable and Robust factors in existing local

systems often need much improvement.[7]

- **Perceivable** content must be presented in ways all users can perceive.
- **Operable** means the user interface and navigation must be easy to use.
- **Understandable** means the information and the operation of the user interface must be understandable.
- **Robust** means the content must be reliably interpreted by various assistive technologies.

For users who are Completely Visually Impaired (CVI), design principles focus on non-visual feedback. This includes heavy reliance on sound and touch feedback. It also requires seamless compatibility with external devices like Braille displays and screen readers.[10] Voice control is already an established, essential component for CVI users. It allows the system to be operated without relying on any visual cues.[10]

2.3.2 Addressing the Needs of Partially Sighted Users (PVI)

A major oversight in earlier accessibility research is the failure to fully address the needs of Partially Visually Impaired (PVI) users. PVI is a wide category.[10] It includes a broad range of vision loss.[10] This ranges from mild to severe impairment.[10] It also includes conditions like color vision deficiency (CVD) .[12]

Many existing solutions focus only on CVI users. This means they do not provide features that fully address the unique need for customizable, color-based interfaces for the PVI group. The degree and type of visual impairment vary greatly among PVI users. Therefore, a single, one-size-fits-all solution is simply not enough for an optimal user experience.[12]

The literature confirms that essential design components for PVI accessibility must be customizable.[10] These elements include adjustable text sizes.[10] They also require larger fonts and, most importantly, high contrast ratios.[10] Without these specialized adaptations, navigation remains difficult. Users will often need sighted assistance, which reduces their independence.

2.3.3 The Limitation of Standard High-Contrast Modes

While high-contrast mode is a common solution, research suggests that relying only on a standard, fixed high-contrast setting is not always sufficient. A simple binary mode, such as a black-and-white scheme, is often too restrictive.[12]

Studies evaluating these simple high-contrast modes show that they comply with minimum WCAG guidelines.[8] However, they often reduce both the aesthetic appeal and the user's perceived functionality of the interface. This suggests that a simple on/off switch for contrast settings does not provide the best possible user experience.[12]

The core issue is the high variability in PVI users' conditions. A student with a specific form of color blindness, such as Deuteranopia, might find that a certain contrast level is better than the system's default setting.[12] Current systems are criticized precisely because accessibility features are not adequately tailored to individual needs.

A truly inclusive system must incorporate per-user customization of color schemes and contrast levels. This is often called a color-based UI. It is necessary to meet the highly individualized nature of PVI requirements. Developing customizable UIs is vital for giving partially sighted users autonomy and independence. This customization is a key distinguishing factor in this research.

2.4 Security and Biometric Authentication in Accessible Systems

Secure and personalized access to academic resources demands strong authentication.[13] For visually impaired users, traditional security methods present both convenience and accessibility hurdles.[13] This pushes the focus toward more advanced biometric solutions.

2.4.1 Inadequacy of Traditional Authentication

Many existing academic platforms use basic security methods. These include Personal Identification Numbers (PINs) or traditional passwords.[13] These methods have significant limitations.[13] From a security standpoint, they often lack the robustness needed to protect sensitive user data. They fail to ensure unique, tailored user experiences. From an accessibility viewpoint, traditional methods are often inconvenient for visually impaired individuals.[13] They can be time-consuming and difficult to use.[13] The need to memorize a sequence or physically type a password restricts user independence. Empirical studies confirm that users with accessibility concerns frequently struggle with or forget traditional credentials like PINs and patterns.[13] This difficulty creates a clear barrier to frequent and independent access.[13]

2.4.2 Biometric Modalities for Enhanced Security

Biometric recognition uses unique physical or behavioral traits for identity verification.[14] This offers enhanced security, reliability, and unparalleled convenience over traditional methods.[14] Biometric traits cannot be lost or shared.[14] This makes them ideal for providing secure, personalized access in environments where memorizing complex credentials is a burden.[13]

The current project proposes to use advanced biometric technologies. Specifically, it will use voice and facial recognition. This implementation aims to improve both security and accessibility at the same time. While this is the goal, integrating these systems requires a careful review of their practical usability for people with disabilities.[13]

2.4.3 Usability Challenges of Biometrics for Disabled Users

While biometrics are convenient, they introduce new Human-Computer Interaction (HCI) challenges.[13] A study compared biometric modalities (face, voice, fingerprint) for users with accessibility concerns.[13] This study found that the group with accessibility concerns consistently performed worse than a control group without these concerns.[13] They had higher verification error rates.[13] They also had more incorrect interactions.[9] Their usage times were also longer across all modalities.[13]

The empirical findings from this research highlight critical limitations for certain modalities:

- **Fingerprint Recognition:** This method showed the highest overall verification error rates. The problems were severe for users with visual disabilities (VID). They were also severe for users with difficulties in fine motor control. Interaction failures were directly linked to problems in correctly placing and maintaining a stationary finger on the sensor.[13]
- **Face Recognition:** This method had a high incidence of non-detected faces. It also recorded frequent incorrect interactions. These issues were often traced back to the difficulty subjects had in correctly holding or positioning the mobile device to capture a clear image. This particularly impacted users with hands and arm disabilities.[13]
- **Voice Recognition (Speaker Recognition):** This method was often seen as non-

intrusive and convenient. However, it still produced errors. Users in the visual disability (VID) group showed higher rates of incorrect interactions and low-quality voice samples. This difficulty was typically attributed to issues with timing the recording button press. Subjects also had problems reading the required sentences from the screen.

The literature suggests that authentication methods requiring minimal physical interaction are generally better for users with disabilities. Voice biometrics fit this requirement well. It is non-intrusive and only requires speech input.[13]

Since the platform's core is built around voice commands, integrating voice *authentication* leverages the exact same input mechanism. This integration minimizes the learning curve. It also avoids the need for separate, motor-skill intensive authentication steps. While research found challenges with low-quality voice samples or difficulty reading sentences, these problems can be fixed. The system can use an automated, audibly repeated prompt system. This is a better solution than requiring users to read a sentence from a screen.[13]

Therefore, advanced biometric authentication, especially voice recognition, is essential. This technology ensures personalized, secure access while respecting accessibility constraints. It moves beyond the inadequate basic security protocols used in many current systems.

2.5 Machine Learning Models for Personalized Audiobook Recommendations

The ability to offer personalized content suggestions is key to improving user engagement.[15] It also helps with academic success. Machine Learning (ML) powered recommendation systems (RS) play a crucial part in curating relevant learning materials on a centralized platform.

2.5.1 Architectures of Recommendation Systems in E-Learning

Recommendation systems use algorithms to suggest items based on a user's history and preferences. In education, the purpose of an RS is to deliver tailored learning experiences.[11] It should reduce student confusion when selecting study materials.[11] Ultimately, this increases understanding and learning capacity.[15]

Historically, RS models relied on techniques like Collaborative Filtering (CF) and Content-

Based Filtering.[16] More recently, the field has shifted toward advanced machine learning and deep learning techniques.[11] Studies show that Neural Networks, including Deep Learning models, are now the most commonly used techniques.[17] They account for nearly half of the analyzed ML-based recommendation systems.[17]

2.5.2 Limitations of Collaborative Filtering in Niche Environments

Collaborative filtering (CF) works well in large commercial systems. It generates recommendations by analyzing the preferences of users who share similar tastes. However, CF suffers from several major limitations when applied to specialized, niche educational environments.[16] An example is a university's specific audiobook library.

The Cold Start and Data Sparsity Problems

Two major pitfalls of CF are the Cold Start Problem and Data Sparsity. The Cold Start Problem occurs when the system tries to recommend items to new users. These users have no prior interaction history. It also happens when trying to suggest new audiobooks that have not yet been sufficiently rated. This is a frequent issue in academic settings where new courses and new student intakes happen regularly.

Data Sparsity refers to the insufficient volume of data in the user-item interaction matrix.[16] Educational audiobooks specific to a university curriculum are inherently specialized. They are low-volume compared to the vast content found on commercial platforms. Insufficient data leads directly to inaccurate or generic recommendations. This limits the system's usefulness in an academic context.[16]

Bias and Lack of Transparency

A further limitation is the inherent bias in traditional CF. CF systems often unintentionally favor popular content. This can cause them to neglect specialized academic materials or niche curriculum topics that might be essential for a particular student. This bias limits true educational discovery. It prevents students from finding highly relevant, specialized materials.[18]

Traditional CF also lacks transparency. It cannot easily explain *why* an item was recommended. For example, it can only say, "because users like you also liked this". This lack of explanation can erode user trust.[18] It also fails to provide educational context.

2.5.3 The Need for Hybrid Recommendation Models

To overcome the challenges of data sparsity, the cold start problem, and inherent bias, the literature strongly recommends using hybrid models.[16] Hybrid approaches combine the strengths of Collaborative Filtering with Content-Based Filtering.[16]

In a hybrid model, content-based filtering uses detailed metadata. This metadata includes the subject, course topic, difficulty level, and language of the audiobook. This method allows the system to make initial recommendations to new users.[16] It suggests new, specialized books by matching content characteristics to the user's academic profile. This is possible even if no other students have rated them yet.[16]

Advanced techniques are also suggested.[17] Specifically, the use of Deep Learning architectures can integrate diverse data types.[17] This provides greater accuracy and personalization in educational content recommendation.[15]

By carefully analyzing user preferences, academic background, listening history, and interaction patterns, the proposed platform can provide highly tailored suggestions. This advanced, machine learning-based system directly addresses the current problem. That problem is where educational resources are scattered, unorganized, and not adapted to meet individual academic needs.

2.6 Synthesis of Literature and Definition of the Research Gap

This critical review confirms that foundational research exists for each of the proposed platform's components. However, there is a consistent, major failure. This is the failure to integrate and localize these solutions into a unified, secure, and linguistically competent system for the specific demographic in question.

2.6.1 Summary of Existing Limitations

The critical analysis reveals consistent gaps. These gaps prevent current solutions from providing the necessary level of accessibility and security. This is especially true for visually impaired and partially sighted university students in Sri Lanka.

Table 2.1: Critical Limitation Found in Literature

Project Component	**Contribution of Existing Work**	**Critical Limitation Found in Literature**
Sinhala Voice Control	ASR exists; some NLP studies on Sinhala morphology are present.[11]	Limited data resources and linguistic complexity hinder accurate command recognition; comprehensive Sinhala voice control is absent in accessibility systems.[8]
Customizable UI (PVI)	WCAG guidelines are established; high-contrast modes are common for CVI.[7]	Accessibility features are not tailored to the diverse needs of partially sighted (PVI) users; reliance on single high-contrast modes often reduces functionality.[12]
Biometric Security	Biometric modalities (voice, face, fingerprint) offer enhanced security over PINs.[13]	Basic authentication methods are still common; implementing biometrics introduces significant HCI challenges and high error rates for disabled users.[13]
ML Recommendations	General RS models (CF) exist; advanced ML is gaining traction in education.[17]	Systems suffer from Cold Start and Data Sparsity in niche academic settings; recommendations lack personalization for local curriculum content.[16]

2.6.2 The Unified Research Gap

The primary research gap is not purely technical. It is one of integration, localization, and specific optimization for the target user group.

International accessibility solutions fail the Sri Lankan student demographic. They ignore the mandatory Sinhala voice recognition functionality. This linguistic gap prevents intuitive, hands-free operation and independent navigation.

Furthermore, previous accessibility research is incomplete in its scope. It usually focuses only on the requirements of Completely Visually Impaired (CVI) users. It neglects the necessary, individualized solutions for Partially Visually Impaired (PVI) students. A simple, standardized high-contrast mode is not enough for the wide spectrum of low-vision users.[12]

Crucially, very few accessible platforms successfully combine two things. They fail to integrate advanced biometric security with an interface that mitigates the high Human-Computer Interaction failure rates.[13] The security feature must be inherently accessible and easy to use.[13]

Finally, general recommendation systems are not suited for specialized academic content. They suffer from data sparsity and the cold start problem.[16] They fail to provide the contextually relevant, curated, and personalized suggestions needed for academic success within a localized university curriculum.

Existing academic work has established the individual foundations of the four required technologies. However, these works have consistently failed to develop a single, integrated platform. This integrated platform must provide comprehensive Sinhala voice control. It must implement customizable color-based interfaces for partially sighted users. It must ensure secure access via tailored biometric authentication. Finally, it must offer contextually relevant, machine learning-powered audiobook recommendations for university students in a low-resource setting. Therefore, this research will design, develop, and deploy this integrated platform. This will create a transformative, inclusive, and effective educational ecosystem for this underserved demographic.

Chapter 3 Methodology

3.1 Research Strategy and Development Approach

The methodology chapter outlines the specific procedures, models, and protocols we systematically employed to realize the Biometric-Secured Voice-Controlled Audiobook Platform. Our core challenge was bridging the gap between sophisticated technologies (AI, biometrics, NLP) and the highly specialized accessibility needs of visually impaired university students in the low-resource context of Sri Lanka. To address this complexity, we deliberately selected a hybrid approach rooted in academic rigor and practical development flexibility.

3.1.1 Overarching Research Paradigm: Design Science Research (DSR)

We recognized that our project was fundamentally about creating an innovative solution to a pervasive, real-world problem the lack of accessible digital learning resources in the local language. Consequently, our research was anchored in the Design Science Research (DSR) paradigm. DSR mandates the construction of an innovative technological artifact (our Voice Access platform) and its subsequent evaluation for utility and efficacy, ensuring the output contributes verifiable knowledge to the field of software engineering and assistive technology.

The DSR process provided the necessary framework for defining the components of our platform (Sinhala ASR, Biometrics, Adaptive UI, ML Recommender) as the technical artifacts designed specifically to solve the limitations identified in Chapter 2. This structure ensured that our work moved beyond simple application development toward a scholarly output. By adhering to DSR principles, we structured the project around cycles of relevance (understanding user needs), design and creation (developing the system), and rigor (justifying the technical choices and evaluating performance), culminating in an artifact demonstrably fit for purpose in the challenging local environment.

3.1.2 Agile and Iterative Development Lifecycle

Given the high complexity and the inherent integration risks associated with linking low-resource language processing and real-time biometric inputs, a rigid, linear development model (like Waterfall) was unsuitable. Instead, we adopted an iterative, modular development lifecycle heavily influenced by Agile methodologies.

This choice was strategically critical for mitigating risk. We segregated the project into distinct development phases, allowing us to simultaneously develop the four highly specialized components: the Sinhala ASR module, the biometric engine, the adaptive front-end, and the recommendation system. This modular approach meant that development teams could work concurrently without blocking each other. For instance, testing the foundational accuracy of the Sinhala ASR model could proceed independently of optimizing the facial recognition detection rate.

The iterative nature of our chosen lifecycle allowed for constant small-scale integration and validation, particularly during the lengthy Development Phase (March to July) and the subsequent Testing Phase (July to August). This flexibility ensured that preliminary feedback from user research such as identifying poor acoustic performance in a non-ideal environment or usability issues with the gesture scheme could be immediately incorporated into the subsequent development sprint, thereby maintaining system reliability and optimizing the overall Human-Computer Interaction (HCI) experience for our target users.

3.1.3 Requirement Elicitation and User Research Protocol

The design of an accessibility-focused platform must be driven purely by user needs, a principle encapsulated by the User-Centric Design (UCD) approach. To ensure the platform met the functional, non-functional, and, critically, the usability requirements of our specific demographic, we formalized a requirement elicitation protocol.

Our protocol involved structured interviews and surveys conducted directly with visually impaired and partially sighted university students in Sri Lanka. This direct engagement allowed us to precisely identify the functional barriers caused by existing systems, such as the linguistic gap (lack of Sinhala ASR) and interface exclusion (inadequate support for Partially Visually Impaired, or PVI, users).

The essential requirements captured through this process directly translated into the

system's core features: the need for hands-free operation (fulfilled by voice and biometrics), the critical demand for audibly repeated instructions and confirmations (Voice Guidance), and the necessity of highly flexible visual customization, beyond simple high-contrast modes, to cater to the diverse needs of the PVI population. This rigorous UCD commitment ensures that our resulting artifact does not merely comply with minimum accessibility standards (WCAG) but provides a genuinely usable and empowering experience tailored to local, specific visual needs.

3.2 Conceptual System Architecture and Design

Our methodological design focused on creating a distributed, layered architecture. This structure was a deliberate technical choice to achieve maximum modularity, scalability, and, importantly, maintain responsiveness for users operating under challenging network conditions, such as those in rural areas with limited internet access.

3.2.1 High-Level Architectural View


We adopted a standard three-tier architecture model, clearly delineating responsibilities to enhance maintainability and performance. This separation ensured that heavy computational tasks were offloaded from the client device to scalable cloud resources.

1. **Presentation Layer (Client):** This tier consists of the Mobile/Web Application built on HTML5, CSS3, and JavaScript. This layer is responsible solely for rendering the Adaptive UI, capturing real-time input (voice/camera), and providing immediate auditory and visual feedback. Crucially, lightweight, real-time AI models for gesture recognition (MediaPipe) and facial detection (FaceAPI.js) were processed entirely client-side to minimize interaction latency.

2. **Application Layer (Cloud Backend):** This layer, hosted utilizing services from both AWS and Google Cloud , encompasses the core business logic. It includes the Authentication Service, the Voice Processing (Biometric NLP) module, and the Audio Book Recommendation Engine. The server logic is managed primarily using PHP. By placing the resource-intensive ML/NLP modules here, we centralize computation and ensure scalability, thereby mitigating the performance risks associated with low-spec user devices.

3. **Data Layer (Database):** A centralized MySQL relational database (voice_access_db) serves as the permanent repository. It stores essential data elements, including user profiles, encrypted biometric templates, audiobook metadata, and historical interaction logs required by the recommendation engine.

This architectural separation is fundamental to achieving key non-functional requirements. The distribution of processing, where front-end input mechanisms rely on optimized client-side JavaScript libraries, prevents the client application from freezing or lagging due to simultaneous heavy server processing, a necessity for maintaining a seamless hands-free experience for visually impaired users.



3.2.2 Technology Stack Selection and Justification

The selection of our technology stack was guided by two factors: maximizing accessibility features and ensuring feasibility within our project constraints. We prioritized open-source, well-documented frameworks capable of supporting highly customized, hands-free interfaces.

Table 3.1: Core Technical Stack Selection and Justification

Component Category	**Chosen Technology**	**Justification Rationale**
Client-Side Vision/HCI	FaceAPI.js & MediaPipe	Chosen for lightweight, real-time client-side processing of video input, essential for low-latency hands-free biometric authentication and gesture control.
Speech I/O	Web Speech API	Mandatory for browser-native Text-to-Speech synthesis (Voice Guidance) and rapid baseline recognition for simple voice commands.
Backend Framework	PHP (API Logic) & MySQL	A widely supported and robust stack capable of secure transactional data handling, including the mandatory use of parameterized queries for security.
Frontend Framework	HTML5, CSS3, JavaScript	Ensures maximum cross-device compatibility and provides native access to CSS filter methods essential for the adaptive UI features.

Our choice to employ client-side AI processing via FaceAPI.js and MediaPipe represents a strategic technical compromise. While comprehensive ASR for Sinhala required a dedicated server-side NLP module, locating the vision and gesture models on the client ensured that the fundamental hands-free interaction elements login and navigation via movement could operate instantaneously, delivering the core accessibility benefit with minimal dependence on cloud latency. This focus validates our methodological emphasis on prioritizing non-standard HCI techniques specifically for disabled users.

3.2.3 Data Flow and Interaction Protocol

The integrity of the system relies on a clean, secure data flow between the presentation and application layers. This flow is initiated by the user's voice or movement input and culminates in a functional response or data change.

1. **Input Acquisition and Pre-processing:** The process begins when the user engages the microphone (Web Speech API) or camera (FaceAPI.js/MediaPipe).[1] Client-side libraries perform the initial extraction of features, such as the facial descriptor vector or the number of fingers raised.

2. **Authentication and Data Transmission:** During biometric login, the client sends the processed biometric sample (e.g., face descriptor) via a secure API call to the PHP backend's api.php specifically utilizing the face_register action.[1]

3. **Server-Side Security and Verification:** The server-side Authentication Service retrieves the corresponding stored biometric template from the MySQL database. A cryptographic comparison is performed, and once the user is verified, the system issues a successful authentication token, enabling navigation to the home.html.

4. **Command Execution:** For navigation or function calls (e.g., "Search Science Books"), recognized text commands are transmitted to the Sinhala NLP module in the Cloud Backend. This module interprets the command's intent (Natural Language Understanding) and translates it into a structured query for the MySQL database or a state change request for the frontend.

5. **Personalized Content Delivery:** User activity and successful command executions feed data to the ML Recommendation Engine. The engine generates ranked audiobook suggestions, retrieved from the database and formatted for auditory presentation, completing the cycle back to the Presentation Layer.

A key element of our data methodology is the defensive programming employed in the PHP backend, specifically the use of parameterized queries (prepared statements like \stmt->prepare). This prevents SQL injection vulnerabilities, a necessary methodological defense when dealing with highly sensitive private data, including biometric templates. This inclusion of secure coding practices at the fundamental API level is crucial for demonstrating responsible handling of high-risk personal identification data.

3.3 Methodological Implementation of Core Objectives

Our core task involved implementing four interdependent technological components, each addressing a specific objective identified in Chapter 1.

3.3.1 Methodology for Secure Biometric Authentication (Objective 3)

We implemented a secure, multi-modal biometric layer that combines facial and voice recognition. This hands-free approach directly addresses the difficulty visually impaired users face with traditional password entry, balancing high security (low False Acceptance Rate, or FAR) with high accessibility (low False Rejection Rate, or FRR).

Facial Recognition Implementation (FaceAPI.js Integration)

For high-speed, client-side facial recognition, we integrated the open-source **FaceAPI.js** library. This library leverages Convolutional Neural Network (CNN) models trained on deep learning principles, which we load immediately upon accessing the biometric login page (login-voice.html).

The authentication process involves three steps handled by three corresponding pre-trained models:

1. **Detection:** The Tiny Face Detector network rapidly identifies the presence of a face in the live video stream captured by the user's camera (navigator.mediaDevices.getUserMedia).

2. **Alignment:** The Face Landmark Network maps key facial feature points, ensuring correct orientation and quality.

3. **Extraction:** The Face Recognition Network generates a unique vector descriptor (embedding) representing the user's face.

During **enrollment**, this unique descriptor vector is sent to the backend (api.php) via the face_register command and stored securely in the MySQL database. During **verification**, the live descriptor is compared against the stored template using a distance metric (typically

Euclidean distance) to determine identity match. This hands-free, high-speed authentication system provides immediate auditory feedback ("Scanning face...", "Login Successful.") to guide the user through the process.

Voice Biometric Module Design (Liveness and Verification Protocols)

To provide redundancy and strengthen security, especially when facial recognition fails due to poor lighting or camera angle , we integrated a voice biometric layer within the Voice Processing module. This feature authenticates based on the unique characteristics of *who* is speaking (speaker identification), leveraging vocal features rather than the content of speech.

Our methodological protocol for this module focused on robustness:

1. **Feature Extraction:** We apply techniques like **Mel-Frequency Cepstral Coefficients (MFCCs)** to extract acoustic features from the user's voice samples.[4] These features are then used to train a statistical model, often a **Hidden Markov Model (HMM)** or a Deep Neural Network (DNN), to create the unique voice print template.[22]

2. **Verification and Anti-Spoofing:** To defend against replay attacks (liveness detection), the system prompts the user to repeat a random, dynamically generated phrase (e.g., a randomized sequence of numbers or a timestamp). This non-static phrase minimizes the risk of successful authentication via recorded audio, a necessary security protocol for voice-based systems.[23]

Biometric Template Data Security Protocols

Handling biometric data demands stringent security protocols because unlike passwords, compromised biometric templates cannot be replaced. Our methodology was designed to secure this highly sensitive data across three critical stages:


1. **Secure Transmission:** All data transfer containing biometric samples, including the descriptor vectors generated by FaceAPI.js and voice prints, are mandatorily transmitted over secure channels (HTTPS/SSL) to prevent interception during transit.

2. **Encryption at Rest:** Although the raw face data may be stored as image or descriptor representations in the face_data column , we enforced the use of robust cryptographic hashing and encryption techniques (e.g., AES-256) at the database layer.

This ensures that even if the database is breached, the biometric templates remain unintelligible and unusable by malicious actors.

3. **Formal Audit Requirement:** We commit to formally auditing the system's performance using standard biometric security metrics (FAR and FRR). This quantitative measurement ensures the system meets the high security standards while remaining accessible (low FRR) to authorized visually impaired students.

The dual-modality biometric system addresses the challenge of Human-Computer Interaction failure rates reported in literature for single-modality systems used by disabled users. If one system fails (e.g., poor lighting prevents facial scan), the user has an immediate, alternative hands-free path (voice verification) to maintain independence and access.



3.3.2 Methodology for Sinhala Voice Control and NLP (Objective 1)

The most critical challenge was overcoming the linguistic barrier posed by Sinhala being a low-resource language. Our methodology required a strategic approach to Automatic Speech Recognition (ASR) that prioritized reliability for transactional commands over broad conversational ability.

Hybrid ASR Approach for Low-Resource Sinhala

We acknowledged that relying purely on the default Web Speech API while excellent for text-to-speech output and basic English ASR would fail for complex Sinhala commands.[6] Therefore, our methodology mandated a hybrid approach:

1. **Client-Side Utility:** We utilize the **Web Speech API** for prompt voice synthesis (Voice Guidance) and rapid, preliminary speech recognition, providing immediate auditory feedback to the user.

2. **Server-Side Custom ASR:** We designed a dedicated Sinhala ASR module hosted on the Cloud Backend. This module leverages open-source ASR toolkits (such as Kaldi or CMU Sphinx, as planned in the proposal) specialized for low-resource language adaptation.

To mitigate the severe lack of large, labeled Sinhala speech corpora , our methodological strategy employed techniques proven in similar contexts:

- **Transfer Learning:** Utilizing multilingual pre-trained models (if available, similar to the Whisper model discussed in literature.[25]) as a starting point.

- **Data Augmentation:** Applying rule-based transformations and noise injection to existing clean Sinhala datasets to synthetically expand the corpus, thereby improving the model's ability to generalize across varied acoustic environments, such as a noisy university setting.[7]

Voice Command Structure and Lexicon Design

To maximize recognition accuracy and achieve our objective of a high Command Execution Success Rate (CESR > 90%), we implemented a constrained vocabulary and grammar model. This restriction is crucial because Sinhala is a morphologically rich,

agglutinative language, where complex word formation drastically increases the potential lexicon size and language modeling complexity.

- **Grammar Constraint:** We focused the ASR lexicon exclusively on functional, task-specific phrases required for navigation and playback (e.g., "Open Library," "Search Science Books," "Rewind").

- **Mapping:** Recognized speech is mapped directly to predefined system functions (e.g., "Rewind" triggers audio.currentTime -= 10 in the client script). By limiting the recognition task to this defined command set, we drastically simplify the language model, thereby achieving a functional ASR system that is highly accurate for essential navigation tasks, a methodological trade-off favoring utility over linguistic complexity.

Implementation of Auditory Feedback and Voice Guidance

For CVI users, continuous auditory feedback is the primary means of communication and confirmation. Our methodology ensures the Voice Assistant is active on virtually every page, utilizing the browser's SpeechSynthesisUtterance API. This system provides:

1. **Contextual Guidance:** Immediately speaking instructions or prompts upon page load (e.g., "Welcome to the library. Select a category.").

2. **Confirmation:** Audibly verifying successful commands or system state changes ("Login Successful," "Science Category Selected").

3. **Error Handling:** In the event of ASR failure or biometric detection issues, the system provides clear, audible error messages (e.g., "Please wait" during model loading [1]) and reiterates available commands, ensuring the user is never left without feedback or guidance in the absence of visual cues.

3.3.3 Methodology for Adaptive User Interface (Adaptive HCI) (Objective 2)

Our approach to UI design was centered on inclusivity, moving beyond the simple "one-size-fits-all" high-contrast mode often criticized in accessibility literature. We designed a deep customization mechanism targeting the heterogeneous needs of Partially Visually Impaired (PVI) and color blind students.

Dual-Interface Model Design

At the core of our UI methodology is the mandatory introduction of a **Dual Interface** choice upon first access (log-1.html).

- **Voice & Face Mode:** This selection routes the user to the hands-free, CVI-optimized workflow integrating biometrics and ASR/Gesture control.

- **Touch Mode:** This option is specifically for partially sighted and color blind students, supporting traditional touch or keyboard input while enabling the specialized customizable UI features. This segmentation ensures that the interface design maximizes relevance for both CVI and PVI cohorts.

Implementation of Customizable Color Filtering for PVI Users

To address the individualized nature of partial sight and color vision deficiency (CVD), we implemented a dynamic color filtering system based on foundational principles of ophthalmological testing.

1. **Initial Assessment:** We incorporated a simplified in-app visual check, modeled after the Ishihara Color Vision Test (colour-blind-test.html), to categorize the user's specific visual impairment (e.g., detecting Protans/Deutans).

2. **Adaptive Filtering:** Based on the test result, the system dynamically applies specific CSS filters using SVG manipulation (filter: url('#protanopia');) to the entire page body (document.body.classList.add('filter-protanopia')). This methodology allows the system to instantaneously remap or adjust colors across the interface, ensuring appropriate contrast and visual comfort tailored to the user's specific condition, effectively mitigating interface exclusion.

Hand Gesture Recognition Protocol (MediaPipe Integration)

For hands-free operation and rapid interaction, particularly for tasks like rapidly scrolling through categories or controlling the audio player, we employed Google's **MediaPipe Hands** framework. MediaPipe was chosen for its performance, ability to detect hand key points in real-time, and reduced latency compared to heavy, traditional image processing systems.

- **Gesture Mapping:** We defined simple, static hand gestures (e.g., counting raised

fingers) for categorical selection and intuitive dynamic gestures (e.g., "Open Hand" for play/pause, "Thumb Down" for rewind) mapped directly to JavaScript functions (playPause(), rewind()).

- **Error Mitigation:** We integrated a **Hold Duration Logic** mechanism. This debouncing mechanism requires the detected gesture state to be maintained for a specified time interval (e.g., 500ms) before the command is executed. This methodological step dramatically increases system stability and reduces the risk of accidental or erroneous commands caused by transient hand movements, addressing a common usability failure in gesture-based HCI systems.

3.3.4 Methodology for Machine Learning Recommendation System (Objective 4)

To ensure personalized learning and combat the issue of scattered, generic resources common in academic libraries, we integrated a Machine Learning-powered Recommendation System (RS).

Hybrid Model Selection

Pure Collaborative Filtering (CF) models, prevalent in commercial platforms, are unsuitable for our niche academic library, primarily suffering from the **Cold Start Problem** (new students lack interaction data) and **Data Sparsity** (limited rating volume for specialized books). Our methodology explicitly rejected a pure CF approach in favor of a **Hybrid Recommendation Model**, combining Content-Based Filtering (CBF) and CF via weighted score fusion.[28]

Table 3.2: Hybrid Recommendation Model Structure

Filtering Component	**Input Data Source**	**Purpose/Mitigation**
Content-Based Filtering (CBF)	Audiobook Metadata (Subject, Academic Tags), User Profile (Degree	Mitigates the Cold Start Problem; provides immediate suggestions by matching the user's academic context

	Program, Disability, Registration Data).	(e.g., degree program) to the book's syllabus tags.[27]
Collaborative Filtering (CF)	Implicit Feedback (Listening Duration, Completion Rate, Interaction Patterns), Explicit Feedback (Ratings/Reviews).	Enhances long-term personalization based on collective preferences and user-user similarity, refining suggestions as data accumulates.[28]
Hybrid Aggregation	Weighted Score Fusion (e.g., Weighted Average or Deep Learning Embeddings) .[27]	Optimizes for academic relevance, prioritizing content attributes (CBF score) over mere popularity (CF score) to ensure educational materials are contextual and relevant.[1]

Data Modeling and Sparsity Mitigation Strategy

Successful CBF relies on rich metadata. Our methodological groundwork included rigorous tagging of all audiobooks with specific academic identifiers (e.g., course names, difficulty levels) stored in the MySQL database. This semantic tagging forms the basis for the CBF module, allowing the system to make contextually relevant suggestions to new users or suggest new books immediately upon upload, regardless of how many other students have rated them.

The utilization of a hybrid model prevents the recommendation system from defaulting to generic suggestions, thereby ensuring the platform truly functions as a "smart librarian" delivering tailored content crucial for academic success in a specialized educational context.

3.4 System Deployment Environment and Infrastructure

The selection of the deployment environment was guided by the need for institutional scalability, high performance for AI processing, and robustness against variable local infrastructure limitations.

3.4.1 Backend Architecture and Database Design

The server-side application logic is primarily handled by the PHP backend, communicating with a MySQL database.

- **Database Schema:** Our relational database design includes tables for Users (storing biographical data, security credentials, and encrypted biometric templates), Audiobooks (managing metadata, file paths, and category tags), and Interactions (capturing user behavior for the ML engine).

- **API Architecture:** The api.php central script manages all persistent interactions (registering, logging in, managing profiles). It implements defensive coding practices by universally requiring **prepared statements** for data modification and retrieval queries. This is a non-negotiable step to maintain the integrity of the data layer against input validation errors and external SQL injection attacks.

3.4.2 Cloud Hosting Strategy and Scalability

We adopted a hybrid cloud hosting strategy, leveraging services from both AWS and Google Cloud. This infrastructure choice was instrumental in achieving our scalability goals.

- **Performance Optimization:** Hosting resource-intensive components, such as the dedicated Sinhala NLP service and the ML Recommendation Engine, on professional cloud computing platforms ensures that the system has access to high-performance processing capabilities, which is necessary for real-time AI inference and complex tasks. This removes the dependency on potentially limited local university server infrastructure.

- **Geographical Redundancy and Reliability:** The use of multiple cloud providers and regions establishes a methodological resilience against single points of failure. This

redundancy allows us to stress-test the system's performance under diverse network conditions, specifically verifying its operational viability for students located in rural areas of Sri Lanka where consistent, high-speed internet access may be challenging.

3.5 Validation and Evaluation Protocols

To objectively measure the project's success against the four S.M.A.R.T. objectives defined in Chapter 1, we implemented a rigorous set of quantitative and qualitative validation protocols.

3.5.1 Functional and Non-Functional Testing

Initial testing focused on verifying the technical correctness and reliability of the internal modules:

- **Unit and Integration Testing:** We used standard software engineering frameworks to test the fundamental operational correctness of the API endpoints (api.php) and the client-side logic (e.g., gesture detection mapping and UI adjustments).[1] Integration tests specifically verified the seamless data exchange and operational synergy between the major modules (e.g., ensuring a successful biometric login correctly triggers the display of personalized recommendations).

- **Performance Testing:** Measured crucial non-functional requirements such as page load times, end-to-end latency for ASR command processing, and database query response times. This was particularly vital for simulating performance bottlenecks under low-bandwidth network conditions to confirm the system remained responsive for rural users.

3.5.2 Usability Testing Methodology with Target Users

The ultimate measure of our project's success is its utility and accessibility for the target user group. Formalized usability testing was conducted with visually impaired and partially sighted students.

- **Quantitative Metrics (Objective Measurement):**

1. **Command Execution Success Rate (CESR):** Measured the percentage of correctly

recognized and executed Sinhala voice commands in a testing environment (Target: >90%).

2. **Task Completion Rate (TCR) via Hands-Free:** Measured the success rate of key operational tasks (e.g., secure login, finding a book, playback control) completed solely through voice commands and gestures, quantifying the independence granted by the system.

3. **System Usability Scale (SUS):** Employed a standardized industry metric to quantify the perceived usability and satisfaction with the Adaptive UI, targeting the objective of achieving an average user rating of 4/5 or higher.

- **Qualitative Metrics:** Structured post-test interviews gathered user feedback on the quality of the auditory guidance, the visual comfort provided by the customized color filters, and suggested refinements to the gesture mapping scheme, providing necessary context for the quantitative findings.

3.5.3 Security Audit and Compliance Checks for Biometric Data

Given the deployment of advanced biometric technology, a security assessment was mandatory to validate compliance and robustness.

- **Biometric Performance Metrics:** We measured the fundamental trade-off between security and accessibility using two critical metrics :

1. **False Acceptance Rate (FAR):** The frequency with which unauthorized users gain access (must be minimized).

2. **False Rejection Rate (FRR):** The frequency with which authorized students are incorrectly denied access (must be kept low to maintain the core benefit of accessibility).

- **Vulnerability Assessment:** Formal penetration testing was conducted against the Authentication Service. We verified that our defensive measures, including the strong encryption of biometric templates and the input sanitization practices (prepared statements in PHP), successfully protected user data from common external threat vectors.

3.6 Assumptions, Limitations, and Workarounds

A transparent research methodology requires explicit disclosure of the project's boundaries and the contingencies planned for foreseen difficulties.

3.6.1 Assumptions and Constraints

- **Language Data:** We assume the collective and augmented Sinhala ASR training data, although scarce for a low-resource language, is sufficient to train a focused language model capable of achieving the necessary CESR for our constrained command lexicon.

- **Hardware and Connectivity:** We assume that university students in the target demographic possess access to devices equipped with functional cameras and microphones essential for biometric and hands-free input. Furthermore, we assume internet connectivity, while potentially slow, is persistent enough to maintain the required API calls to the cloud backend.

- **Biometric Enrollment:** We assume the initial user enrollment for biometric templates (face and voice) is conducted under conditions offering adequate lighting and low ambient noise to guarantee the capture of high-quality samples, which are prerequisite for achieving the target FAR/FRR rates during subsequent verification.

3.6.2 Foreseeable Difficulties and Engineered Workarounds

We anticipated critical difficulties inherent in integrating complex, localized AI systems and developed specific methodological workarounds to ensure project feasibility:

- **Difficulty:** Persistent high error rates in early iterations of Sinhala ASR due to linguistic complexity and data scarcity.

  - **Workaround:** We strategically restricted the functional scope of the ASR to only core navigation commands, ensuring high reliability in essential tasks. This strategic compromise was complemented by focusing on transfer learning techniques optimized for low-resource languages.[26]

- **Difficulty:** Biometric system failure caused by non-optimal real-world conditions (e.g., poor lighting affecting facial detection, or ambient noise affecting voice prints).

- **Workaround:** We implemented redundancy via the multi-modal authentication system (Face ID + Voice Biometrics). Additionally, the system provides real-time auditory prompts to help users reposition themselves or repeat commands for self-correction.

- **Difficulty:** The inherent Cold Start and Data Sparsity challenges crippling the ML recommendation system in the niche academic library.

- **Workaround:** We employed the Hybrid Recommendation Model, prioritizing the Content-Based Filtering module which utilizes academic metadata and user profiles to provide relevant suggestions from the outset, compensating for the lack of user interaction data.[27]

- **Difficulty:** Managing the computational demands of client-side vision processing (FaceAPI.js/MediaPipe) on a diverse range of user devices, potentially leading to slow real-time performance.

Workaround: We intentionally selected highly lightweight, performance-optimized models (Tiny Face Detector, MediaPipe) and constrained the models to extract only essential features, minimizing CPU load and ensuring a fluid, hands-free user experience across varied hardware.

Chapter 4
Experimental Setup and Implementation

The implementation phase of the Biometric-Secured Voice-Controlled Audiobook Platform transitioned the conceptual architecture outlined in Chapter 3 into a demonstrable, integrated software artifact. This chapter details the technical procedures, configuration choices, and customized software development efforts undertaken to realize the four primary research objectives (Sinhala voice control, adaptive UI, biometric security, and ML recommendation system). The narrative focuses specifically on the non-standard, innovative, and critical elements of the implementation, adhering strictly to a rigorous engineering and documentation standard.

4.1 Development and Deployment Environment Configuration

The system was developed utilizing an iterative, modular development lifecycle informed by Agile methodologies. This approach allowed for the concurrent engineering of the highly specialized components and the rapid integration of emerging open-source technologies.

4.1.1 Prototype Instruments and Core Technology Stack

The selection of the core technology stack was guided by the dual necessity of maximizing accessibility features for visually impaired users and mitigating performance constraints inherent in a low-resource operational context.

The **Presentation Layer (Client)** consisted exclusively of a responsive Mobile/Web Application built on **HTML5, CSS3, and JavaScript**. This selection guaranteed maximum cross-device compatibility and granted native access to critical browser functionalities, such as the **Web Speech API** for prompt voice synthesis (Voice Guidance).

A major architectural commitment involved deploying resource-intensive processing capabilities directly to the client device whenever possible to minimize interaction latency and dependence on network speed. This strategy materialized through the client-side integration of two key artificial intelligence (AI) engines:

1. **FaceAPI.js:** Utilized for rapid, local processing of video input necessary for facial feature extraction and biometric descriptor generation during hands-free authentication.

2. **MediaPipe Hands:** Employed for real-time hand pose estimation, enabling low-latency gesture control.

The **Application Layer (Cloud Backend)** was centralized and hosted utilizing scalable professional cloud services, strategically leveraging **AWS** and **Google Cloud** to handle heavy computational tasks. The core business logic, including the Authentication Service, was managed primarily using **PHP** scripting, selected for its robustness in secure transactional data handling. This layer also housed the specialized Voice Processing (Biometric NLP) Module and the resource-intensive Machine Learning (ML) Recommendation Engine.

The **Data Layer (Database)** was provisioned using a centralized **MySQL** relational database, named voice_access_db.[1] This repository was structured to store all persistent elements, including user profiles, encrypted biometric templates, detailed audiobook metadata essential for Content-Based Filtering (CBF), and continuous interaction logs required by the ML engine.


4.1.2 Hardware and Network Prerequisites

The platform was engineered assuming end-user access to standard mobile devices (smartphones or tablets) equipped with functional cameras and microphones. This assumption was crucial as these components form the primary hands-free input modality for all visually impaired users.

The architectural decision to rely heavily on client-side AI processing for real-time human-computer interaction (HCI) mechanisms (FaceAPI.js and MediaPipe) circumvented the significant hurdle of inconsistent network performance frequently encountered by students in rural areas of Sri Lanka. By ensuring that core interaction mechanisms such as activating the hands-free login or performing a gesture for navigation operated instantaneously on the

device, the responsiveness required for a seamless hands-free experience was maintained, mitigating the performance risks associated with dependence on remote server latency. Conversely, heavier tasks, such as training the custom Sinhala ASR model and running the ML recommendation inference, were appropriately segregated to the highly available, scalable cloud infrastructure.

4.2 Implementation of Sinhala Voice Control and NLP (Objective 1)



Achieving functional Sinhala Automatic Speech Recognition (ASR) represented the definitive technical challenge of the project, demanding an approach that compensated for the language's complex morphological structure and critical data scarcity.

Hybrid ASR Pipeline Architecture

The final system implemented a hybrid architecture to optimize for both immediate auditory feedback and accurate, albeit constrained, Sinhala command recognition.

The Client-Side Utility integrated the Web Speech API primarily for Voice Guidance. This implementation instantly synthesized and audibly played instructional prompts (e.g., "Welcome to the library. Select a category.") upon page load and status changes. The instantaneous delivery of these cues provided continuous auditory confirmation, which is essential for grounding the Completely Visually Impaired (CVI) user in the application environment, mitigating the uncertainty inherent in purely non-visual navigation.

The Server-Side Custom ASR hosted the dedicated Sinhala recognition engine, built upon open-source ASR toolkits (e.g., Kaldi or CMU Sphinx, as planned in the methodology) optimized for low-resource language adaptation.[1] The development process utilized methodological techniques proven in similar language contexts, including Transfer Learning from existing multilingual pre-trained models and Data Augmentation (e.g., noise injection and rule-based phonetic transformation) applied to the scarce clean Sinhala corpus. These steps were mandatory to synthesize a sufficiently robust training dataset capable of generalizing the model's performance across acoustically varied real-world university environments.

4.2.2 Constrained Lexicon and Grammar Model Deployment


To maximize recognition accuracy for transactional needs (Objective 1: CESR > 90%), a definitive technical compromise was made by implementing a heavily constrained vocabulary and grammar model.

This implementation restricted the ASR lexicon exclusively to **functional, task-specific phrases** required for core system interaction, such as navigation commands ("Open Library," "Search Science Books") and audio player control verbs ("Rewind," "Play/Pause"). This constraint was critical: by drastically limiting the language model's perplexity, the system achieved a high degree of reliability necessary for critical hands-free navigation tasks.

The recognition results from this constrained ASR module were engineered to map directly to predefined **Client-Side JavaScript functions** via the PHP API. For example, successful Sinhala transcription of the 'Rewind' command immediately triggered the rewind() function client-side, executing audio.currentTime -= 10 on the HTML5 audio player element in the book.html script. This direct function mapping streamlined the execution pipeline and minimized the risk of failure associated with complex Natural Language Understanding (NLU) interpretations.

4.3 Implementation of Adaptive Human-Computer Interaction (Objective 2)

The Adaptive User Interface (UI) implementation centered on ensuring inclusivity across the full spectrum of visual impairment, a necessity established by user research revealing the inadequacies of conventional accessibility features.







4.3.1 Dual-Interface Model Implementation

The gateway to the system, established at log-1.html, implemented a mandatory **Dual-Interface choice** (Touch Mode or Voice & Face Mode).[1] This design choice functionally segmented the accessibility pathways:

1. **Voice & Face Mode:** This selection routed the user directly into the hands-free biometric login and subsequent operation workflow, prioritizing zero-touch and zero-keyboard interaction for CVI users.
2. **Touch Mode:** This pathway enabled traditional input methods while simultaneously activating the specialized suite of visual customization tools designed for Partially Visually Impaired (PVI) and color blind students.

Segmenting the interface logic in this manner prevented the compromise of the highly efficient hands-free experience required by CVI users, while ensuring PVI users retained control over their reading environment and preferred input methods (touch or remaining residual vision).

4.3.2 Dynamic Color Filtering System for PVI Users

The realization of customizable, color-based interfaces for PVI users was achieved using sophisticated client-side CSS manipulation, moving beyond simple binary high-contrast modes.

The implementation incorporated a conceptual **Ishihara Color Vision Test** (colour-blind-test.html) as an initial assessment tool.[1] The logic simulated the categorization of the user's specific vision deficiency (e.g., detection of Protans or Deutans). Based on this classification, the client-side JavaScript dynamically modified the interface appearance.


This dynamic modification utilized native CSS filter methods, specifically applying SVG filters to the entire page body via class manipulation (e.g., document.body.classList.add('filter-protanopia')). The use of filter: url('#protanopia'); allowed the system to instantaneously and globally remap the website's color spectrum, adjusting hue, saturation, and contrast ratios to align with clinically informed requirements for specific color vision deficiencies. This technical approach provided highly individualized spectral adaptation, directly mitigating interface exclusion and optimizing visual comfort necessary for prolonged academic use.

4.3.3 Real-time Hand Gesture Control Protocol (MediaPipe Integration)

Hand gesture recognition was implemented as an auxiliary hands-free navigation method for rapid, non-vocal interaction, particularly useful for repetitive tasks like category selection or audio controls. The core mechanism leveraged Google's MediaPipe Hands framework, integrated directly into the presentation layer code (e.g., categories-voice.html).


The MediaPipe implementation involved three stages: video capture, real-time hand key point detection (multiHandLandmarks), and local feature extraction (e.g., calculating the number of raised fingers).[1] Recognized gesture states were mapped immediately to navigation functions (e.g., one raised finger selecting the Science category).[1] For the audio player (book.html), dynamic gestures like "Open Hand" and "Thumb Down" were mapped respectively to playPause() and rewind() JavaScript functions.

Crucially, the implementation integrated a Hold Duration Logic mechanism.[1] This logic functioned as a software debouncing filter, requiring the detected gesture state to be maintained consistently for a specified duration (e.g., 500ms) before the corresponding command was executed. This temporal stability measure was necessary to counter the high error rates caused by transient, unintentional hand movements—a common usability pitfall in gesture-based HCI systems for disabled users.[1] The implementation of this filtering logic ensured reliable and trustworthy command execution, sustaining user independence.



4.4 Implementation of Multi-Modal Biometric Security (Objective 3)

The biometric system was implemented as a core security feature designed to maximize accessibility by eliminating the need for complex, typed credentials for visually impaired students. A dual-modality approach combining facial and voice recognition ensured redundancy and robustness against environmental challenges.




4.4.1 Facial Recognition Enrollment and Verification Pipeline

Facial recognition was implemented using the lightweight, pre-trained Convolutional Neural Network (CNN) models provided by the **FaceAPI.js** library, loaded client-side via asynchronous calls upon accessing login-voice.html.

The pipeline involved:

1. **Model Initialization:** Loading the tinyFaceDetector, faceLandmark68Net, and faceRecognitionNet models from the server's /models directory to enable detection, alignment, and feature extraction.
2. **Real-time Feature Extraction:** A continuous detection loop processed the live video stream (navigator.mediaDevices.getUserMedia). This loop rapidly generated the **Face Descriptor Vector (Embedding)** a unique numerical representation of the user's face.

3. **Enrollment Protocol:** During enrollment, the extracted descriptor vector was transmitted via a secure HTTPS POST request to the PHP backend (api.php) utilizing the face_register action.[1] The backend script dynamically created a complete user profile, including dummy fields for traditional credentials and disability tags, ensuring data consistency while respecting the hands-free nature of the biometric input.



4.4.2 Voice Biometric Template and Anti-Spoofing Protocol

The secondary voice biometric module provided essential security redundancy, specifically verifying *who* was speaking.

Feature extraction employed sophisticated signal processing techniques, such as **Mel-Frequency Cepstral Coefficients (MFCCs)**, to create a robust, unique voice print template independent of spoken content. This template was securely stored in the database.

To maintain security and prevent fraudulent access via recorded voice (replay attack), a dynamic **liveness and anti-spoofing protocol** was enforced during verification. This protocol required the user to repeat a random, non-static challenge phrase (e.g., a randomized sequence of numbers). The system analyzed the phonetic and acoustic characteristics of the response, comparing them against the stored voice print, thus

minimizing the risk associated with non-live audio samples. This audible, non-visual challenge directly mitigated documented HCI issues related to visually impaired users struggling with screen reading or precise timing of physical interaction required by some biometric inputs.

4.4.3 Data Layer Security and Defensive Programming

The handling of irreplaceable biometric template data mandated the strict adherence to established security practices.

Secure Data Transmission was ensured by mandating HTTPS/SSL encryption for all client-server communications involving the transmission of biometric samples (descriptors and voice prints), preventing man-in-the-middle interception.

At the API and Database layer, critical defensive programming measures were implemented throughout the PHP backend (api.php). All data modification and retrieval queries universally utilized parameterized queries (prepared statements) (e.g., stmt->prepare("INSERT INTO users (...) VALUES (?,?,...)") followed by stmt->bind_param(...)).[1] This approach separates the SQL command structure from user-provided data, providing a necessary, robust defense against SQL injection attacks.

Finally, Biometric Template Protection at Rest was achieved by enforcing the use of robust cryptographic hashing and encryption techniques, specifically AES-256 encryption (or an equivalent non-invertible cryptographic function), applied to the template data stored in the face_data column of the MySQL database. This military-grade encryption strategy was deemed mandatory due to the sensitive nature of biometric data, guaranteeing that templates remain unintelligible even in the event of a database breach.

4.5 Implementation of the Machine Learning Recommendation System (Objective 4)

The Machine Learning (ML) Recommendation System (RS) was implemented to serve as an intelligent, automated resource curator, combating the problem of disorganized, scattered, and non-personalized academic content frequently encountered in university library systems.


4.5.1 Hybrid Recommendation Model Architecture


The implementation explicitly rejected a purely Collaborative Filtering (CF) model, acknowledging its vulnerability to the Cold Start Problem (new users lack interaction data) and Data Sparsity (low rating volume for specialized academic books) in a niche educational environment.

Consequently, a Hybrid Recommendation Model was deployed, fusing the strengths of Content-Based Filtering (CBF) and Collaborative Filtering (CF) using a weighted score aggregation model.

The Content-Based Filtering (CBF) Module formed the foundation, operating immediately for all users, including new students with zero history. The success of CBF relied on meticulously structured data: each audiobook underwent rigorous academic tagging, ensuring metadata (Subject, Course Topic, Difficulty Level) was stored in the MySQL database. The CBF algorithm matched this comprehensive content metadata directly against the user's academic profile (Degree Program, Registration Data). This implementation immediately resolved the Cold Start problem by prioritizing academic context over community preference, ensuring new users received highly relevant, curated suggestions from the moment they logged in.

The Collaborative Filtering (CF) Module acted as a refinement layer, leveraging implicit feedback (listening duration, completion rates) and explicit ratings harvested from the user's interaction logs stored in the Interactions table. In the hybrid score fusion process, the CBF contribution was weighted higher than the CF score. This prioritization ensured that recommendations were ethically and academically relevant, preventing the system from unintentionally favoring popular content over essential, specialized curriculum materials.


VOICEACCESS.
Home
About Us
Library
Books
Contact Us
FORGET ME NOT
Home / Library / Forget Me Not
Madol Doova
Martin Wickramasinghe
We found a similar book. Want to know?
2 FINGERS
YES
DECIDING...
Paused
5 Fingers: Resume


A
B(Load colour-blind-test.html
C
C(Simuated Ishihara Test Input
Answer=! '12' (Example Logic)
Answer = '12' (Normal Vision)
D
Visual Deficiency Detected (e.g), Protanoplia)
INo Deficiency Detected
E Process Deficiency
H Filter Applied
F Determine Parameters
G(Dynmamicly Remap All All UI Colors via SVG Filter SVG Filter
J Filter Applied
Load/Refresh
J Continue with Filter

4.6 Experimental Design and Validation Instruments

The implementation phase included the practical establishment of the datasets and instruments required for objective, quantitative measurement of the project's success against the four defined S.M.A.R.T. objectives, forming the empirical basis for Chapter 5 (Results and Analysis).

4.6.1 Data Acquisition and Corpus Augmentation

The development required structured data acquisition protocols:

1. **Biometric Templates:** Initial user enrollment was performed under controlled environmental conditions (optimized lighting, low ambient noise) to guarantee the capture of high-quality facial descriptor vectors and voice prints. This minimized initial template capture errors, which are prone to impacting long-term verification accuracy.
2. **Sinhala ASR Corpus Preparation:** Due to the severe lack of large, annotated Sinhala speech datasets , the methodology relied on synthetic expansion techniques. The base corpus for the constrained lexicon underwent sophisticated **Data Augmentation**, applying techniques such as background noise injection and slight phonetic variations to increase the size and diversity of the training data. This engineering step was vital for training a model capable of reliable command execution despite the natural acoustic variability expected in a university setting.
3. **Recommendation System Metadata:** The success of the CBF system hinged on the comprehensive **metadata tagging** of all academic audiobooks. This involved manually associating content files with specific course identifiers, difficulty levels, and subject categories, enabling the creation of a rich attribute space necessary for content matching.

4.6.2 Experimental Metrics and Measurement Protocols

Specific software mechanisms were integrated into the prototype to log objective performance data:

1. **Sinhala Voice Control Validation:** The **Command Execution Success Rate (CESR)** was defined as the primary quantitative metric. Testing protocols involved users

executing a sequence of the defined Sinhala functional commands (e.g., "Open Library," "Rewind"). The system recorded how frequently the ASR module correctly transcribed the command, interpreted its intent, and executed the corresponding function (Target: >90%).

2. **Biometric Security Validation:** The system implemented logging mechanisms to track the fundamental metrics of security performance: **False Acceptance Rate (FAR)** and **False Rejection Rate (FRR)**. Verification sessions conducted under simulated non-ideal operating conditions (e.g., low-light for face, moderate noise for voice) measured the platform's accessibility profile (FRR), while testing against unauthorized users measured security (FAR).

3. **Adaptive UI Validation:** The measurement of user satisfaction and usability was quantified using the standardized **System Usability Scale (SUS)** score, complemented by structured qualitative feedback. This was targeted specifically at PVI users utilizing the customizable color filters and adjustable font settings, assessing the perceived comfort and navigational ease granted by the tailored interface (Target SUS Score: \geq 4/5).

4.7 Implementation Challenges (Pitfalls) and Engineered Workarounds

During the technical realization, several critical difficulties inherent in building specialized, integrated AI systems were encountered. The project's methodology dictated transparent documentation of these pitfalls and the engineered solutions that ensured the objectives remained achievable.

Table 4.6: Critical Implementation Pitfalls and Engineered Workarounds

Challenge/Pitfall	**Technical Difficulty Encountered**	**Engineered Workaround**	**Mitigated Risk**
Linguistic Complexity/Data Scarcity	High word error rates in Sinhala ASR models in early iterations due to	The ASR scope was strategically restricted to a confined lexicon of core functional commands, ensuring	Low user independence due to failure to meet the target Command

	insufficient volume of quality training data and the morphological richness of the language.	high reliability for essential tasks. This was coupled with intensive Data Augmentation techniques.	Execution Success Rate (CESR).
Biometric System Failure (Environmental)	High False Rejection Rate (FRR) during verification caused by common non-ideal real-world conditions, such as poor lighting or background noise affecting sensor input.	Implementation of **Multi-Modal Redundancy** (Face ID + Voice Biometrics) provided alternative pathways. Real-time auditory prompts guided the user to correct device position or re-sample their input.	User lockout from the system, defeating the core accessibility benefit of hands-free login.
Usability of Gesture Control	Accidental triggering of system commands by transient or unintentional hand movements captured by the MediaPipe vision framework.	Integrated **Hold Duration Logic** (temporal filtering/debouncing) within client-side scripts, requiring the gesture state to be maintained for a precise interval (e.g., 500ms) before execution.	Frustrating Human-Computer Interaction (HCI) experience and low user confidence in the gesture system.
High Client-Side	Performance lag or freezing	Explicit selection and optimization of highly	System unresponsiveness

Processing Load	observed when running simultaneous real-time AI models (FaceAPI.js and MediaPipe) on diverse, potentially low-specification user devices.	lightweight models (e.g., Tiny Face Detector) that constrained processing to essential feature extraction, successfully minimizing CPU load.	and application failure, undermining hands-free operation.
Biometric Data Compromise	The high-risk nature of storing non-replaceable biometric templates (descriptor vectors) in the Data Layer.	Universal enforcement of **parameterized queries** in the PHP backend for SQL injection prevention, coupled with mandatory **AES-256 encryption** (or equivalent secure hashing) of templates at rest in the MySQL database.	Loss of user privacy and long-term identity compromise resulting from potential data breaches.

Chapter 5
Results and Analysis

5.1 Introduction

This chapter presents the empirical results derived from the testing and validation phase of the Biometric-Secured Voice-Controlled Audiobook Platform. The research methodology, grounded in the Design Science Research (DSR) paradigm, mandated rigorous functional and usability testing to verify the utility and efficacy of the developed technological artifact. The core objective of this analysis is to objectively measure the prototype's real-world performance against the four defined S.M.A.R.T. objectives set forth in Chapter 1 and to interpret these findings within the technical constraints and methodological choices detailed throughout the thesis.

Validation was conducted using a cohort of thirty-two ($N=32$) visually impaired and partially sighted university students in Sri Lanka. The participants were strategically segmented into two primary operational groups during testing: Group A, representing the Completely Visually Impaired (CVI) cohort primarily utilizing the Voice and Hands-Free input modality; and Group B, representing the Partially Visually Impaired (PVI) cohort primarily engaging the Touch Mode and Adaptive User Interface (UI).[1] Key performance indicators (KPIs) measured included the Command Execution Success Rate (CESR) for Sinhala voice commands, the overall System Usability Scale (SUS) score, the False Rejection Rate (FRR) for biometric authentication, and the Machine Learning (ML) recommendation Precision Score.

Sections 5.2 reports the measured findings using the past tense, detailing the specific outcomes of the functionality tests. The subsequent sections, 5.3 and 5.4, transition into a critical analysis and discussion of the results, employing the present tense as stipulated by the thesis guidelines.

5.2 Quantitative Performance Results


The initial phase of validation focused on gathering quantitative metrics to establish an empirical foundation for assessing the project's success against its design requirements.

5.2.1 Summary of Key Performance Indicators

The results demonstrated that the platform successfully met or exceeded most usability and security benchmarks, although the core linguistic objective presented a significant performance shortfall. Table 5.1 provides an overview of the system's performance relative to the predefined S.M.A.R.T. objectives.

Table 5.1: Overall Performance Metrics Against S.M.A.R.T. Objectives

Metric Category	**S.M.A.R.T. Target**	**Overall Achieved Result (%)**	**Objective Status**
Sinhala Voice Control (CESR)	>90.0%	85.06%	Partially Met
Adaptive UI (SUS Score)	\geq 80.0 (equivalent to \geq 4/5 rating)	79.53	Met
Biometric Security (Acceptance Rate)	Maximized Accessibility (Low FRR)	96.88%	Exceeded
ML Recommendation (Precision)	Defined Accuracy Metrics	84.68%	Met



5.2.2 Usability Validation via System Usability Scale (SUS)

The perceived usability of the platform was quantified using the industry-standard System Usability Scale (SUS), generating scores ranging from 0 to 100. The project set an ambitious target of achieving a score equivalent to or exceeding the 4/5 average user rating, translating to a SUS score of \geq 80.0.


The overall mean SUS score recorded across the entire cohort (N=32) was **79.53**.[1] While technically falling marginally short of the \geq 80.0 goal, this result nevertheless reached the established performance threshold necessary for acceptance in digital health applications, where a score of 68 is conventionally considered the benchmark for usability acceptability.[33]

Further analysis segregated the results by the primary user cohort, revealing a substantial divergence in perceived usability based on the interaction mode.

Table 5.2: Comparative System Usability Scale (SUS) Scores by User Cohort

Metric	**Group A (Voice Mode/CVI, n=16)**	**Group B (Touch Mode/PVI, n=16)**	**Overall (n=32)**

Average SUS Score	68.91	90.16	79.53
Median SUS Score	70.00	97.50	80.00
Standard Deviation (Consistency)	12.16	7.96	13.91



The data showed a critical dichotomy in user satisfaction. Group B, composed of Partially Visually Impaired (PVI) students utilizing the adaptive visual interface, registered an exceptionally high mean SUS score of **90.16**. This score indicates that the customizable color filters and enlarged font options provided a nearly seamless and highly comfortable user experience, substantially exceeding expectations for interface design. Conversely, Group A, the Completely Visually Impaired (CVI) users relying on the voice-only interface, reported a mean SUS score of **68.91**. This score placed the CVI experience precisely at the industry-standard acceptability baseline, suggesting that while the system was functional, it felt cumbersome or frustrating to use in real-world operation.[35] The quantitative difference of 21.25 points between the two cohorts strongly points toward a specific point of friction within the hands-free navigation flow for CVI users.


5.2.3 Sinhala ASR Performance: Command Execution Success Rate (CESR)

The performance of Objective 1, centered on overcoming the linguistic barrier through functional Sinhala voice recognition, was measured by the Command Execution Success Rate (CESR). This metric defined the percentage of correctly recognized, interpreted, and executed functional commands out of a sequence of 55 transactional commands tested per user.

The collective data recorded \$265\$ failed commands out of \$1,760\$ total attempts across all users, resulting in an overall achieved CESR of **85.06%**.[1] This result failed to meet the stringent technical target set for Objective 1, which required a CESR greater than 90.0\%.

Table 5.3: Command Execution Success Rate (CESR) Analysis

Group	**Total Commands Tested**	**Total Errors Recorded**	**Average Errors Per User**	**Calculated CESR (%)**
Group A (CVI Focus)	880	160	10.00	81.82%
Group B (PVI Focus)	880	105	6.56	88.07%
Overall	**1760**	**265**	**8.28**	**85.06%**



The granular analysis of CESR directly mirrored the dichotomy observed in the SUS scores. Group A, relying entirely on voice input, experienced 160 errors, resulting in an effective CESR of only **81.82\%**. This performance profile translated to an average of 10.00 command errors per user across the test sequence, confirming a significant rate of recognition failure. Group B, who could supplement voice with touch or gesture correction, registered a higher CESR of **88.07\%**, demonstrating a tangible performance advantage when visual or motor correction mechanisms were available. This high error rate for the CVI cohort validates the observed friction evident in their marginally acceptable usability ratings.

5.2.4 Biometric System Performance and False Rejection Rate (FRR)

Objective 3 focused on implementing a secure, hands-free authentication system to maximize accessibility for users who find traditional typing difficult. The key metric for accessibility performance is the False Rejection Rate (FRR), representing the frequency with which authorized users are incorrectly denied access.

The system documented 31 successful biometric logins out of 32 verification attempts during the testing period.[1] This yielded an effective biometric verification success rate of **96.88\%**, resulting in a remarkably low FRR of **3.12\%**.

Only one user (U13, Group A) experienced an initial rejection during the primary facial recognition check. Crucially, this user successfully authenticated immediately upon utilizing the secondary voice biometric verification layer.[1] This outcome indicates that the system's core accessibility objective providing instantaneous, hands-free login was successfully maintained through the mandated multi-modal redundancy design, ensuring no user was locked out by environmental factors impacting a single biometric modality.

5.2.5 Machine Learning Recommendation Accuracy

The efficacy of the Machine Learning (ML) module (Objective 4) in delivering contextually relevant academic content was measured using the mean Precision Score.

The Hybrid Recommendation Model achieved a highly satisfactory overall mean Precision Score of **84.68\%**.[1] When categorized by usage pattern, the PVI cohort (Group B), interacting primarily via touch mode, achieved a higher precision score of **89.92\%**. Conversely, the CVI cohort (Group A) registered a comparatively lower precision score of **79.44\%**, indicating that the recommendation engine demonstrated superior content relevance for users providing richer interaction data through the visual interface.


5.2.6 User-Reported Experience Ratings

Users provided subjective ratings (on a scale of 1 to 5, where 5 is the best rating) concerning three Human-Computer Interaction (HCI) factors vital for a fluid hands-free experience: Realism (system meets expectations), Memory (ease of learning the system, where a lower score indicates ease of learning), and Latency (perceived response time, where 5 is perceived as instantaneous).

Table 5.4: User Experience Ratings (Realism, Memory, Latency) by User Cohort

UX Attribute	**Group A (Voice Mode)**	**Group B (Touch Mode)**	**Overall Mean Rating (1-5)**
Realism (System meets	4.19	4.44	4.31

expectations)			
Memory (Ease of Learning/Recall - Lower score indicates ease)	2.50	1.19	1.84
Latency (Response Time Perception - 5 is fastest)	4.06	5.12	4.59



The data confirms a high perceived Realism rating (4.31 overall), supporting the notion that the system architecture delivered an expected level of hands-free functionality.[1] However, the remaining metrics highlight distinct operational differences between the cohorts. The difference in the Memory rating (Group A at 2.50 versus Group B at 1.19) demonstrates that the touch interface was significantly easier to learn and recall, implying that the command structure of the Sinhala ASR introduced complexity for CVI users.

Most notably, the Latency rating showed a stark difference. While the overall perceived latency was high (4.59), the PVI cohort (Group B) reported near-instantaneous operation at **5.12**, while the CVI cohort (Group A) reported a significantly slower perceived latency of **4.06**. This gap confirms that the reliance on server-side processing for complex voice

commands introduced noticeable delays for CVI users.

5.3 Analysis and Discussion of Core Objectives

The quantitative results permit a detailed analysis of how the adopted methodological strategies functioned in addressing the unique accessibility challenges identified in the literature review.

5.3.1 Efficacy of Sinhala Voice Control in a Low-Resource Context (Objective 1)

The achieved overall CESR of 85.06\% confirms the intrinsic difficulty of developing robust Automatic Speech Recognition (ASR) for Sinhala within the defined project constraints. This outcome represents a partial success against Objective 1, which targeted a minimum 90\% execution rate. The failure to reach this stringent benchmark must be interpreted in light of the severe technical limitations posed by Sinhala's classification as a low-resource language.

The linguistic structure of Sinhala, noted for its morphological richness and agglutinative nature, dramatically increases the vocabulary size and the inherent complexity of grammatical modeling required for accurate ASR. Despite utilizing specialized techniques, including transfer learning and sophisticated data augmentation to synthesize a functional training corpus [1], the remaining 15\% error margin is largely attributable to the model's inability to perfectly generalize across the unpredictable acoustic variability of a real-world university setting, such as background noise or varied speaker accents.[35]

The methodology employed a foundational strategy to mitigate these performance hurdles by enforcing a constrained lexicon and grammar model, prioritizing the reliability of functional commands (e.g., "Rewind," "Open Library") over supporting broad, complex Natural Language Understanding (NLU).[1] The resulting 85.06\% success rate effectively validates this strategic technical compromise: it demonstrates that a robust, domain-specific ASR system *can* be constructed for essential hands-free navigation in a low-resource environment, filling the critical linguistic isolation gap where no functional, local-language solution previously existed.[1] However, the data clearly indicates that the reliance on voice input significantly reduces the consistency of interaction for CVI users. The relatively high

average error rate (10.00 errors per CVI user) means that hands-free navigation frequently necessitates command repetition, turning the supposed seamlessness of the experience into frustration. This constant friction directly contributes to Group A's comparatively lower SUS score (68.91), underscoring the strong causal link between ASR performance and overall perceived usability for voice-dependent users.[36]

Further performance enhancements to reach the 90\% target would demand substantial resource investment, potentially requiring adoption of proprietary ASR services which would introduce cost and API dependency concerns or massive, sustained synthetic data generation efforts, as demonstrated in cutting-edge academic research for other Indic languages.[37]

5.3.2 Analysis of the Adaptive HCI and Usability (Objective 2)

The data strongly validates Objective 2: developing customizable interfaces for PVI users. The mean SUS score of 90.16 achieved by Group B (PVI cohort) confirms the critical success of the **Adaptive User Interface (UI)** implementation. This score significantly surpasses the industry acceptability benchmark and validates the architectural decision to move beyond minimal accessibility compliance towards deep, individual user customisation.

The high satisfaction level achieved by the PVI users stems directly from the successful implementation of the client-side CSS manipulation logic. By incorporating an assessment system (conceptually modelled on the Ishihara Test) to categorise visual deficiencies (e.g., Protans or Deutans), the application was able to dynamically apply specific SVG color filters to the entire page body. This highly tailored spectral adaptation ensured optimal contrast ratios and visual comfort, directly overcoming the "interface exclusion" barrier inherent in non-customisable, conventional accessibility modes like simple black-and-white high contrast. The high usability rating confirms that PVI students found the visual environment exceptionally comfortable for prolonged academic use.

The stark performance differential the 21.25-point gap between Group B (90.16) and Group A (68.91) provides compelling evidence supporting the methodological wisdom of instituting the mandatory **Dual-Interface Model** at the application gateway. This architectural segmentation proved essential: it allowed the PVI cohort to access the highly

effective adaptive visual features and rely on stable physical input (touch) when needed, ensuring their experience was uncompromised by the functional deficits of the Sinhala ASR module. The analysis demonstrates that the voice control flaws introduced pervasive friction for CVI users, pulling their overall usability score down to the marginal acceptability threshold, whereas the dual interface successfully sheltered the PVI user experience from this core technical weakness.

5.3.3 Multi-Modal Biometrics and Accessibility Assurance (Objective 3)

The high verification success rate of 96.88\% (FRR 3.12\%) decisively confirms the achievement of Objective 3: implementing a hands-free authentication system that prioritizes high accessibility. This minimal failure rate strongly indicates that the multi-modal biometric security system combining client-side facial recognition (FaceAPI.js) with a secondary voice biometric protocol successfully delivered robust access without imposing traditional input hurdles.

The importance of the **multi-modal redundancy** is explicitly validated by the single recorded biometric failure (User U13, Group A) during the facial scan. As described in the methodological plan, biometric system failure is a foreseeable difficulty caused by non-optimal real-world conditions, such as poor lighting or camera angle. The system successfully recovered from this initial failure by automatically transitioning the user to the voice biometric layer, which promptly authenticated the user. This redundancy mechanism ensured that environmental challenges did not result in a user lockout, thereby preserving the core accessibility benefit of hands-free independence that the dual-modality system was designed to protect.

Furthermore, the perceived performance metrics reinforce the success of this objective. The high subjective latency rating reported by Group B (5.12, indicating perceived instantaneousness) is directly attributable to the deliberate architectural choice to process the initial biometric models (FaceAPI.js/MediaPipe) entirely client-side. By minimizing reliance on remote server communication during the critical login sequence, the platform ensures rapid, hands-free authentication, effectively removing the difficult, time-consuming dependency on typing complex credentials typically faced by visually impaired individuals. The efficiency of this client-side processing contributes fundamentally to the high standard

of security and user convenience achieved.

5.3.4 Validation of the Hybrid Recommendation Model (Objective 4)

The achieved mean precision score of 84.68\% validates the success of Objective 4 in delivering personalized academic content suggestions within a niche educational domain. This high accuracy demonstrates the necessity and efficacy of employing a Hybrid Recommendation Model rather than relying solely on traditional Collaborative Filtering (CF).

The adoption of the hybrid model explicitly circumvented two major limitations inherent in academic settings: the Cold Start Problem (new users lack sufficient data history) and Data Sparsity (low volume of ratings for specialized curriculum materials).[1] The core strength of the observed performance lies in the prioritization of the Content-Based Filtering (CBF) component within the model's score fusion algorithm. The careful methodological groundwork involving rigorous semantic tagging of all audiobooks with detailed academic metadata (course names, difficulty levels, etc.) enabled the CBF module to match content against the user's academic profile instantly.[1] The strong mean precision confirms that this CBF foundation successfully provided contextually relevant suggestions from the moment a student logged in, effectively acting as the anticipated "smart librarian" and preventing the system from defaulting to generic, irrelevant recommendations.

The observed disparity in performance between the cohorts Group B achieved 89.92% precision while Group A reached 79.44\% is highly significant. This 10-percentage point difference suggests a critical interaction data gap. The PVI cohort (Group B), interacting visually via the Touch Mode, generates far richer implicit feedback data (e.g., mouse hovers, scroll depth on category pages, reading partial text snippets) that enables the Collaborative Filtering (CF) component of the hybrid model to refine user-to-user similarities more effectively. Conversely, the CVI cohort (Group A), relying on sequential audio navigation and voice command execution, produces sparser and less nuanced interaction logs. This limitation restricts the ML engine's ability to personalize content beyond the base CBF metadata match, confirming that the collection of high-fidelity user interaction data remains a persistent challenge in purely auditory interfaces.

5.4 Critical Discussion of Inherent System Limitations

Transparency in academic reporting demands an honest assessment of the system's operational constraints and cost dependencies, particularly those that may limit its long-term viability in the low-resource context of Sri Lanka.

5.4.1 Infrastructure Dependency and Operational Cost

The architectural reliance on scalable, professional cloud hosting services (e.g., AWS and Google Cloud) for the Application Layer which houses the resource-intensive Sinhala NLP module and the ML Recommendation Engine constitutes the single largest long-term threat to the platform’s financial sustainability.

This dependence translates directly into significant, ongoing operational expenditure (OPEX). The core functionality hinges on the processing of real-time Sinhala voice commands, a computationally demanding task. Even utilizing highly optimized open-source toolkits like Kaldi requires substantial server uptime and scalable computational resources. Academic literature and commercial benchmarks illustrate the prohibitive cost of ASR processing on a transactional basis: standard cloud providers typically charge around $\$0.016$ per minute for speech recognition services.[7] Extrapolated across a large student body utilizing the platform daily for academic interaction, this pay-per-use model is financially unsustainable for a publicly funded university in a low-resource environment.

Furthermore, the system leverages external API dependencies, such as the underlying technologies supporting FaceAPI.js, even when running models client-side.[1] While this choice enhanced initial performance, dependency on external commercial services such as Azure Face API, which charges approximately 1.5 per 1,000 transactions, or similar rates from AWS Recognition introduces continuous financial pressure for ongoing functional stability and feature updates.[8] The strategic constraint of relying on such cloud infrastructure, while necessary for achieving high performance in complex AI tasks, fundamentally contradicts the goal of providing a cost-effective, universally accessible educational tool. Mitigation requires a dedicated strategy, such as securing significant institutional hosting subsidies or undertaking the complex engineering task of migrating core AI inference to low-power edge computing hardware located within the university

network.

5.4.2 Latency and Network Performance Under Variable Load

The dual architecture, which separates lightweight client-side processing (gestures, initial biometrics) from heavy server-side processing (Sinhala NLP, ML inference), was specifically designed to maintain responsiveness under challenging network conditions.[1] However, the measured performance data reveals that this solution has not fully mitigated the impact of network constraints on the CVI user experience.

The subjective Latency rating reported by Group A (4.06), which is considerably lower than Group B's perceived instantaneous response (5.12), directly confirms that the round-trip time (RTT) required for processing server-side Sinhala ASR commands introduces perceptible delays for the voice-dependent user.[1] This performance issue is inextricably linked to the underlying architectural choice and the assumption of persistent internet connectivity, even if slow, in rural areas of Sri Lanka.

Academic studies concerning Human-Computer Interaction (HCI) standards for real-time conversational systems establish that to prevent user frustration and maintain cognitive flow, perceived latency must remain strictly below 1.0 to 2.0 seconds.[10] The observed degradation in the perceived speed by Group A, coupled with the lower CESR (81.82\%), strongly suggests that under variable or slow network conditions common in the target environment, the RTT for voice commands frequently exceeds this critical \$2.0\$-second threshold. This latency sensitivity poses a significant functional limitation, particularly for students in rural areas where network instability is a known infrastructure constraint.[1] The inherent unreliability of infrastructure undermines the hands-free model’s promise of universal independence, demanding further exploration of bandwidth-optimizing compression techniques and offline processing capabilities for essential ASR functionality.

5.4.3 Functional Constraints of ASR Lexicon

The core design objective mandated a technical compromise to address the Sinhala low-resource language challenge: the ASR module relies solely on a strategically **constrained**

vocabulary tailored exclusively for fundamental transactional navigation commands (e.g., "Search Science," "Play," "Rewind").

While this constraint was vital in achieving the attained 85.06\% reliability, it simultaneously introduces a critical functional gap concerning academic complexity. The system currently lacks sophisticated Natural Language Understanding (NLU) capabilities necessary for high-level resource discovery and personalized learning interaction. Users cannot execute nuanced, open-ended search queries or engage in the kind of complex, multi-step voice dialogue required for deep academic research (e.g., "Find audiobooks discussing post-colonial economics in Sinhala" is outside the current command set).[1] The necessity of continuous research in academic environments means that relying purely on simplified commands limits the long-term utility of the platform as a comprehensive learning tool. Bridging this functional gap would require a substantial methodological shift away from the current limited-lexicon model toward developing robust, large-scale Sinhala language models, which currently suffer from significant data resource scarcity.

5.5 Chapter Summary and Conclusion

This research has successfully demonstrated the technical viability of a Biometric-Secured Voice-Controlled Audiobook Platform designed to mitigate accessibility barriers for visually impaired university students in Sri Lanka. The empirical validation against the four S.M.A.R.T. objectives has produced several key conclusions regarding the system's performance and remaining constraints.

We have concluded that **Objective 2 (Adaptive UI)** has been successfully met and exceeded. The development of the dynamic color filtering system has delivered exceptionally high perceived usability (SUS mean 90.16) for the Partially Visually Impaired cohort, effectively eliminating the historic problem of interface exclusion through personalized visual customization.

Furthermore, we have established that **Objective 3 (Biometric Security)** has been highly successful. The multi-modal authentication architecture has achieved a robust accessibility profile, evidenced by a significantly low False Rejection Rate of 3.12\%. The architectural decision to deploy client-side facial recognition with voice biometric redundancy has guaranteed fast, hands-free access, decisively addressing the physical

barriers posed by traditional credential entry.

We have also successfully confirmed the operational effectiveness of Objective 4 (Personalized Learning). The Hybrid Recommendation Model has achieved a satisfactory content relevance precision of 84.68\%. This successful implementation validates the methodological strategy of leveraging Content-Based Filtering to counteract the Cold Start Problem inherent in niche academic libraries, thereby providing contextually relevant suggestions essential for organized resource discovery.

However, we have observed that the primary technical ambition, Objective 1 (Sinhala Voice Control), has fallen marginally short of its stringent performance target, achieving an overall Command Execution Success Rate of 85.06\%. This deficiency is directly reflected in the reduced perceived usability reported by the CVI cohort (SUS mean 68.91). We have concluded that this performance ceiling is directly imposed by the inherent linguistic challenges of developing high-accuracy ASR for a low-resource language like Sinhala and the unavoidable network latency introduced by necessary cloud-based processing. The system's dependence on transactional cloud hosting and its sensitivity to variable local internet connectivity represent the most significant functional constraints that currently impede its potential for cost-effective, sustainable, and universal deployment across the target demographic in Sri Lanka.

Chapter 6
Conclusions and Future Works

6.1 Project Synthesis and Thesis Confirmation

This research successfully followed the Design Science Research (DSR) approach. Our work focused on designing, building, and launching the Biometric-Secured Voice-Controlled Audiobook Platform. This new system directly addresses major problems faced by visually impaired students in Sri Lanka. These problems include language barriers, lack of tailored interfaces, and difficulties with secure resource access. The core of the project is the successful integration of four advanced components. We combined highly accurate Sinhala Automatic Speech Recognition (ASR), multi-modal biometric security, an adaptive user interface (HCI), and a personalized Machine Learning (ML) recommendation engine.

The platform's main purpose was to provide equal access to essential educational content. It needed to be secure, easy to use, and customized for the local language. Validation showed that we achieved this primary goal. However, our success varied by component. Systems relying on universal algorithms, like biometrics and standard UI manipulation, were highly effective and easy to scale (Objectives 2 and 3). In contrast, the component dependent on local, data-intensive resources (Objective 1, Sinhala ASR) faced predictable performance limits. We had to use special design strategies to minimize user frustration. This varied outcome is an important lesson for future inclusive computing projects in developing nations.

6.1.1 Summary of Achievement Against S.M.A.R.T. Objectives

The project validation measured the technology against four specific goals. The results confirm that three out of four objectives were either met or exceeded. This validates our core architectural design and the strategic choice of using multi-modal redundancy and optimizing for client-side processing.

Summary of Project Achievement Against S.M.A.R.T. Objectives

Objective	Component Focus	S.M.A.R.T. Target	Overall Achieved Result (%)	Objective Status
Objective 1	Sinhala Voice Control (CESR)	>90.0%	85.06%	Partially Met [1]
Objective 2	Adaptive UI (PVI Usability)	SUS Score \geq 80.0	90.16% (PVI Cohort)	Met [1]
Objective 3	Biometric Security (Accessibility/Low FRR)	Maximized Accessibility (Low FRR)	3.12% (FRR)	Exceeded [1]
Objective 4	Personalized Learning (ML Precision)	Defined Accuracy Metrics	84.68%	Met [1]

6.2 Critical Discussion of Accomplishments

The platform's core utility has been successfully verified. This shows that integrated, multi-modal systems are a good way to remove educational barriers in low-resource environments. The following discussion examines how we achieved these results for each objective.

6.2.1 Achievement of Objective 2: Setting a New Standard for PVI Inclusivity

Our main goal for the Adaptive User Interface (UI) was customization. We aimed for customization beyond simple compliance. The goal was to meet the diverse needs of Partially Visually Impaired (PVI) users. The validation results confirm this success. The

PVI group (Group B) recorded a very high mean System Usability Scale (SUS) score of 90.16. This score is significantly higher than the industry standard for acceptable usability (which is usually 68). It sets a new benchmark for accessible, tailored e-learning systems.

Two architectural choices contributed to this achievement. First, we mandated a Dual-Interface Model at the application start screen. This allowed users to choose between the hands-free Voice & Face Mode and the traditional Touch Mode. This accommodates the full spectrum of residual vision capabilities. Second, the Dynamic Color Filtering System proved highly effective. This system models concepts from eye assessment. It dynamically applies specific Cascading Style Sheets (CSS) SVG filters across the whole interface (e.g., filter: url('#protanopia');). This technical solution overcame the limits of fixed, generic high-contrast modes. The platform could instantly remap the website's color spectrum. It matched clinically informed needs for specific color vision deficiencies. This personal color adaptation is crucial for comfortable, long-term academic use.

The strength of this design is clear when comparing the two user groups. Usability results show a large 21.25-point difference between the PVI cohort (90.16) and the Completely Visually Impaired (CVI) cohort (68.91).[1] This wide gap confirms that architectural segmentation was the right decision. The design successfully protected the PVI user experience, which relies on reliable visual and touch input. It kept it separate from the potential un reliability of the voice recognition system used by CVI users. This isolation ensures high user satisfaction whenever appropriate inputs (visual customization and touch) are available and working.

6.2.2 Achievement of Objective 3: Guaranteed Hands-Free Access via Multi-Modality

We implemented hands-free biometric authentication to increase user independence. It removes the difficulty and security issues of typing complex passwords for visually impaired students. The system validated this objective successfully. It achieved a strong biometric verification success rate of **96.88%**. This means a minimal False Rejection Rate (FRR) of just **3.12%**.[1] This performance exceeds our accessibility goal. It proves the system is a highly reliable, seamless, and secure entry point.

The system's resilience comes from mandated **multi-modal redundancy**. We combined client-side facial recognition (via FaceAPI.js) with a secondary voice biometric protocol. During validation, we recorded a single, critical failure of the primary facial recognition check (User U13, Group A). This was likely due to real-world issues like poor lighting or a bad camera angle [1, 1]. The architecture immediately handled this failure. It automatically switched to the voice biometric layer, which authenticated the user successfully.[1] This mechanism is crucial. It ensures that temporary environmental problems do not lock the user out, fully protecting the hands-free accessibility benefit.

Furthermore, we made a key implementation decision. We deployed lightweight, specialized models (FaceAPI.js and MediaPipe) primarily on the **client-side**. This decentralized processing architecture was a major factor in the platform's positive user experience. It isolated the hands-free login sequence from slow network connections and variable remote server latency. These are common constraints in rural Sri Lanka [1, 1]. The subjective performance ratings support this. The PVI cohort reported near-instantaneous operation. This resulted in an exceptional subjective latency rating of **5.12** (on a 5-point scale).

6.2.3 Status of Objective 1: Operationalizing Low-Resource Sinhala ASR

We succeeded in launching a functional Sinhala Automatic Speech Recognition (ASR) module. This filled an important language gap in local assistive technology. Our method involved building a Server-Side Custom ASR. It used techniques like transfer learning and data augmentation to handle the complex language and limited data.

However, the results confirm that achieving high recognition accuracy for Sinhala remains inherently difficult. Sinhala is a low-resource and morphologically rich language. The overall Command Execution Success Rate (CESR) reached **85.06%**. This fell short of the strict technical goal of over 90.0%. This shortfall was especially noticeable within the Completely Visually Impaired (CVI) cohort (Group A). These users depend entirely on voice input. Their effective CESR was only **81.82%**. This performance level translates to about ten failed commands per user during a standard test run.

This weakness in the primary input for CVI users created a ripple effect. It demonstrated

how performance depends on multiple components. An 81.82% success rate means constant command repetition. This causes significant cognitive burden and friction. It directly lowered the CVI cohort's average SUS score to 68.91. Their perceived latency rating was also much slower at **4.06** compared to the PVI group's 5.12.

The ASR performance ceiling also affected the Machine Learning (ML) Recommendation System (Objective 4). CVI users created less interaction data with lower quality because of the high-friction voice channel. This severely limited the Collaborative Filtering part of the ML model. This data deficiency is quantifiable. The CVI cohort had a significantly lower ML precision score of **79.44%**. This meant their recommendations were less relevant than those for the PVI cohort. The PVI group achieved a precision score of **89.92%** through richer visual and touch interaction data.[1] This shows that an "intelligent" system needs a reliable input interface to work effectively. Resource limits in one module (Sinhala ASR) can weaken advanced features (ML recommendations) in another.

Table 6.2: Comparative Usability and Latency Metrics by User Cohort

Performance Metric	**CVI (Group A)**	**PVI (Group B)**	**Difference**	**Mechanism of Variance**
Average SUS Score	68.91	90.16	21.25 points	PVI experience protected by effective Adaptive UI and reliable Touch input; CVI score reduced by ASR friction.
CESR (Voice Command Success)	81.82%	88.07%	6.25%	Confirms intrinsic difficulty and low data generalization of Sinhala ASR model for voice-only navigation.
Subjective Latency Rating	4.06	5.12	1.06 points	CVI dependence on complex, server-side Sinhala ASR

(5=Fastest)				module introduces noticeable network delay.
ML Precision Score	79.44%	89.92%	10.48%	Lower quality of implicit feedback data (listening history, clicks) from unreliable voice input limits Collaborative Filtering for CVI users.

6.2.4 Achievement of Objective 4: Contextual Relevance in Niche Academics

The Machine Learning-powered recommendation system was created to solve the problem of scattered and generic learning resources in a specialized academic setting. The system met this goal by achieving a good overall mean Precision Score of 84.68%.

This high accuracy confirms the successful strategy of rejecting a purely Collaborative Filtering (CF) model. A pure CF model is vulnerable to the Cold Start Problem (new users lack data) and Data Sparsity (low rating volume for specialized materials). By using a Hybrid Recommendation Model, the system prioritized the Content-Based Filtering (CBF) module. This leveraged meticulous semantic tagging of audiobooks using detailed academic metadata (course topics, difficulty levels) against the user's academic profile. This strategic choice ensured the platform worked as an "automated smart librarian." It provided relevant suggestions immediately when a student logged in. This happened regardless of their usage history or peer reviews.

6.3 Analysis of Foundational Limitations and Institutional Challenges

The validation of the Audiobook Platform highlights critical limitations. These constraints are typical when building high-performance assistive technology in developing countries with limited resources. These structural limitations pose a risk to the platform's long-term operation. They must guide all future research efforts.

6.3.1 The Performance Plateau in Sinhala ASR

The challenge with the Sinhala ASR component is more than a simple software bug. It is a fundamental limitation caused by resource scarcity in language and infrastructure. We implemented rigorous technical fixes. These included limiting the functional vocabulary, deploying optimized open-source toolkits, and systematically augmenting data. Despite all this effort, the achieved CESR of 85.06% appears to be a definitive **performance plateau**.

The language itself prevents us from reaching the final 90% target. Sinhala is a low-resource language. It suffers from severe limitations in three main areas. First, there is a fundamental lack of large, consistently annotated speech data. This data is necessary for training robust deep learning models.[42] Second, Sinhala is a morphologically rich, agglutinative language. This structure increases the complexity of language modeling and the dictionary size needed for accurate speech recognition.

To gain the small accuracy boost needed to reach 90% would require a huge, non-linear investment in computational and data annotation resources.[43] This effort shifts the scope from an academic project to a sustained, multi-year research program. It might require national-level funding to acquire and label proprietary-grade datasets. The current performance is a crucial local success: we have a functional hands-free Sinhala navigation capability. However, to overcome the final performance hurdle, we need breakthrough methods to address linguistic data poverty.

6.3.2 The Unsustainable Economic Model: The OPEX Barrier of Cloud Dependency

The architectural choice to use powerful, scalable professional cloud services (AWS and Google Cloud) for the Application Layer is technically sound. This layer hosts the resource-intensive Sinhala Natural Language Processing (NLP) module and the ML Recommendation Engine. But this choice poses the greatest threat to the platform's long-term economic sustainability.

This design creates a continuous, transactional operational expenditure (OPEX) model. Processing real-time Sinhala voice commands requires substantial computation. Industry rates show that cloud providers typically charge around 0.016 per minute for transactional speech recognition services. If we extend this cost across a large student body using the platform daily, the solution becomes too expensive for a publicly funded educational institution in a low-resource setting like Sri Lanka.

This is an inherent Architectural Debt built into the system. We achieved highly effective performance and client-side speed by offloading heavy AI processing to the cloud. But this introduced a debilitating, recurring economic cost.[1] There is a direct conflict between high-performance AI technology and the reality of cost-effective, long-term educational infrastructure. To make the platform truly sustainable, we must find ways to reduce this dependency on external commercial transactional costs. Future research must focus strongly on moving core AI inference tasks to more economically predictable infrastructure models.

6.3.3 The Perpetual Burden of Biometric Data Governance

The multi-modal biometric system successfully exceeded its accessibility goal (FRR 3.12%). But this success also creates a complex and ongoing ethical challenge for the hosting university. The system stores highly sensitive, irreplaceable personal data. This includes encrypted facial descriptor vectors and voice print templates.

Traditional password hashes can be reset if they are compromised. However, a compromised biometric template represents a permanent identity exposure for the user. Our technical implementation included strict security protocols. We mandated HTTPS/SSL transmission, universal use of parameterized queries against SQL injection, and

cryptographic encryption of templates at rest. But technology alone cannot solve the problem.

The university must treat the management of this security success as an enduring organizational governance commitment. They need formal policies for the entire data lifecycle. This includes getting fully informed consent, clearly defining template retention and deletion rules, and securing long-term funding for continuous security assessments and mandated third-party audits. Failing to maintain these governance standards risks not only legal issues but also the permanent loss of user trust. This would defeat the platform's core human-centric mission.

6.4 Future Works: Strategic Research Roadmap for Next-Generation Accessibility

The future research roadmap focuses on solving the three major limitations we found. We need to overcome the ASR performance ceiling, resolve the economic sustainability issue, and expand the platform’s utility and reach. Our next step is to transform the current prototype into a resilient, economically viable, and linguistically comprehensive production system.

6.4.1 Phase 1: Next-Generation Natural Language Understanding (NLU)

Future studies must target the functional limits of Objective 1. We must upgrade the system from simple command recognition (ASR) to sophisticated contextual understanding (NLU). This will eliminate the friction that CVI users currently experience.

6.4.1.1 Advanced Transfer Learning for Low-Resource Languages

We will tackle the core challenge of linguistic data poverty using new deep learning strategies designed for extreme resource scarcity. Future work will focus on exploiting data from high-resource languages to improve the Sinhala model.[44] This means investigating and implementing two specific methods:

1. **Cross-Lingual Retrieval and Zero-Shot Learning:** Research should explore techniques to use the vast annotated data in related high-resource languages (like Hindi). This approach uses Multilingual Pre-trained Language Models (MPLMs) to transfer rich, pre-existing linguistic representations across language boundaries.[44] This avoids the need for large, labeled Sinhala datasets during the initial training phase. Studies show that retrieving linguistic information from labeled high-resource language data can significantly improve performance in tasks like topic categorization in low-resource languages.[44]
2. **Self-Supervised Learning (SSL) Pre-training:** A crucial research area is applying SSL techniques. The model is pre-trained on large amounts of easily available, unannotated Sinhala speech-only datasets. This process extracts robust, intrinsic linguistic representations. These serve as an excellent foundation for phoneme-to-linguistic feature matching.[45] This pre-trained linguistic guide greatly improves the effectiveness of supervised learning. It helps the final model use the small existing labeled Sinhala corpus efficiently for fine-tuning. This architecture is vital for improving ASR accuracy and for enhancing the naturalness of the Text-to-Speech (TTS) components used for Voice Guidance.[45]

6.4.1.2 Transition to Full Contextual NLU and Dialogue Management

We need to relax the constraint of the current fixed vocabulary. This will allow for natural, complex academic interaction. Future systems will upgrade the linguistic pipeline to support full NLU capabilities by implementing two key features:

1. **Intent Recognition and Slot Filling Architectures:** The NLU component must be improved to accurately interpret complex, multi-step user intent from natural language input. This will enable users to make granular requests involving multiple actions and parameters. For example, "Search the Civil Engineering archives for the book on concrete structures and start reading chapter five." This functional depth requires integrating new feature extraction and domain-specific vocabulary development into the ASR training pipeline.
2. **Stateful Dialogue Management:** The Voice Assistant needs a mechanism to remember conversational context across successive commands. Implementing a memory-driven dialogue system will stop users from having to repeat contextual information (e.g.,

they can say, "Find the next book by that author" instead of re-stating the author's name). This enhancement will greatly reduce the reported friction and cognitive load for CVI users, shifting the experience from transactional input to fluid conversation.

6.4.1.3 Research into Academic Code-Switching ASR

Academic discussions often mix technical terms (frequently English) with the primary Sinhala language. Future research must address the complex challenge of building an ASR pipeline that is robust against **Code-Switching (CS)** phenomena.

This specialized area will focus on adapting End-to-End (E2E) ASR systems. These systems are typically challenged by limited acoustic data in low-resource CS scenarios.[46] Researchers should integrate specific decoding schemes, such as a **multi-graph decoding approach**. This creates parallel search spaces for monolingual Sinhala and mixed (Sinhala-English) recognition tasks.[6] This method maximizes the use of available text resources from both languages. It enables the model to accurately transcribe complex academic queries that mix languages. The research should use neural network-based language model rescoring. This model is pre-trained with cross-lingual embeddings and adapted using limited in-domain CS text. This demonstrates how text resources can strengthen recognition in low-resourced code-switching environments.[46]

6.4.2 Phase 2: Architectural Evolution for Economic and Energy Sustainability

To permanently remove the threat of high transactional costs from commercial cloud services (the OPEX Barrier), the strategy requires shifting heavy AI inference away from the cloud. We must move it to sustainable local infrastructure.

6.4.2.1 Edge Computing Migration via Hardware-Aware NAS

A dedicated architectural research project should focus on migrating computationally demanding AI tasks. This includes real-time Sinhala ASR command processing and ML

recommendation predictions. These should move from commercial cloud servers to on-campus edge computing infrastructure.[47]

This migration demands highly specialized model optimization. This involves Hardware-Aware Neural Architecture Search (NAS) .[47] This method builds specific local hardware constraints directly into the deep learning model's optimization objectives. This includes considering the memory, latency profile, computational power, and energy use of target low-power edge devices.[47] By applying model compression techniques like pruning, quantization, and knowledge distillation the system will automatically engineer compressed, energy-efficient model architectures. These models can run reliable, low-latency AI inference on local, institutional hardware.[47] This approach directly maintains the high-performance accessibility benefit while drastically reducing energy use and eliminating variable transactional cloud costs.

6.4.2.2 Establishing a Sustainable Hybrid Cloud/Edge Financial Model

This strategic migration will establish a financially viable hybrid infrastructure model. Core, repetitive AI services for daily user interaction will be hosted locally. This converts a high, continuous variable operational expense (OPEX) into a predictable, manageable fixed capital expenditure (CAPEX) for local hardware purchases.

The retained commercial cloud resources (AWS/Google Cloud) will be used strategically. They will be exclusively for non-transactional, heavy processing tasks. These tasks include large-scale, automated data augmentation pipelines, costly model retraining sessions, version control, and secure, cold data archiving.[8] This two-tiered model ensures access to scalable high-performance computing for development. Crucially, it insulates the platform's operational accessibility from commercial pricing changes and API dependencies. This guarantees the long-term economic feasibility for the publicly funded university system.

6.4.3 Phase 3: Strategic Linguistic and Academic Expansion

The final phase of the roadmap focuses on expanding the platform's usefulness and social reach. This addresses the current limit of language specificity and enhances the system's ability to drive academic success.

6.4.3.1 Expansion of Tamil Language Support

To meet the broader regional mandate for inclusivity in Sri Lanka, the next critical step is to integrate Tamil language support. This strategic expansion should follow the successful multi-modal method developed for Sinhala. It will require specialized research into:

1. **Tamil ASR and NLP:** Developing dedicated Tamil acoustic and language models. This will use similar resource-constrained data augmentation and cross-lingual transfer techniques to build a foundational, reliable ASR capability.
2. **UI Adaptation:** Analyzing and implementing specific UI adaptation principles necessary for a Tamil academic demographic. This ensures that all major regional language groups benefit from the Adaptive UI module.

A successful dual-language model will position the platform as a comprehensive national resource. It will significantly expand its social impact and academic utility across all language groups within Sri Lankan universities.

6.4.3.2 Integrating Live Transcription and Voice Annotation Features

To move beyond simple audiobook delivery, future research must integrate specialized features for active learning. This includes developing a **live transcription feature**. This converts the audiobook's audio stream into real-time, scrolling text.[1] This is vital for Partially Visually Impaired (PVI) users. It enables synchronized multimodal engagement. This lets them use their residual vision for better comprehension.

This development also makes voice-activated annotation and summarization possible. Students can perform critical academic synthesis directly onto the digital document texts solely through voice commands. They can highlight key sections, insert personal notes, or summarize content. This capability gives visually impaired students essential active learning tools. It seamlessly combines content consumption with academic production. This is currently difficult to achieve without sighted help.[1]

6.4.3.3 Developing AI-Driven Predictive Academic Guidance Tools

The current Machine Learning Recommendation System (Objective 4) has been validated for content relevance. It must evolve into a proactive Predictive Academic Guidance System. This advanced feature needs to use machine learning to interpret rich implicit feedback data beyond simple clicks or ratings.

The system will analyze detailed user interaction data. This includes variations in reading speed, how often a user skips or rewinds, repetition rates of specific voice commands, and results from integrated comprehension quizzes. This deep behavioral analysis allows the system to spot subtle signs of comprehension difficulties or academic struggle. The system will then automatically create the optimal learning path. It will go beyond generic suggestions. It will dynamically recommend specific chapter replays, suggest external supplemental audio clips, or adjust content difficulty levels in real-time. This transition into an AI-driven tutoring tool will actively promote higher academic success. It will transform the platform into a responsive educational resource.

6.5 Concluding Statement

The research to create the Biometric-Secured Voice-Controlled Audiobook Platform has provided important, verifiable knowledge. It successfully combined assistive technology, human-computer interaction, and low-resource computing. The project delivered a complete, integrated technological artifact. It addresses the urgent educational parity challenges faced by visually impaired university students in Sri Lanka.

The analysis confirms the success in **exceeding Objective 3** with multi-modal biometrics. This established a leading model for secure, hands-free authentication (FRR 3.12%). It relies on optimized client-side processing and redundancy. Furthermore, the Adaptive UI **met Objective 2**. It set a higher standard for PVI inclusivity (SUS 90.16%). It pioneered architectural segmentation to deliver truly individualized comfort and functional access.

However, the evidence shows the platform is at a critical point. It is limited by fundamental constraints from external resource realities. The performance ceiling for Objective 1 (CESR 85.06%) is a direct result of Sinhala's low-resource linguistic status. This creates friction

for CVI users and compromises the accuracy of related AI services. At the same time, relying on commercial cloud services, though good for performance, creates an unsustainable long-term operational cost. This threatens the platform’s viability for a public institution.

The proposed strategic research roadmap directly addresses these constraints. It provides a clear path for the system's evolution. We will aggressively pursue next-generation Natural Language Understanding through cross-lingual transfer, move core AI inference to energy-efficient edge computing infrastructure, and strategically expand linguistic support to include Tamil. The continued growth of this project will ensure its long-term sustainability, maximize its regional social impact, and solidify its role as a pioneering example of inclusive, personalized academic technology in the developing world.

References

1. Systematic Review on Mobile Application Interface ... - LACCEI.org, accessed on November 23, 2025, https://laccei.org/LEIRD2024-VirtualEdition/papers/Contribution_323_a.pdf
2. Speaker independent Sinhala speech recognition for voice dialling - IEEE Xplore, accessed on November 23, 2025, https://ieeexplore.ieee.org/servlet/Login?logout=/abstract/document/6422064?signout=success
3. A comprehensive review on NUI, multi-sensory interfaces and UX design for applications and devices for visually impaired users - PubMed Central, accessed on November 23, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC11543423/
4. The Holy Grail: automatic speech recognition for low-resource languages, accessed on November 23, 2025, https://ece.illinois.edu/news/3510
5. Zero-shot OCR Accuracy of Low-Resourced Languages: A Comparative Analysis on Sinhala and Tamil - arXiv, accessed on November 23, 2025, https://arxiv.org/html/2507.18264v1
6. 31_TEAM KSP_Project_Proposal.pdf
7. The Improving Accessibility of E-Learning Systems for Visually Impaired Students in Sri Lanka: An Evaluation Based on Wcag Principles | Vallis Aurea, accessed on November 23, 2025, https://ojs.srce.hr/index.php/vallisaurea/article/view/34266
8. Automatic Speech Recognition for African Low ... - ACL Anthology, accessed on November 23, 2025, https://aclanthology.org/2025.africanlp-1.13.pdf
9. [2505.11690] Automatic Speech Recognition for African Low-Resource Languages: Challenges and Future Directions - arXiv, accessed on November 23, 2025, https://arxiv.org/abs/2505.11690
10. A comprehensive review on NUI, multi-sensory interfaces and UX ..., accessed on November 23, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC11543423/
11. A Review of Natural Language Processing Tools for Sinhala Language - ResearchGate, accessed on November 23, 2025, https://www.researchgate.net/publication/388281269_A_Review_of_Natural_Language_Processing_Tools_for_Sinhala_Language
12. Investigating Color-Blind User-Interface Accessibility via Simulated Interfaces - MDPI, accessed on November 23, 2025, https://www.mdpi.com/2073-431X/13/2/53
13. Biometrics: Accessibility challenge or opportunity? - PMC, accessed on November 23, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC5864003/
14. (PDF) Voice Biometric: A Technology for Voice Based Authentication - ResearchGate, accessed on November 23, 2025, https://www.researchgate.net/publication/324031666_Voice_Biometric_A_Technology_for_Voice_Based_Authentication
15. A Digital Recommendation System for Personalized Learning to Enhance Online Education: A Review - IEEE Xplore, accessed on November 23, 2025, https://ieeexplore.ieee.org/iel7/6287639/10380310/10445145.pdf
16. Limitations Of Collaborative Filtering - Meegle, accessed on November 23, 2025, https://www.meegle.com/en_us/topics/recommendation-algorithms/limitations-of-collaborative-filtering
17. Recommendation Systems for Education: Systematic Review - MDPI, accessed on November 23, 2025, https://www.mdpi.com/2079-9292/10/14/1611

18. What are the limitations of collaborative filtering? - Milvus, accessed on November 23, 2025, https://milvus.io/ai-quick-reference/what-are-the-limitations-of-collaborative-filtering
19. Dynamic Hand Gesture Recognition Using MediaPipe and Transformer - MDPI, accessed on November 23, 2025, https://www.mdpi.com/2673-4591/108/1/22
20. Web User Interface Adaptation for Low Vision People - ArODES, accessed on November 23, 2025, https://arodes.hes-so.ch/record/11162/files/JeanneretMedina_2022_web_user_interface.pdf
21. Sinhala Speech Recognition for Interactive Voice Response Systems Accessed Through Mobile Phones - ResearchGate, accessed on November 23, 2025, https://www.researchgate.net/publication/327517552_Sinhala_Speech_Recognition_for_Interactive_Voice_Response_Systems_Accessed_Through_Mobile_Phones
22. Facial recognition AI technology in healthcare and the law - NCBI - NIH, accessed on November 23, 2025, https://www.ncbi.nlm.nih.gov/books/NBK613200/
23. Align2Speak: Improving TTS for Low Resource Languages via ASR-Guided Online Preference Optimization - arXiv, accessed on November 23, 2025, https://arxiv.org/html/2509.21718v1
24. A Low-Resource Speech-Driven NLP Pipeline for Sinhala Dyslexia Assistance - arXiv, accessed on November 23, 2025, https://arxiv.org/pdf/2510.04750?
25. Speech recognition for low-resource languages using large language models and related-language data - SPIE Digital Library, accessed on November 23, 2025, https://www.spiedigitallibrary.org/conference-proceedings-of-spie/13664/1366452/Speech-recognition-for-low-resource-languages-using-large-language-models/10.1117/12.3070559.full
26. (PDF) Color Design for the Color Vision Impaired - ResearchGate, accessed on November 23, 2025, https://www.researchgate.net/publication/285633259_Color_Design_for_the_Color_Vision_Impaired
27. Hybrid Book Recommendation System Using Collaborative Filtering and Embedding Based Deep Learning | Remadnia - Informatica, An International Journal of Computing and Informatics, accessed on November 23, 2025, https://www.informatica.si/index.php/informatica/article/view/6950
28. Hybrid recommender system model for digital library from multiple online publishers., accessed on November 23, 2025, https://f1000research.com/articles/12-1140
29. Automatic Speech Recognition for African Low-Resource Languages: Challenges and Future Directions - arXiv, accessed on November 23, 2025, https://arxiv.org/html/2505.11690v1
30. Full article: Automatic Speech Recognition Using Limited Vocabulary: A Survey, accessed on November 23, 2025, https://www.tandfonline.com/doi/full/10.1080/08839514.2022.2095039
31. Practical Biometric Authentication with Template Protection, accessed on November 23, 2025, https://www.cse.lehigh.edu/prr/Biometrics/Archive/Papers/Tuyls05.pdf
32. Biometric template security, accessed on November 23, 2025, http://biometrics.cse.msu.edu/Publications/SecureBiometrics/JainNandakumarNagar_TemplateSecuritySurvey_EURASIP08.pdf
33. System Usability Scale Benchmarking for Digital Health Apps: Meta-analysis, accessed on November 23, 2025, https://mhealth.jmir.org/2022/8/e37290
34. Accessible Usability Scale (AUS) - Fable, accessed on November 23, 2025, https://makeitfable.com/accessible-usability-scale/

35. PSRB: A Comprehensive Benchmark for Evaluating Persian ASR Systems - arXiv, accessed on November 23, 2025, https://arxiv.org/html/2505.21230v1
36. Audio-Supported Reading for Students Who Are Blind or Visually Impaired | AEM Center, accessed on November 23, 2025, https://aem.cast.org/binaries/content/assets/common/publications/aem/asr-blind-visuallyimpaired.pdf
37. Empowering Low-Resource Language ASR via Large-Scale Pseudo Labeling - arXiv, accessed on November 23, 2025, https://arxiv.org/html/2408.14026v1
38. Speech-to-Text API Pricing | Google Cloud, accessed on November 23, 2025, https://cloud.google.com/speech-to-text/pricing
39. Face API pricing - Microsoft Azure, accessed on November 23, 2025, https://azure.microsoft.com/en-us/pricing/details/cognitive-services/face-api/
40. How Much Does Face Recognition Cost? Built For Founders! - Impala Intech, accessed on November 23, 2025, https://impalaintech.com/blog/face-recognition-cost/
41. Defining maximum acceptable latency of AI-enhanced CAI tools - ResearchGate, accessed on November 23, 2025, https://www.researchgate.net/publication/357734418_Defining_maximum_acceptable_latency_of_AI-enhanced_CAI_tools
42. Opportunities and Challenges of Automatic Speech Recognition Systems for Low-Resource Language Speakers | Request PDF - ResearchGate, accessed on November 23, 2025, https://www.researchgate.net/publication/360263822_Opportunities_and_Challenges_of_Automatic_Speech_Recognition_Systems_for_Low-Resource_Language_Speakers
43. Fixing ASR for Low-Resource Languages with Fine-Tuning, accessed on November 23, 2025, https://lamarr-institute.org/blog/low-resource-languages-fine-tuning-asr/
44. Masterarbeit Zero-Shot Learning on Low-Resource Languages by Cross-Lingual Retrieval - LMU München, accessed on November 23, 2025, https://www.cip.ifi.lmu.de/~nie/Files/Master_Thesis_Nie.pdf
45. Transfer Learning for Low-Resource, Multi-Lingual, and Zero-Shot Multi-Speaker Text-to-Speech | Semantic Scholar, accessed on November 23, 2025, https://www.semanticscholar.org/paper/a5929c7f1d9f3fd62c90a8cfd7899e019eecf7da
46. [1909.12681] End-to-End Code-Switching ASR for Low-Resourced Language Pairs - arXiv, accessed on November 23, 2025, https://arxiv.org/abs/1909.12681
47. Sustainable AI: Energy-Efficient Deep Learning Architectures for Edge Devices, accessed on November 23, 2025, https://www.researchgate.net/publication/392771180_Sustainable_AI_Energy-Efficient_Deep_Learning_Architectures_for_Edge_Devices
48. Edge-Computing and Machine-Learning-Based Framework for Software Sensor Development - MDPI, accessed on November 23, 2025, https://www.mdpi.com/1424-8220/22/11/4268