
DKB Documentation

DKB team

Mar 28, 2019

CONTENTS:

1	pyDKB package	1
1.1	Quickstart guide	1
1.2	Subpackages	3
2	Indices and tables	23
	Python Module Index	25
	Index	27

PYDKB PACKAGE

Common library for Data Knowledge Base Dataflow stages development.

Dataflow ETL process (extract-transform-load) for populating internal DKB storages and keeping them up to date

Dataflow stage Logical step of ETL process, implemented as standalone executable program (worker)

Dataflow stages are standalone programs, but can be combined into a pipeline by means of Kafka-based supervising program. For details about program compatibility with the supervisor please check documentation for the Metadata Integration Topology Management System (MInT MS) workers¹. Worker program can be written in any language; pyDKB is intended to simplify this process for Python.

Warning: There are three types of stages corresponding three types of ETL operations: *source connector* (data extraction), *processor* (transformation) and *sink connector* (load to internal DKB storage). Currently pyDKB library can be used only for *processor* stages, but in future versions *connector* stages will also be supported.

1.1 Quickstart guide

To create simple processor stage application first decide input and output data format. In following examples we will work with data in JSON format (for the full list of supported formats check pyDKB.dataflow.messages section of this documentation).

Now let's start writing example processor `welcome.py` and implement message handler – functional part of the stage (operations to be performed on data flow units):

```
from pyDKB.dataflow.messages import JSONMessage

def my_process(stage, message):
    """ Single message processing. """
    input_data = message.content()
    name = input_data.get('name')
    if name:
        out_data = {'message': "Welcome, %s!" % name}
        out_message = JSONMessage(out_data)
        stage.output(out_message)
    return True
```

Function must take two arguments: `stage` (stage context object) and `message` (input message, which should be transformed by our stage). Message is a smallest data unit in the data flow running through the processor, and every message is to be processed independently of previous or following ones. `message.content()` and

¹ WIP

`JSONMessage(out_data)` statements are used to decode/encode message to/from Python `dict` object. Message, passed to the function, is taken from the input data flow; to write new message(s) to the output data flow, `stage.output(out_message)` is used. It can be used as many times as many output messages were generated (or once with the list of messages). In our example, messages without key 'name' will produce no output messages, so `stage.output()` will not be called at all. In terms of data flow it means that the input message is filtered out and will not reach the *sink connector*.

Boolean return value of `my_process()` indicates if the processing was successful or not. If processing failed (False is returned), produced output messages will be dropped to avoid loading sketchy information into the DKB storages.

Now as we have processing logic implemented, we need to turn it into fully functional application. Add following lines to `welcome.py`:

```
import sys
from pyDKB.dataflow.stage import JSONProcessorStage
from pyDKB.dataflow.messages import JSONMessage

def my_process(stage, message):
    <...function code...>

if __name__ == '__main__':
    stage = JSONProcessorStage()
    stage.process = my_process
    stage.parse_args(sys.argv[1:])
    stage.run()
```

First we create stage object and indicate that input and output message format is JSON: `stage = JSONProcessorStage()` (for full list of processors check [pyDKB.dataflow.stage package](#) section of this documentation); then set stage processing function to our function `my_process()`, parse command line arguments (`stage.parse_args(sys.argv[1:])`) and start the stage execution.

Easy, right?

It's time to run our application. Create input data sample `input.ndjson` with following lines:

```
{ "name": "James", "city": "New York" }
{ "user": "Jonathan", "role": "support" }
{ "name": "John Smith" }
```

and type:

```
$ python welcome.py --dest s input.ndjson
{"message": "Welcome, James!"}
{"message": "Welcome, John Smith!"}
```

`--dest s` indicates that output destination is (s)tdout (default destination is file). For full information about modes in which the stage application can be used, run `python welcome.py -h`.

That's it, your first application is ready to be integrated into an ETL process as data processing node. For details about ETL process creation check *MInT Supervisor*² documentation.

² WIP

1.2 Subpackages

1.2.1 pyDKB.common package

Common modules.

Submodules

pyDKB.common.Type module

Abstract class for type definitions.

Example

```
>>> myType = Type("Orange", "Apple")
>>> myType.add("Plum")
>>> t = myType.Orange
>>> if t == myType.Orange:
...     print "Orange!"
... elif t == myType.member("Apple"):
...     print "Apple!"
...
Orange!
>>> if not myType.member("Walnut"):
...     print "Wrong type!"
...
Wrong type!
```

class pyDKB.common.Type.Type(*args)

Bases: object

Abstract class for type definitions.

Member names (*str*) are passed to the constructor as positional arguments.

add(*name*)

Add member.

Parameters *name* (*str*) – name of the member to be added

hasMember(*val*)

Check if the member exists (by value).

Parameters *val* (*int*) – member to be checked

Returns True/False

Return type bool

member(*name*)

Check if the member exists (by name).

Parameters *name* (*str*) – name to be checked

Returns member value or False if member does not exist

Return type int, bool

memberName(*val*)

Return string name of the member.

Parameters `val` (*int*) – member to retrieve name for

Returns member name of False if member does not exist

Return type str, bool

pyDKB.common.custom_readline module

Implementation of “readline”-like functionality for custom separator.

Todo: make import of `fcntl` (or of this module) optional to avoid errors when library is used under Windows.

`pyDKB.common.custom_readline.custom_readline(f, newline)`

Read lines with custom line separator.

Construct generator with readline-like functionality: with every call of `next()` method it will read data from `f` until the `newline` separator is found; then yields what was read.

Warning: the last line can be incomplete, if the input data flow is interrupted in the middle of data writing.

To check if iteration is not over without reading next value, one may `send(True)` to the generator: it will return `True` if there is another message to yield or raise `StopIteration` if nothing left.

Parameters

- `f` (*file*) – readable file object
- `newline` (*str*) – delimiter to be used instead of `\n`

Returns iterable object

Return type generator

Todo:

- make last “line” handling more strict: no `newline == no line`;
 - rethink function name (as “line” is actually a “message”);
 - move functionality to `pyDKB.dataflow.communication`¹ submodule)
-

pyDKB.common.exceptions module

Definition of common modules exceptions

exception `pyDKB.common.exceptions.HDFSException`

Bases: `exceptions.RuntimeError`

Base Exception for HDFS module.

¹ <https://github.com/PanDAWMS/dkb/pull/129>

pyDKB.common.hdfs module

Utils to interact with HDFS.

`pyDKB.common.hdfs.File` (*fname*)

Get and open temporary local copy of HDFS file

Return value: open file object (TemporaryFile).

`pyDKB.common.hdfs.basename` (*path*)

Return file name without path.

`pyDKB.common.hdfs.check_stderr` (*proc, timeout=None, max_lines=1*)

Wait till the end of the subprocess and send its STDERR to STDERR.

Output only MAX_LINES of the STDERR to the current STDERR; if MAX_LINES == None, output all the STDERR.

Return value is the subprocess' return code.

`pyDKB.common.hdfs.dirname` (*path*)

Return dirname without filename.

`pyDKB.common.hdfs.getfile` (*fname*)

Download file from HDFS.

Return value: file name (without directory)

`pyDKB.common.hdfs.join` (*path, filename*)

Join path and filename.

`pyDKB.common.hdfs.listdir` (*dirname, mode='a'*)

List files and/or subdirectories of HDFS directory.

Parameters: *dirname* – directory to list *mode* – 'a': list all objects

'f': list files 'd': list subdirectories

`pyDKB.common.hdfs.makedirs` (*dirname*)

Try to create directory (with parents).

`pyDKB.common.hdfs.movefile` (*fname, dest*)

Move local file to HDFS.

`pyDKB.common.hdfs.putfile` (*fname, dest*)

Upload file to HDFS.

pyDKB.common.json_utils module

Utils to work with JSON (dict) objects.

`pyDKB.common.json_utils.nestedKeys` (*key*)

Transform STRING with nested keys into LIST.

Parameters:

STRING key – dot-separated list of nested keys. If a key contains dot itself, the key must be put between quotation marks.

`pyDKB.common.json_utils.valueByKey` (*json_data, key*)

Return value by a chain (list) of nested keys.

Parameters: *DICT json_data* – to search in **STRING key** – dot-separated list of nested keys

1.2.2 pyDKB.dataflow package

Dataflow organization utils.

Subpackages

pyDKB.dataflow.communication package

pyDKB.dataflow.communication

pyDKB.dataflow.communication.**Message** (*msg_type*)
Return class XXXMessage, where XXX is the passed type.

Subpackages

pyDKB.dataflow.communication.consumer package

Consumer submodule init file.

```
class pyDKB.dataflow.communication.consumer.ConsumerBuilder (config={})  
    Bases: object  
    Constructor for Consumer instance.  
    build (config={})  
        Return constructed consumer.  
    consumerClass = None  
    setSource (source)  
        Set data source for the consumer.  
    setType (Type)  
        Set message type for the consumer.
```

Submodules

pyDKB.dataflow.communication.consumer.Consumer module

pyDKB.dataflow.communication.consumer.Consumer

```
class pyDKB.dataflow.communication.consumer.Consumer.Consumer (config={})  
    Bases: object  
    Data consumer implementation.  
    close ()  
        Close opened data stream and data source.  
    config = None  
    get_message ()  
        Get new message from current source.  
    Return values: Message object False (failed to parse message) None (all input sources are empty)
```

get_source_info()

Return current source info.

get_stream()

Get input stream linked to the current source.

Return value: InputStream None (no sources left to read from)

init_stream()

Init input stream.

log(message, level=3)

Output log message with given log level.

message_class()

Return message class.

message_type = None

next()

Return new Message, read from input stream.

reconfigure(config={})

(Re)initialize consumer with stage config arguments.

reset_stream()

Reset input stream to the current source.

set_message_type(Type)

Set input message type.

stream_is_readable()

Check if input data stream is readable.

Returns True – stream is initialized and not empty, False – stream is empty, None – stream is not initialized

Return type bool, NoneType

exception `pyDKB.dataflow.communication.consumer.Consumer.ConsumerException`

Bases: `pyDKB.dataflow.exceptions.DataflowException`

Dataflow Consumer exception.

pyDKB.dataflow.communication.consumer.FileConsumer module

`pyDKB.dataflow.communication.consumer.FileConsumer`

Data consumer implementation for common (static) files.

TODO: think about:

- updatable files
- pipes (better, from the point of StreamConsumer)
- round-robin (for updatable sources)
- ...

class `pyDKB.dataflow.communication.consumer.FileConsumer.FileConsumer(config={})`

Bases: `pyDKB.dataflow.communication.consumer.Consumer.Consumer`

Data consumer implementation for HDFS data source.

current_file = None

get_source()
Get nearest non-empty source (current or next).

get_source_info()
Return current source info.

input_filenames = None

next_source()
Reset \$current_file to the next non-empty file.

Return value: File descriptor of the new \$current_file None (no files left)

reconfigure (config={})
(Re)initialize consumer with Stage configuration.

source_is_readable()
Check if current source is readable.

Returns None – no source, False – source is empty / fully read, True – source is defined and is not empty

Return type bool, NoneType

pyDKB.dataflow.communication.consumer.HDFSConsumer module

pyDKB.dataflow.communication.consumer.HDFSConsumer

class pyDKB.dataflow.communication.consumer.HDFSConsumer.**HDFSConsumer** (config={})
Bases: *pyDKB.dataflow.communication.consumer.FileConsumer.FileConsumer*

Data consumer implementation for HDFS data source.

reconfigure (config={})
Configure HDFS Consumer according to the config parameters.

pyDKB.dataflow.communication.consumer.StreamConsumer module

pyDKB.dataflow.communication.consumer.StreamConsumer

Data consumer implementation for a single stream.

TODO: think about multiple streams (like a number of named pipes, etc). Perhaps, even merge this class with FileConsumer.

class pyDKB.dataflow.communication.consumer.StreamConsumer.**StreamConsumer** (config={})
Bases: *pyDKB.dataflow.communication.consumer.Consumer.Consumer*

Data consumer implementation for Stream data source.

fd = None

get_source()
Get Stream file descriptor.

get_source_info()
Return current source info.

next_source()

Return None.

As currently we believe that there is only one input stream

reconfigure (*config={}*)

(Re)configure Stream consumer.

pyDKB.dataflow.communication.producer package

Producer submodule init file.

class pyDKB.dataflow.communication.producer.**ProducerBuilder** (*config={}*)

Bases: object

Constructor for Producer instance.

build (*config={}*)

Return constructed producer.

message_type = None

producerClass = None

setDest (*dest*)

Set data destination for the producer.

setSourceInfoMethod (*src_info*)

Set method to get current source info.

setType (*Type*)

Set message type for the producer.

src_info = None

Submodules

pyDKB.dataflow.communication.producer.FileProducer module

pyDKB.dataflow.communication.producer.FileProducer

Data producer implementation for common (static) files.

TODO: think about:

- pipes (better, from the point of StreamProducer)
- multiple parallel dests
- ...

class pyDKB.dataflow.communication.producer.FileProducer.**FileProducer** (*config={}*)

Bases: *pyDKB.dataflow.communication.producer.Producer.Producer*

Data producer implementation for local file data dest.

close ()

Close opened files and remove temporary one.

close_file ()

Close current file.

config_dir (*config={}*)
Configure output directory.

current_file = **None**

default_dir ()
Get default directory name.

dirname (*dirname=None*)
Set/get preferable directory name.

ensure_dir ()
Ensure that current directory for output files exists.

file_info ()
Return output file metadata (name, directory, ...).

get_dest ()
Get destination file descriptor.

get_dest_info ()
Get current destination info.

get_dir ()
Get current directory for output files.

get_filename ()
Return filename, corresponding the source, or timestamp-based.

get_source_info ()
Set current data source, if any.

reconfigure (*config={}*)
(Re)configure producer according to the config hash.

reset_file ()
Resets current file according to the current source info.

Metadata include:

- fd – open file descriptor
- name – file name
- dir – directory name
- local_path – local path to the file

set_default_dir ()
Set default directory name.

subdir (*base_dir, sub_dir=""*)
Construct full path for \$subdir of \$base_dir.

pyDKB.dataflow.communication.producer.HDFSProducer module

pyDKB.dataflow.communication.producer.HDFSProducer

Data producer implementation for common (static) files in HDFS.

TODO: think about:

- pipes (better, from the point of StreamProducer)

- multiple parallel dests
- ...

class `pyDKB.dataflow.communication.producer.HDFSProducer.HDFSProducer` (*config*={})
 Bases: `pyDKB.dataflow.communication.producer.FileProducer.FileProducer`

Data producer implementation for HDFS data dest.

close_file ()
 Close current file and move it to HDFS.

config_dir (*config*={})
 Configure output directory.

ensure_dir ()
 Ensure that current directory for output files exists.

file_info ()
 Return output file metadata (name, directory, ...).

set_default_dir ()
 Set default directory name.

subdir (*base_dir*, *sub_dir*=")
 Construct full path for \$sub_dir of \$base_dir.

pyDKB.dataflow.communication.producer.Producer module

`pyDKB.dataflow.communication.producer.Producer`

class `pyDKB.dataflow.communication.producer.Producer.Producer` (*config*={})
 Bases: `object`

Data producer implementation.

close ()
 Close opened data stream and data dest.

config = `None`

drop ()
 Drop buffered messages.

eop ()
 Write EOP marker to the current dest.

flush ()
 Flush buffered messages to the current dest.

get_dest ()
 Return current destination.

get_dest_info ()
 Return current dest info.

get_stream (*actualize*=`True`)
 Get output stream linked to the current dest.

If \$actualize parameter set to `True`, will try to reset current stream destination; else will use last known destination or `None`.

init_stream()
Init output stream (without real destination).

log (*message*, *level*=3)
Output log message with given log level.

message_class()
Return message class.

message_type = None

reconfigure (*config*={})
(Re)initialize producer with stage config arguments.

reset_stream()
Reset input stream to the current dest.

set_message_type (*Type*)
Set input message type.

write (*msg*)
Put new message to the current dest (buffer).

exception `pyDKB.dataflow.communication.producer.Producer.ProducerException`
Bases: `pyDKB.dataflow.exceptions.DataflowException`
Dataflow Producer exception.

pyDKB.dataflow.communication.producer.StreamProducer module

`pyDKB.dataflow.communication.producer.StreamProducer`

Data producer implementation for a single stream.

TODO: think about multiple streams (like a number of named pipes, etc). Perhaps, even merge this class with `FileProducer`.

class `pyDKB.dataflow.communication.producer.StreamProducer.StreamProducer` (*config*={})
Bases: `pyDKB.dataflow.communication.producer.Producer.Producer`

Data producer implementation for Stream data dest.

fd = None

get_dest ()
Get Stream file descriptor.

get_dest_info ()
Return current dest info.

reconfigure (*config*={})
(Re)configure Stream producer.

pyDKB.dataflow.communication.stream package

`pyDKB.dataflow.communication.stream`

class `pyDKB.dataflow.communication.stream.StreamBuilder` (*fd*, *config*={})
Bases: `object`

Constructor for Stream object.


```

build (config={})
    Create instance of Stream.

message_type = None

setStream (stream)
    Set stream type: 'input' or 'output'.

setType (Type)
    Set message type for the Stream.

streamClass = None

class pyDKB.dataflow.communication.stream.Stream (fd=None, config={})
    Bases: object

    Abstract class for input/output streams.

    EOM = None

    close ()
        Close open file descriptors etc.

    configure (config)
        Stream configuration.

    get_fd ()
        Return open file descriptor or raise exception.

    log (message, level=3)
        Output log message with given log level.

    message_type ()
        Get type of the messages in the stream.

    reset (fd, close=True)
        Reset file descriptor in operation.

        Parameters fd – open file descriptor TODO: IOBase objects

        Returns previous file descriptor (or None)

    set_message_type (msg_type)
        Set type of the messages in the stream.

class pyDKB.dataflow.communication.stream.InputStream (fd=None, config={})
    Bases: pyDKB.dataflow.communication.stream.Stream.Stream

    Implementation of the input stream.

    get_message ()
        Get next message from the input stream.

        Return values: Message object False (failed to parse message) None (no messages left)

    is_readable ()
        Check if current input stream is readable.

        Returns None – not initialized, False – empty, True – not empty

        Return type bool, NoneType

    next ()
        Get next message from the input stream.

```

parse_message (*message*)

Verify and parse input message.

Retrun value: Message object False (failed to parse)

reset (*fd, close=True, force=False*)

Reset current stream with new file descriptor.

Overrides parent method to reset `__iterator` property.

class `pyDKB.dataflow.communication.stream.OutputStream` (*fd=None, config={}*)

Bases: `pyDKB.dataflow.communication.stream.Stream.Stream`

Implementation of the output stream.

configure (*config={}*)

Configure instance.

drop ()

Drop buffer without sending messages anywhere.

eop ()

Signalize Supervisor about end of process.

flush ()

Flush buffer to the output stream.

msg_buffer = []

write (*message*)

Add message to the buffer.

Submodules

`pyDKB.dataflow.communication.stream.InputStream` module

`pyDKB.dataflow.communication.stream.InputStream`

class `pyDKB.dataflow.communication.stream.InputStream.InputStream` (*fd=None, config={}*)

Bases: `pyDKB.dataflow.communication.stream.Stream.Stream`

Implementation of the input stream.

get_message ()

Get next message from the input stream.

Return values: Message object False (failed to parse message) None (no messages left)

is_readable ()

Check if current input stream is readable.

Returns None – not initialized, False – empty, True – not empty

Return type bool, NoneType

next ()

Get next message from the input stream.

parse_message (*message*)

Verify and parse input message.

Retrun value: Message object False (failed to parse)

reset (*fd*, *close=True*, *force=False*)
 Reset current stream with new file descriptor.
 Overrides parent method to reset `__iterator` property.

pyDKB.dataflow.communication.stream.OutputStream module

pyDKB.dataflow.communication.stream.OutputStream

class pyDKB.dataflow.communication.stream.OutputStream.**OutputStream** (*fd=None*,
con-
fig={})

Bases: `pyDKB.dataflow.communication.stream.Stream.Stream`

Implementation of the output stream.

configure (*config={}*)
 Configure instance.

drop ()
 Drop buffer without sending messages anywhere.

eop ()
 Signalize Supervisor about end of process.

flush ()
 Flush buffer to the output stream.

msg_buffer = []

write (*message*)
 Add message to the buffer.

pyDKB.dataflow.communication.stream.Stream module

pyDKB.dataflow.communication.stream.Stream

class pyDKB.dataflow.communication.stream.Stream.**Stream** (*fd=None*, *config={}*)

Bases: `object`

Abstract class for input/output streams.

EOM = `None`

close ()
 Close open file descriptors etc.

configure (*config*)
 Stream configuration.

get_fd ()
 Return open file descriptor or raise exception.

log (*message*, *level=3*)
 Output log message with given log level.

message_type ()
 Get type of the messages in the stream.

reset (*fd*, *close=True*)
 Reset file descriptor in operation.

Parameters `fd` – open file descriptor TODO: IOBase objects

Returns previous file descriptor (or None)

set_message_type (*msg_type*)
Set type of the messages in the stream.

pyDKB.dataflow.communication.stream.exceptions module

pyDKB.dataflow.communication.stream.exceptions

exception pyDKB.dataflow.communication.stream.exceptions.**StreamException**

Bases: [pyDKB.dataflow.exceptions.DataflowException](#)

Exception for Stream operations.

Submodules

pyDKB.dataflow.communication.messages module

pyDKB.dataflow.communication.messages

Definition of abstract message class and specific message classes

class pyDKB.dataflow.communication.messages.**AbstractMessage** (*message=None*)

Bases: object

Abstract message

content ()

Return message content.

decode (*code*)

Decode original from CODE to TYPE-specific format.

Raises ValueError

decoded = None

encode (*code*)

Encode original message from TYPE-specific format to CODE.

Raises ValueError

encoded = None

classmethod extension ()

Return file extension corresponding to this message type.

getOriginal ()

Return original message.

msg_type = None

native_types = []

classmethod typeName ()

Return message type name as string.

exception `pyDKB.dataflow.communication.messages.DecodeUnknownType (code, cls)`
 Bases: `exceptions.NotImplementedError`

Exception to be thrown when message type is not decodable.

exception `pyDKB.dataflow.communication.messages.EncodeUnknownType (code, cls)`
 Bases: `exceptions.NotImplementedError`

Exception to be thrown when message type is not encodable.

class `pyDKB.dataflow.communication.messages.JSONMessage (message=None)`
 Bases: `pyDKB.dataflow.communication.messages.AbstractMessage`

Message in JSON format.

decode (*code=1*)
 Decode original data as JSON.

encode (*code=1*)
 Encode JSON as CODE.

msg_type = 2

native_types = [`<type 'dict'>`]

`pyDKB.dataflow.communication.messages.Message (msg_type)`
 Return class XXXMessage, where XXX is the passed type.

class `pyDKB.dataflow.communication.messages.TTLMessage (message=None)`
 Bases: `pyDKB.dataflow.communication.messages.AbstractMessage`

Messages in TTL format

Single message = single TTL statement

decode (*code=1*)
 Decode original data as TTL.

Currently takes text as it is. TODO: check some formal matter to confirm the string is TTL.

encode (*code=1*)
 Encode TTL as CODE.

msg_type = 3

native_types = [`<type 'str'>`, `<type 'unicode'>`]

pyDKB.dataflow.stage package

Stage submodule init file.

class `pyDKB.dataflow.stage.ProcessorStage (description='DKB Dataflow data processing stage.')`
 Bases: `pyDKB.dataflow.stage.AbstractStage.AbstractStage`

Abstract class to implement Processor stages

Processor stage – is a stage for data processing/transformation.

Class/instance variable description:

- **communication.consumer.Consumer instance** `__input`
- Generator object for output file descriptor OR file descriptor (for (s)stream mode)
`__output`

- List of objects to be “stopped” `__stoppable`

clear_buffer ()

Drop buffered output messages.

configure (*args=None*)

Configure stage according to the config parameters.

If \$args specified, arguments will be parsed anew.

defaultArguments ()

Default parser configuration.

flush_buffer ()

Flush message buffer to the output.

forward ()

Send EOPMarker to the output stream.

get_source_info ()

Get information about current source.

input ()

Generator for input messages.

Returns iterable object. Every iteration returns single input message to be processed.

input_message_class ()

Get input message class.

output (*message*)

Put the (list of) message(s) to the output buffer.

output_message_class ()

Get output message class.

static process (*stage, input_message*)

Transform input_message -> output_message.

To be implemented individually for every stage. Takes the stage as first argument to allow calling output() from inside the function.

Return value: True – processing successfully finished False – processing failed (skip the input message)

run ()

Run process() for every input() message.

set_input_message_type (*Type=None*)

Set input message type.

set_output_message_type (*Type=None*)

Set output message class.

stop ()

Finalize all the processes and prepare to exit.

Submodules

pyDKB.dataflow.stage.AbstractStage module

Definition of an abstract class for Dataflow Stages.

```

class pyDKB.dataflow.stage.AbstractStage.AbstractStage (description='DKB Dataflow stage')
    Bases: object
    Class/instance variable description: * Argument parser (argparse.ArgumentParser)
        __parser

        • Parsed arguments (argparse.Namespace) ARGS
        • Stage config parser (ConfigParser.SafeConfigParser) __config
        • Stage custom config (defaultdict(defaultdict(str))) CONFIG

    add_argument (*args, **kwargs)
        Add specific (not common) arguments.

    args_error (message)
        Output USAGE, error message and exit with code 2.

    config_error (message='Failed to read config file:')
        Output error message and exit with code 3.

    defaultArguments ()
        Config argument parser with parameters common for all stages.

    log (message, level=3)
        Output log message with given log level.

    log_configuration ()
        Log stage configuration.

    output_error (message=None, exc_info=None)
        Output traceback of the passed (or last) error with message.

    parse_args (args)
        Parse arguments and set dependant arguments if needed.

        Exits in case of error with code: 2 – failed to parse arguments 3 – failed to read config file

    print_usage (fd=<open file '<stderr>', mode 'w'>)
        Print usage message.

    read_config ()
        Reads stage custom config file.

        Returns (True/False)

    run ()
        Run the stage.

    set_error (err_type, err_val, err_trace)
        Set object _err variable from the last error info.

    stop ()
        Stop running processes and output error information.

```

pyDKB.dataflow.stage.ProcessorStage module

Definition of an abstract class for Dataflow Data Processing Stages.

USAGE: ProcessorStage [<options>] [<input files>]

OPTIONS:

-s, --source	{ flsh } - where to get data from: local (f)iles, (s)tdin, (h)dfs
-i, --input-dir	DIR - base directory for relative input file names (for local and HDFS sources). If <input files> not specified, all files from the directory will be taken as the input.
-d, --dest	{ flsh } - where to send data to: local (f)iles, (s)tdout, (h)dfs
-o, --output-dir	DIR - base directory for output files (for local and HDFS sources)
--hdfs	<ul style="list-style-type: none">• equivalent to “-source h -dest h”
-m, --mode	MODE - MODE: (f)ile = -source f -dest f (can be rewritten with ‘s’ or ‘h’) (s)tream = -source s (can be rewritten with ‘h’) -dest s (m)apreduce = -source s (can be rewritten with ‘h’) -dest s

```
class pyDKB.dataflow.stage.ProcessorStage.ProcessorStage (description='DKB  
Dataflow data processing  
stage.')
```

Bases: `pyDKB.dataflow.stage.AbstractStage.AbstractStage`

Abstract class to implement Processor stages

Processor stage – is a stage for data processing/transformation.

Class/instance variable description:

- **communication.consumer.Consumer instance** `__input`
- Generator object for output file descriptor OR file descriptor (for (s)tream mode)
`__output`
- List of objects to be “stopped” `__stoppable`

clear_buffer ()
Drop buffered output messages.

configure (*args=None*)
Configure stage according to the config parameters.

If \$args specified, arguments will be parsed anew.

defaultArguments ()
Default parser configuration.

flush_buffer ()
Flush message buffer to the output.

forward ()
Send EOPMarker to the output stream.

get_source_info()
Get information about current source.

input()
Generator for input messages.
Returns iterable object. Every iteration returns single input message to be processed.

input_message_class()
Get input message class.

output(message)
Put the (list of) message(s) to the output buffer.

output_message_class()
Get output message class.

static process(stage, input_message)
Transform input_message -> output_message.
To be implemented individually for every stage. Takes the stage as first argument to allow calling output() from inside the function.

Return value: True – processing successfully finished False – processing failed (skip the input message)

run()
Run process() for every input() message.

set_input_message_type(Type=None)
Set input message type.

set_output_message_type(Type=None)
Set output message class.

stop()
Finalize all the processes and prepare to exit.

Submodules

pyDKB.dataflow.cds module

Extended CDSInvenioConnector allowing us to login via Kerberos

pyDKB.dataflow.dkbID module

Utils to generate unique yet meaningful identifier for DKB objects.

`pyDKB.dataflow.dkbID.dkbID(json_data, data_type)`
Return unique identifier for object of TYPE based on DATA.

pyDKB.dataflow.exceptions module

Definition of DKB Dataflow exceptions

exception `pyDKB.dataflow.exceptions.DataflowException`
Bases: `exceptions.Exception`
Base Exception for Dataflow modules.

pyDKB.dataflow.types module

Type definitions for library objects.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

p

- pyDKB, 1
- pyDKB.common, 3
 - pyDKB.common.custom_readline, 4
 - pyDKB.common.exceptions, 4
 - pyDKB.common.hdfs, 5
 - pyDKB.common.json_utils, 5
 - pyDKB.common.Type, 3
- pyDKB.dataflow, 6
 - pyDKB.dataflow.cds, 21
 - pyDKB.dataflow.communication, 6
 - pyDKB.dataflow.communication.consumer, 6
 - pyDKB.dataflow.communication.consumer.Consumer, 6
 - pyDKB.dataflow.communication.consumer.FileConsumer, 7
 - pyDKB.dataflow.communication.consumer.HDFSConsumer, 8
 - pyDKB.dataflow.communication.consumer.StreamConsumer, 8
 - pyDKB.dataflow.communication.messages, 16
 - pyDKB.dataflow.communication.producer, 9
 - pyDKB.dataflow.communication.producer.FileProducer, 9
 - pyDKB.dataflow.communication.producer.HDFSProducer, 10
 - pyDKB.dataflow.communication.producer.Producer, 11
 - pyDKB.dataflow.communication.producer.StreamProducer, 12
 - pyDKB.dataflow.communication.stream, 12
 - pyDKB.dataflow.communication.stream.exceptions, 16
 - pyDKB.dataflow.communication.stream.InputStream, 14
 - pyDKB.dataflow.communication.stream.OutputStream, 15
 - pyDKB.dataflow.communication.stream.Stream, 15
 - pyDKB.dataflow.dkbID, 21
 - pyDKB.dataflow.exceptions, 21
 - pyDKB.dataflow.stage, 17
 - pyDKB.dataflow.stage.AbstractStage, 18
 - pyDKB.dataflow.stage.ProcessorStage, 19
 - pyDKB.dataflow.types, 22

INDEX

A

AbstractMessage (class in py-DKB.dataflow.communication.messages), 16

AbstractStage (class in py-DKB.dataflow.stage.AbstractStage), 18

add() (pyDKB.common.Type.Type method), 3

add_argument() (pyDKB.dataflow.stage.AbstractStage.AbstractStage method), 19

args_error() (pyDKB.dataflow.stage.AbstractStage.AbstractStage method), 19

B

basename() (in module pyDKB.common.hdfs), 5

build() (pyDKB.dataflow.communication.consumer.ConsumerBuilder method), 6

build() (pyDKB.dataflow.communication.producer.ProducerBuilder method), 9

build() (pyDKB.dataflow.communication.stream.StreamBuilder method), 12

C

check_stderr() (in module pyDKB.common.hdfs), 5

clear_buffer() (pyDKB.dataflow.stage.ProcessorStage method), 18

clear_buffer() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 20

close() (pyDKB.dataflow.communication.consumer.Consumer.Consumer method), 6

close() (pyDKB.dataflow.communication.producer.FileProducer.FileProducer method), 9

close() (pyDKB.dataflow.communication.producer.Producer.Producer method), 11

close() (pyDKB.dataflow.communication.stream.Stream.Stream method), 13

close() (pyDKB.dataflow.communication.stream.Stream.Stream method), 15

close_file() (pyDKB.dataflow.communication.producer.FileProducer.FileProducer method), 9

close_file() (pyDKB.dataflow.communication.producer.HDFSPProducer.HDFSPProducer method), 11

config (pyDKB.dataflow.communication.consumer.Consumer.Consumer attribute), 6

config (pyDKB.dataflow.communication.producer.Producer.Producer attribute), 11

config_dir() (pyDKB.dataflow.communication.producer.FileProducer.FileProducer method), 9

config_dir() (pyDKB.dataflow.communication.producer.HDFSPProducer.HDFSPProducer method), 11

config_error() (pyDKB.dataflow.stage.AbstractStage.AbstractStage method), 19

configure() (pyDKB.dataflow.communication.stream.OutputStream.OutputStream method), 14

configure() (pyDKB.dataflow.communication.stream.OutputStream.OutputStream method), 15

configure() (pyDKB.dataflow.communication.stream.Stream.Stream method), 13

configure() (pyDKB.dataflow.communication.stream.Stream.Stream method), 15

configure() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 18

configure() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 20

Consumer (class in py-DKB.dataflow.communication.consumer.Consumer), 6

ConsumerBuilder (class in py-DKB.dataflow.communication.consumer), 6

consumerClass (pyDKB.dataflow.communication.consumer.ConsumerBuilder attribute), 6

ConsumerException, 7

content() (pyDKB.dataflow.communication.messages.AbstractMessage.Producer method), 16

current_file (pyDKB.dataflow.communication.consumer.FileConsumer.FileConsumer attribute), 7

current_file (pyDKB.dataflow.communication.producer.FileProducer.FileProducer attribute), 10

custom_readline() (in module py-DKB.common.custom_readline), 4

DataflowException, 21

decode() (pyDKB.dataflow.communication.messages.AbstractMessage method), 16
 decode() (pyDKB.dataflow.communication.messages.JSONMessage method), 17
 decode() (pyDKB.dataflow.communication.messages.TTLMessage method), 17
 decoded (pyDKB.dataflow.communication.messages.AbstractMessage attribute), 16
 DecodeUnknownType, 16
 default_dir() (pyDKB.dataflow.communication.producer.FileProducer.FileProducer method), 10
 defaultArguments() (pyDKB.dataflow.stage.AbstractStage.AbstractStage method), 19
 defaultArguments() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 18
 defaultArguments() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 20
 dirname() (in module pyDKB.common.hdfs), 5
 dirname() (pyDKB.dataflow.communication.producer.FileProducer.FileProducer method), 10
 dkbID() (in module pyDKB.dataflow.dkbID), 21
 drop() (pyDKB.dataflow.communication.producer.Producer.Producer method), 11
 drop() (pyDKB.dataflow.communication.stream.OutputStream.OutputStream method), 14
 drop() (pyDKB.dataflow.communication.stream.OutputStream.OutputStream method), 15
 E
 encode() (pyDKB.dataflow.communication.messages.AbstractMessage method), 16
 encode() (pyDKB.dataflow.communication.messages.JSONMessage method), 17
 encode() (pyDKB.dataflow.communication.messages.TTLMessage method), 17
 encoded (pyDKB.dataflow.communication.messages.AbstractMessage attribute), 16
 EncodeUnknownType, 17
 ensure_dir() (pyDKB.dataflow.communication.producer.FileProducer.FileProducer method), 10
 ensure_dir() (pyDKB.dataflow.communication.producer.HDFSProducer.HDFSProducer method), 11
 EOM (pyDKB.dataflow.communication.stream.Stream.Stream attribute), 13
 EOM (pyDKB.dataflow.communication.stream.Stream.Stream attribute), 15
 eop() (pyDKB.dataflow.communication.producer.Producer.Producer method), 11
 eop() (pyDKB.dataflow.communication.stream.OutputStream.OutputStream method), 14
 fd (pyDKB.dataflow.communication.producer.StreamProducer.StreamProducer attribute), 8
 File() (in module pyDKB.common.hdfs), 5
 file_info() (pyDKB.dataflow.communication.producer.FileProducer.FileProducer method), 10
 file_info() (pyDKB.dataflow.communication.producer.HDFSProducer.HDFSProducer method), 11
 FileConsumer (class in pyDKB.dataflow.communication.consumer.FileConsumer), 7
 FileProducer (class in pyDKB.dataflow.communication.producer.FileProducer), 9
 flush() (pyDKB.dataflow.communication.stream.OutputStream.OutputStream method), 14
 flush() (pyDKB.dataflow.communication.stream.OutputStream.OutputStream method), 15
 flush_buffer() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 18
 flush_buffer() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 20
 forward() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 18
 forward() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 20
 G
 get_dest() (pyDKB.dataflow.communication.producer.FileProducer.FileProducer method), 10
 get_dest() (pyDKB.dataflow.communication.producer.Producer.Producer method), 11
 get_dest() (pyDKB.dataflow.communication.producer.StreamProducer.StreamProducer method), 12
 get_dest_info() (pyDKB.dataflow.communication.producer.FileProducer.FileProducer method), 10
 get_dest_info() (pyDKB.dataflow.communication.producer.Producer.Producer method), 11
 get_dest_info() (pyDKB.dataflow.communication.producer.StreamProducer.StreamProducer method), 12
 get_fd() (pyDKB.dataflow.communication.stream.Stream.Stream method), 13

get_fd() (pyDKB.dataflow.communication.stream.Stream.Stream attribute), 8
 get_filename() (pyDKB.dataflow.communication.producer.Producer.Producer method), 10
 get_message() (pyDKB.dataflow.communication.consumer.Consumer.Consumer method), 6
 get_message() (pyDKB.dataflow.communication.stream.InputStream.InputStream method), 13
 get_message() (pyDKB.dataflow.communication.stream.InputStream.InputStream method), 14
 get_source() (pyDKB.dataflow.communication.consumer.FileConsumer.FileConsumer method), 8
 get_source() (pyDKB.dataflow.communication.consumer.StreamConsumer.StreamConsumer method), 8
 get_source_info() (pyDKB.dataflow.communication.consumer.Consumer.Consumer method), 6
 get_source_info() (pyDKB.dataflow.communication.consumer.FileConsumer.FileConsumer method), 8
 get_source_info() (pyDKB.dataflow.communication.consumer.StreamConsumer.StreamConsumer method), 8
 get_source_info() (pyDKB.dataflow.communication.producer.FileProducer.FileProducer method), 10
 get_source_info() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 18
 get_source_info() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 20
 get_stream() (pyDKB.dataflow.communication.consumer.Consumer.Consumer method), 7
 get_stream() (pyDKB.dataflow.communication.producer.Producer.Producer method), 11
 getfile() (in module pyDKB.common.hdfs), 5
 getOriginal() (pyDKB.dataflow.communication.messages.AbstractMessage.AbstractMessage method), 16

H

hasMember() (pyDKB.common.Type.Type method), 3
 HDFSConsumer (class in pyDKB.dataflow.communication.consumer.HDFSConsumer), 8
 HDFSException, 4
 HDFSProducer (class in pyDKB.dataflow.communication.producer.HDFSProducer), 11

I

init_stream() (pyDKB.dataflow.communication.consumer.Consumer.Consumer method), 7
 init_stream() (pyDKB.dataflow.communication.producer.Producer.Producer method), 11
 input() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 18
 input() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 21

M

mkdirs() (in module pyDKB.common.hdfs), 5
 member() (pyDKB.common.Type.Type method), 3
 memberName() (pyDKB.common.Type.Type method), 3
 Message() (in module pyDKB.dataflow.communication), 7
 Message() (in module pyDKB.dataflow.communication.messages), 17
 message_class() (pyDKB.dataflow.communication.consumer.Consumer.Consumer method), 7
 message_class() (pyDKB.dataflow.communication.producer.Producer.Producer method), 12

[message_type \(pyDKB.dataflow.communication.consumer.Consumer.ConsumerClass attribute\), 7](#)
[message_type \(pyDKB.dataflow.communication.producer.Producer.ProducerClass attribute\), 12](#)
[message_type \(pyDKB.dataflow.communication.producer.ProducerBuilder.ProducerBuilder attribute\), 9](#)
[message_type \(pyDKB.dataflow.communication.stream.StreamBuilder.StreamBuilder attribute\), 13](#)
[message_type\(\) \(pyDKB.dataflow.communication.stream.Stream method\), 13](#)
[message_type\(\) \(pyDKB.dataflow.communication.stream.StreamStream method\), 15](#)
[movefile\(\) \(in module pyDKB.common.hdfs\), 5](#)
[msg_buffer \(pyDKB.dataflow.communication.stream.OutputStream attribute\), 14](#)
[msg_buffer \(pyDKB.dataflow.communication.stream.OutputStream.OutputStream attribute\), 15](#)
[msg_type \(pyDKB.dataflow.communication.messages.AbstractMessage attribute\), 16](#)
[msg_type \(pyDKB.dataflow.communication.messages.JSONMessage attribute\), 17](#)
[msg_type \(pyDKB.dataflow.communication.messages.TTLMessage attribute\), 17](#)
N
[native_types \(pyDKB.dataflow.communication.messages.AbstractMessage attribute\), 16](#)
[native_types \(pyDKB.dataflow.communication.messages.JSONMessage attribute\), 17](#)
[native_types \(pyDKB.dataflow.communication.messages.TTLMessage attribute\), 17](#)
[nestedKeys\(\) \(in module pyDKB.common.json_utils\), 5](#)
[next\(\) \(pyDKB.dataflow.communication.consumer.Consumer.Consumer method\), 7](#)
[next\(\) \(pyDKB.dataflow.communication.stream.InputStream method\), 13](#)
[next\(\) \(pyDKB.dataflow.communication.stream.InputStream.InputStream method\), 14](#)
[next_source\(\) \(pyDKB.dataflow.communication.consumer.FileConsumer.FileConsumer method\), 8](#)
[next_source\(\) \(pyDKB.dataflow.communication.consumer.StreamConsumer.StreamConsumer method\), 8](#)
O
[output\(\) \(pyDKB.dataflow.stage.ProcessorStage method\), 18](#)
[output\(\) \(pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method\), 21](#)
[output_error\(\) \(pyDKB.dataflow.stage.AbstractStage.AbstractStage method\), 19](#)
[output_message_class\(\) \(pyDKB.dataflow.stage.ProcessorStage method\), 18](#)
[output_stream \(pyDKB.dataflow.communication.stream.InputStream attribute\), 13](#)
[output_stream \(pyDKB.dataflow.communication.stream.InputStream.InputStream attribute\), 14](#)
[output_stream \(pyDKB.dataflow.communication.stream.OutputStream attribute\), 15](#)
[output_stream \(pyDKB.dataflow.communication.stream.OutputStream.OutputStream attribute\), 15](#)
[parse_message\(\) \(pyDKB.dataflow.communication.stream.InputStream method\), 13](#)
[parse_message\(\) \(pyDKB.dataflow.communication.stream.InputStream.InputStream method\), 14](#)
[print_usage\(\) \(pyDKB.dataflow.stage.AbstractStage.AbstractStage method\), 19](#)
[process\(\) \(pyDKB.dataflow.stage.ProcessorStage static method\), 18](#)
[process\(\) \(pyDKB.dataflow.stage.ProcessorStage.ProcessorStage static method\), 21](#)
[ProcessorStage \(class in pyDKB.dataflow.stage\), 17](#)
[ProcessorStage \(class in pyDKB.dataflow.stage\), 20](#)
[Producer \(class in pyDKB.dataflow.communication.producer.Producer\), 11](#)
[ProducerBuilder \(class in pyDKB.dataflow.communication.producer\), 9](#)
[producerClass \(pyDKB.dataflow.communication.producer.ProducerBuilder attribute\), 9](#)
[ProducerException, 12](#)
[putfile\(\) \(in module pyDKB.common.hdfs\), 5](#)
[pyDKB \(module\), 1](#)
[pyDKB.common \(module\), 3](#)
[pyDKB.common.custom_readline \(module\), 4](#)
[pyDKB.common.FileException \(module\), 4](#)
[pyDKB.common.hdfs \(module\), 5](#)
[pyDKB.common.json_utils \(module\), 5](#)
[pyDKB.common.Type \(module\), 3](#)
[pyDKB.dataflow \(module\), 6](#)
[pyDKB.dataflow.cds \(module\), 21](#)
[pyDKB.dataflow.communication \(module\), 6](#)
[pyDKB.dataflow.communication.consumer \(module\), 6](#)
[pyDKB.dataflow.communication.consumer.Consumer \(module\), 6](#)
[pyDKB.dataflow.communication.consumer.FileConsumer \(module\), 7](#)
[pyDKB.dataflow.communication.consumer.HDFSCConsumer \(module\), 8](#)
[pyDKB.dataflow.communication.consumer.StreamConsumer \(module\), 8](#)

pyDKB.dataflow.communication.messages (module), 16
 pyDKB.dataflow.communication.producer (module), 9
 pyDKB.dataflow.communication.producer.FileProducer (module), 9
 pyDKB.dataflow.communication.producer.HDFSProducer (module), 10
 pyDKB.dataflow.communication.producer.Producer (module), 11
 pyDKB.dataflow.communication.producer.StreamProducer (module), 12
 pyDKB.dataflow.communication.stream (module), 12
 pyDKB.dataflow.communication.stream.exceptions (module), 16
 pyDKB.dataflow.communication.stream.InputStream (module), 14
 pyDKB.dataflow.communication.stream.OutputStream (module), 15
 pyDKB.dataflow.communication.stream.Stream (module), 15
 pyDKB.dataflow.dkbID (module), 21
 pyDKB.dataflow.exceptions (module), 21
 pyDKB.dataflow.stage (module), 17
 pyDKB.dataflow.stage.AbstractStage (module), 18
 pyDKB.dataflow.stage.ProcessorStage (module), 19
 pyDKB.dataflow.types (module), 22

R

read_config() (pyDKB.dataflow.stage.AbstractStage.AbstractStage method), 19
 reconfigure() (pyDKB.dataflow.communication.consumer.ConsumerBuilder method), 7
 reconfigure() (pyDKB.dataflow.communication.consumer.FileConsumerBuilder method), 8
 reconfigure() (pyDKB.dataflow.communication.consumer.HDFSConsumerBuilder method), 8
 reconfigure() (pyDKB.dataflow.communication.consumer.StreamConsumerBuilder method), 9
 reconfigure() (pyDKB.dataflow.communication.producer.FileProducer method), 10
 reconfigure() (pyDKB.dataflow.communication.producer.Producer.ProducerBuilder method), 12
 reconfigure() (pyDKB.dataflow.communication.producer.StreamProducer method), 12
 reset() (pyDKB.dataflow.communication.stream.InputStream method), 14
 reset() (pyDKB.dataflow.communication.stream.InputStream method), 14
 reset() (pyDKB.dataflow.communication.stream.Stream method), 13
 reset() (pyDKB.dataflow.communication.stream.Stream method), 15
 reset_file() (pyDKB.dataflow.communication.producer.FileProducer method), 10
 reset_stream() (pyDKB.dataflow.communication.consumer.ConsumerBuilder method), 7
 reset_stream() (pyDKB.dataflow.communication.producer.Producer.ProducerBuilder method), 12
 run() (pyDKB.dataflow.stage.AbstractStage.AbstractStage method), 19
 run() (pyDKB.dataflow.stage.ProcessorStage method), 18
 run() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 21

S

set_default_dir() (pyDKB.dataflow.communication.producer.FileProducer method), 10
 set_default_dir() (pyDKB.dataflow.communication.producer.HDFSProducer method), 11
 set_error() (pyDKB.dataflow.stage.AbstractStage.AbstractStage method), 19
 set_input_message_type() (pyDKB.dataflow.stage.ProcessorStage method), 18
 set_input_message_type() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 21
 set_message_type() (pyDKB.dataflow.communication.consumer.ConsumerBuilder method), 7
 set_message_type() (pyDKB.dataflow.communication.producer.Producer.ProducerBuilder method), 12
 set_message_type() (pyDKB.dataflow.communication.stream.Stream method), 13
 set_message_type() (pyDKB.dataflow.communication.stream.Stream method), 16
 set_output_message_type() (pyDKB.dataflow.stage.ProcessorStage method), 21
 set_output_message_type() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage method), 21
 setSource() (pyDKB.dataflow.communication.consumer.ConsumerBuilder method), 6
 setSourceInfo() (pyDKB.dataflow.communication.producer.ProducerBuilder method), 9
 setStream() (pyDKB.dataflow.communication.stream.StreamBuilder method), 13
 setType() (pyDKB.dataflow.communication.consumer.ConsumerBuilder method), 6
 setType() (pyDKB.dataflow.communication.producer.ProducerBuilder method), 9

setType() (pyDKB.dataflow.communication.stream.StreamBuilder
method), [13](#)

source_is_readable() (py-
DKB.dataflow.communication.consumer.FileConsumer.FileConsumer
method), [8](#)

src_info (pyDKB.dataflow.communication.producer.ProducerBuilder
attribute), [9](#)

stop() (pyDKB.dataflow.stage.AbstractStage.AbstractStage
method), [19](#)

stop() (pyDKB.dataflow.stage.ProcessorStage method),
[18](#)

stop() (pyDKB.dataflow.stage.ProcessorStage.ProcessorStage
method), [21](#)

Stream (class in pyDKB.dataflow.communication.stream),
[13](#)

Stream (class in pyDKB.dataflow.communication.stream.Stream),
[15](#)

stream_is_readable() (py-
DKB.dataflow.communication.consumer.Consumer.Consumer
method), [7](#)

StreamBuilder (class in py-
DKB.dataflow.communication.stream), [12](#)

streamClass (pyDKB.dataflow.communication.stream.StreamBuilder
attribute), [13](#)

StreamConsumer (class in py-
DKB.dataflow.communication.consumer.StreamConsumer),
[8](#)

StreamException, [16](#)

StreamProducer (class in py-
DKB.dataflow.communication.producer.StreamProducer),
[12](#)

subdir() (pyDKB.dataflow.communication.producer.FileProducer.FileProducer
method), [10](#)

subdir() (pyDKB.dataflow.communication.producer.HDFSProducer.HDFSProducer
method), [11](#)

T

TTLMessage (class in py-
DKB.dataflow.communication.messages),
[17](#)

Type (class in pyDKB.common.Type), [3](#)

typeName() (pyDKB.dataflow.communication.messages.AbstractMessage
class method), [16](#)

V

valueByKey() (in module pyDKB.common.json_utils), [5](#)

W

write() (pyDKB.dataflow.communication.producer.Producer.Producer
method), [12](#)

write() (pyDKB.dataflow.communication.stream.OutputStream
method), [14](#)

write() (pyDKB.dataflow.communication.stream.OutputStream.OutputStream
method), [15](#)