```
UPDATE blinkit_data
SET "Item_Fat_Content" =
CASE
WHEN "Item_Fat_Content" IN ('LF','low fat') THEN 'Low Fat'
WHEN "Item_Fat_Content" ='reg' THEN 'Regular'
ELSE "Item_Fat_Content"
END

SELECT * FROM blinkit_data
SELECT COUNT(*) AS "No.Of Items" FROM blinkit_data

SELECT DISTINCT "Item_Fat_Content" FROM blinkit_data

SELECT CAST(SUM("Total_Sales")/1000000 AS DECIMAL(10,2)) AS "Total_Sales_Millions"
FROM blinkit_data
WHERE "Item_Fat_Content" = 'Low Fat'
WHERE "Outlet_Establishment_Year"= 2022

SELECT CAST(AVG("Total_Sales") AS DECIMAL(10,0)) AS "Average" FROM blinkit_data
WHERE "Item_Fat_Content" = 'Low Fat'

SELECT CAST(AVG("Rating") AS DECIMAL(10,2)) AS "Avg_Rating" FROM blinkit_data

SELECT column_name
From information_schema.columns
where table_name='blinkit_data'

-- granular req
```

```
-- TOTAL SALES BY FAT CONTENT
SELECT "Item_Fat_Content",
		CONCAT(CAST(SUM("Total_Sales")/1000 AS DECIMAL(10,2)),'K') AS "Total_Sales_Thousands",
		CAST(AVG("Total_Sales") AS DECIMAL(10,1)) AS "Average_Sales",
		COUNT (*) AS NO_0f_Items,
		CAST(AVG("Rating") AS DECIMAL(10,2)) AS "Average_Rating"

FROM blinkit_data
GROUP BY "Item_Fat_Content"
ORDER BY "Total_Sales_Thousands" DESC

select ROUND(sum("Total_Sales")::NUMERIC ,2) from blinkit_data

-- TOTAL SALES BY ITEM TYPE
SELECT "Item_Type",
		CAST(SUM("Total_Sales") AS DECIMAL(10,2)) AS "Total_Sales",
		CAST(AVG("Total_Sales") AS DECIMAL(10,1)) AS "Average_Sales",
		COUNT (*) AS NO_0f_Items,
		CAST(AVG("Rating") AS DECIMAL(10,2)) AS "Average_Rating"

FROM blinkit_data
GROUP BY "Item_Type"
ORDER BY "Total_Sales" DESC
LIMIT 5 -- only show top five
```

```
--TOTAL CINTENT FOR TOTAL SALES
SELECT "Outlet_Location_Type",
	COALESCE("Low Fat",0) AS Low_Fat,
	COALESCE("Regular",0) AS Regular
FROM
(
		SELECT "Outlet_Location_Type","Item_Fat_Content",
			CAST(SUM("Total_Sales") AS DECIMAL(10,2)) AS "Total_Sales"
			FROM blinkit_data
			GROUP BY "Outlet_Location_Type","Item_Fat_Content"
) AS SourceTable
PIVOT(
	SUM("Total_Sales")
	FOR "Item_Fat_Content" IN ('Low Fat' AS "Low Fat",'Regular' AS "Regular")
)AS PivotTable
ORDER BY "Outlet_Location_Type";



SELECT
  "Outlet_Location_Type",
  COALESCE(SUM(
    CASE WHEN "Item_Fat_Content" = 'Low Fat'
        THEN "Total_Sales" END
  ), 0)::NUMERIC(10,2) AS low_fat,
 -- COALESCE(SUM(
   -- CASE WHEN "Item_Fat_Content" = 'Regular'
       -- THEN "Total_Sales" END
 -- ), 0)::NUMERIC(10,2) AS regular
```

```
  COALESCE(AVG(
   CASE WHEN "Item_Fat_Content" = 'Regular'
       THEN "Total_Sales" END
 ), 0)::NUMERIC(10,2) AS regular_avg_sale
FROM blinkit_data
GROUP BY "Outlet_Location_Type"
ORDER BY "Outlet_Location_Type";

--total sales by outlet establishment year

SELECT "Outlet_Establishment_Year",
        CAST(SUM("Total_Sales") AS DECIMAL(10,2)) AS "Total_Sales",
        CAST(AVG("Total_Sales") AS DECIMAL(10,1)) AS "Average_Sales",
        COUNT (*) AS NO_0f_Items,
        CAST(AVG("Rating") AS DECIMAL(10,2)) AS "Average_Rating"

FROM blinkit_data
GROUP BY "Outlet_Establishment_Year"
ORDER BY "Outlet_Establishment_Year"  ASC

--Percentage of sales by outlet size
SELECT "Outlet_Size",
        CAST(SUM("Total_Sales") AS DECIMAL(10,2)) AS "Total_Sales",
        CAST((SUM("Total_Sales")*100.0/SUM(SUM("Total_Sales")) OVER()) AS
DECIMAL(10,2)) AS "Sales_Percentage"
FROM blinkit_data
GROUP BY "Outlet_Size"
ORDER BY "Total_Sales" DESC
```

```
--Sales by outlet location type
SELECT "Outlet_Location_Type",
	CAST(SUM("Total_Sales") AS DECIMAL(10,2)) AS "Total_Sales",
	CAST(AVG("Total_Sales") AS DECIMAL(10,1)) AS "Average_Sales",
	CAST((SUM("Total_Sales")*100.0/SUM(SUM("Total_Sales")) OVER()) AS DECIMAL(10,2)) AS "Sales_Percentage",
	COUNT (*) AS NO_0f_Items,
	CAST(AVG("Rating") AS DECIMAL(10,2)) AS "Average_Rating"

FROM blinkit_data
GROUP BY "Outlet_Location_Type"
ORDER BY "Total_Sales"  DESC

--Sales by outlet type
SELECT "Outlet_Type",
	CAST(SUM("Total_Sales") AS DECIMAL(10,2)) AS "Total_Sales",
	CAST(AVG("Total_Sales") AS DECIMAL(10,1)) AS "Average_Sales",
	CAST((SUM("Total_Sales")*100.0/SUM(SUM("Total_Sales")) OVER()) AS DECIMAL(10,2)) AS "Sales_Percentage",
	COUNT (*) AS NO_0f_Items,
	CAST(AVG("Rating") AS DECIMAL(10,2)) AS "Average_Rating"

FROM blinkit_data
GROUP BY "Outlet_Type"
ORDER BY "Total_Sales"  DESC
```