

PAP-WM210 Indoor Wireless AP

Product Specification



Product Overview:

PAP-WM210 is a high-performance dual-band indoor wireless access point independently developed by Panabit. It features an enterprise-grade chipset, delivering both 2.4G and 5G services with a maximum wireless speed of 1167Mbps and includes two 100Mbps Ethernet ports. The front panel supports a dustproof cover and fits standard 86-type wall boxes, ensuring a cleaner wireless environment with more stable access.

Product Features:



Controller-Free Networking

With the Panabit Smart Application Gateway, no additional wireless controller (AC) is needed, lowering costs and minimizing potential failure points, for a streamlined network.



Smart Wireless Optimization

Unified AP and user status view, one-click AP RF and signal settings, and roaming assistance to address sticky client issues by disconnecting based on signal thresholds.



SD-WAN Networking

Supports Panabit's proprietary SD-WAN tunneling and traffic diversion, enabling cost-effective SD-WAN and standard network services.



Zero-Config Plug-and-Play

Supports out-of-the-box plug-and-play with zero configuration—just power up to connect to the network. Allows flexible switching between fat and thin modes without rebooting.



Wireless Security

User isolation ensures WLAN security. Scheduled signal availability disables wireless access after hours for added security during unattended times.



Remote Unified Management

Allows unified management via the Panabit gateway with multiple remote options, including private/public clouds and mobile apps, greatly boosting network management efficiency.

Specification:

RF Design	Dual-path dual RF (2.4G, 5G)
2.4G Frequency Band	2.4GHz – 2.484GHz
2.4G Wi-Fi Protocol	802.11 b/g/n
5G Frequency Band	5.150GHz ~ 5.850GHz
5G Wi-Fi Protocol	802.11 a/n/ac
Spatial Streams	2.4G: 2 spatial streams, 2x2 MIMO 5G: 2 spatial streams, 2x2 MIMO
Antenna Type	Built-in antenna (basic gain 2dBi)
Transmission Speed	1167Mbps (2.4G 300Mbps + 5G 867Mbps)
Wired Ports	2 x 10/100 Base-T Ethernet ports (uplink supports PoE input)
WLAN Features	Supports up to 16 SSIDs Each SSID can be configured with individual VLAN attributes Supports SSID names in both Chinese and English, with independent encryption settings and hiding options Support wireless roaming Supports OPEN and WPA2-PSK encryption
Max Wireless Access	128
Recommended User Access	20
Network Management	Unified management via Panabit Smart Application Gateway, supports private and public cloud management
Power Supply	PoE (48V 0.5A), compatible with 802.3at
Reset Button	Supported (long press to restore factory settings)
Status Indicators	Supported
Max Power Consumption	< 8W
Dimensions	87mm*86mm*35.8mm
Environmental	Operating Temperature: -20°C to 55°C Operating Humidity: 5% to 95% RH (non-condensing)



Beijing Panabit Software Co., Ltd.

Address: 1st floor, New Industry Alliance Building, Phase II, Zhongguancun Software Park, Haidian District, Beijing

Website: www.panabit.com

Support Email: support@panabit.com

*The content in this document is the property of Beijing Panabit Software Co., Ltd. Panabit reserves the right to modify the contents of this document without prior notice to clients.