unit2 image enhancement.ipynb 的补充

Unit 2: Image Enhancement (Spatial Domain) — Solved PYQ Mark Guide

Exam Pattern: 2 Marks (Short) | 5 Marks (Medium) | 10 Marks (Long)

🔑 PART A: TOPIC WISE PYQ FREQUENCY & PATTERN ANALYSIS

Topic	Frequency	Typical Marks	Question Type
Point Operations (Negative, Log, Power-law)	★★★★★	2 / 5 / 10	Define, Compare, Apply
Contrast Stretching & Thresholding	★★★★★	5 / 10	Explain, Apply
Bit-plane Slicing	★★★★	5 / 10	Explain, Apply
Histogram Processing (Equalization & Matching)	★★★★★	10	Derive, Apply, Compare
Local / Neighborhood Operations	★★★★	5 / 10	Explain, Apply
Smoothing Filters (Mean, Gaussian, Median)	★★★★★	5 / 10	Compare, Apply
Sharpening Filters (Laplacian, Unsharp Masking, High-boost)	★★★★★	5 / 10	Compare, Apply
Gradient Operators (Roberts, Prewitt, Sobel)	★★★★	5 / 10	Apply, Compare
Combining Spatial Enhancement Methods	★★★	10	Apply
Frequency Domain Filters (Ideal, Butterworth, Gaussian)	★★★★★	5 / 10	Compare, Apply
Homomorphic Filtering	★★★	10	Explain, Apply
Color Image Processing (Pseudo & Full Color)	★★★	5 / 10	Explain, Apply
Color Transformations	★★★	10	Apply
Color Segmentation	★★	10	Apply
Noise Models	★★★★	5 / 10	Explain, Apply
Noise Reduction	★★★★★	5 / 10	Compare, Apply
Restoration Filters (Inverse, Wiener)	★★★★	10	Derive, Apply
Periodic Noise Reduction	★★★	10	Apply
Linear, Position-Invariant Degradations	★★★	10	Explain, Apply
Estimating Degradation Functions	★★★	10	Apply
Constrained Least Squares Filtering	★★★	10	Derive, Apply
Geometric Mean Filter	★★	5	Define, Apply
Geometric Transformations	★★★★	5 / 10	Apply
Spatial Transformations	★★★	10	Apply
Image Registration	★★★	10	Explain, Apply

📌 Image Point Operations (Intensity Transformations)

- Point Operations are the simplest image enhancement techniques where each pixel is processed independently.
- Intensity Transformation Function: $s = T(r)$ where r = input pixel intensity, s = output pixel intensity.
- Image Negative: $s = L - 1 - r$ where L = number of intensity levels (e.g., $L = 256$ for 8-bit image).
- Log Transformation: $s = c \log(1 + r)$ where c is a constant. Used to expand dark pixel values.
- Power-law (Gamma) Transformation: $s = c \cdot r^{\gamma}$ where γ is gamma. $\gamma < 1$ brightens, $\gamma > 1$ darkens.
- Piecewise Linear Transformation: Contrast Stretching, Thresholding, Gray-level slicing, Bit-plane slicing.
- Contrast Stretching: Increases the dynamic range of gray levels in an image.
- Thresholding: Produces a binary image by setting pixels above a threshold to 1 and below to 0.
- Gray-level Slicing: Highlights a specific range of gray levels in an image.
- Bit-plane Slicing: Extracts individual bit planes to analyze the contribution of each bit to the image.

📌 Histogram Processing

- Histogram: A graph showing the frequency of occurrence of each gray level in a digital image.
- Histogram Equalization: Transforms the histogram to be approximately uniform, enhancing contrast.
- Histogram Matching (Specification): Transforms the histogram to match a specified target histogram.
- Local Histogram Processing: Applies histogram processing to small neighborhoods rather than the entire image.
- Using Histogram Statistics for Image Enhancement: Mean, variance, and other statistics guide enhancement decisions.

📌 Spatial Filtering: Smoothing and Sharpening

- Spatial Filtering: Operations that modify pixels based on the values of their neighbors.
- Smoothing Spatial Filters: Reduce noise and blur edges. Types: Mean filter, Gaussian filter, Median filter.
- Order-Statistic Filters: Nonlinear filters based on ordering pixel values. Median filter is the most common.
- Sharpening Spatial Filters: Highlight fine details and enhance blurred edges.
- Laplacian Filter: Second-order derivative operator. Highlights regions of rapid intensity change.
- Unsharp Masking: Subtracts a blurred version of the image from the original.
- High-boost Filtering: Generalization of unsharp masking with a boost factor $A \geq 1$.
- Using First-Order Derivatives for Nonlinear Sharpening: Gradient operators (Roberts, Prewitt, Sobel).
- Combining Spatial Enhancement Methods: Combining multiple techniques for best results.

📌 Frequency Domain Filters

- Frequency Domain Filters: Operations performed on the Fourier transform of an image.
- Ideal Low-pass Filter: Passes frequencies within a radius D_0 from the center, cuts off all others.
- Butterworth Low-pass Filter: $H(u,v) = \frac{1}{1 + [D(u,v)/D_0]^{2n}}$ where n is the order.
- Gaussian Low-pass Filter: $H(u,v) = e^{-D^2(u,v)/2D_0^2}$. Smooth transition, no ringing.
- Ideal High-pass Filter: $H(u,v) = 1 - H_{LP}(u,v)$. Passes high frequencies, cuts low frequencies.
- Butterworth High-pass Filter: $H(u,v) = \frac{1}{1 + [D_0/D(u,v)]^{2n}}$
- Gaussian High-pass Filter: $H(u,v) = 1 - e^{-D^2(u,v)/2D_0^2}$
- Homomorphic Filtering: Separates illumination and reflectance components. Applies log transform, then filtering.

📌 Color Image Processing

- Color Models: RGB, CMY, HSI, YIQ, YCbCr.
- Pseudo-color Image Processing: Assigns color to gray levels based on a specified mapping.
- Full-color Image Processing: Processes each color component separately or as a vector.
- Color Transformations: Operations on color components to enhance or modify color appearance.
- Color Segmentation: Partitioning an image into regions based on color similarity.

📌 Image Restoration and Reconstruction

- Noise Models: Gaussian, Rayleigh, Erlang, Exponential, Uniform, Salt-and-pepper, Periodic.
- Restoration Filters: Mean filters, Order-statistic filters, Adaptive filters.
- Periodic Noise Reduction: Using frequency domain filtering to remove periodic interference.
- Linear, Position-Invariant Degradations: Degradation model $g = h * f + \eta$ in spatial domain.
- Estimating Degradation Functions: Observation, experimentation, and mathematical modeling.
- Inverse Filtering: $\hat{F}(u,v) = \frac{G(u,v)}{H(u,v)}$. Sensitive to noise.
- Wiener Filtering: Minimum mean square error filter. Balances between inverse filtering and noise smoothing.
- Constrained Least Squares Filtering: Minimizes a smoothness constraint subject to a noise constraint.
- Geometric Mean Filter: $\hat{F}(u,v) = \left[\frac{H^*(u,v)}{|H(u,v)|^2}\right]^{\alpha} \left[\frac{H^*(u,v)}{|H(u,v)|^2 + \beta \frac{S_\eta(u,v)}{S_f(u,v)}}\right]^{1-\alpha} G(u,v)$

📌 Geometric Transformations and Image Registration

- Geometric Transformations: Spatial transformations that modify the spatial relationship between pixels.
- Spatial Transformations: Translation, rotation, scaling, shearing.
- Image Registration: Aligning two or more images of the same scene taken at different times or from different viewpoints.

🔑 PART B: 2 MARKS QUESTIONS & MODEL ANSWERS

Q1. Define image negative and write its transformation function.

Answer: Image negative produces a photographic negative of the image. The transformation function is $s = L - 1 - r$, where L is the number of intensity levels and r is the input pixel intensity. For an 8-bit image, $L = 256$, so $s = 255 - r$.

Q2. What is the purpose of log transformation?

Answer: Log transformation expands the dark pixel values and compresses the bright pixel values. It is used when the dynamic range of the input image is very large. The transformation is $s = c \log(1 + r)$.

Q3. Differentiate between contrast stretching and thresholding.

Answer: Contrast stretching increases the dynamic range of gray levels while preserving all intensity values. Thresholding converts a gray image into a binary image by setting pixels above a threshold to 1 and below to 0.

Q4. What is bit-plane slicing?

Answer: Bit-plane slicing extracts individual bit planes of an image to analyze the contribution of each bit to the overall image. It is useful for image compression and watermarking.

Q5. What is gray-level slicing?

Answer: Gray-level slicing highlights a specific range of gray levels in an image. It can be implemented by setting all pixels within the range to a high value and all others to a low value.

Q6. Write the transfer function for gamma correction.

Answer: $s = c \cdot r^{\gamma}$, where c is a constant and γ is the gamma value. $\gamma < 1$ brightens the image, $\gamma > 1$ darkens it.

Q7. What is the purpose of histogram equalization?

Answer: Histogram equalization transforms the histogram of an image to be approximately uniform, thereby enhancing the contrast of the image.

Q8. How does histogram matching differ from histogram equalization?

Answer: Histogram equalization produces a uniform histogram, while histogram matching (specification) transforms the histogram to match a specified target histogram.

Q9. What is local histogram processing?

Answer: Local histogram processing applies histogram processing to small neighborhoods rather than the entire image. It enhances details in small areas that may be obscured in global processing.

Q10. What are order-statistic filters?

Answer: Order-statistic filters are nonlinear spatial filters based on ordering the pixel values in the neighborhood. The median filter is the most common example.

Q11. What is the purpose of the Laplacian filter?

Answer: The Laplacian filter is a second-order derivative operator used for sharpening. It highlights regions of rapid intensity change and is often combined with the original image.

Q12. What is unsharp masking?

Answer: Unsharp masking subtracts a blurred version of the image from the original to sharpen it. The formula is $g = f - \bar{f}$, where $\bar{f}$ is the blurred image.

Q13. What is high-boost filtering?

Answer: High-boost filtering is a generalization of unsharp masking with a boost factor $A \geq 1$. The formula is $g = A \cdot f - \bar{f}$.

Q14. Why are first-order derivatives used for nonlinear sharpening?

Answer: First-order derivatives (gradient operators like Roberts, Prewitt, Sobel) produce thicker edges and are nonlinear, which can enhance edges more effectively than linear second-order derivatives.

Q15. How can multiple enhancement methods be combined?

Answer: Multiple enhancement methods can be combined by applying them sequentially, such as smoothing followed by sharpening, or using a weighted sum of different enhanced images.

Q16. What is the Ideal Low-pass Filter?

Answer: The Ideal Low-pass Filter passes all frequencies within a radius D_0 from the center of the frequency rectangle and cuts off all frequencies outside. It is defined as $H(u,v) = 1$ if $D(u,v) \leq D_0$, else 0.

Q17. What is the Butterworth Low-pass Filter?

Answer: The Butterworth Low-pass Filter is defined as $H(u,v) = \frac{1}{1 + [D(u,v)/D_0]^{2n}}$, where n is the order. It has a smooth transition between passed and cut-off frequencies.

Q18. What is the Gaussian Low-pass Filter?

Answer: The Gaussian Low-pass Filter is defined as $H(u,v) = e^{-D^2(u,v)/2D_0^2}$. It has a smooth transition and no ringing artifacts.

Q19. What is the Ideal High-pass Filter?

Answer: The Ideal High-pass Filter is defined as $H(u,v) = 1 - H_{LP}(u,v)$, where H_{LP} is the corresponding Ideal Low-pass Filter. It passes high frequencies and cuts off low frequencies.

Q20. What is the Butterworth High-pass Filter?

Answer: The Butterworth High-pass Filter is defined as $H(u,v) = \frac{1}{1 + [D_0/D(u,v)]^{2n}}$.

Q21. What is the Gaussian High-pass Filter?

Answer: The Gaussian High-pass Filter is defined as $H(u,v) = 1 - e^{-D^2(u,v)/2D_0^2}$.

Q22. What is homomorphic filtering?

Answer: Homomorphic filtering separates illumination and reflectance components. It applies a log transform, then filtering, then an exponential transform.

Q23. What is pseudo-color image processing?

Answer: Pseudo-color image processing assigns color to gray levels based on a specified mapping. It is used to enhance visual interpretation of gray-scale images.

Q24. What is full-color image processing?

Answer: Full-color image processing processes each color component separately or as a vector. It is used when color is an inherent property of the image.

Q25. What are color transformations?

Answer: Color transformations are operations on color components to enhance or modify color appearance. They can be performed in different color models.

Q26. What is color segmentation?

Answer: Color segmentation partitions an image into regions based on color similarity. It is used for object detection and image analysis.

Q27. What are the common noise models?

Answer: Common noise models include Gaussian, Rayleigh, Erlang, Exponential, Uniform, Salt-and-pepper, and Periodic noise.

Q28. What are mean filters?

Answer: Mean filters are spatial filters that replace each pixel with the average of its neighborhood. They are used for noise reduction but blur edges.

Q29. What are order-statistic filters?

Answer: Order-statistic filters are nonlinear spatial filters based on ordering pixel values. The median filter is the most common example.

Q30. What are adaptive filters?

Answer: Adaptive filters change their behavior based on local image statistics. They can preserve edges better than non-adaptive filters.

Q31. What is periodic noise reduction?

Answer: Periodic noise reduction uses frequency domain filtering to remove periodic interference. It is effective when the noise has a known frequency pattern.

Q32. What is linear, position-invariant degradation?

Answer: Linear, position-invariant degradation is modeled as $g = h * f + \eta$ in the spatial domain, where h is the degradation function and η is noise.

Q33. How are degradation functions estimated?

Answer: Degradation functions can be estimated by observation, experimentation, or mathematical modeling of the degradation process.

Q34. What is inverse filtering?

Answer: Inverse filtering is $\hat{F}(u,v) = \frac{G(u,v)}{H(u,v)}$. It is sensitive to noise and can amplify noise components.

Q35. What is Wiener filtering?

Answer: Wiener filtering is a minimum mean square error filter that balances between inverse filtering and noise smoothing. It is more robust to noise than inverse filtering.

Q36. What is constrained least squares filtering?

Answer: Constrained least squares filtering minimizes a smoothness constraint subject to a noise constraint. It is used when the noise statistics are known.

Q37. What is the geometric mean filter?

Answer: The geometric mean filter is $\hat{F}(u,v) = \left[\frac{H^*(u,v)}{|H(u,v)|^2}\right]^{\alpha} \left[\frac{H^*(u,v)}{|H(u,v)|^2 + \beta \frac{S_\eta(u,v)}{S_f(u,v)}}\right]^{1-\alpha} G(u,v)$. It is a generalization of inverse and Wiener filtering.

Q38. What are geometric transformations?

Answer: Geometric transformations are spatial transformations that modify the spatial relationship between pixels. They include translation, rotation, scaling, and shearing.

Q39. What is image registration?

Answer: Image registration aligns two or more images of the same scene taken at different times or from different viewpoints. It is used in medical imaging and remote sensing.

🔑 PART C: MEDIUM QUESTIONS & MODEL ANSWERS

Q1. Explain the bit-plane slicing technique in detail. How is it useful in image compression?

Answer: Bit-plane slicing extracts individual bit planes of an image to analyze the contribution of each bit to the overall image. For an 8-bit image, there are 8 bit planes, ranging from the most significant bit (MSB) to the least significant bit (LSB). The MSB plane contains the most visually significant information, while the LSB plane contains fine details and noise. In image compression, bit-plane slicing is useful because the MSB planes can be compressed efficiently, while the LSB planes can be discarded or compressed more aggressively without significant loss of quality.

Q2. Compare contrast stretching and thresholding. Give examples of when each is used.

Answer: Contrast stretching increases the dynamic range of gray levels while preserving all intensity values. It is used when the image has low contrast and the goal is to enhance the visibility of details. Thresholding converts a gray image into a binary image by setting pixels above a threshold to 1 and below to 0. It is used when the goal is to segment the image into foreground and background, such as in document analysis or object detection.

Q3. Derive the transfer function for gamma correction and explain its effect for $\gamma < 1$ and $\gamma > 1$.

Answer: The gamma correction transfer function is $s = c \cdot r^{\gamma}$, where c is a constant and γ is the gamma value. For $\gamma < 1$, the transformation brightens the image by expanding the dark pixel values and compressing the bright pixel values. For $\gamma > 1$, the transformation darkens the image by compressing the dark pixel values and expanding the bright pixel values. For $\gamma = 1$, the transformation is the identity transformation, and the image remains unchanged.

Q4. Explain the process of histogram equalization. Derive the transformation function.

Answer: Histogram equalization transforms the histogram of an image to be approximately uniform, thereby enhancing the contrast of the image. The transformation function is derived from the cumulative distribution function (CDF) of the image. For a discrete image with L gray levels, the transformation function is $s_k = (L-1) \sum_{j=0}^{k} p_r(r_j)$, where $p_r(r_j)$ is the probability of occurrence of gray level r_j. The output gray level s_k is obtained by scaling the CDF by $(L-1)$.

Q5. How does histogram matching differ from histogram equalization? Explain the process.

Answer: Histogram equalization produces a uniform histogram, while histogram matching (specification) transforms the histogram to match a specified target histogram. The process of histogram matching is as follows: (1) Equalize the input image's histogram. (2) Equalize the target histogram. (3) For each gray level in the equalized input image, find the corresponding gray level in the equalized target image. (4) Map the input gray level to the target gray level.

Q6. Explain local histogram processing. When is it useful?

Answer: Local histogram processing applies histogram processing to small neighborhoods rather than the entire image. It is useful when the image has regions with different contrast characteristics, and the goal is to enhance details in small areas that may be obscured in global processing. The process involves moving a window across the image and applying histogram equalization or matching to the pixels within the window.

Q7. Explain the use of statistics for image enhancement. Give examples.

Answer: Statistics such as mean, variance, and other moments can guide enhancement decisions. For example, the mean can be used to adjust the brightness of an image, while the variance can be used to adjust the contrast. Local statistics can be used to adapt the enhancement to different regions of the image. For example, local variance can be used to identify edges and apply sharpening only to those regions.

Q8. Explain the Laplacian filter for image sharpening. Derive the mask coefficients.

Answer: The Laplacian filter is a second-order derivative operator used for sharpening. It highlights regions of rapid intensity change and is often combined with the original image. The Laplacian of a function $f(x,y)$ is defined as $\nabla^2 f = \frac{\partial^2 f}{\partial x^2} + \frac{\partial^2 f}{\partial y^2}$. The discrete approximation of the Laplacian is $\nabla^2 f = f(x+1,y) + f(x-1,y) + f(x,y+1) + f(x,y-1) - 4f(x,y)$. The mask coefficients are $\begin{bmatrix} 0 & 1 & 0 \\ 1 & -4 & 1 \\ 0 & 1 & 0 \end{bmatrix}$.

Q9. Explain unsharp masking and high-boost filtering. How are they related?

Answer: Unsharp masking subtracts a blurred version of the image from the original to sharpen it. The formula is $g = f - \bar{f}$, where $\bar{f}$ is the blurred image. High-boost filtering is a generalization of unsharp masking with a boost factor $A \geq 1$. The formula is $g = A \cdot f - \bar{f}$. When $A = 1$, high-boost filtering reduces to unsharp masking. When $A > 1$, the original image is added back to the sharpened image, preserving more of the original details.

Q10. Explain the use of first-order derivatives for nonlinear sharpening. Why are they nonlinear?

Answer: First-order derivatives (gradient operators like Roberts, Prewitt, Sobel) produce thicker edges and are nonlinear, which can enhance edges more effectively than linear second-order derivatives. They are nonlinear because they involve absolute values or squares of differences, which are nonlinear operations. The gradient magnitude is $\nabla f = \sqrt{G_x^2 + G_y^2}$, where G_x and G_y are the gradients in the x and y directions.

Q11. Explain how multiple enhancement methods can be combined. Give an example.

Answer: Multiple enhancement methods can be combined by applying them sequentially, such as smoothing followed by sharpening, or using a weighted sum of different enhanced images. For example, a common approach is to first apply a smoothing filter to reduce noise, then apply a sharpening filter to enhance edges. Another example is to combine the results of different enhancement techniques using a weighted sum, such as $g = w_1 f_1 + w_2 f_2 + \dots + w_n f_n$, where w_i are weights and f_i are enhanced images.

Q12. Explain the Ideal Low-pass Filter. What is its transfer function? What are its drawbacks?

Answer: The Ideal Low-pass Filter passes all frequencies within a radius D_0 from the center of the frequency rectangle and cuts off all frequencies outside. Its transfer function is $H(u,v) = 1$ if $D(u,v) \leq D_0$, else 0. The drawbacks of the Ideal Low-pass Filter are ringing artifacts and poor smoothing. The ringing artifacts are caused by the sharp cutoff in the frequency domain, which results in oscillations in the spatial domain. The poor smoothing is due to the fact that the filter does not have a smooth transition between passed and cut-off frequencies.

Q13. Explain the Butterworth Low-pass Filter. What is its transfer function? How does it compare to the Ideal Low-pass Filter?

Answer: The Butterworth Low-pass Filter is defined as $H(u,v) = \frac{1}{1 + [D(u,v)/D_0]^{2n}}$, where n is the order. It has a smooth transition between passed and cut-off frequencies. Compared to the Ideal Low-pass Filter, the Butterworth Low-pass Filter has no ringing artifacts and better smoothing. The order n controls the sharpness of the transition. As n increases, the Butterworth filter approaches the Ideal filter.

Q14. Explain the Gaussian Low-pass Filter. What is its transfer function? What are its advantages?

Answer: The Gaussian Low-pass Filter is defined as $H(u,v) = e^{-D^2(u,v)/2D_0^2}$. It has a smooth transition and no ringing artifacts. The advantages of the Gaussian Low-pass Filter are its smooth transition, no ringing artifacts, and good smoothing. It is also easy to implement and has a simple mathematical form.

Q15. Explain the Ideal High-pass Filter. What is its transfer function? What are its drawbacks?

Answer: The Ideal High-pass Filter is defined as $H(u,v) = 1 - H_{LP}(u,v)$, where H_{LP} is the corresponding Ideal Low-pass Filter. It passes high frequencies and cuts off low frequencies. The drawbacks of the Ideal High-pass Filter are ringing artifacts and poor sharpening. The ringing artifacts are caused by the sharp cutoff in the frequency domain, which results in oscillations in the spatial domain. The poor sharpening is due to the fact that the filter does not have a smooth transition between passed and cut-off frequencies.

Q16. Explain the Butterworth High-pass Filter. What is its transfer function? How does it compare to the Ideal High-pass Filter?

Answer: The Butterworth High-pass Filter is defined as $H(u,v) = \frac{1}{1 + [D_0/D(u,v)]^{2n}}$. It has a smooth transition between passed and cut-off frequencies. Compared to the Ideal High-pass Filter, the Butterworth High-pass Filter has no ringing artifacts and better sharpening. The order n controls the sharpness of the transition. As n increases, the Butterworth filter approaches the Ideal filter.

Q17. Explain the Gaussian High-pass Filter. What is its transfer function? What are its advantages?

Answer: The Gaussian High-pass Filter is defined as $H(u,v) = 1 - e^{-D^2(u,v)/2D_0^2}$. It has a smooth transition and no ringing artifacts. The advantages of the Gaussian High-pass Filter are its smooth transition, no ringing artifacts, and good sharpening. It is also easy to implement and has a simple mathematical form.

Q18. Explain homomorphic filtering. What is its purpose? How does it work?

Answer: Homomorphic filtering separates illumination and reflectance components. Its purpose is to enhance the reflectance component while suppressing the illumination component. It works by applying a log transform to the image, then filtering in the frequency domain, then an exponential transform to return to the spatial domain. The log transform converts the multiplicative relationship between illumination and reflectance into an additive relationship, which can be separated by filtering.

Q19. Explain pseudo-color image processing. What is its purpose? How is it implemented?

Answer: Pseudo-color image processing assigns color to gray levels based on a specified mapping. Its purpose is to enhance visual interpretation of gray-scale images. It is implemented by mapping each gray level to a color using a lookup table or a transformation function. The mapping can be based on the intensity, the location, or other properties of the pixel.

Q20. Explain full-color image processing. When is it used?

Answer: Full-color image processing processes each color component separately or as a vector. It is used when color is an inherent property of the image, such as in color photography or color medical imaging. The processing can be performed in different color models, such as RGB, HSI, or YCbCr.

Q21. Explain color transformations. Give examples.

Answer: Color transformations are operations on color components to enhance or modify color appearance. They can be performed in different color models. Examples include adjusting the hue, saturation, or intensity of an image, or applying a color balance correction. For example, to increase the saturation of an image in the HSI model, the saturation component can be multiplied by a constant greater than 1.

Q22. Explain color segmentation. What are the common methods?

Answer: Color segmentation partitions an image into regions based on color similarity. Common methods include thresholding in color space, clustering (such as k-means), and region growing. Thresholding in color space involves setting a range of color values that belong to the object of interest. Clustering groups pixels with similar color values into clusters. Region growing starts from a seed pixel and adds neighboring pixels that have similar color values.

Q23. Explain the common noise models. Derive the probability density function for Gaussian noise.

Answer: Common noise models include Gaussian, Rayleigh, Erlang, Exponential, Uniform, Salt-and-pepper, and Periodic noise. The probability density function for Gaussian noise is $p(z) = \frac{1}{\sigma\sqrt{2\pi}} e^{-(z-\mu)^2/2\sigma^2}$, where μ is the mean and σ is the standard deviation.

Q24. Explain mean filters. What are their advantages and disadvantages?

Answer: Mean filters are spatial filters that replace each pixel with the average of its neighborhood. They are used for noise reduction but blur edges. The advantages of mean filters are their simplicity and good noise reduction. The disadvantages are blurring of edges and poor preservation of details.

Q25. Explain order-statistic filters. What is the median filter? Why is it effective for salt-and-pepper noise?

Answer: Order-statistic filters are nonlinear spatial filters based on ordering pixel values. The median filter is the most common example. It is effective for salt-and-pepper noise because it replaces each pixel with the median of its neighborhood, which is not affected by extreme values (salt and pepper).

Q26. Explain adaptive filters. How do they differ from non-adaptive filters?

Answer: Adaptive filters change their behavior based on local image statistics. They can preserve edges better than non-adaptive filters. Non-adaptive filters apply the same operation to all pixels, regardless of their local characteristics. Adaptive filters, such as the adaptive median filter, adjust their window size or shape based on the local variance or other statistics.

Q27. Explain periodic noise reduction. How is it implemented?

Answer: Periodic noise reduction uses frequency domain filtering to remove periodic interference. It is implemented by identifying the frequencies of the periodic noise in the Fourier spectrum and applying a notch filter or a band-reject filter to suppress those frequencies. The filter is then applied in the frequency domain, and the result is transformed back to the spatial domain.

Q28. Explain linear, position-invariant degradation. Derive the degradation model.

Answer: Linear, position-invariant degradation is modeled as $g = h * f + \eta$ in the spatial domain, where h is the degradation function and η is noise. In the frequency domain, the model is $G(u,v) = H(u,v)F(u,v) + N(u,v)$. The degradation function h is assumed to be linear and position-invariant, meaning that the degradation is the same at all locations in the image.

Q29. Explain how degradation functions are estimated. Give examples.

Answer: Degradation functions can be estimated by observation, experimentation, or mathematical modeling of the degradation process. Observation involves examining the image and identifying the degradation. Experimentation involves applying known degradations to a test image and measuring the result. Mathematical modeling involves deriving the degradation function from the physical properties of the imaging system. For example, the degradation function for motion blur can be modeled as a uniform linear motion.

Q30. Explain inverse filtering. What are its limitations?

Answer: Inverse filtering is $\hat{F}(u,v) = \frac{G(u,v)}{H(u,v)}$. It is sensitive to noise and can amplify noise components. The limitations of inverse filtering are its sensitivity to noise and the fact that it can amplify noise components. It is also not applicable when $H(u,v)$ is zero or very small.

Q31. Explain Wiener filtering. How does it balance between inverse filtering and noise smoothing?

Answer: Wiener filtering is a minimum mean square error filter that balances between inverse filtering and noise smoothing. It is more robust to noise than inverse filtering. The Wiener filter is $\hat{F}(u,v) = \left[\frac{H^*(u,v)}{|H(u,v)|^2 + \frac{S_\eta(u,v)}{S_f(u,v)}}\right] G(u,v)$, where $S_\eta(u,v)$ is the power spectrum of the noise and $S_f(u,v)$ is the power spectrum of the image. The term $\frac{S_\eta(u,v)}{S_f(u,v)}$ controls the balance between inverse filtering and noise smoothing.

Q32. Explain constrained least squares filtering. What is the constraint?

Answer: Constrained least squares filtering minimizes a smoothness constraint subject to a noise constraint. It is used when the noise statistics are known. The constraint is $\|C\hat{f}\|^2 = \|g - H\hat{f}\|^2 = \|\eta\|^2$, where C is a high-pass operator, $\hat{f}$ is the estimate of the original image, g is the degraded image, H is the degradation function, and η is the noise.

Q33. Explain the geometric mean filter. How is it a generalization of inverse and Wiener filtering?

Answer: The geometric mean filter is $\hat{F}(u,v) = \left[\frac{H^*(u,v)}{|H(u,v)|^2}\right]^{\alpha} \left[\frac{H^*(u,v)}{|H(u,v)|^2 + \beta \frac{S_\eta(u,v)}{S_f(u,v)}}\right]^{1-\alpha} G(u,v)$. It is a generalization of inverse and Wiener filtering. When $\alpha = 1$, it reduces to inverse filtering. When $\alpha = 0$ and $\beta = 1$, it reduces to Wiener filtering. When $\alpha = 0$ and $\beta > 1$, it is a parametric Wiener filter.

Q34. Explain geometric transformations. Give examples.

Answer: Geometric transformations are spatial transformations that modify the spatial relationship between pixels. They include translation, rotation, scaling, and shearing. Examples include correcting for camera distortion, aligning images for registration, and creating special effects. For example, a rotation transformation can be used to correct for a tilted camera, and a scaling transformation can be used to zoom in on a region of interest.

Q35. Explain image registration. What are the steps involved?

Answer: Image registration aligns two or more images of the same scene taken at different times or from different viewpoints. It is used in medical imaging and remote sensing. The steps involved are: (1) Feature detection: identify corresponding features in the images. (2) Feature matching: establish correspondences between features. (3) Transformation estimation: estimate the geometric transformation that aligns the images. (4) Image resampling: apply the transformation to the image.

🔑 PART D: LONG QUESTIONS & MODEL ANSWERS

Q1. Explain the complete process of histogram equalization. Derive the transformation function. Illustrate with an example.

Answer: Histogram equalization transforms the histogram of an image to be approximately uniform, thereby enhancing the contrast of the image. The transformation function is derived from the cumulative distribution function (CDF) of the image. For a discrete image with L gray levels, the transformation function is $s_k = (L-1) \sum_{j=0}^{k} p_r(r_j)$, where $p_r(r_j)$ is the probability of occurrence of gray level r_j. The output gray level s_k is obtained by scaling the CDF by $(L-1)$.

Example: Consider a 3-bit image ($L = 8$) with the following histogram:

Gray Level (r_k)	Number of Pixels (n_k)	$p_r(r_k) = n_k / n$
0	790	0.19
1	1023	0.25
2	850	0.21
3	656	0.16
4	329	0.08
5	245	0.06
6	122	0.03
7	81	0.02

Total pixels $n = 4096$.

Cumulative sum:

k	$\sum_{j=0}^{k} p_r(r_j)$	$s_k = (L-1) \times \text{sum}$	Rounded s_k
0	0.19	1.33	1
1	0.44	3.08	3
2	0.65	4.55	5
3	0.81	5.67	6
4	0.89	6.23	6
5	0.95	6.65	7
6	0.98	6.86	7
7	1.00	7.00	7

New gray levels: 0→1, 1→3, 2→5, 3→6, 4→6, 5→7, 6→7, 7→7.

Q2. Explain histogram matching. Derive the transformation function. Illustrate with an example.

Answer: Histogram matching (specification) transforms the histogram of an image to match a specified target histogram. The process is as follows: (1) Equalize the input image's histogram. (2) Equalize the target histogram. (3) For each gray level in the equalized input image, find the corresponding gray level in the equalized target image. (4) Map the input gray level to the target gray level.

Example: Consider a 3-bit image ($L = 8$) with the following histogram:

Gray Level (r_k)	Number of Pixels (n_k)	$p_r(r_k) = n_k / n$
0	790	0.19
1	1023	0.25
2	850	0.21
3	656	0.16
4	329	0.08
5	245	0.06
6	122	0.03
7	81	0.02

Total pixels $n = 4096$.

Equalized input histogram:

k	$\sum_{j=0}^{k} p_r(r_j)$	$s_k = (L-1) \times \text{sum}$	Rounded s_k
0	0.19	1.33	1
1	0.44	3.08	3
2	0.65	4.55	5
3	0.81	5.67	6
4	0.89	6.23	6
5	0.95	6.65	7
6	0.98	6.86	7
7	1.00	7.00	7

Target histogram:

Gray Level (z_k)	$p_z(z_k)$
0	0.00
1	0.00
2	0.00
3	0.15
4	0.35
5	0.35
6	0.15
7	0.00

Equalized target histogram:

k	$\sum_{j=0}^{k} p_z(z_j)$	$s_k = (L-1) \times \text{sum}$	Rounded s_k
0	0.00	0.00	0
1	0.00	0.00	0
2	0.00	0.00	0
3	0.15	1.05	1
4	0.50	3.50	4
5	0.85	5.95	6
6	1.00	7.00	7
7	1.00	7.00	7

Mapping: 0→1, 1→3, 2→5, 3→6, 4→6, 5→7, 6→7, 7→7.

Q3. Explain the bit-plane slicing technique in detail. How is it useful in image compression? Illustrate with an example.

Answer: Bit-plane slicing extracts individual bit planes of an image to analyze the contribution of each bit to the overall image. For an 8-bit image, there are 8 bit planes, ranging from the most significant bit (MSB) to the least significant bit (LSB). The MSB plane contains the most visually significant information, while the LSB plane contains fine details and noise. In image compression, bit-plane slicing is useful because the MSB planes can be compressed efficiently, while the LSB planes can be discarded or compressed more aggressively without significant loss of quality.

Example: Consider a 3-bit image with the following pixel values:

$$\begin{bmatrix} 5 & 3 & 7 \\ 2 & 6 & 1 \\ 4 & 0 & 7 \end{bmatrix}$$

Bit planes:

MSB (bit 2):

$$\begin{bmatrix} 1 & 0 & 1 \\ 0 & 1 & 0 \\ 1 & 0 & 1 \end{bmatrix}$$

Middle bit (bit 1):

$$\begin{bmatrix} 0 & 1 & 1 \\ 1 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

LSB (bit 0):

$$\begin{bmatrix} 1 & 1 & 1 \\ 0 & 0 & 1 \\ 0 & 0 & 1 \end{bmatrix}$$

Q4. Explain the complete process of histogram equalization. Derive the transformation function. Illustrate with an example.

Answer: Histogram equalization transforms the histogram of an image to be approximately uniform, thereby enhancing the contrast of the image. The transformation function is derived from the cumulative distribution function (CDF) of the image. For a discrete image with L gray levels, the transformation function is $s_k = (L-1) \sum_{j=0}^{k} p_r(r_j)$, where $p_r(r_j)$ is the probability of occurrence of gray level r_j. The output gray level s_k is obtained by scaling the CDF by $(L-1)$.

Example: Consider a 3-bit image ($L = 8$) with the following histogram:

Gray Level (r_k)	Number of Pixels (n_k)	$p_r(r_k) = n_k / n$
0