STANDARD CHARTERED · CIB · DATABRICKS

Account Opening Control Tower

Step-by-step implementation guide
Metric views · Genie natural-language analytics · AI/BI dashboard

No SQL required | Genie Code + UI | ~4 hours hands-on

Every step in this guide is either a click path in the Databricks UI or a prompt you paste into Genie Code, the AI assistant built into Databricks. You read what it produces, check it against the green box, and move on.

Prepared by Databricks Solutions Architecture · October 2026 · v1.0

BEFORE YOU BEGIN

How to read this guide

Each step has a dark header saying what you are building and why. Under it, numbered sub-steps are tagged with one of three badges:

UI	Click through the Databricks interface. The blue box tells you exactly where.
Genie Code prompt	Copy the text in the orange box and paste it into Genie Code (the sparkle icon on the right edge of the screen, or `Cmd/Ctrl + I`). Replace anything in `<angle brackets>` with your own values from Step 0.3.
Business sign-off	Pause and get the business owner to confirm before continuing.
WHAT YOU SHOULD SEE	The expected result. If you see this, continue.
IF IT DOESN'T LOOK RIGHT	A fix, usually another prompt.
STOP HERE IF	A result that means a business rule is wrong. Do not continue past it without talking to the business owner.

Who does what

Who	Does	Time
Platform admin (once)	Step 0 — permissions, upload the package, SQL warehouse	20 min
Implementer (you)	Steps 1–7 — everything else in this guide	~3.5 hours
Business owner / KPI owner	Signs off the 10 known cases (2.4), supplies real user questions (5.8), runs UAT (8)	2 hours

The roadmap

0 Prepare — Permissions, upload package, note your names — 20 min

1 Check data — Create schema, profile raw table, confirm formats — 20 min

2 Silver views — Reference tables, typed views, validate, sign off — 45 min

3 Metric views — Governed KPI definitions for TAT, FTR, SLA — 20 min

4 Semantics — Column descriptions so Genie understands — 10 min

5 Genie space — Instructions, expressions, examples, benchmarks — 60 min

6 Dashboard — Six pages built page-by-page from the spec — 60 min

7 Security — Country-level row access — 15 min

8 Go live — UAT checklist and weekly review — 60 min

What you are building

The ingested account-opening table stays untouched. On top of it sit two **Silver views** (one row per task, one row per case) that apply the business rules once. Two **metric views** in Unity Catalog hold the governed KPI definitions. Both the **dashboard** and the **Genie space** read from those metric views, so a number on a chart and an answer to a typed question always agree.

Layer	Objects	Why
Bronze	`<raw_table>`	Already ingested. Never modified.
Reference	`ref_role_team`, `ref_market_cutoff`, `ref_user_entitlement`	Business rules as data — change a row, not code
Silver	`v_task_events`, `v_case_summary`	Typed timestamps, referral flags, TAT, FTR, SLA due dates
Gold	`mv_onboarding_kpis`, `mv_task_kpis`	Governed KPIs with synonyms for Genie
Consumption	Dashboard + Genie space	Same definitions, two interfaces

REFERENCE

The business rules this solution encodes

Confirmed with the CIB business owner on 22 October 2026. If any of these change, see Appendix A for the one-line prompt that updates it.

KPI	Rule
Case status	`Case_stage` is one of Completed, Pending, Cancelled. `Task_Status` is Open or Closed.
Volumes	Count every case regardless of status.
Turnaround time (TAT)	Completed cases only. From the *first task start* to the *last task end*. Calendar hours — weekends, holidays and client wait time all count. Initiated time is *not* the start.
Referral back	A queue returns the case to an earlier queue. In the data this is a *new task row* on the receiving queue with `Reason` populated. Reason is empty on normal rows.
First time right (FTR)	A Completed case with zero referrals.
SLA due date	Initiated before 16:00 market-local → due the same day. Initiated at or after 16:00 → due the next calendar day. Cases received after cutoff are *not* breaches.
SLA breach	Not Completed by end of the due date. Excluded from SLA: Cancelled cases, and cases referred back to the Request Initiator.
Teams	Request Initiator → Client Manager. Request Processor/Checker, Core Banking, Cheque Book, Signatory makers and checkers → CLM Ops. S2B Channel maker/checker → Channels. SLA applies to CLM Ops (Channels to be confirmed).
Default dimensions	Geography = `Booking_Location`. Time = initiated date. `Client_tier` is a priority dimension. Segment/Sub-segment describe the client, not the product.

STEP 0

Before you start

Get permissions, upload the package, and write down the four names every prompt will use.

0.1 Check your permissions UI

WHERE TO CLICK

1. **Catalog** (left nav) → your target catalog → **Permissions** tab.
2. Confirm you have: `USE CATALOG`, `USE SCHEMA`, `CREATE TABLE`, `CREATE VIEW`, `CREATE FUNCTION`.
3. You also need **Can Use** on a SQL warehouse and the ability to create Genie spaces and dashboards (standard for Databricks SQL users).

IF IT DOESN'T LOOK RIGHT

Ask your platform admin to grant anything missing before continuing.

0.2 Upload the implementation package UI

WHERE TO CLICK

1. Download the `scb_onboarding` folder you were given (contains `sql/`, `genie/`, `dashboard/`).
2. **Workspace** (left nav) → your home folder → ⋮ → **Import** → drag the folder or zip in.
3. You should now have `/Workspace/Users/<you>/scb_onboarding/`.

WHAT YOU SHOULD SEE

Genie Code can read these files when you point it to them. You never copy-paste SQL by hand.

0.3 Write down your four names UI

Every prompt in this guide uses these placeholders. Fill in the right-hand column now.

Placeholder	Example	Yours
`<catalog>`	`scb_cib`	_____
`<schema>`	`account_opening`	_____
`<raw_table>`	`acct_opening_raw` — the ingested table	_____
`<warehouse>`	`Serverless Starter Warehouse`	_____
`<you>`	your login email, as shown in the Workspace path	_____

TIP

1. To find the raw table name: **Catalog** → browse to the table → copy its three-part name from the top of the page.

0.4 Open the SQL Editor UI

WHERE TO CLICK

1. **SQL Editor** (left nav) → **+ New query**.
2. Pick `<warehouse>` in the top-right dropdown.
3. Open Genie Code with the sparkle icon on the right edge. You will stay here for Steps 1–4.

STEP 1

Prepare the schema and check the raw data

Create a home for the new objects and make sure the data looks the way the business described it.

1.1 Create the schema Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Create a schema called <schema> in catalog <catalog> if it does not already exist, with the
comment "CIB account opening analytics — Silver views, metric views and reference data". Then set
it as the current catalog and schema for this session and confirm.
```

WHAT YOU SHOULD SEE

A `CREATE SCHEMA IF NOT EXISTS …` statement runs successfully.

1.2 Profile the raw table Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Look at the table <catalog>.<schema>.<raw_table>. Tell me:
(1) the row count,
(2) the distinct values and counts for the columns Case_stage, Task_Status, Role, Client_tier,
Segment and Booking_Location,
(3) five sample values each of Initiated_time, Start_time and End_time so I can see the timestamp
format,
(4) how many rows have _rescued_data populated.
Show the results as tables. Do not change anything.
```

WHAT YOU SHOULD SEE

Value lists for each column. **Save this output** — you will paste it into the Genie space in Step 5.5.

Column	Expected values	If different
`Case_stage`	Completed, Pending, Cancelled	Note the exact spelling — you will need it
`Task_Status`	Open, Closed	Note the exact spelling
`Role`	The 11 roles from Request Initiator to S2B Channel Checker	Any role not in the list → tell the business owner before Step 2
Timestamps	A consistent format, e.g. `2026-10-22 14:05:33`	Unusual format → do Step 1.3

1.3 Fix the timestamp format (only if 1.2 showed something unusual) Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Open the file /Workspace/Users/<you>/scb_onboarding/sql/01_reference_tables.sql. The function
parse_ts lists the timestamp formats it can read. The raw data uses this format: <paste one
sample, e.g. 22-OCT-2026 14:05:33>. Add a matching try_to_timestamp pattern as the FIRST entry in
the COALESCE and show me the edited function. Do not run it yet.
```

STEP 2

Reference tables and Silver views

Apply the business rules once, in two views, and prove they are right on cases the business already knows.

2.1 Create the reference tables and helper function Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Open /Workspace/Users/<you>/scb_onboarding/sql/01_reference_tables.sql. Replace every occurrence of scb_cib.account_opening with <catalog>.<schema>, "USE CATALOG scb_cib" with "USE CATALOG <catalog>", "USE SCHEMA account_opening" with "USE SCHEMA <schema>", and acct_opening_raw with <raw_table>. Then run the whole script. Afterwards show me the contents of ref_role_team and ref_market_cutoff.
```

WHAT YOU SHOULD SEE

11 rows in `ref_role_team` (each role mapped to Client Manager, CLM Ops or Channels) and one row per booking location in `ref_market_cutoff`, all showing `16:00:00`.

IF IT DOESN'T LOOK RIGHT

If your Role values are spelled differently from the 11 in the table (for example `CORE_BANKING_MAKER`), paste this:

FIX PROMPT — ONLY IF ROLES DIFFER

```
In <catalog>.<schema>.ref_role_team the role column must match the raw data exactly. The raw values are: <paste the Role list from Step 1.2>. Update the table so each raw value maps to the right team using this logic: Request Initiator → Client Manager; Processor, Checker, Core Banking, Cheque Book and Signatory roles → CLM Ops; S2B roles → Channels. Keep role_order in process sequence. Show me the result.
```

2.2 Create the Silver views Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Open /Workspace/Users/<you>/scb_onboarding/sql/02_silver_views.sql. Apply the same replacements as before (scb_cib.account_opening → <catalog>.<schema>, the catalog and schema in the USE statements, acct_opening_raw → <raw_table>). If the raw column for cheque book is not exactly Cheque_book_required, replace it with the real column name. Then run the script and confirm both views v_task_events and v_case_summary were created. Finally run: SELECT * FROM v_case_summary LIMIT 5
```

WHAT YOU SHOULD SEE

Two views created. Five case rows with columns such as `case_tat_hrs`, `is_ftr`, `sla_due_date`, `is_sla_breach`.

2.3 Validate the data Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Open /Workspace/Users/<you>/scb_onboarding/sql/05_validation.sql, apply the catalog and schema replacements, and run queries 1 to 8 one at a time. For each, show me the result and one line saying whether it looks healthy. Flag anything where more than 1% of timestamps failed to parse, where a Role is missing from ref_role_team, where Reason appears on a case's first task, or where any task duration is negative.
```

Check	Healthy	If not
Q1 — unparsed timestamps	≈ 0	Go back to 1.3, add the format, re-run 2.1 and 2.2
Q4 — roles not mapped	0 rows	Run the fix prompt in 2.1
Q5 — `reason_on_first_task`	0	See the red box
Q8 — negative durations	0 or a handful	Note the case numbers for the data team; proceed

STOP HERE IF

Q5 is greater than zero. It means Reason is sometimes populated on a case's first task, so "Reason present = referral" does not hold and the FTR logic must change. Tell the business owner and your Databricks contact before going further.

2.4 Sign off on ten known cases Business sign-off

Ask the business owner for **5 case numbers they know were straight-through** and **5 they know were referred back**. Then:

PROMPT — PASTE INTO GENIE CODE

```
From <catalog>.<schema>.v_case_summary show case_no, case_stage, initiated_ts, first_start_ts,
last_end_ts, case_tat_hrs, referral_count, is_ftr, received_after_cutoff, sla_due_date and
is_sla_breach for these cases: <paste the 10 case numbers>. Then, for the first referred case,
show its full task history from v_task_events ordered by task_seq.
```

WHAT YOU SHOULD SEE

Walk through the output with the business owner. The 5 straight-through cases show `is_ftr = true` and `referral_count = 0`; the 5 referred cases show the opposite, and the task history shows the referral row with its Reason.

STOP HERE IF

The business owner disagrees with any TAT, FTR or SLA flag. Everything downstream inherits these rules. Resolve the disagreement first.

STEP 3

Metric views — the governed KPI definitions

Put the four KPIs in Unity Catalog once, with synonyms, so the dashboard and Genie can never disagree.

3.1 Create the case-level metric view Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Open /Workspace/Users/<you>/scb_onboarding/sql/03_mv_onboarding_kpis.sql. Replace
scb_cib.account_opening with <catalog>.<schema> everywhere, including inside the YAML "source:"
line. Run it. If the workspace rejects "version: 1.1", change it to "version: 1.0", remove all
"synonyms:" lines, run again, and tell me you did that. Confirm mv_onboarding_kpis exists.
```

3.2 Create the task-level metric view Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Do the same for /Workspace/Users/<you>/scb_onboarding/sql/04_mv_task_kpis.sql and confirm
mv_task_kpis exists.
```

3.3 Smoke-test the KPIs Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Run validation query 9 from 05_validation.sql (the two metric view queries). Then tell me in plain
English: total cases, completed cases, overall FTR rate, overall SLA breach rate, and the team
with the biggest backlog.
```

WHAT YOU SHOULD SEE

Sensible numbers: FTR somewhere between 0 and 100%, breach rate well below 100%, backlog concentrated in CLM Ops roles.

IF IT DOESN'T LOOK RIGHT

FTR exactly 0% or exactly 100% almost always means the Reason rule is wrong. Revisit 2.3 Q5.

3.4 Certify the views UI

WHERE TO CLICK

1. **Catalog** → `<catalog>.<schema>` → `mv_onboarding_kpis` → ⋮ → **Certify** (if your workspace offers certification).
2. Repeat for `mv_task_kpis` and `v_case_summary`.

WHAT YOU SHOULD SEE

A certified badge next to the three objects in Genie and in the dashboard dataset picker.

STEP 4

Column semantics

Teach Genie what every column means and when not to use it.

4.1 Apply comments and tags UI

WHERE TO CLICK

1. **Workspace** → `scb_onboarding/genie/` → open `05_column_semantics.sql`. It opens in the file editor.
2. Press `Cmd/Ctrl + F`, turn on **Replace**, and replace `scb_cib` with `<catalog>` and `account_opening` with `<schema>` (Replace All for each).
3. Select the whole file (`Cmd/Ctrl + A`), copy, and paste it into a new query in the **SQL Editor** with `<warehouse>` attached.
4. Click **Run all**. The statements run one after another; it takes under a minute.

WHAT YOU SHOULD SEE

About 50 `COMMENT ON COLUMN` statements and three `ALTER VIEW … SET TAGS` statements succeed. Open **Catalog** → `v_case_summary` → **Columns** tab — every column now has a description.

IF IT DOESN'T LOOK RIGHT

One statement fails with "column does not exist"? That column name differs in your data (most likely the cheque-book column). Delete that single line and run again; nothing else depends on it.

STEP 5

Genie space — natural-language questions

Create the space, load the semantics, and measure accuracy with benchmarks before anyone uses it.

5.1 Create the space UI

WHERE TO CLICK

1. Left nav → **Genie** → **+ New** → **Genie space**.
2. Title: `CIB Account Opening Analytics`.
3. Add data **in this order**: `mv_onboarding_kpis`, then `mv_task_kpis`, then `v_case_summary`.
4. **Do not add** the raw table, `v_task_events` or any `ref_` table.
5. Warehouse: `<warehouse>`. Save.

5.2 Open Genie Code inside the space UI

WHERE TO CLICK

1. In the space, click **Configure** (top right).
2. Open the Genie Code panel (sparkle icon). It can now edit this space's settings directly.
3. Every prompt in 5.3 to 5.8 is pasted here, not in the SQL Editor.

5.3 Description, sample questions and general instructions Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Open /Workspace/Users/<you>/scb_onboarding/genie/01_space_setup.md. Apply to this Genie space: (1) the Description from section 2, (2) the five Sample questions from section 2, (3) the General instructions text block from section 3, exactly as written. Show me what you set.
```

5.4 SQL expressions Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Open /Workspace/Users/<you>/scb_onboarding/genie/02_sql_expressions.sql. Each block is a SQL expression for this space's knowledge store: the comment line gives the type (FILTER, MEASURE or DIMENSION), the name, and a "use when the user says" description; the SQL below it is the expression. Add all of them to this space with those names and descriptions. Where a block is marked "(mv_task_kpis)" attach it to that table; otherwise attach it to v_case_summary. List what you added.
```

WHAT YOU SHOULD SEE

Roughly 20 filters, 7 measures and 5 dimensions listed under Configure → Instructions → SQL expressions.

5.5 Value dictionaries Genie Code prompt

This is the single highest-impact accuracy step. It stops Genie guessing *SG* vs *Singapore* or *PLAT* vs *Platinum*.

PROMPT — PASTE INTO GENIE CODE

```
For the data assets in this space, add the following as the known values for these columns so you never guess literals:
<paste the Step 1.2 output for Case_stage, Task_Status, Role, Client_tier, Segment and Booking_Location>
Also add Team values: Client Manager, CLM Ops, Channels. Mark Platinum (or your equivalent top tier) as the highest-priority tier in its description.
```

5.6 Example queries Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Open /Workspace/Users/<you>/scb_onboarding/genie/03_example_queries.sql. Each "-- Q:" line is a user question and the SQL below it is the correct answer. Replace any literal values marked "confirm literal" (such as 'Singapore' or 'Platinum') with the real values from the value dictionary you just added. Then add all pairs as Example SQL queries in this space.
```

5.7 Load benchmarks and run them Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Open /Workspace/Users/<you>/scb_onboarding/genie/04_benchmarks.json. For every entry that has expected_sql, create a benchmark in this space with the question and that SQL as the expected answer, after replacing the literals listed in confirm_literals with real values. For entries that only have expected_behaviour, add the question as a benchmark with no SQL and put the expected behaviour in the notes. Then run all benchmarks and give me the pass rate and the list of failures.
```

WHAT YOU SHOULD SEE

A pass rate. **Target is 90% or higher** before UAT.

IF IT DOESN'T LOOK RIGHT

For each failure, paste this and let Genie Code triage it:

FIX PROMPT — ONE PER FAILED BENCHMARK

```
Benchmark <id> failed. Compare Genie's SQL with the expected SQL and tell me whether the fix belongs in (a) a metric view synonym or comment, (b) a value dictionary entry, (c) a SQL expression, or (d) an example query. Recommend the smallest change and apply it if it is (b), (c) or (d). If it is (a), give me the exact ALTER VIEW or YAML change to run in the SQL Editor.
```

Re-run the benchmarks after each round of fixes. Stop when you are at 90% or better and understand the remaining failures.

5.8 Replace the seed questions with the real ones Business sign-off

When the business owner sends the list of questions users actually ask:

PROMPT — PASTE INTO GENIE CODE

```
Here are the questions our users actually ask: <paste the business owner's list>. For each one, write the correct SQL against the assets in this space, add it as a benchmark, and run it. Report the pass rate and the failures.
```

5.9 Share the space UI

WHERE TO CLICK

1. Space → **Share**.
2. Add the operations and management groups with **Can Run**.
3. Add two named owners with **Can Edit**.

STEP 6

Dashboard

Six pages built one at a time from the spec, reading the same metric views as Genie.

6.1 Create the dashboard and add the metric-view datasets UI

WHERE TO CLICK

1. Left nav → **Dashboards** → **Create dashboard**. Name it `CIB Account Opening Control Tower`.
2. Open the **Data** tab → **+ Add data** → choose `<catalog>.<schema>.mv_onboarding_kpis` (shown as a metric view). Rename the dataset to `kpi`.
3. Repeat for `mv_task_kpis` → rename to `task`.
4. Still in the Data tab, open Genie Code (sparkle icon) and paste the prompt below.

Why add metric views directly? Filtering the dashboard by tier or market then recomputes rates from the underlying cases instead of averaging pre-computed percentages.

6.1 (cont.) Add the SQL datasets Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Open /Workspace/Users/<you>/scb_onboarding/dashboard/02_datasets.sql. It contains six named SQL datasets: cases, funnel, kpi_prev, reasons, journey and last_updated. Create each one as a dataset in this dashboard with that exact name, after replacing scb_cib.account_opening with <catalog>.<schema>. Create the dashboard parameters they use: date_from (date, default 30 days ago), date_to (date, default today) and case_no (string, default empty). Run each dataset once to confirm it returns rows.
```

WHAT YOU SHOULD SEE

Eight datasets in the Data tab: `kpi`, `task`, `cases`, `funnel`, `kpi_prev`, `reasons`, `journey`, `last_updated`.

6.2 Build Page 1 Genie Code prompt

FIRST

1. Switch to the **Canvas** tab. Open Genie Code (sparkle icon).

PROMPT — PASTE INTO GENIE CODE

```
Open /Workspace/Users/<you>/scb_onboarding/dashboard/01_dashboard_spec.md. Build "Page 1 — Executive Summary" exactly as specified in that section: create the page, add every widget in the table using the dataset, type, measures and dimensions listed, apply the formatting from the "Formatting & conventions" section, and arrange them using the Layout line. Add the global filters from the "Global filters" section to the top of the page, bound to the kpi and cases datasets. When done, list the widgets you created.
```

WHAT YOU SHOULD SEE

Four KPI counters across the top, a status donut, two trend charts, a market scorecard table and a heatmap — all showing numbers.

6.2 (cont.) Build Pages 2 to 6 Genie Code prompt

Paste each of these in turn. Wait for one page to finish and check it renders before starting the next.

PAGE 2

```
Using the same spec file, build "Page 2 — Pipeline & Backlog" as specified, including the global filters.
```

PAGE 3

```
Using the same spec file, build "Page 3 — Turnaround Time" as specified, including the global filters. Fix the status filter on this page to Completed, as the spec says.
```

PAGE 4

```
Using the same spec file, build "Page 4 — First Time Right" as specified, including the global filters. If a Sankey widget is not available in this workspace, use the heatmap table fallback described in the spec for widget 4.9.
```

PAGE 5

```
Using the same spec file, build "Page 5 — SLA" as specified, including the global filters.
```

PAGE 6

```
Using the same spec file, build "Page 6 — Case Explorer" as specified. Bind widget 6.1 to the case_no parameter and widget 6.3 to the journey dataset. Leave space on the right for the Genie panel.
```

IF IT DOESN'T LOOK RIGHT

A widget shows no data? Paste this:

FIX PROMPT — BLANK WIDGET

```
Widget <name> on page <n> shows no data. Check which dataset and fields it uses, run the underlying query, and fix the binding or the query.
```

6.3 Connect Genie to the dashboard UI

WHERE TO CLICK

1. Dashboard → ⋮ → **Settings** (or the Genie icon in the toolbar) → **Genie space**.
2. Choose `CIB Account Opening Analytics` — the space you configured in Step 5, **not** the auto-generated one.

6.4 Publish UI

WHERE TO CLICK

1. **Publish** → select **Don't embed credentials** so each viewer's row-level security applies.
2. **Publish**. Then **Share** with the same groups as the Genie space.

WHAT YOU SHOULD SEE

The published link opens for an operations user and shows data for their market only (after Step 7).

STEP 7

Security — operational users see only their markets

Global heads see everything; country teams see their own bookings. One table controls it.

7.1 Fill the entitlement table Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Insert rows into <catalog>.<schema>.ref_user_entitlement.
Global users who see everything: <list of user emails or group names> with is_global = TRUE.
Operational users: <user or group → booking location pairs, e.g. sg-ops-team → Singapore> with
is_global = FALSE.
Show me the table afterwards.
```

7.2 Attach the row filter Genie Code prompt

PROMPT — PASTE INTO GENIE CODE

```
Attach the row filter function <catalog>.<schema>.rf_booking_location to the table <catalog>.
<schema>.<raw_table> on its Booking_Location column so that every view built on it inherits the
restriction. Then confirm by running SELECT DISTINCT booking_location FROM <catalog>.
<schema>.v_case_summary and tell me what I, as the current user, can see.
```

WHAT YOU SHOULD SEE

Ask one operational user and one global user to open the dashboard. The first sees one market; the second sees all.

STEP 8

UAT and go-live

One hour with the business owner, then a weekly habit.

8.1 UAT checklist Business sign-off

#	Test	Pass
1	Page 1 total cases this month matches the existing manual report (allowing for known exclusions)	☐
2	The 10 known cases from Step 2.4 show correct TAT, FTR and SLA flags in Case Explorer	☐
3	FTR rate on Page 4 matches the business's current calculation for the same period	☐
4	A case initiated after 16:00 shows `sla_due_date` = next day and is **not** breached	☐
5	A case referred back to Request Initiator is **excluded** from the SLA population	☐
6	Operational user sees only their market; global user sees all	☐
7	Ask Genie the 5 sample questions — answers match the dashboard numbers	☐
8	Ask Genie "which RM has the most breaches" — it says RM names are not in the data	☐

8.2 Go-live habits UI

SET UP

1. Nominate one owner to check the Genie space **Monitoring** tab every Monday for thumbs-down answers, and re-run benchmarks (prompt 5.7) after any change.
2. In the SQL Editor, record what was deployed:

PROMPT — PASTE INTO GENIE CODE

```
Show me the current definitions of mv_onboarding_kpis and mv_task_kpis and save them to
/Workspace/Users/<you>/scb_onboarding/deployed/ with today's date in the filename.
```

APPENDIX A

Changing the rules later

All of these are run in the SQL Editor with Genie Code, unless stated.

Change	Prompt
A market gets a different cutoff	`Update ref_market_cutoff: set cutoff_local_time to '15:00:00' for booking_location 'Hong Kong'.`
A new role appears in the data	`Add role '<name>' to ref_role_team mapped to team '<team>' with role_order <n> and sla_applicable <true/false>.`
SLA should also apply to Channels	`Set sla_applicable = TRUE for the Channels team in ref_role_team.`
Users call a KPI by a new name	`In the metric view mv_onboarding_kpis, add the synonym 'cycle time' to the measure avg_tat_hrs and recreate the view.`
A Genie question keeps failing	In the Genie space → Genie Code: use the fix prompt from 5.7
Dashboard has become slow	`Convert v_case_summary into a materialized view refreshed every 15 minutes, keeping the same name and columns.`
FTR / SLA targets agreed	In the dashboard → Genie Code: `Add a reference line at <x>% on widgets 1.3, 4.1 and 5.1 and colour the counters red below it.`

APPENDIX B

Troubleshooting prompts

Symptom	Paste into Genie Code
"Permission denied"	`Tell me which privilege is missing for this statement and who can grant it.`
Metric view will not create	`Explain this error. If it is the YAML version, downgrade to 1.0 and remove synonyms; if it is a measure expression, show me which one and propose a fix.`
Numbers differ from the old report	`Compare the row count and completed-case count in v_case_summary for <month> against <raw_table> grouped by Case_stage, and list any cases present in one but not the other.`
Genie gives a wrong answer	`Show me the SQL you generated, explain which instruction or example you used, and tell me what context would have made you choose the right table or measure.`

APPENDIX C

Glossary

Term	Meaning
Case	One client request to open one or more accounts
Task	One unit of work on a case by one role; a case has many tasks
Referral back	A queue returns the case to an earlier queue; creates a new task row with a Reason
FTR	First Time Right — a Completed case with zero referrals
TAT	Turnaround time — first task start to last task end, calendar hours, Completed cases only
SLA due date	Initiated date if initiated before 16:00 local, otherwise the next day
Metric view	A governed KPI definition in Unity Catalog; dashboard and Genie both read it so numbers agree
Genie space	The natural-language question interface for business users
Genie Code	The AI assistant that writes and runs code for you inside Databricks
Benchmark	A test question with a known correct answer, used to measure Genie's accuracy
Value dictionary	The list of real values in a column, given to Genie so it never guesses spellings
Row-level security	A filter that limits which rows each user can see, applied once at the table and inherited everywhere

APPENDIX D

Package contents

File	Used in step	What it is
`sql/01_reference_tables.sql`	2.1	Timestamp parser, role→team map, market cutoffs, entitlement table, row filter
`sql/02_silver_views.sql`	2.2	`v_task_events` and `v_case_summary`
`sql/03_mv_onboarding_kpis.sql`	3.1	Case-level metric view
`sql/04_mv_task_kpis.sql`	3.2	Task/queue-level metric view
`sql/05_validation.sql`	2.3, 3.3	Ten validation queries
`genie/01_space_setup.md`	5.3	Description, sample questions, general instructions
`genie/02_sql_expressions.sql`	5.4	Reusable filters, measures, dimensions
`genie/03_example_queries.sql`	5.6	18 question → SQL pairs
`genie/04_benchmarks.json`	5.7	35 test questions with expected answers
`genie/05_column_semantics.sql`	4.1	Column descriptions and tags
`dashboard/01_dashboard_spec.md`	6.2	Six-page widget-by-widget specification
`dashboard/02_datasets.sql`	6.1	Six SQL datasets with parameters

Prepared by Databricks Solutions Architecture for Standard Chartered Bank, CIB. Business rules as confirmed on 22 October 2026. Questions: contact your Databricks account team.