

Lecture notes on Python Programming

By Jason Pandian

Assistant Professor, Department of Information Technology

LISTS, TUPLES DICTIONARIES AND FUNCTIONS

Lists: list operations, list slices, list methods, list loop, mutability, aliasing, cloning lists, list parameters- Tuples: tuple assignment, tuple as return value- Dictionaries: operations and methods, advanced list processing - list comprehension. Functions and User Defined Functions: Simple and Mathematical Built-in Functions, Recursion -Illustrative Problems

What is List?

- In Python, a list is a versatile data structure used to store a collection of items.
- Lists are ordered, mutable (modifiable), and can contain elements of different data types, including other lists. - They are denoted by square brackets [], with elements separated by commas.

List Basic Examples

```
In [ ]: # Define a list containing integers
my_list = [1, 2, 3, 4, 5]

# Accessing elements of a list using index
print(my_list[0]) # Output: 1

# Define a list containing strings
fruits = ['apple', 'banana', 'orange', 'grape']

# Modifying elements of a list
fruits[0] = 'pear'
print(fruits)      # Output: ['pear', 'banana', 'orange', 'grape']

# Define a list containing mixed data types
```

```

mixed_list = [1, 'hello', 3.14, True]

# List concatenation
new_list = my_list + fruits
print(new_list)    # Output: [1, 2, 3, 4, 5, 'pear', 'banana', 'orange', 'gr

# List slicing
print(my_list[1:3]) # Output: [2, 3]

# Length of a list
print(len(my_list)) # Output: 5

# Nested lists (list containing lists)
nested_list = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]

```

List Operations

Appending Elements `append()`: Adds an element to the end of the list.

```

In [ ]: my_list = [1, 2, 3]
        my_list.append(4)
        print(my_list) # Output: [1, 2, 3, 4]

```

Extending Lists:

`extend()`: Appends elements from another list to the end of the list.

```

In [ ]: my_list = [1, 2, 3]
        another_list = [4, 5, 6]
        my_list.extend(another_list)
        print(my_list) # Output: [1, 2, 3, 4, 5, 6]

```

Inserting Elements:

`insert()`: Inserts an element at a specified position.

```

In [ ]: my_list = [1, 2, 3]
        my_list.insert(1, 5)
        print(my_list) # Output: [1, 5, 2, 3]

```

Removing Elements:

`remove()`: Removes the first occurrence of a specified value.

```

In [ ]: my_list = [1, 2, 3, 4, 3]
        my_list.remove(3)
        print(my_list) # Output: [1, 2, 4, 3]

```

Popping Elements:

pop(): Removes and returns the element at a specified index. If no index is specified, it removes and returns the last element.

```
In [ ]: my_list = [1, 2, 3]
        popped_element = my_list.pop(1)
        print(my_list)      # Output: [1, 3]
        print(popped_element) # Output: 2
```

Indexing:

index(): Returns the index of the first occurrence of a specified value.

```
In [ ]: my_list = [1, 2, 3, 4, 3]
        index = my_list.index(3)
        print(index) # Output: 2
```

Counting:

count(): Returns the number of occurrences of a specified value.

```
In [ ]: my_list = [1, 2, 3, 4, 3]
        count = my_list.count(3)
        print(count) # Output: 2
```

Sorting :

sort(): Sorts the list in ascending order.

```
In [ ]: my_list = [3, 1, 4, 2]
        my_list.sort()
        print(my_list) # Output: [1, 2, 3, 4]
```

Reversing:

reverse(): Reverses the order of the elements in the list.

```
my_list = [1, 2, 3, 4] my_list.reverse() print(my_list) # Output: [4, 3, 2, 1]
```

Copying Lists:

copy(): Returns a shallow copy of the list.

```
In [ ]: my_list = [1, 2, 3]
        copied_list = my_list.copy()
        print(copied_list) # Output: [1, 2, 3]
```

```
In [ ]: # Define a list
        my_list = [1, 2, 3, 4, 5]

        # Append method: adds an element to the end of the list
        my_list.append(6)
        print("After appending 6:", my_list)

        # Extend method: appends elements from another list to the end of the list
        another_list = [7, 8, 9]
        my_list.extend(another_list)
        print("After extending with [7, 8, 9]:", my_list)

        # Insert method: inserts an element at a specified position
        my_list.insert(2, 10)
        print("After inserting 10 at index 2:", my_list)

        # Remove method: removes the first occurrence of a specified value
        my_list.remove(3)
        print("After removing the first occurrence of 3:", my_list)

        # Pop method: removes and returns the element at a specified index, or the last element
        popped_element = my_list.pop(4)
        print("Popped element:", popped_element)
        print("After popping the element at index 4:", my_list)

        # Index method: returns the index of the first occurrence of a specified value
        index_of_2 = my_list.index(2)
        print("Index of 2:", index_of_2)

        # Count method: returns the number of occurrences of a specified value
        count_of_5 = my_list.count(5)
        print("Count of 5:", count_of_5)

        # Sort method: sorts the list in ascending order
        my_list.sort()
        print("After sorting:", my_list)

        # Reverse method: reverses the order of the elements in the list
        my_list.reverse()
        print("After reversing:", my_list)

        # Copy method: returns a shallow copy of the list
        copied_list = my_list.copy()
        print("Copied list:", copied_list)
```

```
In [ ]: name = 'hello'
        name[0:2]
```

List slices

In Python, list slices allow you to access a subset of elements from a list. They provide a convenient way to work with a portion of a list without modifying the original list. Here's how you can use list slices in Python:

```
In [2]: # Create a sample list
my_list = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]

# Basic slicing: [start:stop:step]
# Access elements from index 2 to index 5 (exclusive)
slice_1 = my_list[0:2]
print("Slice 1:", slice_1)
```

Slice 1: [1, 2]

```
In [3]: my_list = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
# Access elements from the beginning to index 6 (exclusive)
slice_2 = my_list[:6]
print("Slice 2:", slice_2)
```

Slice 2: [1, 2, 3, 4, 5, 6]

```
In [4]: my_list = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
# Access elements from index 3 to the end
slice_3 = my_list[3:]
print("Slice 3:", slice_3)
```

Slice 3: [4, 5, 6, 7, 8, 9, 10]

```
In [5]: my_list = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
# Access every second element
slice_4 = my_list[::2]
print("Slice 4:", slice_4)
```

Slice 4: [1, 3, 5, 7, 9]

```
In [6]: my_list = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
# Access elements in reverse order
slice_5 = my_list[::-1]
print("Slice 5:", slice_5)
```

Slice 5: [10, 9, 8, 7, 6, 5, 4, 3, 2, 1]

In Python, slicing syntax follows the pattern [start:stop:step], where: start: The starting index of the slice (inclusive). stop: The ending index of the slice (exclusive). step: The step size for selecting elements (optional, defaults to 1). You can omit any of these parameters, and Python will use default values:

If start is omitted, it defaults to 0 (beginning of the list). If stop is omitted, it defaults to the end of the list. If step is omitted, it defaults to 1 (select every element).

List Loop

```
In [7]: # Create a sample list
my_list = [1, 2, 3, 4, 5]

# Loop through the list and print each element
for element in my_list:
    print(element)
```

1
2
3
4
5

Aliasing

- In Python, aliasing refers to the situation where two or more variables refer to the same object in memory.
- This concept is relevant when working with mutable objects like lists.
- When you create a new variable and assign it the value of another variable containing a list, both variables reference the same list object in memory.
- Therefore, modifications made to one variable will affect the other.

```
In [8]: # Creating a list
original_list = [1, 2, 3, 4, 5]

# Creating an alias by assigning the list to a new variable
alias_list = original_list

# Modifying the alias list
alias_list.append(6)

# Printing both lists
print("Original List:", original_list)
print("Alias List:", alias_list)
```

Original List: [1, 2, 3, 4, 5, 6]
Alias List: [1, 2, 3, 4, 5, 6]

As you can see, when we modify the `alias_list` by appending an element, the change is reflected in the `original_list` as well because both variables reference the same list object in memory.

To avoid aliasing and create a copy of the list instead, you can use slicing or the `copy()` method:

Copy Method

```
In [9]: # Using slicing to create a copy of the original list
copied_list = original_list[:]
```

```
# Modifying the copied list
copied_list.append(7)

# Printing both lists
print("Original List:", original_list)
print("Copied List:", copied_list)
```

Original List: [1, 2, 3, 4, 5, 6]
 Copied List: [1, 2, 3, 4, 5, 6, 7]

List Parameters

```
In [10]: # Define a function that takes a list as a parameter
def process_list(my_list):
    # Iterate through the elements of the list and print each element
    for element in my_list:
        print(element)

# Create a list
my_list = [1, 2, 3, 4, 5]

# Call the function with the list as an argument
process_list(my_list)
```

1
2
3
4
5

```
In [11]: # Define a function that takes two lists as parameters
def merge_lists(list1, list2):
    # Concatenate the two lists and return the result
    return list1 + list2

# Create two lists
list1 = [1, 2, 3]
list2 = [4, 5, 6]

# Call the function with the two lists as arguments
result = merge_lists(list1, list2)
print(result) # Output: [1, 2, 3, 4, 5, 6]
```

[1, 2, 3, 4, 5, 6]

Tuples

- Tuples in Python are immutable sequences, similar to lists, but with the key difference that tuples cannot be modified once created.
- They are typically used to store collections of heterogeneous data, and they support indexing, slicing, and other sequence operations.
- Tuples are defined using parentheses ().

```
In [12]: # Creating a tuple
my_tuple = (1, 2, 3, 'a', 'b', 'c')
print(my_tuple)
```

(1, 2, 3, 'a', 'b', 'c')

```
In [13]: # Accessing elements of the tuple
my_tuple = (1, 2, 3, 'a', 'b', 'c')
print(my_tuple[0]) # Output: 1
print(my_tuple[3]) # Output: 'a'
```

1

a

```
In [14]: # Slicing a tuple
my_tuple = (1, 2, 3, 'a', 'b', 'c')
print(my_tuple[2:5]) # Output: (3, 'a', 'b')
```

(3, 'a', 'b')

```
In [15]: # Tuple unpacking
a, b, c = (1, 2, 3)
print(a) # Output: 1
print(b) # Output: 2
print(c) # Output: 3
```

1

2

3

```
In [16]: # Trying to modify a tuple will result in an error
my_tuple[0] = 10 # Raises TypeError
```

```
-----
TypeError                                Traceback (most recent call last)
Cell In[16], line 2
      1 # Trying to modify a tuple will result in an error
----> 2 my_tuple[0] = 10 # Raises TypeError

TypeError: 'tuple' object does not support item assignment
```

```
In [24]: # Length of a tuple
print(len(my_tuple)) # Output: 6

# Membership test
print('a' in my_tuple) # Output: True

# Increment tuple/ reassign and change tuple
my_tuple = (1, 2, 3, 'a', 'b', 'c')
print(my_tuple)
my_tuple = (0, 2, 3, 'a', 'b', 'c', 'd')
print(my_tuple)
```



```
6
True
(1, 2, 3, 'a', 'b', 'c')
(0, 2, 3, 'a', 'b', 'c', 'd')
```

```
In [25]: # Alaising
my_tuple = (1, 2, 3, 'a', 'b', 'c')
new_tuple = my_tuple
print(new_tuple)

(1, 2, 3, 'a', 'b', 'c')
```

Basic Tuple Assignment

```
In [26]: # Define a tuple
person = ("Mathy", 25, "Chennai")

# Unpack the tuple into individual variables
name, age, city = person

# Print the variables
print("Name:", name)
print("Age:", age)
print("City:", city)
```

```
Name: Mathy
Age: 25
City: Chennai
```

Swap in Tuple

```
In [27]: # Define two variables
a = 5
b = 10

# Swap the values of the variables using tuple assignment
a, b = b, a

# Print the variables after swapping
print("a:", a)
print("b:", b)
```

```
a: 10
b: 5
```

```
In [49]: # Define a tuple
numbers = (1, 2, 3, 4, 5)

# Assign the first three values of the tuple to a single variable
first, second, third, *remaining = numbers

# Print the variables
print("first:", first)
print("second:", second)
```

```
print("third:", third)
print("Remaining:", remaining)
```

```
first: 1
second: 2
third: 3
Remaining: [4, 5]
```

```
In [50]: # Define a tuple
point = (10, 20, 30)

# Unpack the tuple, but ignore the third value using an underscore
x, y, _ = point

# Print the variables
print("x:", x)
print("y:", y)
```

```
x: 10
y: 20
```

Tuple as return value

```
In [ ]: def get_coordinates():
        # Simulate fetching coordinates
        x = int(input("value of x"))
        y = int(input("value of y"))
        return x, y

# Call the function and receive the tuple
coordinates = get_coordinates()

# Unpack the tuple
x, y = coordinates

# Print the coordinates
print("X Coordinate:", x)
print("Y Coordinate:", y)
```

Dictionaries

- Dictionaries in Python are data structures that store key-value pairs.
- They are mutable, unordered collections, allowing you to store and retrieve data based on keys rather than numerical indices.

Creating Dictionaries

Dictionaries are defined using curly braces `{}` with key-value pairs separated by colons `:`.

```
In [33]: # Creating a dictionary
person = {
    "name": "Mathy",
    "age": 25,
    "city": "Chennai"
}
print(person)

{'name': 'Mathy', 'age': 25, 'city': 'Chennai'}
```

Accessing Values

Values in a dictionary can be accessed by specifying the corresponding key.

```
In [34]: # Accessing values in the dictionary
print("Name:", person["name"]) # Output: Mathy
print("Age:", person["age"])   # Output: 30

Name: Mathy
Age: 25
```

Adding and Modifying Values

You can add new key-value pairs or modify existing ones in a dictionary.

```
In [36]: # Adding a new key-value pair
person["gender"] = "Male"

# Modifying an existing value
person["age"] = 26

print("Name:", person["gender"])
print("Age:", person["age"])
print(person)

Name: Male
Age: 26
{'name': 'Mathy', 'age': 26, 'city': 'Chennai', 'gender': 'Male'}
```

Dictionary Methods

Python dictionaries come with several built-in methods for manipulation:

```
In [38]: print(person)

# Getting all keys
keys = person.keys()
print("Keys:", keys) # Output: dict_keys(['name', 'age', 'city', 'gender'])

{'name': 'Mathy', 'city': 'Chennai', 'gender': 'Male'}
Keys: dict_keys(['name', 'city', 'gender'])
```

```
In [39]: # Getting all values
values = person.values()
print("Values:", values) # Output: dict_values(['Mathy', 31, 'Chennai', 'Ma

Values: dict_values(['Mathy', 'Chennai', 'Male'])
```

```
In [43]: # Checking if a key exists
print("city" in person) # Output: True
print("Female" in person['gender'])

True
False
```

```
In [44]: # Removing a key-value pair
del person["age"]

print(person)
```

```
-----
KeyError                                Traceback (most recent call last)
Cell In[44], line 2
      1 # Removing a key-value pair
----> 2 del person["age"]
      4 print(person)

KeyError: 'age'
```

Iteration over key and values

```
In [51]: # Iterating over keys
for key in person:
    print(key, ":", person[key])

name : Mathy
city : Chennai
gender : Male
```

```
In [48]: # Iterating over keys
for key in person.keys():
    print(key, ":", person[key])

name : Mathy
city : Chennai
gender : Male
```

```
In [46]: # Iterating over values
for value in person.values():
    print(value)

Mathy
Chennai
Male
```

```
In [47]: # Iterating over key-value pairs
for key, value in person.items():
```

```
print(key, ":", value)
```

name : Mathy
city : Chennai
gender : Male

Any Questions?

- 1. Python Programming for Beginners: Skyrocket Your Code and Master Python in Less than a Week. Discover the Foolproof, Practical Route to Uncover Insider Hacks, Unlock New Opportunities, and Revolution Kindle Edition by Kit Jackson (Author), 31 May 2023
- 2. Python Programming for Beginners,ISBN-13-979-8870875248, Narry Prince, 2023

For More

[Refer the Lectures/Tutorials GitHub Page](#)