

```
analyst@d40c07e0ca95:~$
```

```
analyst@d40c07e0ca95:~$ whatis cat
```

```
analyst@d40c07e0ca95:~$ whatis cat
cat (1)          - concatenate files and print on the standard output
analyst@d40c07e0ca95:~$
```

```
analyst@d40c07e0ca95:~$ whatis cat
cat (1)          - concatenate files and print on the standard output
analyst@d40c07e0ca95:~$ man cat
```

CAT(1) User Commands

NAME

cat - concatenate files and print on the standard output

SYNOPSIS

cat [OPTION]... [FILE]...

DESCRIPTION

Concatenate FILE(s) to standard output.

With no FILE, or when FILE is -, read standard input.

-A, --show-all
equivalent to -vET

-b, --number-nonblank
number nonempty output lines, overrides -n

-e equivalent to -vE

-E, --show-ends
display \$ at end of each line

-n, --number
number all output lines

-s, --squeeze-blank
suppress repeated empty output lines

-t equivalent to -vT

-T, --show-tabs
display TAB characters as ^I

-u (ignored)

-v, --show-nonprinting

--More--

NAME

cat - concatenate files and print on the standard output

SYNOPSIS

cat [OPTION]... [FILE]...

DESCRIPTION

Concatenate FILE(s) to standard output.

With no FILE, or when FILE is -, read standard input.

-A, --show-all
equivalent to -vET

-b, --number-nonblank
number nonempty output lines, overrides -n

-e equivalent to -vE

-E, --show-ends
display \$ at end of each line

-n, --number
number all output lines

-s, --squeeze-blank
suppress repeated empty output lines

-t equivalent to -vT

-T, --show-tabs
display TAB characters as ^I

-u (ignored)

-v, --show-nonprinting

analyst@d40c07e0ca95:~\$

NAME

cat - concatenate files and print on the standard output

SYNOPSIS

cat [OPTION]... [FILE]...

DESCRIPTION

Concatenate FILE(s) to standard output.

With no FILE, or when FILE is -, read standard input.

-A, --show-all
equivalent to -vET

-b, --number-nonblank
number nonempty output lines, overrides -n

-e equivalent to -vE

-E, --show-ends
display \$ at end of each line

-n, --number
number all output lines

-s, --squeeze-blank
suppress repeated empty output lines

-t equivalent to -vT

-T, --show-tabs
display TAB characters as ^I

-u (ignored)

-v, --show-nonprinting

analyst@d40c07e0ca95:~\$ apropos -a first part file

NAME

cat - concatenate files and print on the standard output

SYNOPSIS

cat [OPTION]... [FILE]...

DESCRIPTION

Concatenate FILE(s) to standard output.

With no FILE, or when FILE is -, read standard input.

-A, --show-all
equivalent to -vET

-b, --number-nonblank
number nonempty output lines, overrides -n

-e
equivalent to -vE

-E, --show-ends
display \$ at end of each line

-n, --number
number all output lines

-s, --squeeze-blank
suppress repeated empty output lines

-t
equivalent to -vT

-T, --show-tabs
display TAB characters as ^I

-u
(ignored)

-v, --show-nonprinting

analyst@d40c07e0ca95:~\$ apropos -a first part file

head (1) - output the first part of files

analyst@d40c07e0ca95:~\$

NAME

cat - concatenate files and print on the standard output

SYNOPSIS

cat [OPTION]... [FILE]...

DESCRIPTION

Concatenate FILE(s) to standard output.

With no FILE, or when FILE is -, read standard input.

-A, --show-all

equivalent to -vET

-b, --number-nonblank

number nonempty output lines, overrides -n

-e

equivalent to -vE

-E, --show-ends

display \$ at end of each line

-n, --number

number all output lines

-s, --squeeze-blank

suppress repeated empty output lines

-t

equivalent to -vT

-T, --show-tabs

display TAB characters as ^I

-u

(ignored)

-v, --show-nonprinting

analyst@d40c07e0ca95:~\$ apropos -a first part file

head (1) - output the first part of files

analyst@d40c07e0ca95:~\$ man useradd

```

USERADD(8)                                     System Management Commands                                     USERADD(8)

NAME
    useradd - create a new user or update default new user information

SYNOPSIS
    useradd [options] LOGIN

    useradd -D

    useradd -D [options]

DESCRIPTION
    useradd is a low level utility for adding users. On Debian, administrators should usually use adduser(8) instead.

    When invoked without the -D option, the useradd command creates a new user account using the values specified on the command line plus the default values from the system. Depending on command line options, the useradd command will update system files and may also create the new user's home directory and copy initial files.

    By default, a group will also be created for the new user (see -g, -N, -U, and USERGROUPS_ENAB).

OPTIONS
    The options which apply to the useradd command are:

    --badname
        Allow names that do not conform to standards.

    -b, --base-dir BASE_DIR
        The default base directory for the system if -d HOME_DIR is not specified. BASE_DIR is concatenated with the account name to define the home directory. If the -m option is not used, BASE_DIR must exist.

        If this option is not specified, useradd will use the base directory specified by the HOME variable in /etc/default/useradd, or /home by default.

    -c, --comment COMMENT
        Any text string. It is generally a short description of the login, and is currently used as the field for the user's full name.

    -d, --home-dir HOME_DIR
        The new user will be created using HOME_DIR as the value for the user's login directory. The default is to append the LOGIN name to BASE_DIR and use that

```

--More--

```

    -d, --home-dir HOME_DIR
        The new user will be created using HOME_DIR as the value for the user's login directory. The default is to append the LOGIN name to BASE_DIR and use that as the login directory name. The directory HOME_DIR does not have to exist but will not be created if it is missing.

    -D, --defaults
        See below, the subsection "Changing the default values".

    -e, --expiredate EXPIRE_DATE
        The date on which the user account will be disabled. The date is specified in the format YYYY-MM-DD.

        If not specified, useradd will use the default expiry date specified by the EXPIRE variable in /etc/default/useradd, or an empty string (no expiry) by default.

    -f, --inactive INACTIVE
        The number of days after a password expires until the account is permanently disabled. A value of 0 disables the account as soon as the password has expired, and a value of -1 disables the feature.

        If not specified, useradd will use the default inactivity period specified by the INACTIVE variable in /etc/default/useradd, or -1 by default.

    -g, --gid GROUP
        The group name or number of the user's initial login group. The group name must exist. A group number must refer to an already existing group.

        If not specified, the behavior of useradd will depend on the USERGROUPS_ENAB variable in /etc/login.defs. If this variable is set to yes (or -U/--user-group is specified on the command line), a group will be created for the user, with the same name as her loginname. If the variable is set to no (or -N/--no-user-group is specified on the command line), useradd will set the primary group of the new user to the value specified by the GROUP variable in /etc/default/useradd, or 100 by default.

    -G, --groups GROUP1[,GROUP2,...[,GROUPN]]
        A list of supplementary groups which the user is also a member of. Each group is separated from the next by a comma, with no intervening whitespace. The groups are subject to the same restrictions as the group given with the -g option. The default is for the user to belong only to the initial group.

    -h, --help
        Display help message and exit.

    -k, --skel SKEL_DIR
        The skeleton directory, which contains files and directories to be copied in the user's home directory, when the home directory is created by useradd.

```

--More--

```

    -d, --home-dir HOME_DIR
        The new user will be created using HOME_DIR as the value for the user's login directory. The default is to append the LOGIN name to BASE_DIR and use that as the login directory name. The directory HOME_DIR does not have to exist but will not be created if it is missing.

    -D, --defaults
        See below, the subsection "Changing the default values".

    -e, --expiredate EXPIRE_DATE
        The date on which the user account will be disabled. The date is specified in the format YYYY-MM-DD.

        If not specified, useradd will use the default expiry date specified by the EXPIRE variable in /etc/default/useradd, or an empty string (no expiry) by default.

    -f, --inactive INACTIVE
        The number of days after a password expires until the account is permanently disabled. A value of 0 disables the account as soon as the password has expired, and a value of -1 disables the feature.

        If not specified, useradd will use the default inactivity period specified by the INACTIVE variable in /etc/default/useradd, or -1 by default.

    -g, --gid GROUP
        The group name or number of the user's initial login group. The group name must exist. A group number must refer to an already existing group.

        If not specified, the behavior of useradd will depend on the USERGROUPS_ENAB variable in /etc/login.defs. If this variable is set to yes (or -U/--user-group is specified on the command line), a group will be created for the user, with the same name as her loginname. If the variable is set to no (or -N/--no-user-group is specified on the command line), useradd will set the primary group of the new user to the value specified by the GROUP variable in /etc/default/useradd, or 100 by default.

    -G, --groups GROUP1[,GROUP2,...[,GROUPN]]
        A list of supplementary groups which the user is also a member of. Each group is separated from the next by a comma, with no intervening whitespace. The groups are subject to the same restrictions as the group given with the -g option. The default is for the user to belong only to the initial group.

    -h, --help
        Display help message and exit.

    -k, --skel SKEL_DIR
        The skeleton directory, which contains files and directories to be copied in the user's home directory, when the home directory is created by useradd.

```

analyst@40c07e0ca95:~\$

```

-d, --home-dir HOME_DIR
    The new user will be created using HOME_DIR as the value for the user's login directory. The default is to append the LOGIN name to BASE_DIR and use that
    as the login directory name. The directory HOME_DIR does not have to exist but will not be created if it is missing.

-D, --defaults
    See below, the subsection "Changing the default values".

-e, --expiredate EXPIRE_DATE
    The date on which the user account will be disabled. The date is specified in the format YYYY-MM-DD.

    If not specified, useradd will use the default expiry date specified by the EXPIRE variable in /etc/default/useradd, or an empty string (no expiry) by
    default.

-f, --inactive INACTIVE
    The number of days after a password expires until the account is permanently disabled. A value of 0 disables the account as soon as the password has
    expired, and a value of -1 disables the feature.

    If not specified, useradd will use the default inactivity period specified by the INACTIVE variable in /etc/default/useradd, or -1 by default.

-g, --gid GROUP
    The group name or number of the user's initial login group. The group name must exist. A group number must refer to an already existing group.

    If not specified, the behavior of useradd will depend on the USERGROUPS_ENAB variable in /etc/login.defs. If this variable is set to yes (or
    -U/--user-group is specified on the command line), a group will be created for the user, with the same name as her loginname. If the variable is set to no
    (or -N/--no-user-group is specified on the command line), useradd will set the primary group of the new user to the value specified by the GROUP variable
    in /etc/default/useradd, or 100 by default.

-G, --groups GROUP1[,GROUP2,...[,GROUPN]]
    A list of supplementary groups which the user is also a member of. Each group is separated from the next by a comma, with no intervening whitespace. The
    groups are subject to the same restrictions as the group given with the -g option. The default is for the user to belong only to the initial group.

-h, --help
    Display help message and exit.

-k, --skel SKEL_DIR
    The skeleton directory, which contains files and directories to be copied in the user's home directory, when the home directory is created by useradd.

```

```
analyst@d40c07e0ca951-$ whatis rm
```

```

    The new user will be created using HOME_DIR as the value for the user's login directory. The default is to append the LOGIN name to BASE_DIR and use that
    as the login directory name. The directory HOME_DIR does not have to exist but will not be created if it is missing.

-D, --defaults
    See below, the subsection "Changing the default values".

-e, --expiredate EXPIRE_DATE
    The date on which the user account will be disabled. The date is specified in the format YYYY-MM-DD.

    If not specified, useradd will use the default expiry date specified by the EXPIRE variable in /etc/default/useradd, or an empty string (no expiry) by
    default.

-f, --inactive INACTIVE
    The number of days after a password expires until the account is permanently disabled. A value of 0 disables the account as soon as the password has
    expired, and a value of -1 disables the feature.

    If not specified, useradd will use the default inactivity period specified by the INACTIVE variable in /etc/default/useradd, or -1 by default.

-g, --gid GROUP
    The group name or number of the user's initial login group. The group name must exist. A group number must refer to an already existing group.

    If not specified, the behavior of useradd will depend on the USERGROUPS_ENAB variable in /etc/login.defs. If this variable is set to yes (or
    -U/--user-group is specified on the command line), a group will be created for the user, with the same name as her loginname. If the variable is set to no
    (or -N/--no-user-group is specified on the command line), useradd will set the primary group of the new user to the value specified by the GROUP variable
    in /etc/default/useradd, or 100 by default.

-G, --groups GROUP1[,GROUP2,...[,GROUPN]]
    A list of supplementary groups which the user is also a member of. Each group is separated from the next by a comma, with no intervening whitespace. The
    groups are subject to the same restrictions as the group given with the -g option. The default is for the user to belong only to the initial group.

-h, --help
    Display help message and exit.

-k, --skel SKEL_DIR
    The skeleton directory, which contains files and directories to be copied in the user's home directory, when the home directory is created by useradd.

```

```
analyst@d40c07e0ca951-$ whatis rm
rm (1)          - remove files or directories
analyst@d40c07e0ca951-$ whatis rmdir
```

```

-D, --defaults
    See below, the subsection "Changing the default values".

-e, --expiredate EXPIRE_DATE
    The date on which the user account will be disabled. The date is specified in the format YYYY-MM-DD.

    If not specified, useradd will use the default expiry date specified by the EXPIRE variable in /etc/default/useradd, or an empty string (no expiry) by
    default.

-f, --inactive INACTIVE
    The number of days after a password expires until the account is permanently disabled. A value of 0 disables the account as soon as the password has
    expired, and a value of -1 disables the feature.

    If not specified, useradd will use the default inactivity period specified by the INACTIVE variable in /etc/default/useradd, or -1 by default.

-g, --gid GROUP
    The group name or number of the user's initial login group. The group name must exist. A group number must refer to an already existing group.

    If not specified, the behavior of useradd will depend on the USERGROUPS_ENAB variable in /etc/login.defs. If this variable is set to yes (or
    -U/--user-group is specified on the command line), a group will be created for the user, with the same name as her loginname. If the variable is set to no
    (or -N/--no-user-group is specified on the command line), useradd will set the primary group of the new user to the value specified by the GROUP variable
    in /etc/default/useradd, or 100 by default.

-G, --groups GROUP1[,GROUP2,...[,GROUPN]]
    A list of supplementary groups which the user is also a member of. Each group is separated from the next by a comma, with no intervening whitespace. The
    groups are subject to the same restrictions as the group given with the -g option. The default is for the user to belong only to the initial group.

-h, --help
    Display help message and exit.

-k, --skel SKEL_DIR
    The skeleton directory, which contains files and directories to be copied in the user's home directory, when the home directory is created by useradd.

```

```
analyst@d40c07e0ca951-$ whatis rm
rm (1)          - remove files or directories
analyst@d40c07e0ca951-$ whatis rmdir
rmdir (1)       - remove empty directories
rmdir (2)       - delete a directory
analyst@d40c07e0ca951-$
```

```

-D, --defaults
    See below, the subsection "Changing the default values".

-e, --expiredate EXPIRE_DATE
    The date on which the user account will be disabled. The date is specified in the format YYYY-MM-DD.

    If not specified, useradd will use the default expiry date specified by the EXPIRE variable in /etc/default/useradd, or an empty string (no expiry) by default.

-f, --inactive INACTIVE
    The number of days after a password expires until the account is permanently disabled. A value of 0 disables the account as soon as the password has expired, and a value of -1 disables the feature.

    If not specified, useradd will use the default inactivity period specified by the INACTIVE variable in /etc/default/useradd, or -1 by default.

-g, --gid GROUP
    The group name or number of the user's initial login group. The group name must exist. A group number must refer to an already existing group.

    If not specified, the behavior of useradd will depend on the USERGROUPS_ENAB variable in /etc/login.defs. If this variable is set to yes (or -U/--user-group is specified on the command line), a group will be created for the user, with the same name as her loginname. If the variable is set to no (or -N/--no-user-group is specified on the command line), useradd will set the primary group of the new user to the value specified by the GROUP variable in /etc/default/useradd, or 100 by default.

-G, --groups GROUP1[,GROUP2,...[,GROUPN]]
    A list of supplementary groups which the user is also a member of. Each group is separated from the next by a comma, with no intervening whitespace. The groups are subject to the same restrictions as the group given with the -g option. The default is for the user to belong only to the initial group.

-h, --help
    Display help message and exit.

-k, --skel SKEL_DIR
    The skeleton directory, which contains files and directories to be copied in the user's home directory, when the home directory is created by useradd.

analyst@d40c07e0ca95:~$ whatis rm
rm (1)             - remove files or directories
analyst@d40c07e0ca95:~$ whatis rmdir
rmdir (1)          - remove empty directories
rmdir (2)          - delete a directory
analyst@d40c07e0ca95:~$ apropos -a create new group

```

```

-e, --expiredate EXPIRE_DATE
    The date on which the user account will be disabled. The date is specified in the format YYYY-MM-DD.

    If not specified, useradd will use the default expiry date specified by the EXPIRE variable in /etc/default/useradd, or an empty string (no expiry) by default.

-f, --inactive INACTIVE
    The number of days after a password expires until the account is permanently disabled. A value of 0 disables the account as soon as the password has expired, and a value of -1 disables the feature.

    If not specified, useradd will use the default inactivity period specified by the INACTIVE variable in /etc/default/useradd, or -1 by default.

-g, --gid GROUP
    The group name or number of the user's initial login group. The group name must exist. A group number must refer to an already existing group.

    If not specified, the behavior of useradd will depend on the USERGROUPS_ENAB variable in /etc/login.defs. If this variable is set to yes (or -U/--user-group is specified on the command line), a group will be created for the user, with the same name as her loginname. If the variable is set to no (or -N/--no-user-group is specified on the command line), useradd will set the primary group of the new user to the value specified by the GROUP variable in /etc/default/useradd, or 100 by default.

-G, --groups GROUP1[,GROUP2,...[,GROUPN]]
    A list of supplementary groups which the user is also a member of. Each group is separated from the next by a comma, with no intervening whitespace. The groups are subject to the same restrictions as the group given with the -g option. The default is for the user to belong only to the initial group.

-h, --help
    Display help message and exit.

-k, --skel SKEL_DIR
    The skeleton directory, which contains files and directories to be copied in the user's home directory, when the home directory is created by useradd.

analyst@d40c07e0ca95:~$ whatis rm
rm (1)             - remove files or directories
analyst@d40c07e0ca95:~$ whatis rmdir
rmdir (1)          - remove empty directories
rmdir (2)          - delete a directory
analyst@d40c07e0ca95:~$ apropos -a create new group
groupadd (8)       - create a new group
analyst@d40c07e0ca95:~$

```