```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema</pre>
  targetNamespace="http://panopto.com/PanoptoSession/v1"
  elementFormDefault="qualified"
  xmlns="http://tempuri.org/XMLSchema.xsd"
  xmlns:mstns="http://tempuri.org/XMLSchema.xsd"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  version="1.0">
  <!-- Describes a collection of playable content on a single timeline for uploading to a Panopto server. -->
  <xs:element name="PanoptoSession">
    <xs:complexType>
      <xs:all>
        <!-- The name of the session. -->
        <xs:element type="xs:string" name="Title"/>
        <!-- A paragraph describing the session contents in detail. -->
        <xs:element type="xs:string" name="Description"/>
        <!-- The date the session was created. -->
        <xs:element type="xs:dateTime" name="Date"/>
        <!-- Video streams in this session. -->
        <xs:element name="Videos">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="Video" minOccurs="0" maxOccurs="unbounded">
                <xs:complexType>
                  <xs:all>
                    <!-- The time at which this video starts relative to session start. Determines its position
on the timeline. -->
                    <xs:element type="xs:duration" name="Start"/>
                    <!-- The filename of the video. Must match exactly to a video filename uploaded in the same
directory as this XML. -->
                    <xs:element name="Filename">
                      <xs:complexType>
                        <xs:simpleContent>
                          <xs:extension base="xs:string">
                            <!-- For convenience, not used by the server, a full path to the file on disk. -->
                            <xs:attribute type="xs:string" name="LocalFilename" use="optional"/>
                          </xs:extension>
                        </xs:simpleContent>
                      </xs:complexType>
                    </xs:element>
                    <!-- A collection of ranges of video to omit from the final playable session. -->
                    <xs:element name="Cuts">
                      <xs:complexType>
                        <xs:sequence>
                          <xs:element name="Cut" minOccurs="0" maxOccurs="unbounded">
                            <xs:complexType>
                              <xs:all>
                                <!-- The start time of the range to cut relative to the video start. -->
                                <xs:element type="xs:duration" name="Start"/>
                                <!-- The duration of the range to cut. -->
                                <xs:element type="xs:duration" name="Duration"/>
                              </xs:all>
                            </xs:complexType>
                          </xs:element>
                        </xs:sequence>
                      </xs:complexType>
                    </xs:element>
                    <!-- A collection of timed entries in the session for navigation and search discovery. -->
                    <xs:element name="TableOfContents">
```

```
<xs:complexType>
                        <xs:sequence>
                          <xs:element name="Entry" minOccurs="0" maxOccurs="unbounded">
                            <xs:complexType>
                              <xs:all>
                                <!-- A title for the table of contents entry to be displayed in a list. -->
                                <xs:element type="xs:string" name="Title"/>
                                <!-- A paragraph of additional text to include with this table of contents
entry. -->
                                <xs:element type="xs:string" name="Description" minOccurs="0"/>
                                <!-- A url to associate with this entry. -->
                                <xs:element type="xs:anyURI" name="Url" minOccurs="0"/>
                                <!-- The time relative to the start of the video where this entry occurs. -->
                                <xs:element type="xs:duration" name="Time"/>
                              </xs:all>
                            </xs:complexType>
                          </xs:element>
                        </xs:sequence>
                      </xs:complexType>
                    </xs:element>
                    <!-- Describes where the video should be positioned for viewers. -->
                    <xs:element name="Type">
                      <xs:simpleType>
                        <xs:restriction base="xs:string">
                          <!-- Positions the video to the left side of the viewer in a smaller window. -->
                          <xs:enumeration value="Primary"/>
                          <!-- Positions the video to the right side of the viewer in a larger window. -->
                          <xs:enumeration value="Secondary"/>
                          <!-- An audio only recording. -->
                          <xs:enumeration value="Audio"/>
                        </xs:restriction>
                        </xs:simpleType>
                      </xs:element>
                    <!-- Transcripts of this stream for closed captioning and search. Must refer to a video
file uploaded with this XML. -->
                    <xs:element name="Transcripts">
                      <xs:complexType>
                        <xs:sequence>
                          <xs:element name="Transcript" minOccurs="0" maxOccurs="unbounded">
                            <xs:complexType>
                              <xs:all>
                                <!-- The filename of the transcript. Must match exactly to a transcript
filename uploaded in the same directory as this XML. -->
                                <xs:element name="Filename">
                                  <xs:complexType>
                                    <xs:simpleContent>
                                      <xs:extension base="xs:string">
                                        <!-- For convenience, not used by the server, a full path to the file
on disk. -->
                                        <xs:attribute type="xs:string" name="LocalFilename" use="optional"/>
                                      </xs:extension>
                                    </xs:simpleContent>
                                  </xs:complexType>
                                </xs:element>
                                <!-- The language the transcript is in. Allows for multiple transcripts in
different languages. -->
                                <xs:element type="xs:string" name="LCID"/>
                                <!-- Describe which service the captions came from. -->
```

```
<!-- Controls whether the captions can be displayed in closed captioning or if
it is only suitable for search. -->
                                <xs:element type="xs:boolean" name="Visible" default="true" minOccurs="0"/>
                              </xs:all>
                            </xs:complexType>
                          </xs:element>
                        </xs:sequence>
                      </xs:complexType>
                    </xs:element>
                  </xs:all>
                </xs:complexType>
              </xs:element>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <!-- Slide shows presented in this session. -->
        <xs:element name="Presentations">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="Presentation" minOccurs="0" maxOccurs="unbounded">
                <xs:complexType>
                  <xs:all>
                    <!-- The time at which this presentation starts relative to session start. Determines its
position on the timeline. -->
                    <xs:element type="xs:duration" name="Start"/>
                    <!-- The filename of the presentation. Must match exactly to a presentation filename
uploaded in the same directory as this XML. -->
                    <xs:element name="Filename">
                      <xs:complexType>
                        <xs:simpleContent>
                          <xs:extension base="xs:string">
                            <!-- For convenience, not used by the server, a full path to the file on disk. -->
                            <xs:attribute type="xs:string" name="LocalFilename" use="optional"/>
                          </xs:extension>
                        </xs:simpleContent>
                      </xs:complexType>
                    </xs:element>
                    <!-- A collection of transitions to slides on the session timeline. -->
                    <xs:element name="SlideChanges">
                      <xs:complexType>
                        <xs:sequence>
                          <xs:element name="SlideChange" minOccurs="0" maxOccurs="unbounded">
                            <xs:complexType>
                              <xs:all>
                                <!-- A title for the slide change to be displayed in the table of contents
list. -->
                                <xs:element type="xs:string" name="Title"/>
                                <!-- A paragraph of additional text to include with this slide. Usually the
full slide text. -->
                                <xs:element type="xs:string" name="Description" minOccurs="0"/>
                                <!-- A url to associate with this entry. -->
                                <xs:element type="xs:anyURI" name="Url" minOccurs="0"/>
                                <!-- The time relative to the start of the presentation where this slide change
occurs. -->
                                <xs:element type="xs:duration" name="Time"/>
                                <!-- The 1-based slide index in the presentation of the slide shown by this
slide change. -->
                                <xs:element type="xs:integer" name="SlideNumber"/>
                              </xs:all>
                            </xs:complexType>
```

<xs:element type="xs:string" name="Source" minOccurs="0"/>

```
</xs:element>
                        </xs:sequence>
                      </xs:complexType>
                    </xs:element>
                  </xs:all>
                </xs:complexType>
              </xs:element>
            </xs:seauence>
          </xs:complexType>
        </xs:element>
        <!-- Static images shown in this session. -->
        <xs:element name="Images" minOccurs="0">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="Image" minOccurs="0" maxOccurs="unbounded">
                <xs:complexType>
                  <xs:all>
                    <!-- The filename of the image. Must match exactly to an image filename uploaded in the
same directory as this XML. -->
                    <xs:element name="Filename">
                      <xs:complexType>
                        <xs:simpleContent>
                          <xs:extension base="xs:string">
                            <!-- For convenience, not used by the server, a full path to the file on disk. -->
                            <xs:attribute type="xs:string" name="LocalFilename" use="optional"/>
                          </xs:extension>
                        </xs:simpleContent>
                      </xs:complexType>
                    </xs:element>
                    <!-- A title for the image in the table of contents list. -->
                    <xs:element type="xs:string" name="Title"/>
                    <!-- A paragraph of additional text to include with this image. -->
                    <xs:element type="xs:string" name="Description" minOccurs="0"/>
                    <!-- A url to associate with this entry. -->
                    <xs:element type="xs:anyURI" name="Url" minOccurs="0"/>
                    <!-- The time relative to the start of the session where this image should be shown. -->
                    <xs:element type="xs:duration" name="Time"/>
                  </xs:all>
                </xs:complexType>
              </xs:element>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <!-- A collection of ranges of the entire session to omit from the final playable output. -->
        <xs:element name="Cuts">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="Cut" minOccurs="0" maxOccurs="unbounded">
                <xs:complexType>
                  <xs:all>
                    <!-- The start time of the range to cut relative to the session start. -->
                    <xs:element type="xs:duration" name="Start"/>
                    <!-- The duration of the range to cut. -->
                    <xs:element type="xs:duration" name="Duration"/>
                  </xs:all>
                </xs:complexType>
              </xs:element>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
```

```
<!-- A collection of strings associated with the session for categorization purposes. -->
        <xs:element name="Tags" minOccurs="0">
          <xs:complexType>
            <xs:sequence>
              <xs:element type="xs:string" name="Tag" minOccurs="0" maxOccurs="unbounded"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <!-- A collection of name and value pairs associated with the session for extensibility purposes. -->
        <xs:element name="Extensions" minOccurs="0">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="Extension" minOccurs="0" maxOccurs="unbounded">
                <xs:complexType>
                  <xs:all>
                    <xs:element type="xs:string" name="Name"/>
                    <xs:element type="xs:string" name="Value"/>
                  </xs:all>
                </xs:complexType>
              </xs:element>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <!-- Any additional file attachments to include with this session. -->
        <xs:element name="Attachments" minOccurs="0">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="Attachment" minOccurs="0" maxOccurs="unbounded">
                <xs:complexType>
                  <xs:all>
                    <!-- The filename of the attachment. Must match exactly to a attachment filename uploaded
in the same directory as this XML. -->
                    <xs:element name="Filename">
                      <xs:complexType>
                        <xs:simpleContent>
                          <xs:extension base="xs:string">
                            <!-- For convenience, not used by the server, a full path to the file on disk. -->
                            <xs:attribute type="xs:string" name="LocalFilename" use="optional"/>
                          </xs:extension>
                        </xs:simpleContent>
                      </xs:complexType>
                    </xs:element>
                    <!-- The MIME type of this file. -->
                    <xs:element type="xs:string" name="MimeType"/>
                  </xs:all>
                </xs:complexType>
              </xs:element>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
      </xs:all>
    </xs:complexType>
  </xs:element>
  <!-- A definition for the globally unique identifier type Panopto uses. -->
  <xs:simpleType name="guid">
    <xs:annotation>
      <xs:documentation xml:lang="en">
        The representation of a GUID, generally the id of an element.
      </xs:documentation>
    </xs:annotation>
    <xs:restriction base="xs:string">
      <xs:pattern value="\{[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12}\}"/>
    </xs:restriction>
  </xs:simpleType>
</xs:schema>
```